

Auction Catalog

FLO EV Charging Operations - Auburn Hills

Auction Date:

Tuesday, Apr 28 2026

Bidding Starts: 10:30 AM EDT

BidItUp Auctions Worldwide
1101 E. Tropicana Avenue
Suite 3033
Las Vegas, NV 89119

Phone: (818) 508-7034
Email: auctions@biditup.com

Lot Number	Lot Title & Description	Serial Number
0A	LOT LIST COMING SOON!	
0B	<p>How to Bid: This auction features two distinct bidding formats: one online-only before the live webcast auction and one during the live webcast event.</p> <p>Online-Only Bidding Prior to the live webcast, you can place bids online for the auction lots. This allows you to start the bidding process and potentially win the items before the live event.</p> <p>Proxy Bidding Proxy bidding allows you to submit a maximum bid without participating in the live webcast event. Once your proxy bid is placed, the system will automatically bid on your behalf at the increments specified by the auctioneer.</p> <p>Even if you set a proxy bid, you can still actively participate in the live webcast auction if you choose.</p> <p>Example of Proxy Bidding: Let's say Mr. Smith is interested in bidding on lots 4 and 5 but is unable to attend the live event. He can log in ahead of time, place a maximum bid of \$100 for each lot, and set his proxy bid. If Mr. Jones places a bid of \$25 on lot 4, Mr. Smith's proxy bid of \$100 will place him as the highest bidder at \$50. If no one else bids, Mr. Smith wins the lot at \$50. However, if a bidder during the live webcast places a bid of \$60, Mr. Smith's proxy will automatically increase his bid to \$70.</p> <p>Recommendation: To increase your chances of winning, we suggest setting maximum proxy bids for the lots you're interested in. The system will bid for you up to your max bid. Additionally, you can participate in the live virtual webcast to monitor the auction and increase your max bid if you are outbid.</p> <p>Important Note: You are allowed to bid both online and during the live webcast. If you're approved to bid, you may participate in both the online-only auction and the live virtual webcast auction.</p> <p>Important Auction Tips: Multiple Platforms: This auction is being held on multiple platforms. In the case of a tie bid, the auctioneer may ask for a tie-breaker or award the bid to the last, fastest bidder if the tie is not resolved.</p> <p>Choice Lots: When a lot is offered as a choice, the highest bidder can select one or more items from a grouping at the bid price. The bidder can take as many lots as desired at that price.</p> <p>Line and Piece Meal Lots: Some lots may be offered as a line (bulk lot) or piecemeal (individual pieces). When lots are offered both ways, the highest aggregate sum of the individual bids or the highest bulk bid will determine the winning bid.</p> <p>Tie-Breaking Process: This auction will be held as a simulcast event across multiple platforms. If a tie occurs, the auctioneer will attempt to break the tie. If a tie cannot be resolved, the auctioneer may, at their discretion, award the lot to the last fastest bidder.</p> <p>Bid Button and Increments: When you click the bid button online, your bid will be placed automatically at the increment specified by the auctioneer. Custom bid amounts cannot be entered.</p> <p>By following these guidelines, you can participate in both the online and live auction formats and increase your chances of winning your desired lots. Happy bidding!</p>	

Register 24 hours prior to the start of the auction.

A valid credit card, billing address, office address, email address and company address are required to bid online.

If you have a resale certificate or exemption, please provide a PDF copy to our office so that we may amend your invoice properly. In the email please provide your bidder number, your registration information and the name of the auction. This can be emailed to auctions@biditup.com.

First-time registrants - in order to bid for this auction, you MUST HAVE:

- 1) A deposit, 25% of expected purchases or \$1,000 minimum or
- 2) Be in good standing with other auctions held by members of the Industrial Auctioneers Association or
- 3) Belong to the IAA or MDNA or
- 4) Have successfully bid and picked up at 2+ auctions on bidspotter.com

Form of deposit: wire transfer (for wire instructions, please email customerservice@biditup.com).

Please note, all international bidders, or bidders spending over \$20,000 are required to submit a deposit via wire transfer of 25% of your maximum estimated bid. For example, if you are planning to spend a maximum of \$100,000 at auction, a wire transfer must be sent to us of \$25,000 prior to the sale to allow you to bid.

The same deposit requirement is applied for bidders with negative remarks on Bidspotter. You must provide a 25% deposit of your maximum estimated spend limit to be approved for the sale.

If you have any questions on approval, please email customerservice@biditup.com.

Once you have registered with Bidspotter, and Registered for this Auction, we will be notified. If you are approved, you will receive an approval notification status. If you have not been approved, please call us so we may help you through the process: (818) 508-7034

If you need help with registering for Bidspotter: BidSpotter Customer Service Support Department. Have a question pertaining to the bidding process? Visit our Frequently Asked Questions! You can also start a live chat with a Bidspotter Support Representative by selecting Live Chat at the top of Bidspotter.com. More information on our chat system can be found by clicking here.

Customer Support Hours:

Monday - Thursday, 8:00 AM EST - 10:00 PM EST

Friday, 8:00 AM EST - 6:30 PM EST

Email: support@bidspotter.com

Office: (253) 858-6777

Toll Free: (866) 597-2437 for Frequently Asked Questions

OC

BIDITUP AUCTIONS WORLDWIDE, INC.
BIDDERS BINDING CONTRACT

BIDITUP AUCTIONS WORLDWIDE, INC, HEREIN AFTER REFERRED TO AS BIDITUP, AUCTIONEER AND SELLER. BIDDER HEREIN AFTER REFEREED TO AS BIDDER, REGISTERED BIDDER, PURCHASER, UNDERSIGNED AND BUYER. THIS AUCTION WILL BE CONDUCTED PER THE TERMS AND CONDITIONS BELOW AND SUPERSEDED BY ALL OTHER PROVISIONS, AMENDMENTS, MODIFICATIONS AND ANNOUNCEMENTS ADDED BY AUCTIONEER AT ANYTIME PRIOR TO OR DURING THE AUCTION SALE AND OR AS POSTED ON WWW.BIDITUP.COM. BIDDER HEREBY AGREES AND ACKNOWLEDGES AUCTIONEER IS NOT RESPONSIBLE OR LIABLE FOR BIDDERS ACKNOWLEDGEMENT OF ANY SUCH ANNOUNCEMENTS AND BIDDER ASSUMES ALL RISKS AND LIABILITIES BELOW ONCE IT BIDS.

AUCTIONEER SHALL HAVE THE RIGHT TO MAKE IMAGE AND AUDIO VIDEO RECORDINGS OF THE AUCTION, TO USE SAID RECORDINGS AND IF DEEMED APPROPRIATE IN AUCTIONEERS SOLE DISCRETION TO MAKE THIS PUBLIC. BUYERS HEREBY GIVE THEIR PERMISSION AND CONSENT BY PARTICIPATING IN THE AUCTION.

Auctioneer at its sole discretion may deny entry, registration or bidding at any time to any person or entity. Bidder's paddles and invoices are nontransferable. All bids made by the holder of the bid paddle will be the responsibility of the Registered Bidder, Bidder and the Undersigned. All sales are final and there are no refunds, returns, credits, exchanges or rebids once the Auctioneer knocks down the item or declares it sold to the Bidder.

The Bidder, Registered Bidder, Purchaser, Undersigned and Buyer agree a successful bid at auction constitutes a legally binding contract of sale and this contract is binding upon the Registered Bidders Company, the Bidder, Purchaser, Undersigned and Buyer personally for all amounts due and owing at the conclusion of bidding and time of invoice. BUYER BEWARE AND CAVEAT EMPTOR.

"THE BUYER ALONE IS RESPONSIBLE FOR CHECKING THE QUALITY AND SUITABILITY OF GOODS BEFORE A PURCHASE IS MADE."

Auctioneer makes no representations, warranties, promises, covenants or guarantees, expressed or implied, as to defects in or the completeness or accuracy of the description in any advertising of any item(s) being auctioned and is not responsible for any advertising discrepancies, descriptions, nomenclature or inaccuracies of any kind. ALL ITEMS ARE SOLD ON AN "AS IS, WHERE IS" BASIS AND WITH ALL FAULTS WITHOUT EXCEPTION AND WITH REMOVAL AT BUYERS SOLE RISK AND EXPENSE. THE AUCTIONEER MAKES NO REPRESENTATIONS, WARRANTIES, PROMISES, COVENANTS OR GUARANTEES OF ANY KIND, EXPRESSED OR IMPLIED, AS TO THE NATURE, QUALITY, DURABILITY, CAPABILITY, FUNCTION, PERFORMANCE, VALUE OR CONDITION OF THE ITEM(S) BEING AUCTIONED OR ITS (THEIR) SUITABILITY FOR ANY USE. THE AUCTIONEER EXPRESSLY AND SPECIFICALLY DISCLAIM, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OD

The Undersigned hereby waives, releases, remises, acquits and forever discharges the Auctioneer, and their respective employees, agents, or any other person acting on behalf of the Auctioneer, of and from, and shall indemnify and hold the Auctioneer and their respective employees, agents, or other persons acting on behalf of the Auctioneer and against any claims, actions, causes of action, demands, rights, damages, costs, expenses or compensation whatsoever, direct or indirect, known or unknown, foreseen or unforeseen, which the undersigned now has or which may arise in the future on the account of or in any way growing out of or connected with any defects, latent or otherwise, or the physical condition of any item(s) purchased or any law or regulation applicable thereto. The undersigned specifically waives the provisions of California Civil Code section 1542, which provides: "A general release does not extend to claims which the creditor does not know or suspect to exist in his favor at the time of executing the release, which if known by him must have materially affected his settlement with the debtor."

The Auctioneer encourages the Undersigned to avail itself of the opportunity to make inspections prior to bidding and/or purchasing. The Undersigned hereby acknowledges that it has inspected or voluntarily waived said inspection of all of the items upon which it will be bidding and/or does purchase. Once the Auctioneer knocks down the item or declares it sold to the Bidder, there are no credits, returns, exchanges, refunds or rebidding unless at the Auctioneers sole discretion and such request for rebid is made directly to the Auctioneer and within no more than 5 minutes from the Bidder after the item has been sold. No claim will be considered for allowance or rescission of any sales based upon failure of the property to correspond with any standard expected.

In order to participate in the auction, all Bidders must provide Auctioneer a 25% deposit, in cash, cashier's check or company check accompanied by a bank letter of guarantee of unqualified payment to Auctioneer, or a wire transfer (with a wire transfer fee included) of your maximum expected spending. The final payment in full of Bidders invoice must be received by Auctioneer within the first banking day 24 hours after the auction or the Buyer will be in default of this Contract. The Auctioneer will charge all Bidders a taxable sur charge buyer's premium on its invoice. The Undersigned shall provide proof satisfactory to the Auctioneer of its entitlement to claim exemption from sales tax, which proof must be representative of the same industry as the item(s) that are purchased. In the absence of proof satisfactory to the Auctioneer, the Buyer shall pay all taxes. The Auctioneer will not be responsible for any Department of Motor Vehicle fees, tax, registration, licensing, penalties, smog certificate or fees. Certain vehicles as announced and/or noted in the auction catalogue or on Buyers invoice will be sold "AS IS," with a Bill of Sale only, Each titled item will be charged a \$75 title transfer fee. If available by Auctioneer, titles will be sent to Buyers approximately 7-10 business days after receipt of payment. There will be no refunds if Auctioneer is unable to produce a title. Sales tax on Motor Vehicles is the responsibility of the Buyer to be remitted to its appropriate states Department of Motor Vehicles. All vehicles are sold "AS IS, WHERE IS, WITH NO WARRANTIES EXPRESSED OR IMPLIED." It is the Buyer's responsibility to inspect the vehicle to verify accurate description, model, year, mileage, condition and any and all details pertaining to the vehicle. Auctioneer is not responsible for any inaccuracies of any kind. Credit cards are not accepted.

TERMS AND CONDITIONS CONTINUED...

Auction sales and items are subject to cancellation without prior notice.

The Auctioneer reserves the right to augment this auction with items from additional sellers. These items may be interspersed and not specially identified throughout the auction sale.

The Auctioneer shall regulate all matters relating to the conduct of the auction and the Auctioneer's decisions shall be final and binding on all bidders.

The Auctioneer reserves the right to group, regroup, reduce, add to or delete lots as well as accept or reject any or all bids at the Auctioneer's sole and absolute discretion.

The Auctioneer reserves the right to offer any or all of the items in bulk at any time during the auction at the Auctioneer's sole and absolute discretion.

The Auctioneer shall determine the bidding increments and the Auctioneer may bid on any item(s) to protect its financial interest or indebtedness at its sole and absolute discretion.

Immediately upon the Auctioneer announcing sold or knockdown and the Auctioneer has declared the Undersigned to be the Purchaser, all items comprising of the lot become the sole and absolute responsibility of the Undersigned and the Undersigned shall thereupon and thereafter assume all risk of loss (including, but not restricted to loss by way of theft or damage) and liability relating to such items. The Undersigned is advised to pre-arrange insurance coverage for its purchases as there will be no refunds for missing, lost, damaged or stolen items unless and only at the Auctioneer's sole discretion. The Auctioneer shall in no event be liable to the Purchaser for non-delivery of any item(s) for any reason except for the return to the Buyer of the deposit or other sums paid for such non-delivered items. This non-delivery period extends from the knock down until the time allotted for the removal process concludes. In no event will the Auctioneer's liability to the Undersigned exceed the amount actually paid by the Undersigned. THE UNDERSIGNED HEREBY ACKNOWLEDGES AND AGREES THAT THE AUCTIONEER SHALL NOT BE LIABLE FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL DAMAGES.

Title to and possession of the item(s) shall not pass to the Undersigned until the Auctioneer has received payment for all items duly purchased in full. All items and the entirety of the Purchaser's invoice require payment in full prior to Auctioneer releasing any items. If all the items are not paid in full by Purchaser for any reason, and Purchaser has provided Auctioneer any monetary consideration, Auctioneer will retain all the items and the monetary consideration paid by Purchaser to mitigate Auctioneer's financial damages caused by Purchaser. If after the subsequent mitigation amounts (if any) received by Auctioneer exceed the amount of the Purchaser's invoice and below, the auctioneer will refund such amounts to the Purchaser once determined by Auctioneer in its sole discretion. The Purchaser hereby agrees items purchased at this auction will be invoiced in totality, although in some cases separately priced on the invoice, the total amount due Auctioneer of the Purchaser's invoice is deemed a single contract if in the event of a legal dispute.

If for any reason the Undersigned fails to pay the full amount of its invoice within the first banking day 24 hours after the auction, and/or fails to remove all of its items on or before the date posted on Purchaser's invoice, and/or fails to comply with any other terms and conditions of this Contract, all the items on the Purchaser's invoice will be considered abandoned and the Auctioneer in its sole discretion and without further notice to Purchaser may remove, dispose of, scrap, resell at public or private sale any or all the items and the Undersigned hereby agrees to pay to Auctioneer any monetary mitigation deficiency and costs as a result thereof, including all removal, rent, lay and hold over fees. The bidder understands and acknowledges that there is sufficient consideration by both parties to perform, and that if payment in full is not made within the specific time outlined in the contract, the bidder is agreeing to be bound by a "consent judgment" and is in violation and in default of contract. By signing below you are consenting to the terms of a judgment entered against you and are waiving your rights to any court hearing. In addition, relating to such disposition together with all charges, including attorney, court and legal fees, interest and any and all other expenses in connection with such disposition, plus a \$500.00 per diem administrative fee per item until such item(s) is (are) removed.

The Undersigned agrees that the Auctioneer may retain all deposits previously received and apply such deposits to any such deficiency without further notice to Purchaser. Purchaser hereby agrees that "time is of the essence" in regards to this Contract regarding payment of its invoice and removal of its items. For purposes of clarity, Purchaser further acknowledges and agrees Auctioneer will be monetarily damaged for the subsequent disposal of any item(s) for any reason and that the Purchaser will be responsible to pay Auctioneer for all of the above and any other such monetary mitigation deficits, damages known and unknown, and any and all other cost to Auctioneer to collect and enforce this Contract. Any monetary deficiencies to the Auctioneer become the debt of the Undersigned.

This Agreement shall be construed and interpreted according to the laws of the State of California. The Bidder further agrees to have Burbank California as the Forum City & State in the event any lawsuit is initiated by either party. If any action based on the performance, breach or interpretation of this Agreement is brought, the prevailing party in such action (as determined by the court or other body having jurisdiction) shall be entitled to recover from the losing party all actual costs and expenses of litigation or arbitration, including attorney's fees, court costs, costs of investigation, and other costs related to such proceeding.

AUCTIONEER DOES NOT WARRANT THAT THE FUNCTIONS, FEATURES OR CONTENT CONTAINED IN THE ONLINE OR WEBCAST BIDDING PLATFORM OR SOFTWARE, INCLUDING ANY THIRD-PARTY SOFTWARE, PRODUCTS OR OTHER MATERIALS USED IN CONNECTION WITH THE WEBSITE OR BIDDING WILL BE TIMELY, SECURE, UNINTERRUPTED OR ERROR-FREE, OR THAT DEFECTS WILL BE CORRECTED. AUCTIONEER RESERVES THE RIGHT TO ACCEPT AND OR REJECT AND OR REMOVE ANY ELECTRONIC BIDS FOR ANY REASON AT ANY TIME IN ITS ABSOLUTE SOLE DISCRETION. BIDDER AGREES ALL OF ITS ELECTRONIC BIDS ARE BINDING REGARDLESS OF ORDER AND OR TIME IN WHICH THEY ARE ACCEPTED OR REJECTED.

OE

OF	<p>TERMS AND CONDITIONS FOR DISCONNECT AND REMOVAL: All electrical disconnect, liquid removal, rigging, loading, broom cleaning, trash & debris removal, floor stud removal and transportation are the sole and absolute responsibility of the Undersigned. The undersigned agrees to remove its purchases in full, with no abandonment privileges from the premises on or before the date on the Buyers invoice. No item(s), no matter how small, may be removed while the auction is in progress. Representatives of the Auctioneer at the Auctioneer's sole discretion may stay one hour after the auction is completed for the removal of small items. All small subject to disappear items must be removed by 4:00 PM on the day following the auction. The Undersigned must present the Auctioneers personnel with proof of valid workers compensation insurance and a commercial general liability insurance certificate in a minimum amount of \$2,000,000.00 combined single limit per occurrence coverage naming the Auctioneer, the Seller and the Landlord as additional insured. If available at Auctioneers sole and absolute discretion, bridge cranes and hoist may be used by the Undersigned if crane insurance is included on the above certificate and only with the written permission of the crane owner. Should any pits, floor bolts or hazards of any type exist after removal of equipment, it is the responsibility of the Undersigned, at its cost, to reasonably safe guard these areas using generally accepted safety practices, such as safety tapes, pipes or bars welded in place or suitable safety barriers acceptable to the Auctioneer. All floor bolts and/or anchoring fasteners are to be cut flush to the floor and the area left broom clean and all debris removed. It is the responsibility of the Undersigned to be sure that the power to the item(s) is off and then to safely disconnect all electrical wiring and utility piping from the item(s) and to cap at the first electrical or air junction of the item(s). Item(s) are to be staged for loading in the area assigned by the Auctioneer's personnel. It is the Undersigned's responsibility to secure all safety equipment to meet all applicable government safety standards in using or removing any items purchased. Certain items may contain residual chemicals and/or hazardous materials. The Undersigned hereby agrees to indemnify and hold harmless the Auctioneer from any and all damages, claims or liabilities from any injuries to persons or property of any type whatsoever caused by the Undersigned, its agents, employees or contractors during the sale or during the removal, use or operation of the purchased item(s). Any hydraulic fluid removal and/or oil leaks are the Undersigned's responsibility to remove and clean up. The Undersigned must take full responsibility for compliance with applicable environmental laws and exercise all reasonable care to ensure that there is no release to the environment of any hazardous wastes or substances as defined in applicable Federal, State and Local Statues, Regulations, Rules or Ordinances. No trucks are to be left running in an enclosed building. The Auctioneer is not liable for personal belongings left on premises. Any surface or structural damage to the premises including but not limited to the walls, ceilings, floors, overhead doors, gates and/or any other item(s), etc. will be the Undersigned's sole responsibility. The Undersigned will not be permitted to leave with its purchases until repairs are made. Theft will not be tolerated and Auctioneer reserves the right to inspect all trucks, toolboxes and rigger cases, etc. Instances of theft will result in immediate termination of removal privileges and full prosecution by law. All quantities must be checked prior to removal, as adjustments will not be made thereafter. These terms and conditions together with any amendments or modifications, expressly made by the Auctioneer at the time of the auction constitute all the terms and conditions with respect to the sale of items at this auction. There are no representations, warranties, terms, conditions, undertakings or collateral agreements except as hereinabove provided I acknowledge that I have provided BidItUp Auctions Worldwide, Inc. a signed check for which I am the authorized signatory for all purposes, without restriction, sufficient to pay this negotiable instrument upon demand. I authorized BidItUp to obtain my financial information from any source and complete the check as necessary for the amount of my invoice at the auction to be presented for payment. I agree to pay all cost of collections including attorney's fees, to pay interest at the rate of 18%, unless prohibited by law, and in such case at the highest amount permitted by law from the date of issuance of this check if dishonored by a financial institution, to waive any requirement of presentment, to the exclusive jurisdiction of the executed Auction Bidders Agreement for any dispute relating to this instrument. A credit instrument is identical to a personal check. Willfully drawing or passing a credit instrument knowing there are insufficient funds in an account upon which may be drawn, or with the intent to defraud, is a crime which may result in criminal prosecution.</p>	
OG	<p>IMPORTANT PAYMENT INFORMATION Thank you for your interest in our Auction Event! Please see the below information regarding payment. Invoices will be sent out 24 hours AFTER the close of the auction. PAYMENT Payment is due 48hrs after invoices have been released - \$250 fee may apply to late payments Invoices paid with card will incur a 3.5% additional processing fee Card Payments: ONLY USE IF PAYING WITH CREDIT CARD OR DEBIT CARD MAX LIMIT OF \$2,500 (additional 3.5% card processing fee) Wire Payments: if paying by wire Please note if you send us the incorrect payment amount and require a reimbursement, a \$100 fee will apply WE DO NOT ACCEPT ACH - if you send us an ACH, a \$100 fee will apply Methods of payment: Credit/ Debit Card (includes 3.5% convenience fee) Wire Transfer TAXES/ TAX EXCEPTIONS International bidders: NO EXCEPTIONS: You must pay the full amount due. Once we receive a "Bill of Lading" after shipment, we will refund your taxes via ACH/Wire. Please note it is the bidder's responsibility to provide bank information to process the ACH/Wire. Domestic Bidders: Please complete the tax form provided by our accounting team and return to auctions@biditup.com. Once received and approved, tax will be removed from your invoice. Please note, it is the bidder's responsibility to provide tax exemption information.</p>	
OH	<p>Removal will be by appointment ONLY. There will be a link in your invoice to create an appointment- please note all appointments must be made AFTER processing payment successfully. DO NOT SCHEDULE AN APPOINTMENT IF YOU HAVE NOT RECEIVED A PAID IN FULL INVOICE FROM ACCOUNTING.</p>	

1	Brady BradyPrinter i7100 Label Printer; Model#: i7100 Voltage: 100-240V Current: 2A Max. Frequency: 50-60Hz	
2	Brady BradyPrinter i7100 Label Printer; Model#: i7100 Voltage: 100-240V Current: 2A Max. Frequency: 50-60Hz	
3	Better Packages Better Pak 555e Label Printer; Model: BP555eS Power Supply: 115VAC, 60Hz, 4.0 A	
4	Better Packages Better Pak 555e Label Printer; Model: BP555eS Power Supply: 115VAC, 60Hz, 4.0 A	
5	Better Packages Better Pak 555e Label Printer; Model: BP555eS Power Supply: 115VAC, 60Hz, 4.0 A	
6	Cricut Explore High-Speed Smart Cutting Machine; Model#: CXPL203 Speed and Precision: Operates up to 2X faster than the Explore Air 2. Smart Materials Compatibility: Enables cutting, writing, and scoring without a mat for up to 12 ft (3.6 m). Versatility: Compatible with 6 different tools (sold separately) for cutting, scoring, and adding foil effects. Material Range: Cuts 100+ materials, including cardstock, vinyl, iron-on, glitter paper, and bonded fabric.	
7	HP LaserJet Pro MFP 4101fdne Monochrome Laser Printer; Model#: Z2618E Power Supply: 100-127V, AC, 50/60Hz, 6.4A	
8	MakerBot Replicator+ 3D Printer, w/ MakerBot True Blue Filament; Model#: PABH65 Power Supply: 100-240V, 0.76-0.43 A, 50/60Hz	
9	Lot of Assorted Brady Printer Labels / Permasleeves; To Include: - Assorted Sizes - Heat Shrink Permasleeves	
10	Fiogohumi Portable Air Conditioner A019BDJ; Model#: A019BDJ Cooling Power: 10,000 BTU, capable of cooling spaces in minutes. Functions: 3-in-1 (Cool, Fan, Dehumidifier). Efficiency: 6.5 - 7.0 CEER rating using R32 refrigerant, which is more eco-friendly. Control: LED display panel and remote control. Portability: 4 casters/wheels and handles for movement. Installation: Includes a window mount kit. Noise Level: Approximately 53dB.	
11	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
12	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
13	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
14	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
15	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
16	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
17	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
18	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
19	Hakko FA-430 ESD-Safe, 2-port Fume Extraction System; Part Number: FA430-16 Power Consumption: 120V AC, 110W - 120W Max Airflow: 4.1 m ³ /min (145 cfm) single duct / 4.7 m ³ /min (167 cfm) two ducts Static Pressure: 1500 Pa (0.44 in. Hg) Noise Level: 44 - 53 dB(A) @ 1m Filtration: 99.97% efficiency @ 0.3µm (with optional HEPA filters) Dimensions: 330 (W) x 366 (H) x 343 (D) mm (13.0 x 14.4 x 13.5 in.) Weight: 7.5 kg (16.5 lb.)	
20	Lot of Assorted Hakko Filters; To Include: Hakko A1001 Activated Carbon Filter, Hakko FA-430 Carbon Odor Filters, Hakko A1585 Pre-Filters	
21	Hakko FX951-66 Soldering Station; Model#: FX951-66 Power Supply: 120V-75W, 60Hz	

22	Hakko FX951-66 Soldering Station; Model#: FX951-66 Power Supply: 120V-75W, 60Hz	
23	Hakko FX951-66 Soldering Station; Model#: FX951-66 Power Supply: 120V-75W, 60Hz	
24	Hakko FR-410 Desoldering Station, w/ Accessories; Model#: FR-410 Power Supply: 120V, 190W, 60Hz	
25	JBC ESD-Safe Two-Tool Control Unit, w/ Stands; Model#: DDE-1C Power Supply: 110-130V, 50/60Hz, 190W To Include: (2) JBC Stands	
26	Lot of Assorted Soldering Accessories; To Include: Flux Glow Core, Polymide Kapton Dots, Soldering Tips, Etc.	
27	(4) Hakko FA-400 EDS-Safe Smoke Absorbers; Model#: FA-400 Power Supply: 120V, 19W, 60Hz	
28	Pantone Xrite RM200QC Spectrocolorimeter Kit; Model#: RM200 Power Supply: 5V @ 500 mA	
29	Mitutoyo Absolute Digimatic 24" Digital Caliper; Range: 0- 24" (600mm)	
30	(3) Mitutoyo Digital Calipers; To Include: - (1) 12" Digital Caliper - (2) 6" Digital Calipers	
31	IGaging 6" Digital Height Gauge, w/ Hard Case; 6-inch (150mm) range and an accuracy of ± 0.001 "	
32	RexBeti 0-25mm 0.001mm Digital Micrometer; Resolution: 0.001mm/0.00005" Repeatability: 0.001mm/0.00005" Battery: CR1632	
33	M0 Minus 50pcs Pin Gauge Set; Size: 0.011" - 0.060" Accuracy: +.0000", -.0002"	
34	FBA Steel Rectangular Gage Block Set; Sizes: .0500 - 4.000"	
35	AWS Torque Transducer, w/ ACT Finish First Test Panels; Model#: ITI-750 Capacity: 750lbs Range: 90% of FS	
36	Uline H-1117 Measurement Scale; Capacity: 65 lbs Div.: 0.005 lbs	
37	(4) Uline Stainless Steel Calibration Weights, w/ (2) Assorted Weights; To Include: - (1) 1 Lb Weight - (1) 2 lb Weight - (1) 5 lb Weight - (2) 10 lb Weights - (1) 50 lb Weight	
38	Trescal WT3-201M Wire Terminal Tester Mark-10; Model#: WT3-201M Capacity: 200 lbs Power Supply: 100-240VAC, 50 /60Hz, 200W Accuracy: $\pm 0.2\%$ of Full Scale	
39	AWS MTMDP-3 Torque Display; Model#: MTMDP-3S Accuracy: Bidirectional accuracy of $\pm 0.5\%$ of indicated reading within 10–100% of the calibrated range. Operating Modes: Includes Track, Peak, and 1st Peak modes. Power: NiMH rechargeable batteries providing 8–12 hours of continuous use with a 4-hour recharge time. Output: RS-232 serial output for data management. Engineering Units: 8 user-selectable units, including Oz.in., Lb.in., Lb.ft., Nm, cNm, KgCm, gfCm, and Kgfm	
40	AWS MTMDP-3 Torque Display; Model#: MTMDP-3S Accuracy: Bidirectional accuracy of $\pm 0.5\%$ of indicated reading within 10–100% of the calibrated range. Operating Modes: Includes Track, Peak, and 1st Peak modes. Power: NiMH rechargeable batteries providing 8–12 hours of continuous use with a 4-hour recharge time. Output: RS-232 serial output for data management. Engineering Units: 8 user-selectable units, including Oz.in., Lb.in., Lb.ft., Nm, cNm, KgCm, gfCm, and Kgfm	
41	VVV-Group Coating Thickness Gauge; Model#: CM-208Z Measuring Range: 0 to 120 mils (0 to 3000 μm). Resolution: Ultra-high resolution of 0.001 mils (0.1 micron) for measurements up to 10 mils. Accuracy: $\pm (1\%$ of reading + 2 $\mu\text{m})$. Probe Material: The sensor tip is made of technical ruby to enhance wear resistance and durability. Data Handling: Includes internal memory for up to 2,000 measurements and a USB interface for data transfer to PC software. Environmental Resistance: Engineered to operate in harsh conditions, including high dust, humidity, and temperature fluctuations (-10 to +50°C).	
42	RisePro Thermocouple Thermometers; Power Supply: 9V Measurement Range: -200°C to 1372°C (-328°F to 2501°F). High Accuracy: $\pm 1^\circ\text{C}$ ($\pm 1^\circ\text{F}$) for temperatures above -100°C, and $\pm 2^\circ\text{C}$ ($\pm 3.6^\circ\text{F}$) for lower ranges. Multi-Channel Display: Equipped with four K-type thermocouple inputs (T1–T4) to track multiple heat sources at once. User Functions: Includes a large backlit LCD screen, Max/Min/Average value hold, data hold, and an auto power-off feature after 10 minutes of inactivity. Power Source: Operates on a single 9V battery (NEDA 1604 or IEC 6F22), as indicated on the device's back panel.	
43	FLIR TG165-X MSX Thermal Camera; Model#: TG165-X Imaging & Optical: 80 × 60 IR resolution, <70 mK thermal sensitivity, 8.7 Hz image frequency, and 51° × 66° Field of View (FOV). Measurement: -25°C to 300°C (-13°F to 572°F) range, 24:1 distance-to-spot ratio. Accuracy: $\pm 1.5^\circ\text{C}$ ($\pm 3^\circ\text{F}$) for 50°C to 100°C; $\pm 2.5^\circ\text{C}$ ($\pm 5^\circ\text{F}$) for 0°C to 50°C/100°C to 300°C.	

44	Extech CFM/CMM Thermo-Anemometer, w/ Vane Probe; Model#: AN100 Simultaneous Display: The dual LCD shows air velocity or flow volume and temperature at once. Measurement Modes: It measures air velocity in five units (ft/min, m/s, km/h, mph, knots) and air volume in CFM or CMM. Advanced Averaging: Includes a 20-point average function for more accurate airflow volume readings. Internal Memory: Users can store up to eight area dimensions (ft ² or m ²) to simplify repeat calculations during power-ups. Vane Sensor: Features a low-friction 2.83" (72mm) ball-bearing vane wheel on a 3.9ft (120cm) cable for flexible positioning.	
45	Fluke 115 True RMS Multimeter; Model#: 117 Voltage AC/DC: Up to 600 V. Current AC/DC: 10 A (20 A overload for 30 seconds). Resistance: 0.1 to 40 M . Capacitance: 1 nF to 9,999 F. Frequency: 5 Hz to 50 kHz. Diode Test: 2.000 V. Additional Features: Min/Max/Avg, auto/manual ranging, continuity test. Safety Rating: CAT III 600 V.	
46	Fluke 117 True RMS Digital Multimeter; Model#: 117 Voltage AC/DC: 600 V Accuracy (DC Voltage): 0.5% + 2 Accuracy (AC Voltage): 1.0% + 3 (45 Hz to 500 Hz), 2.0% + 3 (500 Hz to 1 kHz) Current AC/DC: 10 A (20 A overload for 30 seconds max) Resistance: 0.1 to 40 M Frequency: 5 Hz to 100 kHz Capacitance: 1000 F LoZ: Low input impedance prevents false readings (~3 k)	
47	Fluke 117 True RMS Digital Multimeter; Model#: 117 Voltage AC/DC: 600 V Accuracy (DC Voltage): 0.5% + 2 Accuracy (AC Voltage): 1.0% + 3 (45 Hz to 500 Hz), 2.0% + 3 (500 Hz to 1 kHz) Current AC/DC: 10 A (20 A overload for 30 seconds max) Resistance: 0.1 to 40 M Frequency: 5 Hz to 100 kHz Capacitance: 1000 F LoZ: Low input impedance prevents false readings (~3 k)	
48	Fluke 87 V True RMS Digital Multimeter; Model#: 87 V True-rms Voltage (AC/DC): Up to 1000 V (0.1 mV resolution). True-rms Current (AC/DC): 10 A (20 A for up to 30 s, 0.01 µA resolution). DC Accuracy: . AC Accuracy: (True-rms). Frequency: 200 kHz (0.005 Hz resolution). Resistance: Up to 50 M . Capacitance: 0.01 nF to 9,999 µF. Temperature: -200.0 °C to 1090 °C (-328.0 °F to 1994.0 °F).	
49	Fluke 177 True RMS Multimeter; Model#: 177 Voltage DC/AC: 0.1 mV to 1000V Current DC/AC: 0.01 mA to 10A Resistance: 0.1 to 50 M Capacitance: 1 nF to 10,000 F Frequency: 2 Hz to 100 kHz Basic DC Accuracy: (0.09% + 2) Display: 6000-count digital, 4/sec update Safety Rating: CAT III 1000V / CAT IV 600V	
50	Fluke 177 True RMS Multimeter; Model#: 177 Voltage DC/AC: 0.1 mV to 1000V Current DC/AC: 0.01 mA to 10A Resistance: 0.1 to 50 M Capacitance: 1 nF to 10,000 F Frequency: 2 Hz to 100 kHz Basic DC Accuracy: (0.09% + 2) Display: 6000-count digital, 4/sec update Safety Rating: CAT III 1000V / CAT IV 600V	
51	Fluke 177 True RMS Multimeter; Model#: 177 Voltage DC/AC: 0.1 mV to 1000V Current DC/AC: 0.01 mA to 10A Resistance: 0.1 to 50 M Capacitance: 1 nF to 10,000 F Frequency: 2 Hz to 100 kHz Basic DC Accuracy: (0.09% + 2) Display: 6000-count digital, 4/sec update Safety Rating: CAT III 1000V / CAT IV 600V	
52	Pico Technology TA057 Differential Probe; Model#: TA057 Bandwidth: DC to 25 MHz (-3 dB). Attenuation Ratios: Switchable between 20:1 and 200:1. Voltage Limits: Differential Range: ±140 V at 20:1; ±1400 V at 200:1. Common Mode Range: ±1400 V (1000 V RMS). Safety Rating: CAT III. Input Impedance: 4 MΩ // 5.5 pF per side to ground. Accuracy: ±2%.	
53	Pico Technology TA057 Differential Probe; Model#: TA057 Bandwidth: DC to 25 MHz (-3 dB). Attenuation Ratios: Switchable between 20:1 and 200:1. Voltage Limits: Differential Range: ±140 V at 20:1; ±1400 V at 200:1. Common Mode Range: ±1400 V (1000 V RMS). Safety Rating: CAT III. Input Impedance: 4 MΩ // 5.5 pF per side to ground. Accuracy: ±2%.	
54	Pico Technology TA057 Differential Probe; Model#: TA057 Bandwidth: DC to 25 MHz (-3 dB). Attenuation Ratios: Switchable between 20:1 and 200:1. Voltage Limits: Differential Range: ±140 V at 20:1; ±1400 V at 200:1. Common Mode Range: ±1400 V (1000 V RMS). Safety Rating: CAT III. Input Impedance: 4 MΩ // 5.5 pF per side to ground. Accuracy: ±2%.	
55	Pico Technology TA057 Differential Probe; Model#: TA057 Bandwidth: DC to 25 MHz (-3 dB). Attenuation Ratios: Switchable between 20:1 and 200:1. Voltage Limits: Differential Range: ±140 V at 20:1; ±1400 V at 200:1. Common Mode Range: ±1400 V (1000 V RMS). Safety Rating: CAT III. Input Impedance: 4 MΩ // 5.5 pF per side to ground. Accuracy: ±2%.	
56	Pico Technology TA057 Differential Probe; Model#: TA057 Bandwidth: DC to 25 MHz (-3 dB). Attenuation Ratios: Switchable between 20:1 and 200:1. Voltage Limits: Differential Range: ±140 V at 20:1; ±1400 V at 200:1. Common Mode Range: ±1400 V (1000 V RMS). Safety Rating: CAT III. Input Impedance: 4 MΩ // 5.5 pF per side to ground. Accuracy: ±2%.	
57	Pico Technology TA057 Differential Probe; Model#: TA057 Bandwidth: DC to 25 MHz (-3 dB). Attenuation Ratios: Switchable between 20:1 and 200:1. Voltage Limits: Differential Range: ±140 V at 20:1; ±1400 V at 200:1. Common Mode Range: ±1400 V (1000 V RMS). Safety Rating: CAT III. Input Impedance: 4 MΩ // 5.5 pF per side to ground. Accuracy: ±2%.	
58	Fluke Networks Set; To Include: - (1) Fluke Networks MicroScanner - (1) Fluke Networks Intellitone Pro 200 Probe -(1) Fluke Networks JackRapid Jack Termination Tool - Accessories	
59	Lot of Assorted Probes/Charging Cables; To Include: Pomona Electrical Wires, Triad Charging Adapters, Clips, Etc.	
60	Datalogic D2590 QuickScan Barcode Scanner, w/ Stand & USB Cable; Model#: D2590 Scanning Capability: 1D, 2D (including QR, Data Matrix, PDF417), Postal, and Digimarc codes. Sensor Resolution: 1 Megapixel (1280 x 800 pixels). Motion Tolerance: Up to 30 inches per second (IPS). Durability: IP52 rating for dust and water resistance; withstands drops from up to 5 feet (1.5 m). Aiming System: Features a precision blue triangle aiming system and Datalogic's patented "Green Spot" technology for successful read confirmation. Connectivity: Multi-interface support for USB (including Type-C), RS-232, and Keyboard Wedge.	
61	Datalogic D2590 QuickScan Barcode Scanner, w/ Stand & USB Cable; Model#: D2590 Scanning Capability: 1D, 2D (including QR, Data Matrix, PDF417), Postal, and Digimarc codes. Sensor Resolution: 1 Megapixel (1280 x 800 pixels). Motion Tolerance: Up to 30 inches per second (IPS). Durability: IP52 rating for dust and water resistance; withstands drops from up to 5 feet (1.5 m). Aiming System: Features a precision blue triangle aiming system and Datalogic's patented "Green Spot" technology for successful read confirmation. Connectivity: Multi-interface support for USB (including Type-C), RS-232, and Keyboard Wedge.	
62	Datalogic D2590 QuickScan Barcode Scanner, w/ Stand & USB Cable; Model#: D2590	

63	(5) MeanWell HLG-150H-24AB High-Efficiency 151.2W AC/DC LED Drivers; Model: HLG-150H-24AB (AB-Type) Output: 24V DC, 3.8A ~ 6.3A (adjustable) Power: 151.2 Watts Input Voltage: 90 ~ 305VAC (supports 277VAC) Efficiency: Up to 94% Dimming: 3-in-1 dimming (1~10VDC, PWM signal, or resistance) Protection: IP65 rated, metal housing for, short circuit/over current/over voltage/over temperature protection Safety: UL8750, Type HL, Class I Division 2 (hazardous locations) Operating Temp: -40 ~ +90°C	
64	(2) Cosel PJA600F-24 AC Power Supplies; Model#: PJA600F-24 Power Supply: AC100-240V, 50/60Hz, 7.5A	
65	MeanWell SE-1000-24 AC/DC Power Supply; Model#: SE-1000-24 Power Supply: 100-120VAC, 17.5 A	
66	MeanWell HEP-1000-24 Power Supply; Model#: HEP-1000-24 Power Supply: 100-120VAC, 7.3 A, 50/60Hz	
67	BK Precision 1687B DC Switching Mode Power Supply; Model#: 1687B Power Supply: 100-240V, 50/60Hz, max 4.6 A	
68	BK Precision 1687B DC Switching Mode Power Supply; Model#: 1687B Power Supply: 100-240V, 50/60Hz, max 4.6 A	
69	Hioki 3333 Power HiTester; Model#: 3333 Power Supply: 100-240V, 50/60Hz, 20VA	
70	ZIMMER Precision Analyzer LMG641; Model #: LMG641 Power Supply: 100-240V, 47-63Hz, max. 200W	
71	ZIMMER Precision Power Analyzer; Model #: LMG641 Power Supply: 100-240V, 47-63Hz, max. 200W	
72	(3) ZIMMER Precision Current Transducers PCT 200; Model#: PCT200 Ratio: 1:500	
73	GWINSTEK GPT-9802 AC/DC Withstanding Voltage Tester; Model#: GPT-9802 Power Supply: Max. 500VA	
74	GWINSTEK GPT-9804 AC/DC Withstanding Voltage/Insulation Resistance/ Ground Bond Tester; Model#: GPT-9804 Power Supply: Max. 500VA	
75	GWINSTEK GPT-9802 AC/DC Withstanding Voltage Tester; Model#: GPT-9802 Power Supply: Max. 500VA	
76	GWINSTEK GPT-9802 AC/DC Withstanding Voltage Tester; Model#: GPT-9802 Power Supply: Max. 500VA	
77	GWINSTEK GPT-9802 AC/DC Withstanding Voltage Tester; Model#: GPT-9802 Power Supply: Max. 500VA	
78	GWINSTEK GPT-9802 AC/DC Withstanding Voltage Tester; Model#: GPT-9802 Power Supply: Max. 500VA	
79	GWINSTEK GPT-9802 AC/DC Withstanding Voltage Tester; Model#: GPT-9802 Power Supply: Max. 500VA	
80	GWINSTEK GDS-1102B Digital Storage Visual Persistence Oscilloscope; Model#: GDS-1102B Power Supply: AC 100-240V Frequency: 50-60Hz Power Max: 30W	
81	GWINSTEK GDS-1102B Digital Storage Visual Persistence Oscilloscope; Model#: GDS-1102B Power Supply: AC 100-240V Frequency: 50-60Hz Power Max: 30W	
82	GWINSTEK GDS-1102B Digital Storage Visual Persistence Oscilloscope; Model#: GDS-1102B Power Supply: AC 100-240V Frequency: 50-60Hz Power Max: 30W	
83	GWINSTEK GDS-1104B Digital Storage Visual Persistence Oscilloscope; Model#: GDS-1104B Power Supply: AC 100-240V, 50 /60Hz, 30W	
84	GWINSTEK GDS-1104B Digital Storage Visual Persistence Oscilloscope; Model#: GDS-1104B Power Supply: AC 100-240V, 50 /60Hz, 30W	
85	GWINSTEK GSB-01 Multiplex Scanner Box; Model#: GSB-01 Power Supply: AC 100-240V, 50/60Hz, 50VA Max.	
86	GWINSTEK GSB-02 Multiplex Scanner Box; Model#: GSB-02 Power Supply: AC 100-240V, 50/60Hz, 50VA	
87	Digi XBEE MultiProgrammer; Model#: Digi XBEE Simultaneous Programming: Configures up to six modules at once; multiple programmers can be connected to a single PC to further increase throughput. Interchangeable Header Boards: Supports all Digi XBee form factors—Through-Hole (TH), Surface-Mount (SMT), and Micro-mount (MMT)—via swappable header boards. Automated Operation: Designed for "unattended programming," allowing operators to focus on swapping modules while the software handles the update process. Visual Status Indicators: Each socket features dedicated LEDs to indicate module detection, programming progress, and success or failure alerts. Data Tracking: Operators can export session logs or save them to a database for quality control and traceability.	

88	Digi XBEE MultiProgrammer; Model#: Digi XBEE Simultaneous Programming: Configures up to six modules at once; multiple programmers can be connected to a single PC to further increase throughput. Interchangeable Header Boards: Supports all Digi XBee form factors—Through-Hole (TH), Surface-Mount (SMT), and Micro-mount (MMT)—via swappable header boards. Automated Operation: Designed for "unattended programming," allowing operators to focus on swapping modules while the software handles the update process. Visual Status Indicators: Each socket features dedicated LEDs to indicate module detection, programming progress, and success or failure alerts. Data Tracking: Operators can export session logs or save them to a database for quality control and traceability.	
89	Digi XBEE MultiProgrammer; Model#: Digi XBEE Simultaneous Programming: Configures up to six modules at once; multiple programmers can be connected to a single PC to further increase throughput. Interchangeable Header Boards: Supports all Digi XBee form factors—Through-Hole (TH), Surface-Mount (SMT), and Micro-mount (MMT)—via swappable header boards. Automated Operation: Designed for "unattended programming," allowing operators to focus on swapping modules while the software handles the update process. Visual Status Indicators: Each socket features dedicated LEDs to indicate module detection, programming progress, and success or failure alerts. Data Tracking: Operators can export session logs or save them to a database for quality control and traceability.	
90	Digi Development Board, w/ Module; Manufacturer: Digi International. Key Interfaces: Micro SD Card slot. Audio Ports: Includes "LINE IN" and "MIC" (Microphone) jacks. Communication: An "XBEE ANTENNA" port for wireless connectivity modules. I2S Configuration: Headers for digital audio communication (DOUT, MCLK, DIN, SCLK).	
91	Keysight Scienlab SL1040A Charging Discovery System; Model#: SL1040A Power Supply: 24V DC Current: 3A	
92	Keysight Scienlab SL1040A Charging Discovery System; Model#: SL1040A Power Supply: 24V DC Current: 3A	
93	Delta Regis CESLT955 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
94	Delta Regis CESL829 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
95	Delta Regis CESLT835M Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
96	Delta Regis CESLT845M Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
97	Delta Regis CESLT835M Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
98	Delta Regis CESL828 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
99	Delta Regis CESL829 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
100	Delta Regis CESLT955 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
101	Delta Regis CESLT835M Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
102	Delta Regis CESLT945 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
103	Delta Regis CESLT955 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
104	Delta Regis CESLT955 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
105	Delta Regis CESL829 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
106	Delta Regis CESLT835M Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT940HL Power Supply/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	

124	Delta Regis CESL823 Drop Down Electric Torque Screwdriver, w/ Delta Regis BECT620C Adapter Cable/ DR90-10103 Balancer; Torque Range: 6.0 - 12.0 Nm (53 - 106 in-lbs) Voltage: 40V DC Free Speed: 880 / 660 RPM (variable) Drive Size: 1 /4" Hex Motor Type: Brushless Length: 306 mm (12 in)	
125	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
126	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
127	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
128	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
129	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
130	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
131	Sumake ED219P1 Corded Push-To-Start Electric Screwdriver; Model#: ED921P1 Torque Range: 2.6 - 16.7 in-lbs (3.0 - 19.0 kgf-cm / 0.29 - 1.89 N.m). Speed: 1,000 RPM (fixed). Drive Size: 1/4" Hex. Start Type: Push-to-Start. Clutch Type: Full Auto Shut-Off. Voltage: 115VAC (230V options available). Weight: 1.21 lbs (550g). Length: 9.65 inches (245mm). Grip Diameter: 1.42 inches (36mm). Capacity: Machine Screws 2.6-3.5mm, Tapping Screws 2.6-3.0mm.	
132	Delta Regis ESL301 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
133	Delta Regis ESL301 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
134	Delta Regis ESL302 Inline Lever-Start Electric Screwdriver; Torque Range: 1.47 - 4.41 Nm (13 - 39 in-lbs). Speed: 500 RPM (Free Speed). Start Type: Lever Start. Voltage: 120 VAC (Direct Plug-in, no external transformer needed). Clutch Type: Auto Shut-off (provides high repeatability). Drive Size: 1/4" Hex. Weight: 0.7 kg / 1.6 - 1.7 lbs. Length: 269 mm / 10.6 inches. Diameter: 41 mm / 1.6 inches. Series: ESL3.	
135	Atlas Copco EBL55 Inline Brushless Electric Screwdriver; Torque Range: 0.2Nm - 1.2Nm(1.8 - 10.6 in-lb) Speed: 910 RPM (free speed) Motor Type: Brushless d.c. (15W) Screw Capacity: M2-M3 Weight: 1.1 lbs Length: 215mm (approx.) Bit Drive: 1 /4" Hex Shut-off System: Mechanical Clutch Noise Level: < 70dBa Features and Functionality Versatile Operation: The tool can be configured for either push or lever start.	
136	Atlas Copco EBL55 Inline Brushless Electric Screwdriver; Torque Range: 0.2Nm - 1.2Nm(1.8 - 10.6 in-lb) Speed: 910 RPM (free speed) Motor Type: Brushless d.c. (15W) Screw Capacity: M2-M3 Weight: 1.1 lbs Length: 215mm (approx.) Bit Drive: 1 /4" Hex Shut-off System: Mechanical Clutch Noise Level: < 70dBa Features and Functionality Versatile Operation: The tool can be configured for either push or lever start.	
137	Atlas Copco EBL55 Inline Brushless Electric Screwdriver; Torque Range: 0.2Nm - 1.2Nm(1.8 - 10.6 in-lb) Speed: 910 RPM (free speed) Motor Type: Brushless d.c. (15W) Screw Capacity: M2-M3 Weight: 1.1 lbs Length: 215mm (approx.) Bit Drive: 1 /4" Hex Shut-off System: Mechanical Clutch Noise Level: < 70dBa Features and Functionality Versatile Operation: The tool can be configured for either push or lever start.	
138	Atlas Copco EBL55 Inline Brushless Electric Screwdriver; Torque Range: 0.2Nm - 1.2Nm(1.8 - 10.6 in-lb) Speed: 910 RPM (free speed) Motor Type: Brushless d.c. (15W) Screw Capacity: M2-M3 Weight: 1.1 lbs Length: 215mm (approx.) Bit Drive: 1 /4" Hex Shut-off System: Mechanical Clutch Noise Level: < 70dBa Features and Functionality Versatile Operation: The tool can be configured for either push or lever start.	
139	Atlas Copco EBL12 Inline Brushless Electric Screwdriver; Torque Range: 0.2Nm - 1.2Nm(1.8 - 10.6 in-lb) Speed: 910 RPM (free speed) Motor Type: Brushless d.c. (15W) Screw Capacity: M2-M3 Weight: 1.1 lbs Length: 215mm (approx.) Bit Drive: 1 /4" Hex Shut-off System: Mechanical Clutch Noise Level: < 70dBa Features and Functionality Versatile Operation: The tool can be configured for either push or lever start.	
140	Atlas Copco EBL12 Inline Brushless Electric Screwdriver; Torque Range: 0.2Nm - 1.2Nm(1.8 - 10.6 in-lb) Speed: 910 RPM (free speed) Motor Type: Brushless d.c. (15W) Screw Capacity: M2-M3 Weight: 1.1 lbs Length: 215mm (approx.) Bit Drive: 1 /4" Hex Shut-off System: Mechanical Clutch Noise Level: < 70dBa Features and Functionality Versatile Operation: The tool can be configured for either push or lever start.	

141	Atlas Copco EBL Drive Controller; Input Voltage: 100-240 V a.c. (47-63 Hz) Output Voltage: Max 30 V d.c. Power Consumption: 65 W Dimensions: 88 x 210 x 52 mm Weight: Approx. 0.7 kg (1.54 lb) Compatibility: EBL series screwdrivers (e.g., EBL12, EBL25)	
142	Atlas Copco EBL Drive Controller; Input Voltage: 100-240 V a.c. (47-63 Hz) Output Voltage: Max 30 V d.c. Power Consumption: 65 W Dimensions: 88 x 210 x 52 mm Weight: Approx. 0.7 kg (1.54 lb) Compatibility: EBL series screwdrivers (e.g., EBL12, EBL25)	
143	Atlas Copco EBL Drive Controller; Input Voltage: 100-240 V a.c. (47-63 Hz) Output Voltage: Max 30 V d.c. Power Consumption: 65 W Dimensions: 88 x 210 x 52 mm Weight: Approx. 0.7 kg (1.54 lb) Compatibility: EBL series screwdrivers (e.g., EBL12, EBL25)	
144	Atlas Copco EBL Drive Controller; Input Voltage: 100-240 V a.c. (47-63 Hz) Output Voltage: Max 30 V d.c. Power Consumption: 65 W Dimensions: 88 x 210 x 52 mm Weight: Approx. 0.7 kg (1.54 lb) Compatibility: EBL series screwdrivers (e.g., EBL12, EBL25)	
145	Atlas Copco EBL Drive Controller; Input Voltage: 100-240 V a.c. (47-63 Hz) Output Voltage: Max 30 V d.c. Power Consumption: 65 W Dimensions: 88 x 210 x 52 mm Weight: Approx. 0.7 kg (1.54 lb) Compatibility: EBL series screwdrivers (e.g., EBL12, EBL25)	
146	Atlas Copco EBL Drive Controller; Input Voltage: 100-240 V a.c. (47-63 Hz) Output Voltage: Max 30 V d.c. Power Consumption: 65 W Dimensions: 88 x 210 x 52 mm Weight: Approx. 0.7 kg (1.54 lb) Compatibility: EBL series screwdrivers (e.g., EBL12, EBL25)	
147	(8) Delta Regis DR90-10103 Balancers; Model#: DR90-10103 Capacity: 1.5–3.0 lbs (0.68–1.36 kg). Travel Distance: 6 feet (1.8 meters). Cable Material: Durable steel cable. Adjustment: Features an adjustable retract force to accommodate specific tool weights within its range. Primary Use: Designed for mounting directly above assembly areas to prolong power tool service life and maintain a clear workspace.	
148	Keyence GL-R24L-R Body-Protection Type Safety Light Curtain Receiver; Model: GL-R24L-R (Receiver) Protection Height: 920 mm (39.57" total length) Number of Axes: 24 Detection Capability: Operating Distance: 0.2 to 15 m Response Time (OFF to ON): 7 ms Operating Voltage: 24 VDC Environmental Rating: IP65/IP67 Operating Temperature: -10 to +55°C (no freezing) Beam Axis Spacing: 40 mm	
149	Keyence GL-R24L-T Body-Protection Type Safety Light Curtain Transmitter; Model: GL-R24L-T (Transmitter) Protection Height: 1005 mm (39.57") Number of Axes: 24 Beam Pitch: 40 mm Detection Range: 0.2 to 15 m (approx. 0.66 to 49.21') Effective Aperture Angle: Max. (at 3m or more) Response Time: 7 ms Environmental Rating: IP65/IP67 Operating Temperature: -10 to +55°C Synchronisation: Optical or Wire (configured by wiring) Dimensions: 38 mm x 40 mm (width x depth), and 1005 mm high Cable: 5-wire system for simplified wiring	
150	Keyence GL-R24L-T Body-Protection Type Safety Light Curtain Transmitter; Model: GL-R24L-T (Transmitter) Protection Height: 1005 mm (39.57") Number of Axes: 24 Beam Pitch: 40 mm Detection Range: 0.2 to 15 m (approx. 0.66 to 49.21') Effective Aperture Angle: Max. (at 3m or more) Response Time: 7 ms Environmental Rating: IP65/IP67 Operating Temperature: -10 to +55°C Synchronisation: Optical or Wire (configured by wiring) Dimensions: 38 mm x 40 mm (width x depth), and 1005 mm high Cable: 5-wire system for simplified wiring	
151	Keyence GL-R24L-R Body-Protection Type Safety Light Curtain Receiver; Model: GL-R24L-R (Receiver) Protection Height: 920 mm (39.57" total length) Number of Axes: 24 Detection Capability: Operating Distance: 0.2 to 15 m Response Time (OFF to ON): 7 ms Operating Voltage: 24 VDC Environmental Rating: IP65/IP67 Operating Temperature: -10 to +55°C (no freezing) Beam Axis Spacing: 40 mm	
152	Lot of Assorted Wires / Connector Cables; To Include: Gwinstek Tester Cables, FreelinWade Blue Nyl 5/16 x 2.32 x 100' Tubing, Etc.	
153	Lot of Assorted Lighting / Desk Attachments; To Include: Hitti Magnifyiny Desk Lamps, Lamicall Desk Stands, Gloss day UV Flashlights, Etc.	
154	Lot of Assorted Brackets, Cord Protectors, Transfer Tape; To Include: - Tripp-Lite Universal Thin Client Mounts, - Tape Man Blue 12" x 300' Tranfer Tape w/ Tack Layflat Adhesive - TwistandSeal Cord Protectors	
155	Lot of Assorted Plastic Containers / Uline Molded Fiberglass Trays, Cardboard Boxes; To Include - Assorted Plastic Containers (22" x 17" x 6") / (16" x 11" x 6") / (7" x 4" x 3") - Assorted Molded Fiberglass Trays (25" x 17") - Uline Assorted 12" x 6" x 4" Conductive Bins	
156	Lot of Assorted Uline Rubber Table Mats, Plastic Tubing / Hose; To Include: - Uline 2' x 3' Rubber Table Mats - Foam Mats - Plastic Tubing	
157	Lot of Assorted Electrical Wire / Aluminum Wire / Copper Wire Spools, Etc.; To Include: - Special Cables 300' Besilen Insulated Conductor Copper Wire - Monoprice Cat6A Ethernet Bulk Cable - Celentec CAT6 UTP Conductor Wire - Electrical Wire Spools	
158	Lot of Assorted Mechanical Hardware / Connectors, Wires / Cables, Etc.; To Include: - Eaton Arrow Harts - IDEC Control Units - Hammond Ground Wire Kits - DigiKey Connectors - Hubbell Wiring Devices - Carraige Bolts	
159	Lot of Assorted Mechanical Hardware / Connectors, Wires / Cables, Etc.; To Include: - Assorted Relays - Parker Connectors - Assorted Electrical Cables / Wires - Panduit Cable Ties - Core Pulse Wires - Eaton Fuses - White Rodgers DC Power Contactors	
160	Granite Surface Plate; Dimensions: 36" x 24" x 4"	
161	Hammond Manufacturing Mega A1.T3 Custom Control Cabinet; To Include: - (1) MeanWell HEP-1000-24 Power Supply - Assorted AB Relays - (3) Fuji Electric SC-E4/G 3-Pole, 80A IEC Magnetic Contactors - (5) WEG Terminals - (6) Fuji Electric SC-E6 Magnetic Contactors Part#: EN4SD483610LG	

162	Weigmann Mega A1.T3 Custom Control Cabinet; To Include: - (1) MeanWell HEP-1000-24 Power Supply - Assorted AB Relays - (3) Fuji Electric SC-E4/G 3-Pole, 80A IEC Magnetic Contactors - (5) WEG Terminals - (6) Fuji Electric SC-E6 Magnetic Contactors Part#: N412483610CLG	
163	Weigmann Mega A1.T3 Custom Control Cabinet; To Include: - Assorted AB Relays - (4) Fuji Electric SC-E4/G 3-Pole, 80A IEC Magnetic Contactors - (4) WEG Terminals - (6) Fuji Electric SC-E6 Magnetic Contactors Part#: N412483610CLG	
164	Hammond Manufacturing Mega A1.T3 Custom Control Cabinet; To Include: - (1) MeanWell HEP-1000-24 Power Supply - Assorted AB Relays - (3) Fuji Electric SC-E4/G 3-Pole, 80A IEC Magnetic Contactors - (5) WEG Terminals - (6) Fuji Electric SC-E6 Magnetic Contactors Part#: EN4SD483610LG	
165	Custom Stelpro SCH48T Fan System - (5) Units; Model#: SCH48T Power Supply: 240/208V, 20/17.30 A, 1 Phase, 60Hz, 4800 /3600W Dimensions: 32" x 10" x 23"	
166	Custom Stelpro SCH48T Fan System - (5) Units; Model#: SCH48T Power Supply: 240/208V, 20/17.30 A, 1 Phase, 60Hz, 4800 /3600W Dimensions: 32" x 10" x 23"	
167	Custom Stelpro SCH48T Fan System - (5) Units; Model#: SCH48T Power Supply: 240/208V, 20/17.30 A, 1 Phase, 60Hz, 4800 /3600W Dimensions: 32" x 10" x 23"	
168	Custom Stelpro SCH48T Fan System - (5) Units; Model#: SCH48T Power Supply: 240/208V, 20/17.30 A, 1 Phase, 60Hz, 4800 /3600W Dimensions: 32" x 10" x 23"	
169	Lot of (4) Control Power Supply Boxes, w/ Cables; To Include: (4) Control Power Supply Boxes, w/ Cables	
170	Lot of (4) Custom Functional Tester Control Boxes; To Include: (4) Custom Functional Tester Control Boxes	
171	Lot of (4) Custom EQBF0001 Control Boxes; To Include: (4) Custom EQBF0001 Control Boxes	
172	GWINSTEK GSB-01 Multiplex Scanner Box; Model#: GSB-01 Power Supply: AC 100-240V, 50/60Hz, 50VA Max.	
173	GWINSTEK GSB-02 Multiplex Scanner Box; Model#: GSB-02 Power Supply: AC 100-240V, 50/60Hz, 50VA Max.	
174	GWINSTEK GPT-9804 AC/DC Withstanding Voltage/Insulation Resistance/ Ground Bond Tester; Model#: GPT-9804 Power Supply: Max. 500VA	
175	ZIMMER Precision Analyzer LMG641; Model #: LMG641 Power Supply: 100-240V, 47-63Hz, max. 200W	
176	Keysight Scienlab SL1040A Charging Discovery System; Model#: SL1040A Power Supply: 24V DC Current: 3A	
177	Keysight Scienlab SL1040A Charging Discovery System; Model#: SL1040A Power Supply: 24V DC Current: 3A	
178	Tripp-Lite Smart UPS: Single Phase, 1.5 kVA Power Rating, 120 V AC Input, 110 V_115 V_120 V Output; Model#: EUPS0401 Power Supply: Single Phase, 1.5 kVA Power Rating: 120 V AC	
179	Phase 3 Connectors Powersafe Sequential Mating Power Distribution Box; Maximum Rated Voltage to Earth: 2KVac Current Rating: Up to 800A Rear Terminals: M12 x 25 threaded studs Micro Switch rating: 250VAC / 3A Manufactured to ISO 9001: 2015	
180	Phase 3 Connectors Powersafe Sequential Mating Power Distribution Box; Maximum Rated Voltage to Earth: 2KVac Current Rating: Up to 800A Rear Terminals: M12 x 25 threaded studs Micro Switch rating: 250VAC / 3A Manufactured to ISO 9001: 2015	
181	Battery Hub Control Box; To Include: - Connector Cables/Wires - Attached Tooling **Not Including Tagged Items**	
182	Custom Swap Stripped Testing Terminal, w/ EV Charging Cables;	
183	Averna FLO Ultra EOL AC Distribution Cabinet; Project Name: FLO Roadrunner Project#: O-32890 Part#: 031375-X0000-A Power Supply: 480V, 3 Phase, 150A, 60Hz To Include: (1) FLO Ultra EOL Tester HMI	
184	Averna FLO Ultra EOL DC Distribution Cabinet; Project Name: FLO Roadrunner Project#: O-32890 Part#: 031375-X0000-A Power Supply: 480V, 3 Phase, 150A, 60Hz To Include: (1) FLO Ultra EOL Tester HMI	
185	Assorted AC/DC Cabinet / Wire Cage Spare Parts / Twist-Lock Parts; To Include: - AC Main Breaker Spare Parts - AC Main Contactor Spare Parts - AC/DC Cabinet Spare Parts - Wire Cage Spare Parts	
186	Keysight Scienlab SL1830A Regenerative DC Emulator, w/ Rittal Air/Water Heat Exchanger; Model#: SL1830A Power Supply: 1000V, 600A, 180kW	
187	Keysight Scienlab SL1830A Regenerative DC Emulator, w/ Rittal Air/Water Heat Exchanger; Model#: SL1830A Power Supply: 1000V, 600A, 180kW	
188	Keysight Scienlab SL1830A Regenerative DC Emulator, w/ Rittal Air/Water Heat Exchanger; Model#: SL1830A Power Supply: 1000V, 600A, 180kW	

189	Keysight Scienlab SL1830A Regenerative DC Emulator, w/ Rittal Air/Water Heat Exchanger; Model#: SL1830A Power Supply: 1000V, 600A, 180kW	
190	Lauda UC-24 Ultra Cool Chiller; Model#: L003309 Part Numbers: Working Temperature Range: -10 to 35 °C Cooling Output (at 20°C): 30.9 kW (50 Hz) Cooling Output (at 10°C): 24.3 kW Temperature Stability: ±0.5 K Ambient Temperature Range: -15 to 50 °C Filling Volume (Water Tank): 35 L Pump Type: Industrial block pump Max Pump Pressure: 4.7 bar (50 Hz) / 6.8 bar (60 Hz) Max Pump Flow Rate: 166 L/min (50 Hz) / 200 L/min (60 Hz) Dimensions (WxDxH): 720 x 910 x 1250 mm Net Weight: ~180-184 kg Noise Level: 64.7 dB(A) In/Outlet Connection: Power Supply: 400 V 60Hz	
191	Averna FLO Canopy Test Bench Station, w/ BlueLine Lift Smart Cable Hoist; Part#: 031576-M1000-A Project#: O-33987 Operating Voltage: 110VAC/15A/60Hz	
192	KoneCranes 1/2 Ton Crane; Capacity: 1/2 Ton	
193	Kone Cranes 1/2 Ton Electric Chain Hoist; Capacity: 1/2 Ton	
194	Kone Cranes 1/2 Ton Electric Chain Hoist; Capacity: 1/2 Ton	
195	BlueLine Series 2000 Canopy Test Electric Hoist; Model#: PA400B Capacity: 880/440 lbs	
195A	BlueLine Series 2000 Canopy Test Electric Hoist; Model#: PA400B Capacity: 880/440 lbs	
196	Lot of Assorted Hoist Parts / Straps / Chains / Slings; To Include: - Assorted Liftex Slings - Uline Straps - Assorted Straps - Assorted Chains - Edge Banding Veneer Trim	
197	Lot of Assorted Industrial Safety Floor Mats; To Include: - Assorted Sizes (72" x 36" / 60" x 36" / 48" x 36")	
198	(9) Uline Retractable Belt Stanchions, w/ (5) Uline Safety Helmets; 40-inch tall, 18-gauge steel posts with 11-foot, yellow /black, "Caution" or safety stripes	
199	Lot of (2) Uline 50 Gal Mobile Spill Kits / (4) Justrite 10 Gal. Oil Waste Cans / Arc Protection Gear; To Include: - (2) Uline 50 Gal Mobile Spill Kits - (4) Justrite 10 Gal. Oil Waste Cans - Arc PPE Gear (Gloves, Etc.)	
200	Lot of Assorted Cleaning Supplies / Industrial Wipes / Safety Signs; To Include: - (7) Boxes of Ormadus Industrial Wipes - Cleaning Supplies / Wipes (Windex, Lysol, Goo Gone) - Vigon EFM Flux Residue Cleaner - (2) Safety Posts - Assorted Safety Signs	
201	Lot of Assorted Safety Equipment; To Include: - Uline S-2421GPW Inpsection Tags - Westward Durable Foam Kneepads - BucketBoss Duckwear Superwaist Aprons - Condor Lifting Belts	
202	Lot of Assorted PPE / Safety Equipment; To Include: - Assorted Uline Nitrile Coated Gloves - HDX Corded Earplugs - Uline Disposable Face Masks - XAdvance Nitrile Gloves - Uline H-5053 Safety Glasses - Lens Cleaning Wipes	
203	Carpenter Mfg. Co. Model 59 Floor-Standing Wire Prefeed / DeReeler; Electrical: 115 VAC, 60 Hz, 2.0 Amps (as shown on the label). Maximum Feed Speed: 550 feet per minute. Capacity: Maximum Spool Weight: 110 pounds. Maximum Spool Diameter: 28 inches (711.2 mm). Maximum Spool Width: 14 inches (355.6 mm). Maximum Material Size: 0.437 inches (11.1 mm) outside diameter (OD).	
204	Vevor Micro-Computer Cutting Machine; Power Supply: 110V	
205	Yoolle-Tools Striping Machine, w/ (5) Canisters of Rust-Oleum Inverted Professional Striping Paint; To Include: (5) Canisters of Rust-Oleum Inverted Professional Striping Paint	
206	Uline Banding Cart, w/ Tensioner / Cutter; Portable dispenser designed to hold large coils of strapping material. It typically features an automatic brake to prevent the coil from over-unwinding.	
207	Uline Banding Cart, w/ Tensioner / Cutter; Portable dispenser designed to hold large coils of strapping material. It typically features an automatic brake to prevent the coil from over-unwinding.	
208	Toyota HPT2U8 Pallet Jack; Capacity: 5500 lbs	
209	Toyota HPT2U8 Pallet Jack; Capacity: 5500 lbs	
210	Toyota HPT2U8 Pallet Jack; Capacity: 5500 lbs	
211	Toyota HPT2U8 Pallet Jack; Capacity: 5500 lbs	
212	Toyota HPT2U8 Pallet Jack; Capacity: 5500 lbs	
213	Toyota HPT2U8 Pallet Jack; Capacity: 5500 lbs	

214	manual hand winch pallet stacker; The Vestil VWS-770-AA is a manual hand winch pallet stacker designed for lifting loads up to 770 lbs to a maximum height of 60 inches. It is characterized by its maintenance-free design and adjustable components that allow it to handle both open and closed-bottom pallets. Capacity: 770 lbs at a 15-inch horizontal load center; capacity decreases for loads longer than 30 inches. Lift Range: Forks can be raised from a lowered height of 1 9/16" up to a maximum of 60" (some sources list 59"). Winch Mechanism: Lifts at a rate of approximately 1 inch per handle revolution. Adjustability: Forks adjust from 6¼" to 26¾" wide, and straddle legs adjust from 42¼" to 54" wide. Mobility: Includes two rigid front wheels and two rear swivel casters equipped with brakes for maneuvering.	
214A	ULINE 5 Step Safety Ladder; Mobile safety ladder	
214B	3 Step Safety Ladder; Mobile safety ladder	
215	2021 Heli CBS10J Pallet Stacker; Model#: CBS10J Rated Capacity: 2200 lbs Max Lift Height: 117" Rated Voltage: 12V Total Weight 1100 lbs Battery Weight: 66 lbs	
216	John Deere 244 P Compact Wheel Loader; Model#: 244 / P Engine: Yanmar 4TNV98CT (4-cylinder, turbocharged) Net Power: 71 HP @ 2400 RPM Torque: 206 lb-ft) @ 1560 RPM Displacement: 3.3 L Emission Standard: EPA Final Tier 4/EU Stage V Skid Steer Dimensions: 144" x 45" x 48"	
217	Toyota Traigo 80-Volt Electric Pneumatic Forklift; Model: Toyota 9FBMK20T / 05-9FBMK20T Production Years: 2022 - 2025 Type: 4-Wheel Electric Counterbalanced Forklift (80V) Capacity: 2.0 Tons (approx. 4,000 lbs) Series: 9 Series - Traigo 80	
218	Toyota Electric Forklift Truck; Model#: RF1-BH1X45 Weight Max: 8737 lbs Volts: 36	
219	EP Battery Charger 36V; Model: LF3 36-140-483 3-phase B0Hz 3x208Vac 21.9 A 30Amp 3-phase B0Hz 3x240Vac 18.8 A 25Amp 3-phase 60Hz 3x480Vac 9.5 A 15Amp Date of Manufacture 2022-01-18 Number of cells Type 18 Pb/LeadAcid (36Vnom) Battery Capacity 720-1050 AH / 7-12H Weight (K) 75(166 lbs) Protection class IP 21	
220	Alpine Battery Charger Model: EHT40/500B; Model No. EHT40/500B Serial No. 28334.1-1-01 SPEC: FG 9495 Circuits: 1 Battery Type: LA Cells: 40 BCI Code: 80D6C8 Base Model No. 500 A HR ACV: 208/ 240/ 480 PH. 3 ACA: 28/ 24.3/ 12.1 Hz: 60 DCV: 80 DCA: 80 Date Code: 23K Charging Technologies Inc.	
221	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
222	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
223	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
224	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
225	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
226	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
227	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
228	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
229	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
230	Topper Industrial Utility Cart; Model#: 808-50133-00SS000 Capacity: 3000 lbs	
231	Dewalt 1/4" Cordless Impact Driver Model: DCF887; Torque: Delivers a maximum of 1,825 in-lbs (approx. 205 Nm). Speed Settings: Three speed modes for versatility: Speed 1 (Precision Drive): 0–1,000 RPM (designed to prevent overtightening and fastener damage). Speed 2: 0–2,800 RPM. Speed 3: 0–3,250 RPM. Impacts per Minute (IPM): Rated at 0–3,800 IPM. Chuck: 1 /4-inch hex, quick-release, one-handed loading chuck. Lighting: Three-LED "Halo" ring with a 20-second delay after trigger release to eliminate shadows. Weight: approximately 2.0 lbs	
232	Dewalt 1/2" Cordless Drill Driver Model: DCD791; Performance: Features a high-speed transmission with two speed settings: 0–550 RPM and 0–2,000 RPM. Chuck: Equipped with a 1/2-inch metal ratcheting chuck for superior bit-gripping strength. Dimensions: It is highly compact at only 6.9 inches front-to-back and weighs approximately 3.4 lbs (including battery), making it suitable for tight spaces. Lighting: Includes a 3-mode LED light with a spotlight mode that features a 20-minute shutoff function.	
233	Dewalt 1/2" Cordless Drill Driver Model: DCD791; Performance: Features a high-speed transmission with two speed settings: 0–550 RPM and 0–2,000 RPM. Chuck: Equipped with a 1/2-inch metal ratcheting chuck for superior bit-gripping strength. Dimensions: It is highly compact at only 6.9 inches front-to-back and weighs approximately 3.4 lbs (including battery), making it suitable for tight spaces. Lighting: Includes a 3-mode LED light with a spotlight mode that features a 20-minute shutoff function.	

234	Dewalt 1/2" Cordless Drill Driver Model: DCD791; Performance: Features a high-speed transmission with two speed settings: 0–550 RPM and 0–2,000 RPM. Chuck: Equipped with a 1/2-inch metal ratcheting chuck for superior bit-gripping strength. Dimensions: It is highly compact at only 6.9 inches front-to-back and weighs approximately 3.4 lbs (including battery), making it suitable for tight spaces. Lighting: Includes a 3-mode LED light with a spotlight mode that features a 20-minute shutoff function.	
235	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
236	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
237	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
238	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
239	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
240	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
241	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
242	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
243	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
244	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
245	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
246	(2) Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
247	2 Dewalt Cordless Driver Model: DCF680; 8V MAX cordless screwdriver Speed Control: Motion-activated variable speed ranging from 0–430 RPM. Torque: Maximum torque is rated at 23–60 inch-pounds, with a 15-position adjustable clutch for precision fastening. Battery: Uses an 8V MAX Lithium-Ion battery that typically charges in one hour. Chuck: Features a 1/4-inch hex quick-release chuck that securely locks bits in place.	
248	Dewalt Corded Angel Grinder Model: DWE402; Performance: Equipped with an 11-amp AC/DC motor delivering up to 11,000 RPM and 1,400 max watts out. Dust Ejection System: Increases durability by ejecting damaging dust and debris that enters the tool through air intake vents. Quick-Change™ Wheel Release: Allows for tool-free wheel removal without needing a wrench. One-Touch™ Guard: Features 360-degree rotation that can be adjusted with a single action. Ergonomics: Designed with a small gripping surface and a 2-position side handle for improved comfort during extended use. Brush System: Uses oversized brushes that provide twice the life of previous models and includes an auto-off feature that shuts down the tool when brushes need replacement.	
249	Rotozip Rotosaw Spiral Saw SS355 W/ RotoZip Drywall Zip Bits; high-performance spiral saw designed for precise plunge and freehand cuts in various materials, including drywall, wood, and tile. It features a 5.5 Amp MagnaCore motor that delivers 30,000 RPM, providing a high power-to-weight ratio for a tool weighing approximately 2.5 to 3.18 lbs.	

250	Ryobi Cordless Jig Saw Model: JS651L1D; Corded 6.1 Amp variable speed orbital jig saw Motor: 6.1 Amp motor. Speed: Variable speed dial ranging from 0 to 3,200 SPM (strokes per minute). Orbital Action: 4-position SpeedMatch selector for aggressive or smooth cuts. Blade Type: Toolless blade clamp that accepts T-shank blades. Bevel Capacity: Base adjusts from 0° to 45° left or right for angled cuts. Visibility: Features a high-intensity LED work light and a built-in dust blower to clear the cut line.	
251	Milwaukee 2" Die Grinder Cat.No 2486-20; Cordless 12V Performance: Delivers 20% more power than typical pneumatic counterparts. Speed Control: 3-Mode RPM control with a maximum speed of 21,000 RPM (some sources list 20,000 RPM) and a responsive variable-speed trigger. Collet Size: 1/4 inch. Dimensions: Height of 10.1", length of 2.2", and width of 1.9". Weight: Approximately 1.2 lbs (bare tool) or 1.6 lbs with battery.	
252	Milwaukee 2- Speed Driver Cat No. 2402-20; Milwaukee M12 FUEL 1/4" Hex 2-Speed Screwdriver (Cat No. 2402-20) Motor: POWERSTATE Brushless motor providing up to 325 in-lbs of peak torque. Speed Settings: Two ranges: 0–450 RPM (Low) and 0–1,700 RPM (High). Chuck Type: 1/4" Hex Quick Change for rapid bit swaps. Weight: Approximately 2.0 lbs (bare tool), making it suitable for one-handed overhead use.	
253	Milwaukee 2- Speed Driver Cat No. 2402-20; Milwaukee M12 FUEL 1/4" Hex 2-Speed Screwdriver (Cat No. 2402-20) Motor: POWERSTATE Brushless motor providing up to 325 in-lbs of peak torque. Speed Settings: Two ranges: 0–450 RPM (Low) and 0–1,700 RPM (High). Chuck Type: 1/4" Hex Quick Change for rapid bit swaps. Weight: Approximately 2.0 lbs (bare tool), making it suitable for one-handed overhead use.	
254	Milwaukee 2- Speed Driver Cat No. 2402-20; Milwaukee M12 FUEL 1/4" Hex 2-Speed Screwdriver (Cat No. 2402-20) Motor: POWERSTATE Brushless motor providing up to 325 in-lbs of peak torque. Speed Settings: Two ranges: 0–450 RPM (Low) and 0–1,700 RPM (High). Chuck Type: 1/4" Hex Quick Change for rapid bit swaps. Weight: Approximately 2.0 lbs (bare tool), making it suitable for one-handed overhead use.	
255	Milwaukee 2- Speed Driver Cat No. 2402-20; Milwaukee M12 FUEL 1/4" Hex 2-Speed Screwdriver (Cat No. 2402-20) Motor: POWERSTATE Brushless motor providing up to 325 in-lbs of peak torque. Speed Settings: Two ranges: 0–450 RPM (Low) and 0–1,700 RPM (High). Chuck Type: 1/4" Hex Quick Change for rapid bit swaps. Weight: Approximately 2.0 lbs (bare tool), making it suitable for one-handed overhead use.	
256	Milwaukee 1/4" Impact Driver Cat No. 2553-20; Torque: 1,300 in-lbs of fastening torque. Speed Settings: 4-Mode DRIVE CONTROL. Mode 1: 0-1,300 RPM. Mode 2: 0-2,400 RPM. Mode 3: 0-3,300 RPM. Mode 4: Self-Tapping Screw Mode to reduce stripping and breaking. Dimensions: Length of 5.1 inches and a weight of 1.76 lbs (tool only). Chuck: 1/4" Hex Quick Change.	
257	Milwaukee 1/4" Impact Driver Cat No. 2553-20; Torque: 1,300 in-lbs of fastening torque. Speed Settings: 4-Mode DRIVE CONTROL. Mode 1: 0-1,300 RPM. Mode 2: 0-2,400 RPM. Mode 3: 0-3,300 RPM. Mode 4: Self-Tapping Screw Mode to reduce stripping and breaking. Dimensions: Length of 5.1 inches and a weight of 1.76 lbs (tool only). Chuck: 1/4" Hex Quick Change.	
258	Milwaukee 1/4" Impact Driver Cat No. 2553-20; Torque: 1,300 in-lbs of fastening torque. Speed Settings: 4-Mode DRIVE CONTROL. Mode 1: 0-1,300 RPM. Mode 2: 0-2,400 RPM. Mode 3: 0-3,300 RPM. Mode 4: Self-Tapping Screw Mode to reduce stripping and breaking. Dimensions: Length of 5.1 inches and a weight of 1.76 lbs (tool only). Chuck: 1/4" Hex Quick Change.	
259	Milwaukee Rivet Tool Cat No. 2550-20; Pulling Force: 2,000 lbs. Stroke Length: 0.8 inches. Rivet Capacities: Pulls 3/32", 1/8", 5/32", and 3/16" rivets. Material Compatibility: Works with aluminum, steel, and stainless steel rivets. Dimensions: Compact 6.5" length; weighs 4.3 lbs excluding battery. Features: Integrated belt hook, LED light, on-board nose piece storage, and a mandrel collection container.	
260	Milwaukee Rivet Tool Cat No. 2550-20; Pulling Force: 2,000 lbs. Stroke Length: 0.8 inches. Rivet Capacities: Pulls 3/32", 1/8", 5/32", and 3/16" rivets. Material Compatibility: Works with aluminum, steel, and stainless steel rivets. Dimensions: Compact 6.5" length; weighs 4.3 lbs excluding battery. Features: Integrated belt hook, LED light, on-board nose piece storage, and a mandrel collection container.	
261	Milwaukee Rivet Tool Cat No. 2550-20; Pulling Force: 2,000 lbs. Stroke Length: 0.8 inches. Rivet Capacities: Pulls 3/32", 1/8", 5/32", and 3/16" rivets. Material Compatibility: Works with aluminum, steel, and stainless steel rivets. Dimensions: Compact 6.5" length; weighs 4.3 lbs excluding battery. Features: Integrated belt hook, LED light, on-board nose piece storage, and a mandrel collection container.	
262	Milwaukee Rivet Tool Cat No. 2550-20; Pulling Force: 2,000 lbs. Stroke Length: 0.8 inches. Rivet Capacities: Pulls 3/32", 1/8", 5/32", and 3/16" rivets. Material Compatibility: Works with aluminum, steel, and stainless steel rivets. Dimensions: Compact 6.5" length; weighs 4.3 lbs excluding battery. Features: Integrated belt hook, LED light, on-board nose piece storage, and a mandrel collection container.	
263	(2) Milwaukee LED Worklights Cat No. 2735-20; Brightness: 100 to 160 Lumens. Run Time: Up to 29 hours when used with an M18 XC5.0 battery. Beam Distance: 50 feet. Adjustability: 135° rotating head (some sources specify 90°). Durability: IP54 rated for water and dust resistance, with an impact-resistant lens and a sealed aluminum head.	
264	Milwaukee Fuel Brushless Deep Cut Band Saw Cat No. 2729-20 18v; W/ Vise Chain Stand Cutting Capacity: 5" x 5" in a single pass. Blade Speed: Variable speed from 0 to 380 SFPM (Surface Feet Per Minute). Blade Length: Standard 44-7/8" x 1/2" x .020" band saw blades. Weight: Approximately 15 lbs. Technology: REDLINK PLUS™ Intelligence provides overload protection and optimized performance through system communication.	
265	Milwaukee 7 1/4" Tilt-LOK Adjustable Handle Circular Saw; Cat No. 6390-20 corded 15-amp power tool featuring a unique 8-position adjustable handle designed for maximum comfort in various cutting applications Motor: 15 Amp, 120V AC/DC. Blade Speed: 5,800 No Load RPM. Cutting Capacity: 2-7/16" at 90°, 1-13/16" at 45°, and 1-11/16" at 50°. Bevel Capacity: Up to 50° with tool-free adjustments. Construction: Magnesium shoe for reduced weight and durability, with a 9-foot fixed cord.	
266	Milwaukee 1/0 AWG - 750 MCM AL THHN / XHHW BUSHING KIT; 49-16-BKITA, And Assorted Milwaukee and Diablo Hole Saws	

267	Assorted tools and materials; This lot contains an assortment of - Milwaukee M12 and M18 battery chargers - (1) M18 battery and (2) M12 batteries - (2) tool soft carry cases - (1) Milwaukee fan - assortment of different sized heat shrink tubing	
268	Assorted DeWALT batteries and chargers; This lot contains - (25) 8V max lithium ion battery chargers. Model: DCB095 - (3) 20v, 2ah batteries - (20) 8V batteries	
269	DeWALT tool bags AND storage box; This lot contains (12) DeWALT tool bags and a tough system 2.0 lock in, roll out box. The box. Is 16" tall x 20" wide x 12" deep.	
270	Bosch 8.5 Amp Corded 1-1/8 in. SDS-Plus Variable Speed Concrete/Masonry Rotary Hammer Drill with Carrying Case; 8.5 Amp Corded 1-1/8 in. SDS-Plus Variable Speed Concrete/Masonry Rotary Hammer Drill with Carrying Case Model: GBH2-281	
271	Pneumatic Crimping Tools; Model: AM-10 Applicable Air Pressure: 0.5-0.7 Mpa Operating Air Pressure: 0.5 ~ 0.7 MPa (72 ~ 101 PSI) Output Force: 1.3 Tons at 0.5 MPa air pressure Weight: 3.5 kg (approx. 7.7 lbs) Crimping Capacity: Non-insulated terminals: up to 16 mm ² Pre-insulated terminals: up to 6 mm ² Tube (ferrule) terminals: up to 35 mm ²	
272	Temco Hydraulic Crimping Tool Model: TH0005; Crimping Range: 10 AWG through 600 MCM. Force: 11 US Tons. Die Sets: Includes 32 die sets (16 standard sizes and 16 "plus" sizes for non-standard or thin-wall lugs). Crimp Type: "True-Hex" crimp which applies uniform pressure to prevent "wings" and ensure high pull-out resistance. Materials: Black oxide-coated forged steel head and dies to prevent chipping and corrosion. Weight: Approximately 24 lbs (11.23 kg).	
273	Hydraulic Hyclat Crimping Tool HWC-10T; Crimping Range: 12 AWG to 2/0 AWG (4mm ² to 70mm ²). Die Sizes: 4, 6, 8, 10, 16, 25, 35, 50, and 70 mm ² . Maximum Stroke: 10mm to 12mm (approx. 0.43 inches). Weight: Approximately 6.25 to 6.6 lbs. Dimensions: 12" L x 2.36" W (30.5 cm). Materials: 45# Steel body with 40Cr steel crimping head.	
274	GreenLee 11-Ton Hydraulic Knockout Kit W/ Hand Pump; 1/2" to 2" Conduit Model: 7306SB Capacity: Up to 10 gauge mild steel or 12 gauge stainless steel. Conduit Sizes: Includes punches and dies for 1/2" to 2" conduit. Punch Force: 11 tons of hydraulic force. Key Features: Laser markings for part identification, alignment markings for accuracy, and knurled edges for better grip.	
275	Aoben RIVIT Nut Tool AB7002-16; High Leverage Design: The 16-inch handles feature double compound hinges that maximize leverage, allowing for easier operation compared to shorter 13- or 14-inch tools. Quick-Change Head: A specialized spring-loaded mandrel design enables tool-free, rapid changes of mandrels and nose pieces. Durable Construction: Built from thick, heat-treated alloy steel to resist corrosion and increase long-term durability. Portability: The complete kit is housed in a rugged, blow-molded carrying case where each component fits into a dedicated slot to prevent damage during transport.	
276	Assorted crimpers and wire strippers; This lot contains an assortment of wire crimpers and strippers. There are Phoenix contact crimpers as well.	
277	Assorted hand crimpers; This lot contains an assortment of handheld crimpers.	
278	Assorted hand crimpers; This lot contains an assortment of handheld crimpers. APP and Crimpfox brands.	
279	Assorted small cutters and pliers; This lot contains a variety of cutters and pliers both Klein and Xcelite brands.	
280	Assorted wire strippers and clamps; This lot contains an assortment of wire strippers and hand clamps.	
281	Assorted channel locks and cutters; This lot contains channel lock brand channel locks in many sizes. It also contains did sized Klein brand cutters.	
282	Assorted Allen keys; This lot consists of an assortment of Allen keys. Some are T-Handel and some are sets. Metric and standard in size.	
283	Assorted screwdrivers; This lot contains an assortment of different sized screwdrivers, flat head, Phillips and torx. Standard and electrical use.	
284	Assorted screwdrivers; This lot contains an assortment of different sized screwdrivers, flat head and Phillips. Standard and electrical use.	
285	Assorted wrenches; These wrenches are Westward brand, black, all different sizes in standard and metric.	
286	Assorted wrenches and adjustable wrenches; This lot has 1/4" ratcheting wrenches, 1 1/2", 27mm, 33mm wrenches and (3) adjustable wrenches.	
287	Assortment of hammers/mallets; This lot contains a total of (9) hammers. Different sized mallets and claw hammers.	
288	(4) ratcheting hand crimps; The Molex 63819-0901 is a PremiumGrade manual ratcheting hand crimp tool specifically engineered for Mini-Fit Jr. male and female terminals. Wire Gauge Compatibility: Optimized for 18–24 AWG (0.80–0.20 mm ²) wires. Ratcheting Mechanism: Features a full-cycle ratchet to ensure complete, secure crimps every time. Precision Locator: Includes a user-friendly terminal locator and wire stop to hold terminals in the exact position for crimping.	
289	(5) PRO-CRIMPER III; The TE Connectivity 354940-1 is a PRO-CRIMPER III commercial-grade hand crimping tool frame. It is a versatile, manual ratcheting tool designed for field installation, repair, and prototyping. Modular Design: Features a slotted jaw design for easy installation and removal of interchangeable die sets. Ratchet Control: Equipped with a user-adjustable ratchet that ensures a complete crimping cycle and allows handle pressure to be set for optimal performance.	

290	(6) Zip tie tools; The ABB Thomas & Betts Ty-Rap ERG50 is a professional-grade, ergonomic cable tie installation tool designed to tension and flush-cut nylon cable ties with a tensile strength between 18 and 50 lbs. It is widely used by electricians and assembly workers to ensure consistent bundling without leaving sharp edges.	
291	(6) Zip tie tools; The ABB Thomas & Betts Ty-Rap ERG50 is a professional-grade, ergonomic cable tie installation tool designed to tension and flush-cut nylon cable ties with a tensile strength between 18 and 50 lbs. It is widely used by electricians and assembly workers to ensure consistent bundling without leaving sharp edges.	
292	(6) Uline zips tie tools; These are a professional-grade, ergonomic cable tie installation tool designed to tension and flush-cut nylon cable ties with a tensile strength between 18 and 50 lbs.	
293	(2) handheld cabinet jacks; This is a manual mechanical tool designed to precisely lift, level, and support heavy objects with one hand, making it ideal for solo projects. Precision Control: A squeeze handle raises the load in small increments, while a quick-release lever allows for immediate or controlled lowering. Integrated Measuring: As seen in your image, many models feature an integrated ruler/scale on the shaft to help achieve exact height adjustments.	
294	(2) Mag-Mates; The Mag-Mate B090 is a professional-grade, handheld manual lifting magnet designed for the quick retrieval and transport of steel parts, sheets, or metal scraps. It features a unique trigger release handle that allows for effortless, one-handed operation and load release.	
295	(5) self-adjusting combination wire strippers; The Xcelite SAS3210 is a professional-grade, self-adjusting combination wire stripper and cutter designed for precision work in electronics, automotive, and telecommunications. It is widely recognized for having one of the widest stripping capacities in its class, handling wire gauges from 32 AWG to 10 AWG (0.02 – 10.0 mm ²) without requiring manual adjustments.	
296	(2) BESSEY clamps; Clippix (XC Series) Standard Spring Clamps: These are lightweight polyamide spring clamps available in various sizes from 3/4" to 3" capacities. They feature ergonomic handles with soft-grip inserts and pivoting jaw pads to ensure a flat grip on surfaces.	
297	(4) Erwin clamps; ERWIN quick clamps. made with reinforced nylon bodies and heat-treated steel bars. Medium-Duty (SL300): These deliver 300 lbs of sustained pressure. They use an I-beam bar to prevent flexing and bowing.	
298	(3) DeWALT clamps; DeWALT clamps. made with reinforced nylon bodies and heat-treated steel bars. (1) Small (Light-Duty): These provide 35 lbs of clamping force and are typically 4-1/2" in length. They are intended for light holding and delicate projects. (2) Large (Heavy-Duty): Providing 300 lbs of force with a 3-1/4" throat depth, these are a standard choice for most woodworking.	
299	(2) C-clamps; (2) 8" Wilton C-clamps. These are a versatile manual tool featuring a C-shaped frame and a threaded screw mechanism used to hold workpieces together or secure them to a surface. They are essential in woodworking, metalworking, and welding due to their high clamping pressure and simple, portable design.	
300	Electrical crimpers; Nicopress crimping tools are professional-grade instruments manufactured by National Telephone Supply for creating permanent terminations in wire rope and aircraft cable.	
301	Crimping tools; (1) greenlee K09 (1) Molex MCT-8200 These crimping tools are primarily used for copper connectors.	
302	Pipe wrenches; (1) RIDGID pipe wrench, 24", 3/4"-3". (1) Tohnichi pipe wrench, 12", 1/2"-3".	
303	Prybar and ratchet extensions; This lot consists of (1) DeWALT 24" prybar and (2) Gearwrench 24", 3/8" ratchet extensions.	
304	SHRINKFAST LP Gas Torch; Model 999 Power Output: 168,000 BTU/H. Operating Pressure: 22 PSIG. Fuel Type: Propane Gas only. Performance: Designed to shrink-wrap a standard 40" x 48" x 60" pallet in approximately two minutes. Cool-Touch Design: Utilizes a patented combustion cycle that allows the flame to burn outside the nozzle, keeping the tool cool enough to touch during operation. Lightweight: The gun itself weighs approximately 2.2 lbs, making it highly portable for large industrial or marine projects.	
305	Black & Decker Heat Gun; Temperature Settings: Two distinct modes, typically 750°F and 1,000°F. Power: Rated at approximately 1,350 Watts	
306	Heat Gun; Portable mini heat gun Model: MF300 Power: 300 Watts Voltage Support: 50Hz–60Hz Maximum Temperature: Typically reaches approximately 200°C (392°F).	
307	(2) Value Max Caulking Guns; 9" manual applicator for standard 1/10 gallon (10 oz) caulk cartridges Design: It typically features a 360-degree rotatable barrel for flexibility in tight spaces and a built-in spout cutter to open sealant tubes. Ease of Use: It includes a trigger comfort grip to reduce hand fatigue and an iron smooth rod for steady application.	
308	Lot Of Assorted Tape Measures, Rafter Square And Levelers; Assortment of Levelers, Squares, & tape measures	
309	Vevor Crane Scale Model: SF918; Cap.300KG Capacity Range: 0.3 lbs (0.15 kg) to 660 lbs (300 kg). Measurement Units: Can switch between pounds (lb), kilograms (kg), and Newtons (N). Dimensions: 12.32 x 3.34 x 1.45 inches (313 x 85 x 37 mm). Weight: The unit itself weighs approximately 1.38 lbs (0.63 kg). Power Source: Operates on two 1.5V AAA batteries.	
310	Staple guns and chalk line; This lot has (2) staple guns, one is a traditional gun and the other is a Bostitch hammer gun. This includes a box of 3/8" staples. Also, a DeWALT chalk line with a 4oz bottle of chalk.	
311	Benchmark hand RIVIT Gun; Equipped with non-slip vinyl or rubber hand grips and a spring-loaded handle for comfort and easy rivet loading.	

312	phoenix contact pps compact Cutting Tool 1104980; Dimensions: 1099 mm (Length) x 173 mm (Width) x 610 mm (Height). Lever Length: 580 mm, designed for optimum leverage to minimize user strain. Material: Constructed from anodized steel with a black finish. Weight: Approximately 4.5 kg to 5.5 kg depending on packaging. Max Material Thickness: 1.5 mm.	
313	Lot of (5) CDI TORQUE PRODUCTS Drivers; 3-40lbs Model/Part Number (P/N): 401SM. Torque Range: 5 to 40 inch-pounds (in-lb). Drive Size: 1/4-inch female hex drive. Accuracy: Features a ±6.0% accuracy reading from 20% to 100% of the full scale.	
314	Lot of (5) CDI TORQUE PRODUCTS Drivers; 3-40 lbs CDI 401SM: This is a micro-adjustable torque screwdriver with a primary scale range of 5 to 40 inch-pounds. It features a 1/4-inch female hex drive and a positive locking pull-down adjustment knob. CDI 1047: One of the screwdrivers is labeled as P/N 1047 with a specified torque of 2.5 in-lbs. This model typically features a cam-over design that slips once the target torque is reached, preventing damage to sensitive components.	
315	Lot of (5) CDI TORQUE PRODUCTS Drivers; 3-40 lbs CDI 401SM: A micro-adjustable torque screwdriver with a range of 5 to 40 inch-pounds. It features an accuracy of +/- 6% and a 1/4-inch female hex drive. CDI 151SM: A micro-adjustable model with a lower torque range, typically 3 to 15 inch-pounds. Like the 401SM, it uses a 1/4-inch hex bit holder. Pre-set Models (e.g., 401SP, 151SP): Several tools in the bin (like the one labeled 151SM with a pink band) may be pre-set versions. These are designed for high-volume assembly where only one torque setting is needed, preventing unauthorized user adjustment.	
316	Lot of (5) CDI TORQUE PRODUCTS Drivers; 3-40 lbs CDI 401SM: A micro-adjustable torque screwdriver with a range of 5 to 40 inch-pounds. It features an accuracy of +/- 6% and a 1/4-inch female hex drive. CDI 151SM: A micro-adjustable model with a lower torque range, typically 3 to 15 inch-pounds. Like the 401SM, it uses a 1/4-inch hex bit holder. Pre-set Models (e.g., 401SP, 151SP): Several tools in the bin (like the one labeled 151SM with a pink band) may be pre-set versions. These are designed for high-volume assembly where only one torque setting is needed, preventing unauthorized user adjustment.	
317	Lot of (5) Torque Drivers; (3) CDI 5-40 Lbs Drivers (2) Sturtevant Richmond 1.3 lbs	
318	Lot of Seekonk Precision Tools; Drivers and Wrenches (4) MC-200 (4) model It-m (1) model It-l	
319	Lot of (11) WERA Torque Drivers; (4) Appearing New WERA Torque Drived (4) WERA 7430 (1) 7450 ESD (2) 7440	
320	Lot of (12) centric RF 5lb torque wrenches; Model: ct-sma 11 Torque Value: Preset to 5 in-lbs. Hex Size: 5/16", which is standard for SMA male connectors. Type: Click Type, which provides an audible or tactile "click" once the preset torque is reached. Tolerance: ±8%	
321	Tap and die set; This is an Irwin Hanson 117 piece set. #4-#12 1/4"-1/2"	
322	Tool set; Westward tool set with a hard shell carry case. Tools consist of 3/8" ratchet, standard and metric sockets and Allen wrenches.	
323	CDI Torque wrench's; This lot contains (4) CDI torque wrench's. 0-50 IN-lb / 0-5.4 nm 1/4" drive.	
324	CDI Torque wrench's; This lot contains (5) CDI torque wrench's. 0-250 IN-lb / 0-27.7 nm 3/8" drive.	
325	Lot (3) Torque Wrenches; (1) CDI torque products 10002 MRMH 110NM (2) Sturtevant Richmond three SDR 200I 200 inch pound 200in lbs	
326	Torque wrench's; This lot contains (4) CDI torque wrench's. 0-100 ft.lb / 0-132 nm 3/8" drive.	
327	Torque wrench's; This lot contains (4) CDI torque wrench's. 0-100 ft.lb / 0-132 nm 3/8" drive.	
328	Torque wrench's; This lot contains (4) Sturtevant Richmond torque wrench's. 0-200 IN-LB 3/8" drive.	
329	Torque wrench's; This lot contains (5) Sturtevant Richmond torque wrench's. 0-200 IN-LB 3/8" drive.	
330	Torque wrench's; This lot contains (4) Sturtevant Richmond torque wrench's. 0-200 IN-LB 3/8" drive.	
331	(7) CDI torque products torque wrnehces; (6) 501MRMH Torque Wrench (1) 2502MRMH	
332	Lot of (10) Ratchet Wrenches; (5) Westward 1/4" Drive (1) wright (1) Porto 1/2" drive (3) Porto 3/8" drive	
333	Assorted sockets; This lot contains an assortment of 1/2" drive sockets and adapters.	
334	Assorted shop tools; This lot consists of (2) wall hooks, (1) RIDGID chain vice, model- BC-410A and a hard case tool box with standard tools including a small drill.	
335	Roller rack with an materials assortment; This lot contains a 6' tall by 26" wide, double sided roller rack that consists of material such as sockets, zip ties, screws, nuts, washers, terminal blocks, impact adapters, sharpie markers and more.	

336	Assorted office and warehouse materials; This lot consists of office and warehouse materials such as scissors, break away box cutters, rollers, utility blades, files and tweezers.	
337	Assorted industrial supplies; This lot is a pallet that contains an assortment of supplies such as - lock out tag out boxes - grinding sheild - flash lights - zip ties and tape - SDS binder station - tablet harness's and adjustable phone/tablet clip on mount.	
338	Saw horses; Stanley saw horses. 800lbs, quick set up and breakdown and extension top. 2' tall x 2' wide.	
339	Vector Arbor Press; VEVOR Arbor Press, no1 Cast Iron Heavy-duty Manual Desktop Arbor Press, Precision Hand Press for Stamping, Bending,	
340	Tape dispenser; Uline tape dispenser, multi roll tape dispenser.	
341	Tape dispenser; Uline tape dispenser, multi roll tape dispenser.	
342	Lot of Assorted GT-Lite Linkable Shop Lights; To Include: - GT-Lite Model#: GT-SL5000-Link Shop Lights	
343	Uline IN7620 Inscale Floor Scale, w/ LP7510A Inscale Control Module; Model#: IN7620 Capacity: 5,000 lbs	
344	Gardner Denver RNC Series Air Dryer; Model#: RNC250A4C2 Rated Capacity: 250 SCFM@ 100 PSIG	
345	Gardner Denver Integra Base-Mounted Rotary Screw Air Compressor; Model: EFC99A HP: 30 116 CFM @ 125 psi Electrical Requirements: 230 Volts Approx Dimensions: 34 x 48 x 66 Approx Weight: 1,280 lbs Hours: 55,682	
346	Gardner Denver Integra Base-Mounted Rotary Screw Air Compressor; Model: EFC99A HP: 30 116 CFM @ 125 psi Electrical Requirements: 230 Volts Approx Dimensions: 34 x 48 x 66 Approx Weight: 1,280 lbs Hours: 72,541	
347	2002 Manchester-TX 240 Gal. Tank; CAT#: 302428 CRN#: F0628.1C SH#: .227 HD#: .186 Capacity: 240 Gal.	
348	Lot of Assorted FlexPipe Casters, Flexpipe Brackets / Connectors, Etc.; To Include: - Flexpipe Casters - Flexpipe Connectors - Flexpipe Brackets	
349	Lot of Assorted Flexpipe Brackets / Stands, Etc.; To Include: - Flexpipe Connectors - Assorted Flexpipe Brackets - Assorted Flexpipe Assembly Pieces - Flexpipe Stands	
350	Lot of Assorted Assembly Pieces; To Include: - Brackets - Clips - Bolts - Screws	
351	Assorted FlexPipe Assembly Parts; To Include: - Piping - Conveyor - Table Pieces Dimensions: 34" x 19" x 32" **Includes All FlexPipe Carts in Facility**	
352	(10) Leviton® 3100P6W Pin & Sleeve Plugs; Model#: 31P6W Power Supply: 250 VAC, 100 A, 2 Poles, 3 Wires, Blue	
353	(2) ReelCraft Drop Cables; Model#: L-45451233A Cord Length & Type: 45 feet of 12/3 SJE00W cable. Electrical Rating: 20 Amps, 125 Volts AC. Outlet Configuration: Single NEMA 5-20R receptacle. Input (Pigtail): 4-5 foot feeder cord with a NEMA 5-20P straight blade plug. Construction: Robotically welded 14-gauge steel base with a powder-coated finish for corrosion resistance. Dimensions: Approximately 12.63" L x 9.38" W x 13.25" H. Weight: 28 lbs.	
354	Lot of Assorted Electrical Hardware; To Include: - Plug Outlets/ Housings - Electrical Boxes (Eaton/Siemens) - Connectors	
355	Lot of Assorted Electrical Hardware; To Include: - Electrical Control Boxes - Outlets / Housings - Power Boxes	
356	(11) Custom EOLT Core+ Testing Modules/Boxes; To Include: All Contents	
357	Lot of Assorted Pittsburgh 1500 lb Cap. Vehicle Dollys; Model#: 67338 Capacity: 1500 lbs	
358	(14) DataLogic QD2500 Barcode Scanners; Model#: QD2500 Scanning Performance: Equipped with 1 MP optics (1280 x 800 pixels) for superior depth of field and omnidirectional reading. It supports high motion tolerance of 30 IPS. User Feedback: Includes Datalogic's patented "Green Spot" technology, which projects a green light directly on the barcode for immediate good-read feedback, alongside an adjustable-tone beeper and a good-read LED. Durability: The device is built to withstand over 10 million trigger presses and repeated drops to concrete from 1.5 m (5.0 ft). It has an IP52 environmental sealing rating for protection against dust and water. Connectivity: Features a multi-interface design supporting RS-232, USB, and Keyboard Wedge. Modern models also include USB-C connectivity options. Specialized Modes: Features Motionix motion-sensing technology, which automatically detects when the scanner is picked up to switch between handheld and presentation modes.	
359	HP EliteOne 840 23.8" G9 All-In-One PC; Processor: Intel Core i5-12500 (3.0 GHz base, up to 4.6 GHz, 18 MB cache, 6 cores) or i5-14500. Memory: 8GB or 16GB DDR5-4800/5600 MHz SDRAM (up to 64GB supported, 2 SODIMM slots). Storage: 256GB - 2TB PCIe NVMe TLC M.2 SSD. Display: 23.8-inch diagonal, FHD (1920 x 1080), IPS, anti-glare, 250-300 nits, 72% NTSC	

383	Pallet racking; 10 Sections of Pallet Racking (9) Uprights 18' x 42" (2) Uprights 16' x 42" (58) 8' Beams And Wire Decking	
384	Pallet racking; 10 Sections of Pallet Racking (9) Uprights 18' x 42" (2) Uprights 16' x 42" (58) 8' Beams And Wire Decking	
385	Pallet racking; 5 Sections of Pallet Racking (6) Uprights 18' x 42" (30) 8' Beams And Wire Decking	
386	Pallet racking; 6 Sections of Pallet Racking (7) Uprights 18' x 42" (36) 8' Beams And Wire Decking	
387	Pallet racking; 4 Sections of Pallet Racking (3) Uprights 18' x 42" (2) Uprights 16' x 42" (2) Uprights 8' x 42" (22) 8' Beams And Wire Decking	
388	Safety Cage T Structure Aluminum W/ PVC Lined Fencing 25' x 16' x 9'; 3 Entrance doors (NO CONTENTS)	
389	Safety Cage T Structure Aluminum W/ PVC Lined Fencing 25' x 17' x 9'; 4 Entrance doors (NO CONTENTS)	
390	(4) 6-tier Uline steel shelf; This heavy duty 6-tier shelf measures at 6' tall x 4' wide x 2' deep per shelving unit. *Contents Included*	
391	(3) 6-tier Uline steel shelf; This heavy duty 6-tier shelf measures at 6' tall x 4' wide x 2' deep per shelving unit. *Contents Included*	
392	(3) Sections of Heavy Duty Metal Shelving; Contents not included	
393	(4) Sections of 6 Tier Heavy Duty Metal Shelving; 6' Height 4' With 2' Depth (Contents not included)	
394	(5) Sections of 6 Tier Metal Shelving Heavy Duty; Contents not included	
395	(3) 6-tier Uline steel shelf; This heavy duty 6-tier shelf measures at 6' tall x 4' wide x 2' deep per shelving unit. *contents are not included*	
396	(5) Sections of 6 Tier Heavy Duty Metal Shelving; 6' Height 4' With 2' Depth (Contents not included)	
397	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels.	
398	Work station table; Work station Table measurements: 6' long x 3' deep x 3' tall. It sits on 3" caster wheels.	
399	Work station; This work station is 6' long x 30" deep and has adjustable legs from 22" - 48". *Contents are not included*	
400	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels.	
401	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels.	
402	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
403	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. *Contents are not included*	
404	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. *Contents are not included*	
405	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. *Contents are not included*	
406	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. Comes with 5-tier steel shelf. *Contents are not included*	
407	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
408	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
409	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
410	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	

411	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
412	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
413	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
414	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
415	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (2) metal shelf. 5 total shelves. *Contents are not included*	
416	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. This lot comes with (1) metal shelf. 5 total shelves. *Contents are not included*	
417	Work station table; Work station Table with 6' x 3' peg board. measurements: 8' long x 3' deep x 3' tall. *Contents are not included*	
418	Work Station 95" x 35" x 35"; Adjustable table	
419	Linak Adjustable Table 6' x 30" (48" Max Hight); W/ Hutch Dimensions: explicitly listed as 72"W x 30"D (6' x 2.5'). Height Range: Models have been documented with a range of 22" to 48".	
420	Adjustable Table 47" x 30" (No Power Supply); Work station/ table	
421	Mobile Work Station 95" x 35" x 37"; Mobile work table	
422	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 6' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
423	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 6' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
424	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 4' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
425	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 4' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
426	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 4' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
427	PVC roller work station; This is a work station that consists of rollers to easily move parts or material while inspecting. There is a shelf to mount monitors or store sample parts. Measuring in at 100" long x 30" deep x 7' tall.	
428	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 5' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
429	Work station; Work station with adjustable leg height, custom frame for monitor setup and lighting. Table dimensions: 4' long x 30" deep. Adjustable height from 22"- 48" *Contents are not included*	
430	Mobile Work Station 71" x 35" x 36; Mobile work station	
431	Mobile Work Station 71" x 35" x 36; Mobile work station	
432	Work station; This work station is 4' long x 30" deep and has adjustable legs from 22"- 48". *Contents are not included*	
433	3-tier shelf; This is a 3-tier storage shelf measuring at 65" long x 26" deep x 47" tall. *Contents are not included*	
434	Work station; This work station is 6' long x 30" deep and has adjustable legs from 22"- 48". *Contents are not included*	
435	Work station with peg board; Work station with attached peg board. Table measurements: 8' long x 3' deep x 3' tall. Peg board sits 3' tall x 8' long. *Contents are not included*	
436	Work station table; Work station Table measurements: 6' long x 3' deep x 3' tall. It sits on 3" caster wheels. *Contents are not included*	
437	Work station table; Work station Table measurements: 6' long x 3' deep x 3' tall. It sits on 3" caster wheels. *Contents are not included*	
438	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels. *Contents are not included*	

439	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels. *Contents are not included*	
440	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels. *Contents are not included*	
441	Work station table; Work station Table measurements: 8' long x 3' deep x 3' tall. It sits on 3" caster wheels. *Contents are not included*	
442	Linak Adjustable Table 5' X 29"; Adjustable work table	
443	Lot of Assorted LINAK Spare Parts; To Include: - Assorted Model#: DF2 Extensions	
444	Lot of Assorted Uline Spare Parts; To Include: - Shelving Units	
445	(3) Assorted Racking Units; Dimensions: 36" x 18" x 75"	
446	Uline H-1563M-Y Flammable Storage Cabinet; Model#: H-1563M-Y Capacity: 30 Gal. Exterior Dimensions: 43" x 18" x 44" (W x D x H). Interior Dimensions: 39.8" x 14.8" x 40.1" (W x D x H). Weight: 216 lbs. Shelf Capacity: 350 lbs per shelf. Shelves: Includes 1 adjustable galvanized steel shelf that can be moved in 3" increments.	
447	Uline PPE Metal Cabinet; Dimensions: 36" x 24" x 72"	
448	Lot of (3) Assorted Storage Units; To Include: - (1) 5-Drawer Filing Cabinet - (1) Industrial Metal Storage Shelf - (1) Industrial "Tree" Storage Shelf	
449	Lockers; To Include: All Contents	
450	Uline PPE Metal Cabinet; Dimensions: 36" x 24" x 72"	
451	Uline Metal Industrial Cabinet; Dimensions: 36" x 24" x 72"	
452	4-Drawer Industrial Filing Cabinet, w/ Jingur Cabinet; To Include: All Contents	
453	Ideal Oil Paper Shedder; Model#: Ideal 2604 CC Power Supply: 120V, 1PH, 60Hz, 0.640kW, 8.0A	
454	HP LaserJet Pro MFP 4101 fan; Product#: 2Z618F Power Supply: 100-127V AC, 50/60Hz, 6.4A	
455	Brady BradyPrinter i7100 Label Printer; Model#: i7100 Voltage: 100-240V Current: 2A Max. Frequency: 50-60Hz	
456	(2) Assorted Intermac Label Printers; To Include: - (1) Intermac PC43d Label Printer (Model#: PC43d) - (1) Intermac PC43t Label Printer (Model#: PC43t)	
457	Samsung 65" Monitor; Model#: LH65BETHLGFYGO Resolution: 4K UHD (3840 x 2160) with a Crystal Processor 4K for upscaling content. Brightness & Contrast: Features a brightness of 250 nits and a typical contrast ratio of 4,700:1. Panel Type: 60Hz E-LED BLU (Edge-lit LED) with a 3-sided bezel-less slim design. HDR Support: Supports HDR10+ and HLG formats to enhance detail in bright and dark scenes.	
458	Polycom Poly Studio All-In-One USB Video Bar, w/ Touch Screen Control; Model#: P009 Camera: UHD 2160p (4K) resolution with a 120-degree ultra-wide field of view and 5x electronic zoom (EPTZ). Audio: Six-element beamforming microphone array with a 12-15 ft (3.7-4.6m) pickup range and 90 dB output stereo speakers. Intelligent Features: Poly Acoustic Fence and NoiseBlockAI technologies to eliminate distracting background noise. Connectivity: USB 3.0 Type-C (plug-and-play), Bluetooth 4.2, and Wi-Fi (802.11a/b/g/n/ac) for remote management via Poly Lens.	
459	Samsung 75" Monitor; Model#: BE75T-H Resolution: 4K UHD (3840 x 2160) for sharp, detailed images. Signage Capabilities: Includes content management via the Samsung Business TV app, allowing for easy, customizable advertising. Performance: 8ms response time and a 178°/178° viewing angle. Connectivity: Features 2 HDMI ports, USB input, Ethernet, Wi-Fi, and Bluetooth. Audio: Built-in dual speakers. Design: VESA wall mountable (400 x 400mm) with an included stand. Durability: Features an on/off timer for automatic operation and a PIN code to protect display settings.	
460	Samsung 65" Monitor; Model#: BE65T-H Resolution: 3840 x 2160 (4K UHD). Brightness: 250 nits (typical). Contrast Ratio: 4700:1. Refresh Rate: 60 Hz. Response Time: 8 ms (G-to-G). HDR Support: Compatible with HDR10 and HDR10+.	
461	Polycom Poly Studio All-In-One USB Video Bar; Model#: P009 Video Quality: Ultra HD 4K resolution (2160p) at 30 fps. Field of View: 120° diagonal wide-angle lens. Audio: Six-element beamforming microphone array with a 15-foot (4.6m) pickup range. Connectivity: USB 3.0 Type-C, Bluetooth 4.2, and Wi-Fi 802.11a/b/g/n/ac. Zoom: 5x digital zoom. Physical: Dimensions are roughly 27.5 x 4.1 x 2.8 inches (70 x 10.5 x 7 cm); weight is 6.3 lbs with the stand.	

462	Samsung 75" Tv; Display: 75-inch 4K UHD (3840 x 2160) LED panel with a 60Hz refresh rate. Processor: Crystal Processor 4K for optimized color and upscaling. HDR Support: Compatible with HDR10 and HDR10+. Connectivity: 2 HDMI ports, 1 USB port, Ethernet (LAN), Wi-Fi 5, and Bluetooth 4.2. Audio: 2-channel built-in speakers with 20W output. Mounting: Supports VESA 400 x 400 mm wall mounts.	
463	Polycam Poly Studio All-In-One USB Video Bar; Model#: P009 Audio Quality: Features a 6-microphone array with a 12-foot pickup range, NoiseBlockAI, and Acoustic Fence technology to minimize background noise. Video Performance: 4K sensor with 5x digital zoom, automatic group framing, and active speaker tracking. Connectivity & Setup: Simple USB plug-and-play setup, with Wi-Fi/Bluetooth for management. Compatibility: Certified for Microsoft Teams and Zoom, and compatible with Skype for Business and other UC apps. Design: Compact, all-in-one design suitable for rooms with 10-15 participants.	
464	Samsung 75" Monitor; Model#: BE75T-H 4K UHD (3840 x 2160) commercial LED display designed for 16/7 business operations. Featuring a 60Hz refresh rate, 250-nit brightness, and 3-sided bezel-less design, it is ideal for digital signage and presentations.	
465	Conference Room; To Include: All Contents Table Dimensions: 14' x 54" x 29"	
466	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
467	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
468	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
469	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
470	Office Room; To Include: All Contents Desk Dimensions: 6' x 3' x 30"	
471	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
472	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
473	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
474	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
475	Office Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
476	Conference Room;	
477	Office Room; To Include: All Contents Desk Dimensions: 66" x 30" x 65"	
478	Conference Room; To Include: All Contents Desk Dimensions: 9' x 71" x 65"	
479	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) HP P24H-G4 Monitor	
480	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) HP P24H-G4 Monitor	
481	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) HP P24H-G4 Monitor	
482	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) HP P24H-G4 Monitor	
483	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) HP P24H-G4 Monitor	
484	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) ViewSonic VA2459-smh Monitor	
485	(2) Assorted Monitors; To Include: - (1) ĒLO ET2402L Monitor - (1) HP P24H-G4 Monitor	
486	(2) Assorted Monitors; To Include: - (1) ĒLO ET2202L Monitor - (1) HP P24H-G4 Monitor	
487	Cafeteria Furniture / Appliances;	

488	Cubicles / Office Chairs; To Include: All Contents	
489	(51) Trash cans; This lot contains a total of (51) trash cans. All Rubbermaid brand. - (16) 55 gallon cans - (6) 10 gallon cans - (29) 12 gallon cans	
490	Lot of Assorted Cleaning Supplies; Brooms Mops Vacuums	
491	(3) maintenance carts; These (3) carts are constructed of steel, have 2" casters and each of them come with contents. Cart measurements: 32" long x 14" wide x 30" tall. Contents include- an assortment of hardware.	
492	(3) maintenance carts; These (3) carts are constructed of steel, have 2" casters and each of them come with contents. Cart measurements: 32" long x 14" wide x 30" tall. Contents include- an assortment of hardware.	
493	Electric vehicle charging Handel; The REMA model REV-C1-150C is a CCS 1 DC fast charge electric vehicle (EV) inlet designed to be installed in a vehicle to accept high-voltage direct current (DC) charging, as well as alternating current (AC) charging. Current Rating (DC) 150A max Voltage Rating (DC) 600V DC max Current Rating (AC) 30A max Voltage Rating (AC) 240V AC max Maximum Charge Performance 90 kW Operating Temperature -30°C to +50°C Environmental Rating UL Type 3R Construction (designed for outdoor use) Terminals Male terminals on vehicle receptacle, silver-plated copper Temperature Sensor Integrated PT1000 sensor	
494	Electric vehicle charging Handel; The REMA model REV-C1-150C is a CCS 1 DC fast charge electric vehicle (EV) inlet designed to be installed in a vehicle to accept high-voltage direct current (DC) charging, as well as alternating current (AC) charging. Current Rating (DC) 150A max Voltage Rating (DC) 600V DC max Current Rating (AC) 30A max Voltage Rating (AC) 240V AC max Maximum Charge Performance 90 kW Operating Temperature -30°C to +50°C Environmental Rating UL Type 3R Construction (designed for outdoor use) Terminals Male terminals on vehicle receptacle, silver-plated copper Temperature Sensor Integrated PT1000 sensor	
495	Electric vehicle charging Handel; The REMA model REV-C1-150C is a CCS 1 DC fast charge electric vehicle (EV) inlet designed to be installed in a vehicle to accept high-voltage direct current (DC) charging, as well as alternating current (AC) charging. Current Rating (DC) 150A max Voltage Rating (DC) 600V DC max Current Rating (AC) 30A max Voltage Rating (AC) 240V AC max Maximum Charge Performance 90 kW Operating Temperature -30°C to +50°C Environmental Rating UL Type 3R Construction (designed for outdoor use) Terminals Male terminals on vehicle receptacle, silver-plated copper Temperature Sensor Integrated PT1000 sensor	
496	Electric vehicle charging Handel; The REMA model REV-C1-150C is a CCS 1 DC fast charge electric vehicle (EV) inlet designed to be installed in a vehicle to accept high-voltage direct current (DC) charging, as well as alternating current (AC) charging. Current Rating (DC) 150A max Voltage Rating (DC) 600V DC max Current Rating (AC) 30A max Voltage Rating (AC) 240V AC max Maximum Charge Performance 90 kW Operating Temperature -30°C to +50°C Environmental Rating UL Type 3R Construction (designed for outdoor use) Terminals Male terminals on vehicle receptacle, silver-plated copper Temperature Sensor Integrated PT1000 sensor	
497	FLO AUB-19132 EV Charger Station; To Include: - (2) Model#: AUB-19132 CoRe+	
498	FLO AUB-19132 EV Charger Station; To Include: - (2) Model#: AUB-19132 CoRe+	
499	FLO AUB-19132 EV Charger Station; To Include: - (2) Model#: AUB-19132 CoRe+	
500	Tripp-Lite Series Smart LCD Line-Interactive UPS; Model#: Smart1500LCD Capacity: 1500VA / 900W Voltage: 120V AC (Nominal), AVR corrects 75V-147V down to 120V Runtime: Approx. 4.4 minutes at full load (900W), 11.8 minutes at half load (450W) Outlets: 8 x NEMA 5-15R	
501	Tripp-Lite Series Smart LCD Line-Interactive UPS; Model#: Smart1500LCD Capacity: 1500VA / 900W Voltage: 120V AC (Nominal), AVR corrects 75V-147V down to 120V Runtime: Approx. 4.4 minutes at full load (900W), 11.8 minutes at half load (450W) Outlets: 8 x NEMA 5-15R	
502	UniFi Switch Pro 48 PoE Layer 3 Gigabit Switch; Networking Interfaces: (48) 1 GbE RJ45 Ports, (4) 10G SFP+ Ports PoE Interfaces: (40) PoE+ (IEEE 802.3at) and (8) PoE++ (IEEE 802.3bt) Total PoE Budget: 600W Switching Capacity: 176 Gbps Throughput: 88 Gbps Layer 3 Features: Inter-VLAN routing, static routing, and DHCP server Management: Ethernet In-Band, 1.3" LCM touch screen	
503	UniFi Switch Pro 48 PoE Layer 3 Gigabit Switch; Networking Interfaces: (48) 1 GbE RJ45 Ports, (4) 10G SFP+ Ports PoE Interfaces: (40) PoE+ (IEEE 802.3at) and (8) PoE++ (IEEE 802.3bt) Total PoE Budget: 600W Switching Capacity: 176 Gbps Throughput: 88 Gbps Layer 3 Features: Inter-VLAN routing, static routing, and DHCP server Management: Ethernet In-Band, 1.3" LCM touch screen	
504	UniFi Switch Pro 48 PoE Layer 3 Gigabit Switch; Networking Interfaces: (48) 1 GbE RJ45 Ports, (4) 10G SFP+ Ports PoE Interfaces: (40) PoE+ (IEEE 802.3at) and (8) PoE++ (IEEE 802.3bt) Total PoE Budget: 600W Switching Capacity: 176 Gbps Throughput: 88 Gbps Layer 3 Features: Inter-VLAN routing, static routing, and DHCP server Management: Ethernet In-Band, 1.3" LCM touch screen	
505	UniFi Switch Pro 48 PoE Layer 3 Gigabit Switch; Networking Interfaces: (48) 1 GbE RJ45 Ports, (4) 10G SFP+ Ports PoE Interfaces: (40) PoE+ (IEEE 802.3at) and (8) PoE++ (IEEE 802.3bt) Total PoE Budget: 600W Switching Capacity: 176 Gbps Throughput: 88 Gbps Layer 3 Features: Inter-VLAN routing, static routing, and DHCP server Management: Ethernet In-Band, 1.3" LCM touch screen	

506	D-Link DES-1210-28P 28-Port Fast Ethernet Web Smart Switch; Model#: DES-1210-28P Interfaces: 24 x 10/100 Mbps PoE ports, 2 x Gigabit RJ45, 2 x Combo 10/100/1000BASE-T/SFP. PoE Standards: IEEE 802.3af (15.4W) and 802.3at (30W) compliant. Switching Capacity: 12.8 Gbps. Forwarding Rate: 9.5 Mpps. MAC Address Table: 8K entries. Management: Web-based GUI, SmartConsole Utility, SNMP, and compact Command Line.	
507	APC Electric Switched Rack PDU; Model#: AP7900B Input Voltage: 100V - 120V AC Input Connection: NEMA 5-15P (15A) Output Voltage: 120V Output Connections: 8 x NEMA 5-15R (switched) Maximum Load: 15A (12A derated for North America) Capacity: 1.44 kVA	
508	APC Electric Switched Rack PDU; Model#: AP7900B Input Voltage: 100V - 120V AC Input Connection: NEMA 5-15P (15A) Output Voltage: 120V Output Connections: 8 x NEMA 5-15R (switched) Maximum Load: 15A (12A derated for North America) Capacity: 1.44 kVA	
509	UniFi Switch Pro 48 PoE Layer 3 Gigabit Switch; Networking Interfaces: (48) 1 GbE RJ45 Ports, (4) 10G SFP+ Ports PoE Interfaces: (40) PoE+ (IEEE 802.3at) and (8) PoE++ (IEEE 802.3bt) Total PoE Budget: 600W Switching Capacity: 176 Gbps Throughput: 88 Gbps Layer 3 Features: Inter-VLAN routing, static routing, and DHCP server Management: Ethernet In-Band, 1.3" LCM touch screen	
510	UniFi Switch Standard 48 PoE Managed Layer 2 Switch; Ports: 48x 1Gbps RJ45 Ports, 4x 1Gbps SFP Ports PoE Capability: 32 ports support 802.3at PoE+ (Max per port) Total PoE Budget: Switching Capacity: 104 Gbps Weight: 9.97 lbs Management: 1.3" touchscreen, Ethernet In-Band	
511	UniFi Switch Lite 16 PoE Managed Layer 2 Switch; Networking Interfaces: 16x 10/100/1000 Mbps RJ45 Ethernet Ports. PoE Interfaces: 8x PoE+ IEEE 802.3af/at (Ports 1-8). Total PoE Budget: 45 Watts. Switching Capacity: 32 Gbps. Forwarding Rate: 24 Mpps. Management: UniFi Network Application (Layer 2 switching). Dimensions: 191.7 x 185 x 43.7 mm	
512	UniFi AC SHD (UAP-AC-SHD) High-Performance, Indoor/Outdoor Wi-Fi 5 Access Point; Networking: (2) Gigabit Ethernet Ports (supports bridging). Performance: 802.11ac Wave 2, 4x4 MU-MIMO, up to total radio rate. Radio Configuration: Dedicated security radio for real-time spectrum monitoring and threat management. Power Method: 802.3at PoE+ (44-57V DC). Antennas: Dual-port, dual-polarity,	
513	DYMO Rhino 5200 Handheld Industrial Thermal Transfer Printer; Label Types: IND labels (Flexible Nylon, Heat-Shrinkable Tube, Permanent Polyester, Vinyl). Print Resolution: 180 dpi. Print Speed: 10 mm/sec. Display: Backlit, two-line display (14 characters). Barcodes: Code 39 and Code 128. Memory: Stores over 100 custom labels. Durability: Built-in rubber bumper to protect against falls.	
514	TP-Link ER7206 Omada Gigabit Multi-WAN VPN Router; Performance: ~940 Mbps NAT throughput (DHCP/Static), 200 Mbps IPS throughput, 177 Mbps WireGuard VPN, 34 Mbps OpenVPN. Ports: 1x Gigabit SFP WAN, 1x Gigabit RJ45 WAN, 4x Gigabit RJ45 WAN/LAN, 1x USB 3.0 (for LTE/backup). WAN Functionality: Supports up to 4 WAN ports, Load Balancing, Link Backup, and Policy Routing. VPN Support: IPsec, OpenVPN, WireGuard, L2TP, PPTP, and GRE. Management: Fully integrated with Omada Software/Hardware/Cloud Controller for centralized management.	
515	Microsoft HoloLens 2 Mixed Reality Headset; Model#: HoloLens2 Processor: Qualcomm Snapdragon 850 Compute Platform. Holographic Processing Unit (HPU): Second-generation custom-built HPU. RAM: 4GB LPDDR4x System DRAM. Storage: 64GB UFS 2.1. Display: 2K 3:2 light engines (waveguides). Resolution: 2048 x 1080 per eye. Field of View: ~43 degrees horizontal (roughly double the original HoloLens). Camera: 8MP stills, 1080p30 video recording. Sensors: 4 visible light cameras, 2 IR cameras (for eye-tracking), 1MP ToF depth sensor, accelerometer, gyroscope, magnetometer. Connectivity: Wi-Fi 5 (802.11 ac 2x2), Bluetooth 5.0, USB Type-C.	
516	Poly GC8 (Model P024) 8-inch, USB-Connected Touch Controller, w/ Cam; Model#: P024 Purpose: Provides intuitive meeting management (join, mute, volume, camera) for Teams Rooms. Display: 8-inch LCD touch screen. Ports: 1x USB Type-C (to PC), 1x USB Type-A (for accessories), 1x 3.5mm headset jack, 1x Mini HDMI (for content sharing). Sensor: Built-in PIR motion sensor.	
517	Lot of Assorted Jabra GN40 Headsets; Audio & Microphone: 20mm speaker drivers with a 50Hz - 20,000Hz frequency response (music mode) and 100Hz - 14,000Hz (speak mode). Uses a 2x MEMS microphone system with -38dBV/Pa sensitivity. Comfort & Design: Weighs as little as 45g (1.5 oz), featuring angled ear cushions with a pressure-relieving maze pattern. Available in stereo (binaural) or mono (monaural) versions. Connectivity: Wired USB-A or USB-C connection. Controls & Features: In-line controller for call management, busylight, and volume, plus a programmable button. Safety & Durability: Includes Jabra SafeTone™ 2.0 and PeakStop 105 for hearing protection. Built with durable materials,, offering a three-year warranty.	
518	(2) Sifely S Smart Locks; Manufacturer: Sifely Item Weight: 4.29 pounds Product Dimensions: 7 x 3 x 1.12 inches Color: Satin Nickel Material: Zinc Alloy Batteries Included: No Batteries Required: Yes Batteries Type: AAA Batteries Operational Temperature Range: 14 F to 158 F (-10C to 70C	
519	(5) ErgoTron LX Desk Monitor Arms; Screen Size: Up to 34" Weight Capacity: 7 to 25 lbs (3.2 to 11.3 kg) Vertical Lift: 13" (33 cm) Extension Range: Up to 25" (64 cm) from base Tilt Range: 70° Backward, 5° Forward Pan/Rotation: 360°	
520	(3) Poly Studio E70 Vesa Mounts; Model#: E70	
521	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2402L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	
522	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2402L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	
523	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2402L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	

524	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2202L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	
525	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2202L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	
526	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2202L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	
527	(2) ELO 23.8-inch Professional-Grade, 10-point TouchPro PCAP (projected capacitive) Touchscreen Monitors; Model#: ET2202L Display Size: 23.8-inch diagonal (Active matrix TFT LCD) Resolution: 1920 x 1080 @ 60Hz (Full HD) Touch Technology: TouchPro PCAP (10-touch) Brightness: 250 nits (panel), 225 nits (with touch) Aspect Ratio: 16:9	
528	(4) HP P24h G4 23.8" Monitors; Model#: P24h	
529	(4) HP P24h G4 23.8" Monitors; Model#: P24h	
530	(4) HP P24h G4 23.8" Monitors; Model#: P24h	
531	(3) HP P24h G4 23.8" Monitors, (1) ViewSonic; Model#: P24h	
532	(5) HP P24h G4 23.8" Monitors; Model#: HP P24h G4 **Monitor Only, No Stand**	
533	(5) HP P24h G4 23.8" Monitors; Model#: HP P24h G4 **Monitor Only, No Stand**	
534	(5) HP P24h G4 23.8" Monitors; Model#: HP P24h G4 **Monitor Only, No Stand**	
535	(5) HP P24h G4 23.8" Monitors; Model#: HP P24h G4 **Monitor Only, No Stand**	
536	(4) ViewSonic 24" Monitors; Model#: VA2459-smh **To Include: Monitors Only, No Stands**	
537	(5) ViewSonic 24" Monitors; (5) ViewSonic 24" Monitors Model#: VA2459-smh **to Include: Monitors Only, No Stands**	
538	(5) ViewSonic 24" Monitors; (5) ViewSonic 24" Monitors Model#: VA2459-smh **to Include: Monitors Only, No Stands**	
539	(1) HP Bang & Olufsen;	
540	(14) Assorted Monitor Stands; To Include: - (10) Intel vPro i5 Stands - (1) HP Stand - (3) ViewSonic Stands	
541	(4) Assorted HP Laptops; To Include: - (2) HP ZBook Firefly 15 G8 - (1) HP EliteBook 840 G7 - (1) HP EliteBook 860 G9	
542	(4) HP Windows 2067 128 GB Tablets; Model#: 2067	
543	(4) HP Windows 2067 128 GB Tablets; Model#: 2067	
544	(4) Assorted Tablets; To Include: - (2) HP 2067 Windows Tablets - (2) Apple A2602 Tablets	
545	Tripp-Lite Secure KVM Switch; Model#: B002A-UH2A4	
546	Fortinet FortiGate 100F High-Performance Next-Generation Firewall; Model#: FG-100F	
547	(4) UniFi Network USW Flex Mini Compact 5-Port Gigabit Switches; Model#: USW-Flex Mini	
548	(4) UniFi Network USW Flex Mini Compact 5-Port Gigabit Switches; Model#: USW-Flex Mini	
549	Lot of Assorted Logitech Compact Wireless Keyboards; Model#: MK360 / Y-R0012	
550	Assorted Wireless Keyboards / Computer Mice; To Include: - Logitech - HP	

551	Lot of Assorted HP Thin Client / ProDesk Desktop Mini PCs; To Include: - Power Adapter Cables Product#: 691Y9UT#ABA	
552	(2) Intermac PC43t Label Printers; Model#: PC43t	
553	(2) Intermac PC43t Label Printers; Model#: PC43t	
554	(3) Intermac PC43d Label Printer; Model#: PC43d	
555	(2) Zebra GK420d Label Printers; Model#: GK420d	
556	(3) Assorted Label Printers; To Include: - (2) Dymo 550 LabelWriters - (1) Phomemo D520BT Label Printer	
557	Origami Metal Storage Rack, w/ Assorted Power Adapter Cables / Cisco Conference Phones; Dimensions: 36" x 30" x 58"	
558	Origami Metal Storage Rack, w/ Assorted Power Adapter Cables / Zebra DS22 Barcode Scanners; Dimensions: 36" x 30" x 58"	
559	Origami Metal Storage Rack, w/ Assorted Power Adapter Cables; Dimensions: 36" x 30" x 58"	
560	(3) Uline 6138 Heavy Duty Industrial Shelves; To Include: All Contents Dimensions: 36" x 18" x 75"	
561	Sandusky Elite Storage Cabinet with Locking Handle - 36"Wx18"Dx72"H; To Include: All Contents Dimensions: 36" x 18" x 72"	
562	(5) Assorted Backpacks; To Include: - (4) Targus 15.6" Balance EcoSmart Backpacks - (1) HP 6B8Y1AA Laptop Backpac	
563	Lot of Assorted ErgoTron LX Desk Monitor Arm Spare Parts;	
564	Peartington 2-Door Mobile Storage Cabinet; To Include: All Contents Dimensions: 25" x 21" x 41"	
565	(2) Mobile Storage Carts, w/ (2) Assorted Step-Stools;	
566	(3) Assorted Werner Ladders; To Include: - (1) 6' Werner Fiberglass Ladder - (1) 10' Werner Fiberglass Ladder - (1) 20' Werner Fiberglass Ladder	
567	Assorted Lot of Outdoor Maintenance Supplies; To Include: - (1) Lesco Backpack Sprayer (4 gal.) - Assorted Grass/Weed Killer - (2) Buckets of Uline S-14954 Ice Melt, w/ Scoops	
568	(2) Uline Industrial Material Carts; Dimensions: 45" x 25" x 33"	
569	Samsung 65" Monitor, w/ StarTech STNDMTV70 Stand; Model#: BE65T-H	
570	Sony a6100 24.2MP APS-C Mirrorless Camera, w/ Tamron 17 - 70mm F/2.8 Di III-A VC RXD Lens; Resolution: 24.2 megapixels, APS-C Exmor CMOS sensor. 4K Video: UHD 4K () at 24p/25p/30p (100 Mbps max). Processing: 2.4x oversampling, full pixel readout, no pixel binning. Full HD: Up to 120fps for slow motion. ISO Range: 100-32,000 (expandable to 51,200).	
571	Ebmpapst K3G250-PR17-J9 High-Performance EC Centrifugal Fan; Model Series: K3G250 (RadiPac series) Voltage: 380-480 VAC, 3-Phase (50/60Hz) Power Consumption: ~710W - 1160W Speed: Approx. 3400 - 4000 RPM Airflow: High efficiency, with models in this series providing over 2000 Material: Mixed plastics/metal, typically black	
572	Ebmpapst K3G250-PR17-J9 High-Performance EC Centrifugal Fan; Model Series: K3G250 (RadiPac series) Voltage: 380-480 VAC, 3-Phase (50/60Hz) Power Consumption: ~710W - 1160W Speed: Approx. 3400 - 4000 RPM Airflow: High efficiency, with models in this series providing over 2000 Material: Mixed plastics/metal, typically black	
573	Ebmpapst K3G250-PR17-J9 High-Performance EC Centrifugal Fan; Model Series: K3G250 (RadiPac series) Voltage: 380-480 VAC, 3-Phase (50/60Hz) Power Consumption: ~710W - 1160W Speed: Approx. 3400 - 4000 RPM Airflow: High efficiency, with models in this series providing over 2000 Material: Mixed plastics/metal, typically black	
574	Ebmpapst K3G250-PR17-J9 High-Performance EC Centrifugal Fan; Model Series: K3G250 (RadiPac series) Voltage: 380-480 VAC, 3-Phase (50/60Hz) Power Consumption: ~710W - 1160W Speed: Approx. 3400 - 4000 RPM Airflow: High efficiency, with models in this series providing over 2000 Material: Mixed plastics/metal, typically black	
575	Ebmpapst K3G250-PR17-J9 High-Performance EC Centrifugal Fan; Model Series: K3G250 (RadiPac series) Voltage: 380-480 VAC, 3-Phase (50/60Hz) Power Consumption: ~710W - 1160W Speed: Approx. 3400 - 4000 RPM Airflow: High efficiency, with models in this series providing over 2000 Material: Mixed plastics/metal, typically black	

681	(4) Noark Ex9C115 IEC Industrial Contactors; Model#: EX9C115 Frame Size: 115A Poles: 3 Rated Operational Current (AC-3, 400V): 115A Rated Operational Current (AC-1, 400V): 160A Rated Power (AC-3, 400V): 55 kW Auxiliary Contacts: 2NO + 2NC (standard) Coil Voltage Options: Wide range AC/DC (24-600V options) Mounting: 35mm DIN rail or panel mount	
682	(4) Noark Ex9C115 IEC Industrial Contactors; Model#: EX9C115 Frame Size: 115A Poles: 3 Rated Operational Current (AC-3, 400V): 115A Rated Operational Current (AC-1, 400V): 160A Rated Power (AC-3, 400V): 55 kW Auxiliary Contacts: 2NO + 2NC (standard) Coil Voltage Options: Wide range AC/DC (24-600V options) Mounting: 35mm DIN rail or panel mount	
683	(4) Noark Ex9C115 IEC Industrial Contactors; Model#: EX9C115 Frame Size: 115A Poles: 3 Rated Operational Current (AC-3, 400V): 115A Rated Operational Current (AC-1, 400V): 160A Rated Power (AC-3, 400V): 55 kW Auxiliary Contacts: 2NO + 2NC (standard) Coil Voltage Options: Wide range AC/DC (24-600V options) Mounting: 35mm DIN rail or panel mount	
684	(4) Noark Ex9C115 IEC Industrial Contactors; Model#: EX9C115 Frame Size: 115A Poles: 3 Rated Operational Current (AC-3, 400V): 115A Rated Operational Current (AC-1, 400V): 160A Rated Power (AC-3, 400V): 55 kW Auxiliary Contacts: 2NO + 2NC (standard) Coil Voltage Options: Wide range AC/DC (24-600V options) Mounting: 35mm DIN rail or panel mount	
685	(4) Noark Ex9C115 IEC Industrial Contactors; Model#: EX9C115 Frame Size: 115A Poles: 3 Rated Operational Current (AC-3, 400V): 115A Rated Operational Current (AC-1, 400V): 160A Rated Power (AC-3, 400V): 55 kW Auxiliary Contacts: 2NO + 2NC (standard) Coil Voltage Options: Wide range AC/DC (24-600V options) Mounting: 35mm DIN rail or panel mount	
686	(4) Noark Ex9C115 IEC Industrial Contactors; Model#: EX9C115 Frame Size: 115A Poles: 3 Rated Operational Current (AC-3, 400V): 115A Rated Operational Current (AC-1, 400V): 160A Rated Power (AC-3, 400V): 55 kW Auxiliary Contacts: 2NO + 2NC (standard) Coil Voltage Options: Wide range AC/DC (24-600V options) Mounting: 35mm DIN rail or panel mount	
687	Assorted NOARK Ex9S32A4A 32A frame Rotary Handle Manual Motor Starters; Model#: Ex9S32A4A Current Range: 2.5 - 4.0 Amps Frame Size: 32A Protection Type: Thermal-Magnetic Operating Voltage: 600 Vac (UL/CSA), 690 Vac (IEC) Interrupting Rating: High (e.g., up to 65kA at 240Vac/480Y/277Vac) Trip Class: 10	
688	Assorted Noark Ex9CS09D10B 9-Amp (AC-3) Miniature IEC Contactors; Manufacturer: Noark Electric Series: Ex9CS Type: Miniature IEC Contactor (3-Pole) Operating Current (AC-3): 9 A Coil Voltage: 24 Vdc Auxiliary Contacts: 1NO (1 Normally Open) Mounting: 35mm DIN rail or panel Dimensions: Approximately 58mm (H) x 68mm (W) x 45mm (L)	
689	Assorted Noark Ex9CS09D10B 9-Amp (AC-3) Miniature IEC Contactors; Manufacturer: Noark Electric Series: Ex9CS Type: Miniature IEC Contactor (3-Pole) Operating Current (AC-3): 9 A Coil Voltage: 24 Vdc Auxiliary Contacts: 1NO (1 Normally Open) Mounting: 35mm DIN rail or panel Dimensions: Approximately 58mm (H) x 68mm (W) x 45mm (L)	
690	Pallet of Assorted AQ Wiring Harnesses / Safety Current Sensors / MB-Control Fan Devices; Part#: ASHR0343 / ASHR0433 / ASHR0351 To Include: Pallet of Assorted AQ Wiring Harnesses / Safety Current Sensors / MB-Control Fan Devices	
691	Pallet of Assorted AQ Safety-PMX Wiring / CMS- Sensor- Upper Limit / MB-Power Cables, Etc.; Part#: ASHR0353 / ASHR0335 / ASHR0318 To Include: Pallet of Assorted AQ Safety-PMX Wiring / CMS- Sensor- Upper Limit / MB-Power Cables, Etc.	
692	Assorted AQ HPC1 Power-Contactors- AC / Matrix Sharing Cables; Part#: ASHR0324-D / ASHR0343	
693	Pallet of Spooled Rubber Trim; Part#: MEGS0067 N.W: 8.4 kg G.W: 7.1 kg Measurement: 40 x 41 x 26cm	
694	Pallet of Spooled Rubber Trim; Part#: MEGS0068A N.W: 8.4 kg G.W: 7.1 kg Measurement: 40 x 41 x 26cm	
695	Lot of Assorted Electrical Hardware; To Include: - (3) EV Charging Cables	
696	Lot of Assorted Electrical Hardware; To Include: - (2) EV Charging Cables - Boxes of Electrical Wiring	
697	Lot of Assorted Plastic HPC1 Canopies / Status Light Holders; To Include: 8 Pallets	
698	(4) Pallets of Spare Material; To Include: - (4) Pallets of Spare Material	
699	Pallets of Assorted Spare Material; To Include: 5 Pallets of Spare Material	
700	(2) Pallets of Plastic Age Products HPC1-Post-End Caps / UL-CCS1 "Gun Holster"; Part#: MEDS0744 / MEDS0850	
701	(2) Pallets of Assorted Plastic Spare Material; To Include: - Assorted Plastic Spare Material	
702	Lot of Assorted Spare Material; To Include: - 3 Pallets of Spare Materials (Spare Assembly Doors, Ac Panel Assmebly, Shell Assembly Panel)	
703	Pallet of Safety ForkLift Guides; Part#: MEDS0798-P-19 Rev: C PO#: OV2013712 WO#: 367579	
704	Pallet of Safety Forlift Extensions; Part#: MEDS1090-P19	
705	(3) Pallets of Spare Material; To Include: -(3) Pallets of Spare Material (AC Panels, Braces, Brackets, DC Panels, Etc.)	

706	Assorted Spare Material; To Include: - Assorted Spare Material	
707	Assorted Spare Material; To Include: - Assorted Spare Material	
708	Assorted Sized Cardboard Boxes, Rolling / Packing Foam; To Include: - Assorted Sizes (95" x 20" x 7" / 20" x 14" x 10" / 48" x 24" x 12" / 12" x 10" x 8" / 18" x 18" x 14"	
709	FLO AAA-15653 SmartTwo EV Charging Dock / Phoenix Contact Charging Cable; Model#: AAA-15653	
710	FLO AAA-15653 SmartTwo EV Charging Dock / Phoenix Contact Charging Cable; Model#: AAA-15653	
711	FLO CoRe+ Max EV Charging Dock / Harting Charging Cable; Model#: CoRe+ Max	
712	FLO CoRe+ Max EV Charging Dock / Harting Charging Cable; Model#: CoRe+ Max	
713	Assorted Spare Material; To Include: Assorted Spare Material	