

Auction Catalog

Xalt Energy - Day 3 of 6 - XALT Energy | Midland, Michigan Day 3: Lithium-Ion
Battery Manufacturing Lines, Coating & Automation

Auction Date:

Thursday, Apr 02 2026

Bidding Starts: 10:00 AM EDT

BidItUp Auctions Worldwide
1101 E. Tropicana Avenue
Suite 3033
Las Vegas, NV 89119

Phone: (818) 508-7034
Email: auctions@biditup.com

Lot Number	Lot Title & Description	Serial Number
0A	LOT LIST COMING SOON!	
0B	<p>How to Bid: This auction features two distinct bidding formats: one online-only before the live webcast auction and one during the live webcast event.</p> <p>Online-Only Bidding Prior to the live webcast, you can place bids online for the auction lots. This allows you to start the bidding process and potentially win the items before the live event.</p> <p>Proxy Bidding Proxy bidding allows you to submit a maximum bid without participating in the live webcast event. Once your proxy bid is placed, the system will automatically bid on your behalf at the increments specified by the auctioneer.</p> <p>Even if you set a proxy bid, you can still actively participate in the live webcast auction if you choose.</p> <p>Example of Proxy Bidding: Let's say Mr. Smith is interested in bidding on lots 4 and 5 but is unable to attend the live event. He can log in ahead of time, place a maximum bid of \$100 for each lot, and set his proxy bid. If Mr. Jones places a bid of \$25 on lot 4, Mr. Smith's proxy bid of \$100 will place him as the highest bidder at \$50. If no one else bids, Mr. Smith wins the lot at \$50. However, if a bidder during the live webcast places a bid of \$60, Mr. Smith's proxy will automatically increase his bid to \$70.</p> <p>Recommendation: To increase your chances of winning, we suggest setting maximum proxy bids for the lots you're interested in. The system will bid for you up to your max bid. Additionally, you can participate in the live virtual webcast to monitor the auction and increase your max bid if you are outbid.</p> <p>Important Note: You are allowed to bid both online and during the live webcast. If you're approved to bid, you may participate in both the online-only auction and the live virtual webcast auction.</p> <p>Important Auction Tips: Multiple Platforms: This auction is being held on multiple platforms. In the case of a tie bid, the auctioneer may ask for a tie-breaker or award the bid to the last, fastest bidder if the tie is not resolved.</p> <p>Choice Lots: When a lot is offered as a choice, the highest bidder can select one or more items from a grouping at the bid price. The bidder can take as many lots as desired at that price.</p> <p>Line and Piece Meal Lots: Some lots may be offered as a line (bulk lot) or piecemeal (individual pieces). When lots are offered both ways, the highest aggregate sum of the individual bids or the highest bulk bid will determine the winning bid.</p> <p>Tie-Breaking Process: This auction will be held as a simulcast event across multiple platforms. If a tie occurs, the auctioneer will attempt to break the tie. If a tie cannot be resolved, the auctioneer may, at their discretion, award the lot to the last fastest bidder.</p> <p>Bid Button and Increments: When you click the bid button online, your bid will be placed automatically at the increment specified by the auctioneer. Custom bid amounts cannot be entered.</p> <p>By following these guidelines, you can participate in both the online and live auction formats and increase your chances of winning your desired lots. Happy bidding!</p>	

Register 24 hours prior to the start of the auction.

A valid credit card, billing address, office address, email address and company address are required to bid online.

If you have a resale certificate or exemption, please provide a PDF copy to our office so that we may amend your invoice properly. In the email please provide your bidder number, your registration information and the name of the auction. This can be emailed to auctions@biditup.com.

First-time registrants - in order to bid for this auction, you MUST HAVE:

- 1) A deposit, 25% of expected purchases or \$1,000 minimum or
- 2) Be in good standing with other auctions held by members of the Industrial Auctioneers Association or
- 3) Belong to the IAA or MDNA or
- 4) Have successfully bid and picked up at 2+ auctions on bidspotter.com

Form of deposit: wire transfer (for wire instructions, please email customerservice@biditup.com).

Please note, all international bidders, or bidders spending over \$20,000 are required to submit a deposit via wire transfer of 25% of your maximum estimated bid. For example, if you are planning to spend a maximum of \$100,000 at auction, a wire transfer must be sent to us of \$25,000 prior to the sale to allow you to bid.

The same deposit requirement is applied for bidders with negative remarks on Bidspotter. You must provide a 25% deposit of your maximum estimated spend limit to be approved for the sale.

If you have any questions on approval, please email customerservice@biditup.com.

Once you have registered with Bidspotter, and Registered for this Auction, we will be notified. If you are approved, you will receive an approval notification status. If you have not been approved, please call us so we may help you through the process: (818) 508-7034

If you need help with registering for Bidspotter: BidSpotter Customer Service Support Department. Have a question pertaining to the bidding process? Visit our Frequently Asked Questions! You can also start a live chat with a Bidspotter Support Representative by selecting Live Chat at the top of Bidspotter.com. More information on our chat system can be found by clicking here.

Customer Support Hours:

Monday - Thursday, 8:00 AM EST - 10:00 PM EST

Friday, 8:00 AM EST - 6:30 PM EST

Email: support@bidspotter.com

Office: (253) 858-6777

Toll Free: (866) 597-2437 for Frequently Asked Questions

OC

BIDITUP AUCTIONS WORLDWIDE, INC.
BIDDERS BINDING CONTRACT

BIDITUP AUCTIONS WORLDWIDE, INC, HEREIN AFTER REFERRED TO AS BIDITUP, AUCTIONEER AND SELLER. BIDDER HEREIN AFTER REFEREED TO AS BIDDER, REGISTERED BIDDER, PURCHASER, UNDERSIGNED AND BUYER. THIS AUCTION WILL BE CONDUCTED PER THE TERMS AND CONDITIONS BELOW AND SUPERSEDED BY ALL OTHER PROVISIONS, AMENDMENTS, MODIFICATIONS AND ANNOUNCEMENTS ADDED BY AUCTIONEER AT ANYTIME PRIOR TO OR DURING THE AUCTION SALE AND OR AS POSTED ON WWW.BIDITUP.COM. BIDDER HEREBY AGREES AND ACKNOWLEDGES AUCTIONEER IS NOT RESPONSIBLE OR LIABLE FOR BIDDERS ACKNOWLEDGEMENT OF ANY SUCH ANNOUNCEMENTS AND BIDDER ASSUMES ALL RISKS AND LIABILITIES BELOW ONCE IT BIDS.

AUCTIONEER SHALL HAVE THE RIGHT TO MAKE IMAGE AND AUDIO VIDEO RECORDINGS OF THE AUCTION, TO USE SAID RECORDINGS AND IF DEEMED APPROPRIATE IN AUCTIONEERS SOLE DISCRETION TO MAKE THIS PUBLIC. BUYERS HEREBY GIVE THEIR PERMISSION AND CONSENT BY PARTICIPATING IN THE AUCTION.

Auctioneer at its sole discretion may deny entry, registration or bidding at any time to any person or entity. Bidder's paddles and invoices are nontransferable. All bids made by the holder of the bid paddle will be the responsibility of the Registered Bidder, Bidder and the Undersigned. All sales are final and there are no refunds, returns, credits, exchanges or rebids once the Auctioneer knocks down the item or declares it sold to the Bidder.

The Bidder, Registered Bidder, Purchaser, Undersigned and Buyer agree a successful bid at auction constitutes a legally binding contract of sale and this contract is binding upon the Registered Bidders Company, the Bidder, Purchaser, Undersigned and Buyer personally for all amounts due and owing at the conclusion of bidding and time of invoice. BUYER BEWARE AND CAVEAT EMPTOR.

"THE BUYER ALONE IS RESPONSIBLE FOR CHECKING THE QUALITY AND SUITABILITY OF GOODS BEFORE A PURCHASE IS MADE."

Auctioneer makes no representations, warranties, promises, covenants or guarantees, expressed or implied, as to defects in or the completeness or accuracy of the description in any advertising of any item(s) being auctioned and is not responsible for any advertising discrepancies, descriptions, nomenclature or inaccuracies of any kind. ALL ITEMS ARE SOLD ON AN "AS IS, WHERE IS" BASIS AND WITH ALL FAULTS WITHOUT EXCEPTION AND WITH REMOVAL AT BUYERS SOLE RISK AND EXPENSE. THE AUCTIONEER MAKES NO REPRESENTATIONS, WARRANTIES, PROMISES, COVENANTS OR GUARANTEES OF ANY KIND, EXPRESSED OR IMPLIED, AS TO THE NATURE, QUALITY, DURABILITY, CAPABILITY, FUNCTION, PERFORMANCE, VALUE OR CONDITION OF THE ITEM(S) BEING AUCTIONED OR ITS (THEIR) SUITABILITY FOR ANY USE. THE AUCTIONEER EXPRESSLY AND SPECIFICALLY DISCLAIM, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OD

The Undersigned hereby waives, releases, remises, acquits and forever discharges the Auctioneer, and their respective employees, agents, or any other person acting on behalf of the Auctioneer, of and from, and shall indemnify and hold the Auctioneer and their respective employees, agents, or other persons acting on behalf of the Auctioneer and against any claims, actions, causes of action, demands, rights, damages, costs, expenses or compensation whatsoever, direct or indirect, known or unknown, foreseen or unforeseen, which the undersigned now has or which may arise in the future on the account of or in any way growing out of or connected with any defects, latent or otherwise, or the physical condition of any item(s) purchased or any law or regulation applicable thereto. The undersigned specifically waives the provisions of California Civil Code section 1542, which provides: "A general release does not extend to claims which the creditor does not know or suspect to exist in his favor at the time of executing the release, which if known by him must have materially affected his settlement with the debtor."

The Auctioneer encourages the Undersigned to avail itself of the opportunity to make inspections prior to bidding and/or purchasing. The Undersigned hereby acknowledges that it has inspected or voluntarily waived said inspection of all of the items upon which it will be bidding and/or does purchase. Once the Auctioneer knocks down the item or declares it sold to the Bidder, there are no credits, returns, exchanges, refunds or rebidding unless at the Auctioneers sole discretion and such request for rebid is made directly to the Auctioneer and within no more than 5 minutes from the Bidder after the item has been sold. No claim will be considered for allowance or rescission of any sales based upon failure of the property to correspond with any standard expected.

In order to participate in the auction, all Bidders must provide Auctioneer a 25% deposit, in cash, cashier's check or company check accompanied by a bank letter of guarantee of unqualified payment to Auctioneer, or a wire transfer (with a wire transfer fee included) of your maximum expected spending. The final payment in full of Bidders invoice must be received by Auctioneer within the first banking day 24 hours after the auction or the Buyer will be in default of this Contract. The Auctioneer will charge all Bidders a taxable sur charge buyer's premium on its invoice. The Undersigned shall provide proof satisfactory to the Auctioneer of its entitlement to claim exemption from sales tax, which proof must be representative of the same industry as the item(s) that are purchased. In the absence of proof satisfactory to the Auctioneer, the Buyer shall pay all taxes. The Auctioneer will not be responsible for any Department of Motor Vehicle fees, tax, registration, licensing, penalties, smog certificate or fees. Certain vehicles as announced and/or noted in the auction catalogue or on Buyers invoice will be sold "AS IS," with a Bill of Sale only, Each titled item will be charged a \$75 title transfer fee. If available by Auctioneer, titles will be sent to Buyers approximately 7-10 business days after receipt of payment. There will be no refunds if Auctioneer is unable to produce a title. Sales tax on Motor Vehicles is the responsibility of the Buyer to be remitted to its appropriate states Department of Motor Vehicles. All vehicles are sold "AS IS, WHERE IS, WITH NO WARRANTIES EXPRESSED OR IMPLIED." It is the Buyer's responsibility to inspect the vehicle to verify accurate description, model, year, mileage, condition and any and all details pertaining to the vehicle. Auctioneer is not responsible for any inaccuracies of any kind. Credit cards are not accepted.

TERMS AND CONDITIONS CONTINUED...

Auction sales and items are subject to cancellation without prior notice.

The Auctioneer reserves the right to augment this auction with items from additional sellers. These items may be interspersed and not specially identified throughout the auction sale.

The Auctioneer shall regulate all matters relating to the conduct of the auction and the Auctioneer's decisions shall be final and binding on all bidders.

The Auctioneer reserves the right to group, regroup, reduce, add to or delete lots as well as accept or reject any or all bids at the Auctioneer's sole and absolute discretion.

The Auctioneer reserves the right to offer any or all of the items in bulk at any time during the auction at the Auctioneer's sole and absolute discretion.

The Auctioneer shall determine the bidding increments and the Auctioneer may bid on any item(s) to protect its financial interest or indebtedness at its sole and absolute discretion.

Immediately upon the Auctioneer announcing sold or knockdown and the Auctioneer has declared the Undersigned to be the Purchaser, all items comprising of the lot become the sole and absolute responsibility of the Undersigned and the Undersigned shall thereupon and thereafter assume all risk of loss (including, but not restricted to loss by way of theft or damage) and liability relating to such items. The Undersigned is advised to pre-arrange insurance coverage for its purchases as there will be no refunds for missing, lost, damaged or stolen items unless and only at the Auctioneers sole discretion. The Auctioneer shall in no event be liable to the Purchaser for non-delivery of any item(s) for any reason except for the return to the Buyer of the deposit or other sums paid for such non delivered items. This non-delivery period extends from the knock down until the time allotted for the removal process concludes. In no event will the Auctioneers liability to the Undersigned exceed the amount actually paid by the Undersigned. THE UNDERSIGNED HEREBY ACKNOWLEDGES AND AGREES THAT THE AUCTIONEER SHALL NOT BE LIABLE FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL DAMAGES.

Title to and possession of the item(s) shall not pass to the Undersigned until the Auctioneer has received payment for all items duly purchased in full. All items and the entirety of the Purchasers invoice require payment in full prior to Auctioneer releasing any items. If all the items are not paid in full by Purchaser for any reason, and Purchaser has provided Auctioneer any monetary consideration, Auctioneer will retain all the items and the monetary consideration paid by Purchaser to mitigate Auctioneers financial damages caused by Purchaser. If after the subsequent mitigation amounts (if any) received by Auctioneer exceed the amount of the Purchasers invoice and below, the auctioneer will refund such amounts to the Purchaser once determined by Auctioneer in its sole discretion. The Purchaser hereby agrees items purchased at this auction will be invoiced in totality, although in some cases separately priced on the invoice, the total amount due Auctioneer of the Purchasers invoice is deemed a single contract if in the event of a legal dispute.

If for any reason the Undersigned fails to pay the full amount of its invoice within the first banking day 24 hours after the auction, and/or fails to remove all of its items on or before the date posted on Purchasers invoice, and/or fails to comply with any other terms and conditions of this Contract, all the items on the Purchasers invoice will be considered abandoned and the Auctioneer in its sole discretion and without further notice to Purchaser may remove, dispose of, scrap, resell at public or private sale any or all the items and the Undersigned hereby agrees to pay to Auctioneer any monetary mitigation deficiency and costs as a result thereof, including all removal, rent, lay and hold over fees. The bidder understands and acknowledges that there is sufficient consideration by both parties to perform, and that if payment in full is not made within the specific time outlined in the contract, the bidder is agreeing to be bound by a "consent judgment" and is violation and in default of contract. By signing below you are consenting to the terms of a judgment entered against you and are waiving your rights to any court hearing. In addition, relating to such disposition together with all charges, including attorney, court and legal fees, interest and any and all other expenses in connection with such disposition, plus a \$500.00 per diem administrative fee per item until such item(s) is (are) removed.

The Undersigned agrees that the Auctioneer may retain all deposits previously received and apply such deposits to any such deficiency without further notice to Purchaser. Purchaser hereby agrees that "time is of the essence" in regards to this Contract regarding payment of its invoice and removal of its items. For purposes of clarity, Purchaser further acknowledges and agrees Auctioneer will be monetarily damaged for the subsequent disposal of any item(s) for any reason and that the Purchaser will be responsible to pay Auctioneer for all of the above and any other such monetary mitigation deficits, damages known and unknown, and any and all other cost to Auctioneer to collect and enforce this Contract. Any monetary deficiencies to the Auctioneer become the debt of the Undersigned.

This Agreement shall be construed and interpreted according to the laws of the State of California. The Bidder further agrees to have Burbank California as the Forum City & State in the event any lawsuit is initiated by either party. If any action based on the performance, breach or interpretation of this Agreement is brought, the prevailing party in such action (as determined by the court or other body having jurisdiction) shall be entitled to recover from the losing party all actual costs and expenses of litigation or arbitration, including attorney's fees, court costs, costs of investigation, and other costs related to such proceeding.

AUCTIONEER DOES NOT WARRANT THAT THE FUNCTIONS, FEATURES OR CONTENT CONTAINED IN THE ONLINE OR WEBCAST BIDDING PLATFORM OR SOFTWARE, INCLUDING ANY THIRD-PARTY SOFTWARE, PRODUCTS OR OTHER MATERIALS USED IN CONNECTION WITH THE WEBSITE OR BIDDING WILL BE TIMELY, SECURE, UNINTERRUPTED OR ERROR-FREE, OR THAT DEFECTS WILL BE CORRECTED. AUCTIONEER RESERVES THE RIGHT TO ACCEPT AND OR REJECT AND OR REMOVE ANY ELECTRONIC BIDS FOR ANY REASON AT ANY TIME IN ITS ABSOLUTE SOLE DISCRETION. BIDDER AGREES ALL OF ITS ELECTRONIC BIDS ARE BINDING REGARDLESS OF ORDER AND OR TIME IN WHICH THEY ARE ACCEPTED OR REJECTED.

OE

OF	<p>TERMS AND CONDITIONS FOR DISCONNECT AND REMOVAL: All electrical disconnect, liquid removal, rigging, loading, broom cleaning, trash & debris removal, floor stud removal and transportation are the sole and absolute responsibility of the Undersigned. The undersigned agrees to remove its purchases in full, with no abandonment privileges from the premises on or before the date on the Buyers invoice. No item(s), no matter how small, may be removed while the auction is in progress. Representatives of the Auctioneer at the Auctioneer's sole discretion may stay one hour after the auction is completed for the removal of small items. All small subject to disappear items must be removed by 4:00 PM on the day following the auction. The Undersigned must present the Auctioneers personnel with proof of valid workers compensation insurance and a commercial general liability insurance certificate in a minimum amount of \$2,000,000.00 combined single limit per occurrence coverage naming the Auctioneer, the Seller and the Landlord as additional insured. If available at Auctioneers sole and absolute discretion, bridge cranes and hoist may be used by the Undersigned if crane insurance is included on the above certificate and only with the written permission of the crane owner. Should any pits, floor bolts or hazards of any type exist after removal of equipment, it is the responsibility of the Undersigned, at its cost, to reasonably safe guard these areas using generally accepted safety practices, such as safety tapes, pipes or bars welded in place or suitable safety barriers acceptable to the Auctioneer. All floor bolts and/or anchoring fasteners are to be cut flush to the floor and the area left broom clean and all debris removed. It is the responsibility of the Undersigned to be sure that the power to the item(s) is off and then to safely disconnect all electrical wiring and utility piping from the item(s) and to cap at the first electrical or air junction of the item(s). Item(s) are to be staged for loading in the area assigned by the Auctioneer's personnel. It is the Undersigned's responsibility to secure all safety equipment to meet all applicable government safety standards in using or removing any items purchased. Certain items may contain residual chemicals and/or hazardous materials. The Undersigned hereby agrees to indemnify and hold harmless the Auctioneer from any and all damages, claims or liabilities from any injuries to persons or property of any type whatsoever caused by the Undersigned, its agents, employees or contractors during the sale or during the removal, use or operation of the purchased item(s). Any hydraulic fluid removal and/or oil leaks are the Undersigned's responsibility to remove and clean up. The Undersigned must take full responsibility for compliance with applicable environmental laws and exercise all reasonable care to ensure that there is no release to the environment of any hazardous wastes or substances as defined in applicable Federal, State and Local Statues, Regulations, Rules or Ordinances. No trucks are to be left running in an enclosed building. The Auctioneer is not liable for personal belongings left on premises. Any surface or structural damage to the premises including but not limited to the walls, ceilings, floors, overhead doors, gates and/or any other item(s), etc. will be the Undersigned's sole responsibility. The Undersigned will not be permitted to leave with its purchases until repairs are made. Theft will not be tolerated and Auctioneer reserves the right to inspect all trucks, toolboxes and rigger cases, etc. Instances of theft will result in immediate termination of removal privileges and full prosecution by law. All quantities must be checked prior to removal, as adjustments will not be made thereafter. These terms and conditions together with any amendments or modifications, expressly made by the Auctioneer at the time of the auction constitute all the terms and conditions with respect to the sale of items at this auction. There are no representations, warranties, terms, conditions, undertakings or collateral agreements except as hereinabove provided I acknowledge that I have provided BidItUp Auctions Worldwide, Inc. a signed check for which I am the authorized signatory for all purposes, without restriction, sufficient to pay this negotiable instrument upon demand. I authorized BidItUp to obtain my financial information from any source and complete the check as necessary for the amount of my invoice at the auction to be presented for payment. I agree to pay all cost of collections including attorney's fees, to pay interest at the rate of 18%, unless prohibited by law, and in such case at the highest amount permitted by law from the date of issuance of this check if dishonored by a financial institution, to waive any requirement of presentment, to the exclusive jurisdiction of the executed Auction Bidders Agreement for any dispute relating to this instrument. A credit instrument is identical to a personal check. Willfully drawing or passing a credit instrument knowing there are insufficient funds in an account upon which may be drawn, or with the intent to defraud, is a crime which may result in criminal prosecution.</p>	
OG	<p>IMPORTANT PAYMENT INFORMATION Thank you for your interest in our Auction Event! Please see the below information regarding payment. Invoices will be sent out 24 hours AFTER the close of the auction. PAYMENT Payment is due 48hrs after invoices have been released - \$250 fee may apply to late payments Invoices paid with card will incur a 3.5% additional processing fee Card Payments: ONLY USE IF PAYING WITH CREDIT CARD OR DEBIT CARD MAX LIMIT OF \$2,500 (additional 3.5% card processing fee) Wire Payments: if paying by wire Please note if you send us the incorrect payment amount and require a reimbursement, a \$100 fee will apply WE DO NOT ACCEPT ACH - if you send us an ACH, a \$100 fee will apply Methods of payment: Credit/ Debit Card (includes 3.5% convenience fee) Wire Transfer TAXES/ TAX EXCEPTIONS International bidders: NO EXCEPTIONS: You must pay the full amount due. Once we receive a "Bill of Lading" after shipment, we will refund your taxes via ACH/Wire. Please note it is the bidder's responsibility to provide bank information to process the ACH/Wire. Domestic Bidders: Please complete the tax form provided by our accounting team and return to auctions@biditup.com. Once received and approved, tax will be removed from your invoice. Please note, it is the bidder's responsibility to provide tax exemption information.</p>	
OH	<p>Removal will be by appointment ONLY. There will be a link in your invoice to create an appointment- please note all appointments must be made AFTER procesing payment successfully. DO NOT SCHEDULE AN APPOINTMENTIF YOU HAVE NOT RECEIVED A PAID IN FULL INVOICE FROM ACCOUNTING.</p>	

3000	Anode Mixing Entirety	
3001	2011 Kokam Anode PD Mixer (PD1); 2011 Kokam Anode PD Mixer Model: KM-J300-DK-04 Serial:DK-PDA-1110-01 W/ Siemens Simatic HMI IPC477C Pro	
3002	Kokam Anode PD2 Tank Mixer With Lift Tower ; Mechine Name : Cathode PD Mixer Tank Model Name : KM-J300-DK-04 Serial Number DK~POC-1110-01 Weight 1100Kg - PD800002~ Size : 41,080 W, 800H Year of Manufacture :2011 Model Name : KM-J300-DK-04 Serial number : DK-PDA-1110-02 Weight:~13000Kg Size : 2,800 x 5,600 x 3,600 (WxHxD) PD800005 - HIGH SPEED MOTOR : 37Kw,4P,460V/60Hz LOW SPEED MOTOR : 37Kw,4P,460V/60Hz HYDRAULIC MOTOR :5.5Kw,4P, 460V /60Hz Year of Manufacture : 2011	
3003	Kokam Anode Polishing Tank (PT1); 2011 Kokam Anode Polishing Tank Model: KM-J300-DK-04 Serial: DK-PTA-1110-01 Capacity: 779L W/ Mitsubishi Graphic Operation Terminal GOT1000 HMI	
3004	Kokam Anode Polishing (PT) Tank ; Model#: KM-J300-DK-04 SN#: DK-PTA-1110-02 Date of Mfg: 2011 Capacity: F. 779L Weight: 5,900 Kg Size: 1,840 W, 3,800 H, 2,700 D High Speed Motor: 11Kw, 4P, 460V, 60Hz Low Speed Motor: 5.5Kw, 4P, 460V, 60Hz Hydraulic Motor: 1.5Kw, 4P, 460V, 60Hz	
3005	Kokam Anode Slurry Storage (SS) Tank ; Model#: KM-J300-DK-04 SN#: DK-STA-1110-01 Date of Mfg: 2011 Capacity: F. 779L Weight: 5,300 Kg Size: 1,650 W, 3,800H, 2,510D Low Speed Motor: 5.5Kw, 4P, 460V, 60Hz Hydraulic Motor: 1.5Kw, 4P, 460V, 60Hz	
3006	Kokam Anode Slurry Storage (SS) Tank ; Model#: KM-J300-DK-04 SN#: DK-STA-1110-02 Date of Mfg: 2011 Capacity: F. 779L Weight: 5,300 Kg Size: 1,650 W, 3,800H, 2,510D Low Speed Motor: 5.5Kw, 4P, 460V, 60Hz Hydraulic Motor: 1.5Kw, 4P, 460V, 60Hz	
3007	Industrial Vacuum System; This heavy-duty Industrial Vacuum System is engineered for high-capacity material handling and demanding filtration requirements. Designed as a turnkey solution, it combines superior suction power with an integrated Filter Chamber to ensure maximum particulate separation and pump protection. The system features a dedicated Air Blast function—ideal for automated filter cleaning via reverse-pulse technology or pressurized material discharge—ensuring continuous operation without manual downtime. Completed with a high-efficiency Exhaust Assembly, the unit operates with reduced noise levels and clean air output, meeting strict industrial workplace standards. Key Feature: Multi-stage filtration for fine dust and heavy debris. Performance: Seamless transition between high-vacuum intake and air-blast discharge. Durability: Heavy-duty housing designed for 24/7 industrial environments.	
3008	Industrial Vacuum System; This heavy-duty Industrial Vacuum System is engineered for high-capacity material handling and demanding filtration requirements. Designed as a turnkey solution, it combines superior suction power with an integrated Filter Chamber to ensure maximum particulate separation and pump protection. The system features a dedicated Air Blast function—ideal for automated filter cleaning via reverse-pulse technology or pressurized material discharge—ensuring continuous operation without manual downtime. Completed with a high-efficiency Exhaust Assembly, the unit operates with reduced noise levels and clean air output, meeting strict industrial workplace standards. Key Feature: Multi-stage filtration for fine dust and heavy debris. Performance: Seamless transition between high-vacuum intake and air-blast discharge. Durability: Heavy-duty housing designed for 24/7 industrial environments.	
3009	Ross FDA-0300 Binder Mixer ; Model:FDA-0300, S/n: 109372C, With Mitsubishi GOT1000 Controller	
3009A	Marathon motor and Waukesha 074-015 pump; The Marathon KVD254THFNA is a 7.5 HP, 1200 RPM, 3-Phase severe duty electric motor. It is specifically designed for high efficiency and reliability in harsh industrial environments. Attached to this motor is a Waukesha 074-015 pump requires an electric motor typically in the range of 0.75 HP to 1.5 HP, depending on the desired flow rate and operating pressure of your specific application.	
3009B	Raychem T-100 Binder Valve System	
3009C	Siemens Simatic HMI IPC477C Pro; Siemens Simatic HMI IPC477C Pro	
3010	Industrial Temperature Controller ; With Mokon DP4448QS, 460v 3-Phase	
3011	DigiTrace 920 Series Heat Traci g Controller Assembly ; Model: 920*E14FWQ1*SIS320*SS3120, S/n: 134651400, 277V 1-Phase	
3012	Gladwin Tank MFG V-1310 Slurry Binder Holding Tank; Stainless Steel; Agitator Powered by 7HP Marathon Motor; Accord Controls UltraSwitch DNF-3ET1N Flow Meter; Air Torque Actuator; 168 PSIG Test Pressure; 3,900 lbs Empty Weight; S/N 2864	
3012A	Marathon 7.5HP Motor and Viking MagDrive Pump; Model: KVD254THFNA9076BDL; 1175 RPM; 460V; S/N C0073468-04/07-02	
3012B	Endress + Hauser Promass 80 Flow Meter; Dust-Ignition Proof; 20-55VAC / 16-62VDC, 15VA/W, 60Hz; S/N E6009B16000	
3013	Industrial Temperature Controller ; With Mokon DP4448QS, 460v 3-Phase	
3014	Graco Husky 1590 Pump W/ Air Filter; Graco Husky 1590 Air Operated Double Diaphragm Pump W/ Top-Flo Valves and Rosedale Products Filter Model: MC4-12-2P-*500-SVNPBD	
3015	Graco Husky 1590 Air Operated Double Diaphragm Pump ; Graco Husky 1590 Air Operated Double Diaphragm Pump Part No. 084311 W/ Top-Flo Valves	

3016	Graco Husky 1590 Air Operated Double Diaphragm Pump ; Graco Husky 1590 Air Operated Double Diaphragm Pump Part No. 084311 W/ Top-Flo Valves	
3017	Graco Husky 1590 Pump / Filtration Unit	
3018	Graco Husky 1590 Pump / Filtration Unit	
3019	Graco Husky 1590 Pump / Filtration Unit	
3020	Total Water Pretreatment / RO Skid; Powered by WEG 3HP Motor S/N SO2151-EP-240226-01	
3021	Total Water High Purity Softening Skid; Aquifine Optivenn UV Monitoring System and Chamber; (2) GrundfosX 98572757-P1-2425 Pumps; Shelco MicroGaurdian Filter S/N SO2151-EP-240226-02	
3022	Aqueous Slurry Vacuum De-aeration and Recovery System. ; This system was built by Highland Equipment in December 2024. The Ultimate Solution for Precision Binder Processing Engineered specifically for water-based chemistries (CMC, PAA, SBR), this integrated vacuum system is designed to handle the unique challenges of aqueous binder systems. It provides the high-suction power required for rapid de-aeration while protecting your hardware from moisture and particulate carryover. Bubble-Free Slurry: Achieve superior de-aeration for smoother coatings and higher-density electrodes. Extended Pump Life: The advanced filtration chamber shields the pump from moisture-induced corrosion and binder clogs. Turnkey Integration: Designed for seamless connection to industrial mixers, coating lines, and drying ovens.	
3022A	Emerson micro motion flow sensor; The Emerson Micro Motion CMF100M328N2B2E3ZZ is a high-performance ELITE Series Coriolis mass flow and density meter designed for demanding industrial applications requiring highly accurate and repeatable measurement of liquids, gases, or slurries. Model: CMF100 (ELITE Peak Performance Flow and Density Meter). Wetted Parts Material: M (316L Stainless Steel), offering corrosion resistance for a wide range of fluids. Line Size: 1-inch (DN25) process connections, a common size for industrial process lines. Pressure Rating: 1450 psig (100 barg) maximum working pressure. Flow Accuracy (Liquid): Standard $\pm 0.10\%$ of rate. Density Accuracy: Standard $\pm 0.0005 \text{ g/cm}^3$ ($\pm 0.5 \text{ kg/m}^3$).	
3022B	Baldor motor with attached S.S pump; heavy-duty Baldor 25 HP Explosion Proof Severe Duty Motor. This motor is designed for hazardous environments like chemical plants, oil and gas facilities, and wastewater treatment plants. Horsepower (HP) 25 HP @ 60 Hz Voltage 230/460 V (also 190/380 V at 50Hz) RPM (Speed) 3520 RPM @ 60 Hz Phase 3 Phase Frame Size 284TSCY Enclosure XPFC (Explosion-Proof Fan Cooled) Material Cast Iron construction IP Rating IP55 Weight 525 lbs Hazardous Area Certification UL and CSA certified for Class 1, Division 1, Groups C & D, and Class 2, Division 1, Groups E, F, & G locations.	
3022C	Bauer motor with SPX pump; Bauer BG Series Helical Geared Motor designed for versatile industrial applications. BG40 Gearbox Series & Size Helical geared motor, size 40. 11W Mounting & Shaft Type Likely a foot or flange mounting option with specific output shaft characteristics. D11LA4 Motor Type & Power A specific motor frame designation, typically indicating a 4-pole motor. AV Voltage/Frequency Option Indicates a specific winding for a standard mains connection (110V to 690V, 50/60Hz). C1 Corrosion Protection Specifies the lowest level of corrosion protection, suitable for indoor, very low environmental pollution areas according to DIN ISO 12944-5. The SPX pump model O15-UTS is a sanitary, positive displacement Waukesha Universal Twin Screw (TS) Series pump, designed primarily for hygienic applications in the food, beverage, dairy, and pharmaceutical industries. Model O15-UTS (Universal Twin Screw) Max Operating Speed Up to 3500 RPM Max Differential Pressure Up to 375 PSI (25.5 bar) Temperature Range -40°F (-40°C) to 300°F (149°C) Port Sizes 1.5" body port, 2" cover port Wetted Materials 316L Stainless Steel body, cover, and shaft; Waukesha "88" non-galling alloy screws Displacement per Revolution 0.04 gallons (0.15 liters) Approximate Weight 87 lb (39 kg)	
3022D	Emerson micro motion flow sensor; The Emerson Micro Motion CMF100M328N2B2E3ZZ is a high-performance ELITE Series Coriolis mass flow and density meter designed for demanding industrial applications requiring highly accurate and repeatable measurement of liquids, gases, or slurries. Model: CMF100 (ELITE Peak Performance Flow and Density Meter). Wetted Parts Material: M (316L Stainless Steel), offering corrosion resistance for a wide range of fluids. Line Size: 1-inch (DN25) process connections, a common size for industrial process lines. Pressure Rating: 1450 psig (100 barg) maximum working pressure. Flow Accuracy (Liquid): Standard $\pm 0.10\%$ of rate. Density Accuracy: Standard $\pm 0.0005 \text{ g/cm}^3$ ($\pm 0.5 \text{ kg/m}^3$).	
3023	2011 Kokam Anode MIXER 2 Control Panel System (P11-P16) ; Model#: KM-J300-DK-04 SN#: DK-MA-1110-02 Date of Mfg: 2011 Rated Voltage: 460 VAC, 3 Phase, 60Hz Pneumatic Power: 5kg/cm ² Rated Current: 210A Current Max: 227A Capacity: 9.6 KVA Weight: 1,800 Kg Size: 4,800 W, 1,950 H, 600 D P11: Disconnection Panel P12: Inverter Panel 1 P13: Inverter Panel 2 P14: Inverter Panel 3 P15: PLC Panel P16: Barrier Panel	
3024	Kokam Anode MIXER 2 Control Panel System (P11-P16) ; Model#: KM-J300-DK-04 SN#: DK-MA-1110-01 Date of Mfg: 2011 Rated Voltage: 460 VAC, 3 Phase, 60Hz Pneumatic Power: 5kg/cm ² Rated Current: 210A Current Max: 227A Capacity: 9.6 KVA Weight: 1,800 Kg Size: 4,800 W, 1,950 H, 600 D	
3025	2012 Brabender Technology Bag Dump Station; 2012 Brabender Technology Bag Dump Station (Anode Line 1) Serial: WO18746/1 W/ Brabender Bag Dump Station Frame Serial: WC18746/1	
3026	2012 Brabender Technology Bag Dump Station; Includes Bag Dump Station, Bag Dump Tower, DDW-MS6-FW80/5Plus-200 ISC Stainless Vibrating Chute, MFG: 2012	
3027	Glovebox w/Allen Bradley E-Stop Control Panel; To Include: SacMaster Bulk Bag Discharge System	
3028	Super Sack Dump Station; This system is specifically designed to safely and efficiently unload bulk materials (powders, solids, grains, etc.) from large flexible intermediate bulk containers (FIBCs), or "super sacks". The system works by supporting the bag with a forklift or hoist system, sealing the bag spout to the hopper inlet and using the glove box to facilitate a safe, contained material transfer into a downstream process, such as a pneumatic conveyor or mixer.	

3029	SchenkAccuRate Mechatron Volumetric/Gravimetric Anode Vibration Feeder; Model#: MODMC-IG-1A SN#: 149574-01A-MECGM Empty Weight: 348lbs	
3030	SchenckAccuRate Anode Vibration Feed Hopper ; Schenck PES-17238 Load Cell, SchenckAccuRate MechaTron Feeders	
3031	Donaldson Torit Delta P Plus; The Donaldson Torit Delta P Plus is a solid-state electronic controller used for monitoring and managing the filter cleaning systems on industrial dust collectors. It is not a type of motor, but rather part of the control panel automation. Monitors Differential Pressure: It continuously measures and displays the pressure drop (Delta P, or (Delta P)) across the dust collector filters, indicating their condition.Automates Cleaning: The controller is programmed with high and low pressure setpoints. When the pressure reaches the high limit (filters are dirty), it automatically triggers the "air blast" or reverse pulse cleaning cycle to clean the filters. The cleaning stops when the low limit is reached.Cleaning Modes: The "Plus" model specifically offers three cleaning modes: differential pressure cleaning, down-time cleaning (cleaning after the main fan shuts off), and a combination of both.Alarm Function: It includes an alarm output to alert operators if filter conditions fall outside of safe parameters.	
3032	Mitsubishi HMI; The Mitsubishi GOT1000 is a series of Graphic Operation Terminals (GOT), which are industrial Human-Machine Interface (HMI) touch-panel displays used to monitor and control automated machinery.	
3033	Mettler Toledo Scale Meter and Mitsubishi HMI; Mettler Toldeo IND560 Harsh Floor Scale Meter [FLOOR MUST BE PATCHED IF YOU REMOVE SCALE] Mitsubishi Electric GOT2000 HMI Operator Panel	
3034	Star Crane & Hoist/Harrington 2 Ton Electric Chain Crane ; Max Lift Capacity: 4000lbs These use an electric motor for powered lifting and lowering, offering much faster and less strenuous operation. Capacity 2 Tons (4,000 lbs) Voltage Standard 208-230V / 460V Three-Phase Lifting Speed Varies, typically 8 to 14 FPM (feet per minute) Duty Rating H4 Heavy Duty or 60-minute duty rating Brake System Electromagnetic "Smart Brake" with failsafe design	
3035	Harrington chain lift; These use an electric motor for powered lifting and lowering, offering much faster and less strenuous operation. Capacity 2 Tons (4,000 lbs) Voltage Standard 208-230V / 460V Three-Phase Lifting Speed Varies, typically 8 to 14 FPM (feet per minute) Duty Rating H4 Heavy Duty or 60-minute duty rating Brake System Electromagnetic "Smart Brake" with failsafe design	
3036	Speedair hose reel; The Speedaire model 31XG63 is a heavy-duty, spring-return hose reel designed for use with both air and water. Drive Type Spring Return Hose Length 75 feet Hose Inside Diameter 1/2 inch I.D. Max Operating Pressure 300 psi Hose Material PVC (Polyvinyl Chloride) Reel Material Steel, powder-coated green for corrosion resistance Fittings 1/2 inch MNPT (Male National Pipe Thread) brass fittings Mounting Location Adjustable for bench, cart, ceiling, floor, truck, or wall mounting	
3037	Speedair hose reel; The Speedaire model 31XG63 is a heavy-duty, spring-return hose reel designed for use with both air and water. Drive Type Spring Return Hose Length 75 feet Hose Inside Diameter 1/2 inch I.D. Max Operating Pressure 300 psi Hose Material PVC (Polyvinyl Chloride) Reel Material Steel, powder-coated green for corrosion resistance Fittings 1/2 inch MNPT (Male National Pipe Thread) brass fittings Mounting Location Adjustable for bench, cart, ceiling, floor, truck, or wall mounting	
3038	Anode Mixing PLC Control Panel and Components; PanelMatic Enclosure; Mitsubishi Q63P PLC Board [Modules: (1) Q13UDEHCPU0, (1) Q12DCCPU-V, (1) QJ1E71-100, (3) Q64AD-GH, (1) Q68DAIN, (2) QY10, (1) QY80]; (2) Phoenix Contact Quint-PS/1AC/24DC/20 DIN Rail Power Supplies; Misc. AB, Vincotech, Phoenix Components	
3039	Lot of (3) Barcode Scanner Systems ; Hand held scanner, CanaKit Multi-port, Elecrow Display	
3040	Paint Booth ; Paint Booth 208" x 291" x 136"	
3041	Stainless Pressurable Mixing Tank	
3042	Pressure pot with Parker air motor; The Parker TAM4-030S is a Taiyo Radial Piston Air Motor, which is a compact, pneumatic motor that runs on compressed air instead of electricity. The pot is stainless steel and approximately a 20 gallon capacity, 2' tall and 2' diameter.	
3043	Pressure pot with Parker air motor; The Parker TAM4-030S is a Taiyo Radial Piston Air Motor, which is a compact, pneumatic motor that runs on compressed air instead of electricity. The pot is stainless steel and approximately a 20 gallon capacity, 2' tall and 2' diameter.	
3044	Graco Quantm i80 Pump; Part#: TE80-0004 SN#: FK24A5017 Max WPR: 100-7 Weight: 110lbs	
3045	(2) Rittal Control Panels	
3046	Miscellaneous industrial supplies ; This lot contains miscellaneous supplies such as 1" chemical resistant hose at approximately 10', stainless steel pipe fittings and painting supplies.	
3047	Stainless steel work bench and contents; This lot contains a stainless steel work bench and all contents pictured. These contents include graco air diaphragm pump, air actuated valves and actuators. Work bench measurements- 30" deep x 6' long x 33" tall.	
3048	Lyon 30 Gal. Flammable Storage Cabinet ; Model#: 5440 Capacity: 30 Gal. Dimensions: Approx. 43" x 18" x 44"	
3049	Contents of Drawer ; To Include: Chemraz and Jamesbury Parts and Valves, SS Fittings, Clamps	

3050	Contents of Drawer; To Include: Assorted Size Tri-Clamps (1.5", 2", 3",4.5"),	
3051	Content of Drawer; Includes: Assorted T-Shape and 90 Degree Elbow Flanged SS Fittings	
3052	Contents Of Drawer; To Include: U-line Polly Bags, Gaskets, Hose, Screen Filter	
3053	Contents of Drawer; To Include: Pall Corporation Filter, (2) Kitz Rack-and-Pinion Actuator, Spit-Lock Washers, Bolts, Cables, Brush Heads, Extension Cords, Etc.	
3054	Contents of Drawer; To Include: HFT 30' Retractable Cord Reel, Vacuum Attachments, Scott Pressure Gauges, Bolts, Valves, Etc.	
3055	Contents of Drawer; To Include: Bearings, Hose Head, Washers, Gauges, Etc.	
3056	Contents of Drawer ; To Include: O-Rings, Connectors, Cables, Rods, Bearings, Etc.	
3057	Metal rack with miscellaneous industrial supplies ; This lot contains a 6.5' tall x 4' wide x 2' deep metal rack with (6) shelves. Contents on shelf are a variety of stainless steel pipe fittings. *cabinet pictured is not included *	
3058	Metal rack with miscellaneous industrial supplies ; This lot contains a 6.5' tall x 4' wide x 2' deep metal rack with (3) shelves. Contents on shelf are a variety of hoses and stainless steel fittings. *cabinet pictured is not included *	
3059	RIDGID work box ; The RIDGID 2048-OS work box (also known as the 48 in. Universal Storage Chest) is a heavy-duty, steel jobsite storage box with a capacity of 16 cubic feet, designed for securing tools on construction sites, in trucks, or in garages. This lot contains miscellaneous hoses, extension cords, caulk, tape and S.S hardware.	
3060	Dayton Floor Scrubber ; Dayton Walk Behind Floor Scrubber Model: 40PM20	
3061	Utility pumps; This lot contains (2) utility pumps. These can be used to drain washing machines and other applications. 5/8" garden hose fitting connection. Includes (1) extra impeller, gasket and hose with puddle vac.	
3062	Heavy duty valves; This lot contains (2) heavy duty valves. These valves are air actuated.	
3063	(4) V Head Pipe Stand ; (3) Westward V Head Pipe Stand 2500lbs Model: 22XR01	
3064	Graco Husky 1050; Husky 1050 Air-Operated Double Diaphragm Transfer Pump	
3065	Dewalt 60v Brushless Power Cleaner Model: DCPW1000	
3066	Heavy-Duty Stronghold 2-Door Steel Wardrobe Cabinet ; Model: .46-WR-241G, Dimensions: 48" W x 24" D x 78" H	
3067	Heavy-Duty Stronghold 2-Door Steel Wardrobe Cabinet ; Model: .46-WR-241G, Dimensions: 48" W x 24" D x 78" H	
3068	Rack With Contents ; To Include: MISC SS Flanged Parts, Valves, T-Filters, Tri-Straps, Elbows, and Hardware, Rack Dimensions: 78" x 24" x 77" (HxDxW)	
3069	Global Upright Storage Locker 1-Unit; Dimensions: 12" x 18" x 78" (WxDxH)	
3070	Justrite 21 Gallon Oil Waste Can ; Model: 09700 Red	
3071	Stainless Steel Table No Content 6' x 29" x 34"	
3072	Westward 5 Drawer Rolling Tool Cabinet	
3073	Metal standup work station; This lot contains a steel stand up work station from global industrial. It measures- 2' deep x 2' wide x 6.5' tall. This stand has a built in metal peg board and comes with a variety of PPE.	
3074	NSF Metal Table ; **Contents Not Included**	
3075	Optima OP-902 Digital Weight Indicator ; Model#: OP-902	
3076	Sumner Projack Tri-Pod Stand; Capacity: 2500lbs, Max Height: 49"	

3077	Aluminum rack with miscellaneous supplies; This lot contains an aluminum rack that is 69" tall x 2' deep x 6' long. Contents included are galvanized super strut, EMT conduit, (2) metal folding chairs, (2) small pieces of copper tubing, "floor wet" sign, S.S strut and plate.	
3078	Drum handler ; high-performance drum handling attachments and portable lifting systems. These units are designed to safely lift, transport, and stack 30, 55, or 85-gallon drums made of steel, plastic, or fiber. They utilize a "Parrot-Beak" or automatic clamping mechanism that grips the drum's top lip without requiring hydraulic or electrical connections. Standard single-drum units handle roughly 750 to 1,000 lbs	
3079	Engine hoist; The Torin Big Red 2-ton engine hoist is a heavy-duty, hydraulic, and foldable shop crane designed for safely lifting engines and other heavy components with a capacity of up to 4,000 lbs. It features a telescoping boom and six swivel casters for maneuverability. Capacity 2 Tons (4,000 lbs / 1814 kg) Construction Heavy-duty, high-grade steel Power Source Hydraulic (via an 8-ton long vertical ram jack) Lift Range Approximately 1 inch to 90 inches Boom Positions Four adjustable positions (0.5-ton, 1-ton, 1.5-ton, and 2-ton capacities) Casters Six 360-degree swiveling steel casters for mobility Design Foldable for easy storage	
3080	Harrington 3 Ton Hoist; Model CF4 Code CF030 3 Ton Hook	
3081	2016 Jungheinrich Electric Pallet Hand Truck; Type: 24V 2 PZB 150 SN#: G00693360 Date of Mfg: 2016 Nominal Voltage: 24 Number of Cells: 12 Capacity: 150Ah Weight: 151 kg	
3082	IPC Floor Scrubber; IPC Eagle CT15 14" Battery Operated Automatic Scrubber with On-Board Charger	
3083	Rock River Job Site Storage	
3084	Eagle Acid and Corrosive Storage Cabinet Model- CRA-1925; Eagle Acid and Corrosive Storage Cabinet Model- CRA-1925 (No Content)	
3085	Storage Shelf (No Content)	
3086	Global Industrial Metal Work Station; This lot contains a steel stand up work station from global industrial. It measures- 2' deep x 2' wide x 6.5' tall. This stand has a built in metal peg board. **Contents Included**	
3087	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3088	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3089	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3090	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3091	HAFCOVAC Pneumatic 55-Gallon Drum Vacuum	
3092	Polytron has detector ; The Dräger Polytron 2 XP is an explosion-proof fixed gas detector transmitter for continuous monitoring of combustible gases/vapors or toxic gases and oxygen in ambient air. Gases Detected Combustible gases (LEL), Oxygen ((text{O}_{2})), and various toxic gases (e.g., (text{H}_{2}text{S}), CO, (text{Cl}_{2}), (text{NH}_{3})).Sensing Principle Uses either catalytic bead, infrared (IR), or electrochemical (EC) sensors depending on the specific model variant. Output Signals 4 to 20 mA analog, plus digital HART and RS-485 interface for communication.Power Supply 10 to 32 VDC (3-wire) or 12 to 30 VDC	
3093	Dräger Polytron 2 XP Tox Toxic Gas Detector ; Sensor Type: Electrochemical (EC) for toxic gases Output Signals: 4-20 mA (analog), HART, and RS-485 (digital). Operating Voltage: 10 to 32 VDC. Relays (Optional): 3 relays (2 for gas alarms, 1 for fault). Relay Ratings: 250VAC/30VDC, 5A. Display: 2-line, 20-character backlit LCD	
3093A	Drager Toxic Gas Detector Model: Polytron 2 XP	
3094	8' Werner Fiberglass Ladder	
3095	6' Werner Fiberglass Ladder	
3096	12' Werner Fiberglass Ladder	

3097	8' Werner Fiberglass Ladder	
3098	6' Werner Fiberglass Ladder	
3099	Slurry Binder Powder Feed Systems ENTIRETY [Lots 3100-3106]	
3100	Coperion SacMaster Bulk Powder Bag Discharge Station; Powder Bag Discharge Station w/ Glove Box for Complete Discharge	
3101	2011 Schenck AccuRate MODMC-1G-1A Vibrating Powder Feed Funnel; Full Vibration Plate, Controls Included; S/N 149574-03A-MECGM	
3102	Hapman Screw Conveyor Powder Feeding System; Hapman System for Powder Feeding, Components: -Helix Flexible Screw Conveyor -Hapman Glove Box -Baldor Motor for Feeder Head S/N X17228 A0	
3103	Mitsubishi GOT1000 HMI; Mitsubishi Operator Terminal and Wall Mount Arm	
3104	Harrington 2 Ton Hoist ; Spring Balanced Hook; Pendant Included	
3105	Speedaire 31XG63 Hose Reel ; 1/2" 75' Hose, 300 Max PSI	
3106	Binder Mix/Solids PLC Control Panel; (2) Mitsubishi Base Units (1) Model: Q38DB, and (1) Model: Q68B, (2) Mitsubishi Melsec model: Q63P Module, (1) Q13UDEHCPU, (1) Q12DCCPU-V, (1) QJ71E71-100, (7) Q64AD-GH, (1) Q68DAIN, (1) QX80, and (1) QY10 Module (2) Phoenix Contact Quint Power Order Number: 2866776	
3107	Pall Series Filter Assemblies; These assemblies are designed for medium and light hydraulic and lubrication fluids in industrial and mobile OEM applications. Pressure Rating: Maximum acceptable working pressure of 6,500 psi (450 bar). Flow Capacity: Can handle flows up to 70 gpm (265 L/min). Port Sizes: Available in 1" and 1-1/4" ports. Construction: Features a forged steel bowl and ductile iron head for high fatigue resistance (rated per NFPA/T2.6.1-1991). Element Technology: Uses Ultipor® III or coreless filter elements with high collapse pressure ratings.	
3108	Dräger Polytron 2 XP Tox Toxic Gas Detector ; Sensor Type: Electrochemical (EC) for toxic gases Output Signals: 4-20 mA (analog), HART, and RS-485 (digital). Operating Voltage: 10 to 32 VDC. Relays (Optional): 3 relays (2 for gas alarms, 1 for fault). Relay Ratings: 250VAC/30VDC, 5A. Display: 2-line, 20-character backlit LCD	
3109	Nilfisk GM 60 Wet/Dry Vac; 110/120V; Caster Wheels	
3110	12' Louisville Fiberglass Ladder ; Capacity: 300 lbs	
3111	True-Arc 4-Step Platform Ladder; Capacity: 500lbs, Platform: 36" x 36"	
3112	Hoffman Server Rack ; Consist of (1) Commscope Uniprise Switch (1) Cisco IE 3010 Switch (1) APC UPS (1) Sola Portable Regularor MCR500	
3113	Hoffman IT Enclosure and Components; Contents: -Cisco IE 3010 Network Switch -Uniprise Cat 5E -Malcom VIP LLE	
3114	Cathode Mixing Entirety	
3115	2011 Kokam Cathode PD Mixer (PD1); 2011 Kokam Cathode PD Mixer Model: KM-J300-DK-04 Serial:DK-PDA-1110-022011 W/ Siemens Simatic HMI IPC477C Pro	
3116	Kokam Cathode PD2 Mixer Tank with Tower ; Machine Name : Cathode PD Mixer Model Name : KM-J300-DK-04 Serial number : DK-PDC-1110-02 Weight: ~ 13000Kg, Size : 2,800 W, 5,600 H, 3,600 D - PD800003 - HIGH SPEED MOTOR : 37Kw,4P, 460V/60Hz LOW SPEED MOTOR : 37Kw,4P,460V/60Hz, HYDRAULIC MOTOR:5.5Kw,4P,460V/60Hz Year of Manufacture: 2011	
3117	2011 Kokam Anode Polishing (PT) Tank ; Model#: KM-J300-DK-04 SN#: DK-PTC-1110-01 Date of Mfg: 2011 Capacity: F. 779L Weight: 5,900 Kg Size: 1,840 W, 3,800 H, 2,700 D High Speed Motor: 11Kw, 4P, 460V, 60Hz Low Speed Motor: 5.5Kw, 4P, 460V, 60Hz Hydraulic Motor: 1.5Kw, 4P, 460V, 60Hz W/ Mitsubishi GOT1000 HMI	
3118	Kokam Cathode PT2 Mixer Tank with Tower; Machine Name: Cathode Polishing Tank Model Name KM-J300-DK-04 Serial Number :DK-PTC-1110-02 CAPACITY : F. 779L Weight: ~5,900Kg Size : 1,340 W. 3,800 H, 2,700 D HIGH SPEED MOTOR : 11Kw, 4P,460V/60Hz, LOW SPEED MOTOR : 5.5Kw,4P, 460V/60Hz, HYDRAULIC MOTOR : 1.5Kw,4P,460V/60Hz Year of Manufacture: 2011	
3119	2011 Kokam Cathode Slurry Storage Caninet ; Model: KM-J300-DK-04 Serial: DK-STC-1110-10 Capacity: 779L	
3120	2011 Kokam Cathode Slurry Storage Caninet ; Model: KM-J300-DK-04 Serial: DK-STC-1110-02 Capacity: 779L	

3121	Industrial Vacuum System; This heavy-duty Industrial Vacuum System is engineered for high-capacity material handling and demanding filtration requirements. Designed as a turnkey solution, it combines superior suction power with an integrated Filter Chamber to ensure maximum particulate separation and pump protection. The system features a dedicated Air Blast function—ideal for automated filter cleaning via reverse-pulse technology or pressurized material discharge—ensuring continuous operation without manual downtime. Completed with a high-efficiency Exhaust Assembly, the unit operates with reduced noise levels and clean air output, meeting strict industrial workplace standards. Key Feature: Multi-stage filtration for fine dust and heavy debris. Performance: Seamless transition between high-vacuum intake and air-blast discharge. Durability: Heavy-duty housing designed for 24/7 industrial environments.	
3122	Industrial Vacuum System; This heavy-duty Industrial Vacuum System is engineered for high-capacity material handling and demanding filtration requirements. Designed as a turnkey solution, it combines superior suction power with an integrated Filter Chamber to ensure maximum particulate separation and pump protection. The system features a dedicated Air Blast function—ideal for automated filter cleaning via reverse-pulse technology or pressurized material discharge—ensuring continuous operation without manual downtime. Completed with a high-efficiency Exhaust Assembly, the unit operates with reduced noise levels and clean air output, meeting strict industrial workplace standards. Key Feature: Multi-stage filtration for fine dust and heavy debris. Performance: Seamless transition between high-vacuum intake and air-blast discharge. Durability: Heavy-duty housing designed for 24/7 industrial environments.	
3123	Kokam Cathode Mixing Control Panel System (P11-P16); Model#: KM-J300-DK-04 SN#: DK-MA-1110-02 Date of Mfg: 2011 Rated Voltage: 460 VAC, 3 Phase, 60Hz Pneumatic Power: 5kg/cm ² Rated Current: 210A Current Max: 227A Capacity: 9.6 KVA Weight: 1,800 Kg Size: 4,800 W, 1,950 H, 600 D P11: Disconnection Panel P12: Inverter Panel 1 P13: Inverter Panel 2 P14: Inverter Panel 3 P15: PLC Panel P16: Barrier Panel	
3124	Kokam Cathode Mixing Control Panel System (P11-P16); Model#: KM-J300-DK-04 SN#: DK-MA-1110-02 Date of Mfg: 2011 Rated Voltage: 460 VAC, 3 Phase, 60Hz Pneumatic Power: 5kg/cm ² Rated Current: 210A Current Max: 227A Capacity: 9.6 KVA Weight: 1,800 Kg Size: 4,800 W, 1,950 H, 600 D P11: Disconnection Panel P12: Inverter Panel 1 P13: Inverter Panel 2 P14: Inverter Panel 3 P15: PLC Panel P16: Barrier Panel	
3125	Industrial Temperature Controller ; With Mokon DP4448QS, 460v 3-Phase	
3126	Graco Husky 1590 Pump W/ Air Filter; Graco Husky 1590 Air Operated Double Diaphragm Pump W/ Top-Flo Valves and Rosedale Products Filter Model: MC4-12-2P-*-500-SVNPBD	
3127	Graco Husky 1590 Pump W/ Air Filter; Graco Husky 1590 Air Operated Double Diaphragm Pump W/ Top-Flo Valves and Rosedale Products Filter Model: MC4-12-2P-*-500-SVNPBD	
3128	Graco Husky 1590 Pump W/ Air Filter; Graco Husky 1590 Air Operated Double Diaphragm Pump W/ Top-Flo Valves and Rosedale Products Filter Model: MC4-12-2P-*-500-SVNPBD	
3129	Graco Husky 1590 Pump W/ Air Filter; Graco Husky 1590 Air Operated Double Diaphragm Pump W/ Top-Flo Valves and Rosedale Products Filter Model: MC4-12-2P-*-500-SVNPBD	
3130	Graco Husky 1590 Air Operated Double Diaphragm Pump; Graco Husky 1590 Air Operated Double Diaphragm Pump W/ Filter and Valves	
3131	Graco Husky 1590 Air Operated Double Diaphragm Pump; Graco Husky 1590 Air Operated Double Diaphragm Pump	
3132	2012 Brabender Technology Bag Dump Station; Includes Bag Dump Station, Bag Dump Tower, DDW-MS6-FW80/5Plus-200 ISC Stainless Vibrating Chute, MFG: 2012	
3133	2012 Brabender Technology Bag Dump Station; Includes Bag Dump Station, Bag Dump Tower, DDW-MS6-FW80/5Plus-200 ISC Stainless Vibrating Chute, MFG: 2012	
3134	2012 Brabender Bag Dump Station ; 2012 Brabender Bag Dump Station Serial: W018746/3 W/ 2012 Brabender Bag Dump Frame Serial: W018746/3	
3135	2012 Brabender Bag Dump Station ; 2012 Brabender Bag Dump Station Serial: W018746/4 W/ 2012 Brabender Bag Dump Frame Serial: W018746/4	
3136	Super Sack Dump Station; This system is specifically designed to safely and efficiently unload bulk materials (powders, solids, grains, etc.) from large flexible intermediate bulk containers (FIBCs), or "super sacks". The system works by supporting the bag with a forklift or hoist system, sealing the bag spout to the hopper inlet and using the glove box to facilitate a safe, contained material transfer into a downstream process, such as a pneumatic conveyor or mixer.	
3137	2012 Schenck Accurate Mechatron Feeder; Type: MODMC-IG-2A Serial: Z1M100028	
3138	Super Sack Dump Station; This system is specifically designed to safely and efficiently unload bulk materials (powders, solids, grains, etc.) from large flexible intermediate bulk containers (FIBCs), or "super sacks". The system works by supporting the bag with a forklift or hoist system, sealing the bag spout to the hopper inlet and using the glove box to facilitate a safe, contained material transfer into a downstream process, such as a pneumatic conveyor or mixer.	
3139	2012 SchenckAccuRate Mechatron Volumetric/Gravimetric Anode Vibration Feeder; Type#: MODMC-IG-2A SN#: 1100206128-10B-MECGM Empty Weight: 348lbs Date of Mfg: 2012	
3140	Glovebox w/Allen Bradley E-Stop Control Panel; To Include: SacMaster Bulk Bag Discharge System	
3141	SchenckAccuRate Anode Vibration Feed Hopper ; Schenck PES-17238 Load Cell, SchenckAccuRate MechaTron Feeders	

3142	Glovebox w/Allen Bradley E-Stop Control Panel; To Include: SacMaster Bulk Bag Discharge System	
3143	SchenckAccuRate Anode Vibration Feed Hopper ; Schenck PES-17238 Load Cell, SchenckAccuRate MechaTron Feeders	
3144	Harrington chain lift; These use an electric motor for powered lifting and lowering, offering much faster and less strenuous operation. Capacity 2 Tons (4,000 lbs) Voltage Standard 208-230V / 460V Three-Phase Lifting Speed Varies, typically 8 to 14 FPM (feet per minute) Duty Rating H4 Heavy Duty or 60-minute duty rating Brake System Electromagnetic "Smart Brake" with failsafe design	
3145	Harrington chain lift; These use an electric motor for powered lifting and lowering, offering much faster and less strenuous operation. Capacity 2 Tons (4,000 lbs) Voltage Standard 208-230V / 460V Three-Phase Lifting Speed Varies, typically 8 to 14 FPM (feet per minute) Duty Rating H4 Heavy Duty or 60-minute duty rating Brake System Electromagnetic "Smart Brake" with failsafe design	
3146	Harrington chain lift; These use an electric motor for powered lifting and lowering, offering much faster and less strenuous operation. Capacity 2 Tons (4,000 lbs) Voltage Standard 208-230V / 460V Three-Phase Lifting Speed Varies, typically 8 to 14 FPM (feet per minute) Duty Rating H4 Heavy Duty or 60-minute duty rating Brake System Electromagnetic "Smart Brake" with failsafe design	
3147	Harrington chain lift; These use an electric motor for powered lifting and lowering, offering much faster and less strenuous operation. Capacity 2 Tons (4,000 lbs) Voltage Standard 208-230V / 460V Three-Phase Lifting Speed Varies, typically 8 to 14 FPM (feet per minute) Duty Rating H4 Heavy Duty or 60-minute duty rating Brake System Electromagnetic "Smart Brake" with failsafe design	
3148	Donaldson Torit Major Solids Feeder/Dust Collector, w/ Donaldson Torit Delta P Plus Downtime Clean ; Donaldson Torit Cathode Major Solids Feeder, w/ Donaldson Torit Delta P Plus Downtime Clean and Mitsubishi GOT1000 HMI	
3149	Mitsubishi Electric GOT2000 Graphic Operation Terminal HMI, w/ Mettler Toledo IND560 Weighing Terminal & Floor Scale; Mettler Toldeo IND560 Harsh Floor Scale Meter [FLOOR MUST BE PATCHED IF YOU REMOVE SCALE] Mitsubishi Electric GOT2000 HMI Operator Panel	
3150	Paint Booth; Paint Booth 208" x 291" x 136"	
3151	(3) Elecrow Screens W/ CanaKit Raspberry Pi 4 Board Computer	
3152	Hoffman Wall Server Cabinet ; W/ Uniprise Cat5E Switch (2) Cisco IE 3010	
3153	(2) Mitsubishi Base Units W/ Modules; (1) Mitsubishi Base Unit Model: Q38DB, (1) Mitsubishi Base Unit Model: Q65B, (2) Melsec Q63P, (1) Q12DCCPU-V, (1) QJ71E71-100, (1) Q64AD-GH, (1) Q68DAIN, (1) QX80, (3) QY10, (1) Q68ADI And (2) Phoenix Contact Quint Power Order-No 2866776	
3154	Control Station For Brabender Bag Dump Station	
3154A	Control Station For Brabender Bag Dump Station	
3155	INOUE PDF-50 PD Mixer; S/n: PD300005, MFG: 2010	
3156	XDry Corp 2-Door Tall Dry Cabinet; Model#: XD2-702-01 Rated voltage: AC110V Operating frequency: 50/60Hz Power consumption: Max 410W Ave 39.6W Temperature Fuse: 184°C Serial No.: XD2-702-100224-03 Capacity: 700 Liters RH Range: 1% - 50% (maintains low, controllable humidity) Dimensions (External): 620 x 1840 x 780mm Dimensions (Internal): 610 x 1560 x 730mm Weight: 115 kg Power Consumption: 63W, 700W, Voltage: Available in 110V or 220V, 50/60 Hz Compliancy: IPC/JEDEC J-STD-033 and J-STD-020 Shelving: 5 stainless steel shelves included (adjustable)	
3157	Purair hood vent; The Purair P40 is a specific model within the Air Science Purair Advanced Series of ductless fume hoods, a type of self-contained laboratory enclosure designed to protect users and the environment from hazardous vapors. Safety & Protection: Provides high operator protection from fume and particle hazards by using a robust multi-stage filtration system. Filtration: Utilizes Air Science's Multiplex Filtration Technology, which allows for a variety of specific filters (e.g., GP Plus for solvents/organics, ACID for inorganic acids, or HEPA/ULPA for particulates) to be installed depending on the specific chemicals used. Airflow Monitoring: Features a continuous air velocity monitoring system and a filter blockage alarm to alert the operator to unsafe conditions. Construction: Typically made with an epoxy-coated steel or optional polypropylene construction with clear side and back panels. Energy Efficiency: As a ductless system, it recirculates filtered air back into the room, which eliminates the need for external ductwork and reduces HVAC energy costs. Power requirements, 120vac, attached power cord.	
3158	Sartorius scale; Sarorius is a leading global provider of high-precision weighing technology, primarily used in laboratory research, pharmaceutical manufacturing, and industrial quality control.	
3159	portable bench weighing scale; The Adam Equipment LBK 65a is a compact, portable bench weighing scale designed for laboratory and industrial applications such as basic weighing, parts counting, and percentage weighing. Maximum Capacity: 65 lbs / 30 kg Readability: 0.01 lb / 5 g Weighing Units: g, kg, lb, oz, lb:oz Pan Size: 9.8" x 7.1" / 250 mm x 180 mm, made of stainless steel Display: Large, green backlit LCD display Power: AC adapter and internal rechargeable battery (providing approx. 70-90 hours of operation) are included. 120vac power requirement.	
3160	Eagle 16 Gallon Flammable Storage Cabinet ; Model: 1906	

3161	SCE Poly Hazardous Materials Storage Caninet; Dimensions: 12"x16"x15.5" (WxDxH)	
3162	File cabinet; Steel file cabinet with (4) drawers. Measurements- 42" wide x 20" deep x 50" tall. * No contents included, file cabinet only*	
3163	File cabinet; Steel file cabinet with (4) drawers. Measurements- 42" wide x 20" deep x 50" tall. * No contents included, file cabinet only*	
3164	Metric Rack of Assorted Items; To Include: Latex Gloves, Wypall Cloth Rags, Aluminum Containers, Red Metal Containers, Bowls, Etc.	
3165	3-Drawer File Cabinet; Dimensions: 15"x22"x27" (WxDxH)	
3166	Steel rack with miscellaneous industrial supplies ; This lot contains industrial supplies such as - aluminum pipe fittings, (13) stainless steel filters, valves, (2) boxes of plastic sheeting and a metal rack. Rack measurements- 33" wide x 2' deep x 66" tall. Sitting on 3" caster wheels for easy transportation.	
3167	Shop vac; The Cat C06V is a durable, stainless steel wet/dry shop vacuum with a 6.6-gallon capacity and powerful suction, ideal for job sites, workshops, and general facility cleaning. Capacity 6.6 gallons Peak Horsepower 3.5 HP Suction Power 115 CFM (cubic feet per minute) Water Lift 78 inches Tank Material Stainless Steel Hose Length 8.2 feet	
3168	Pressure Pot; The pot is stainless steel and approximately a 20 gallon capacity, 2' tall and 2' diameter.	
3169	Stainless Steel Tank	
3170	Stainless Steel Tank	
3171	Pressure pot with Parker air motor; The Parker TAM4-030S is a Taiyo Radial Piston Air Motor, which is a compact, pneumatic motor that runs on compressed air instead of electricity. The pot is stainless steel and approximately a 20 gallon capacity, 2' tall and 2' diameter.	
3172	Graco diaphragm pump; This lot contains a Graco 1050 refers to the Graco Husky 1050 Air-Operated Double Diaphragm (AODD) Pump, a robust industrial pump designed for efficient fluid transfer in applications like chemical handling, oil transfer, and general manufacturing. It is not a paint sprayer. This pump comes with a S.S enclosure and transport cart.	
3173	Shelving of Assorted Flanged Fittings, T-Fittings, Manual Valves, Etc. ; To Include: Magnet Filters, Transition Pipes, Filter Housings, Clamps, Manual Valves, Air Valves, Hosing, Etc.	
3174	Elma X-Tra 550 LSM Industrial Ultrasonic Cleaner; Model#: D-78224 Singer SN#: 199985061 Power Supply: 220-240V, 1700W, 50/60Hz	
3175	Graco Husky 1590 Air Operated Double Diaphragm Pump ; Maximum Fluid Pressure: 120 psi (8.4 bar) Maximum Flow Rate: 100 GPM (378.5 LPM) Fluid Inlet/Outlet Size: 1-1/2 inch (38.1 mm) NPT or ANSI Flange Max Air Consumption: 125 scfm Air Inlet Size: 1/2 inch npt(f) Max Solids Size: 0.1875 inch (4.8 mm) Weight: Approx 38.5 lbs (varies by material) Maximum Suction Lift: 18 ft (5.4 m)	
3176	Graco Husky 1590 Air Operated Double Diaphragm Pump ; Maximum Fluid Pressure: 120 psi (8.4 bar) Maximum Flow Rate: 100 GPM (378.5 LPM) Fluid Inlet/Outlet Size: 1-1/2 inch (38.1 mm) NPT or ANSI Flange Max Air Consumption: 125 scfm Air Inlet Size: 1/2 inch npt(f) Max Solids Size: 0.1875 inch (4.8 mm) Weight: Approx 38.5 lbs (varies by material) Maximum Suction Lift: 18 ft (5.4 m)	
3177	(3) Regency NSF Tables, w/ Assorted Materials; To Include: Wrenches, Hammers, Trays, Screwdrivers, Bottles, Valves, Funnels, Latex Gloves, Plastic Bins, Tough Guy Wipes, Rods, Spare Parts, Etc.	
3178	Global Pump Rebuild Workbench Station; Overall Dimesions:	
3179	Heavy-Duty Stronghold 2-Door Steel Wardrobe Cabinet ; Model: .46-WR-241G, Dimensions: 48" W x 24" D x 78" H	
3180	Global Industrial Metal Work Station; This lot contains a steel stand up work station from global industrial. It measures- 2' deep x 2' wide x 6.5' tall. This stand has a built in metal peg board. **Contents Included**	
3181	Hoffman Server Rack ; To Include: CommScope Uniprise CAT5E, (2) Cisco IE 3010, Valcom VIP-LLE, Cisco IP Phone Power Injector	
3182	RIDGID 2048OS Jobsite Storage Chest; Dimensions:48 in (W) x 24 in (D) x 28 in (H)	
3183	Lyon 30 Gal. Flammable Storage Cabinet ; Model#: 5440 Capacity: 30 Gal. Dimensions: Approx. 43" x 18" x 44" * This lot does not include contents*	
3184	File cabinet; Steel file cabinet with (4) drawers. Measurements- 42" wide x 20" deep x 50" tall. * No contents included, file cabinet only*	

3185	Spill kit; The PIG Spill Kit (KIT217) is a 16-gallon universal mobile spill kit designed for rapid response to spills of oils, coolants, solvents, and water in industrial settings. It comes in a gray cart with eight-inch wheels for easy mobility. Absorbency Up to 16 gallons Container Type Mobile cart with swing-out doors and 8-inch rubber wheels Fluid Absorbed Oils, coolants, solvents, water (universal) Color Gray (hides grime and blends in with industrial environments) Mobility Narrow width to fit through standard doors and aisles Security Lockable for added security	
3186	Parts cleaning machine; The Chicago Electric Power Tools 94702 is a 20-gallon capacity, electric-pump parts washer designed for use with non-corrosive, water-based cold cleaning solvents. It is not a heated machine. Tank Capacity 20 gallons Solvent Capacity Approximately 12 gallons of working fluid is recommended Power Source Corded-electric (120V, 60Hz, 0.23A) Max Flow Rate 5.25 GPM (Gallons Per Minute), or 20 Liters per minute Construction Formed 18-gauge sheet steel Dimensions 21.5" L x 31" W x 34.5" H (lid closed)	
3187	NSF steel work bench; commercial-grade product that meets strict public health and safety standards, making it ideal for food preparation or sanitary environments like hospitals and laboratories. *contents not included in lot*	
3188	Justrite 21 Gallon Oil Waste Can ; Model: 09700 Red	
3189	Westward 5 Drawer Rolling Tool Cabinet	
3190	Stainless Steel Table No Content 6' x 29" x 34"	
3191	Lot of Assorted Lockers, w/ Assorted Spare Aluminum Fittings; To Include: Tensco, Global Industrial	
3192	Lockers; This lot contains (2) 3-locker sets. Measurements of both lockers are 6' tall x 3' wide x 1' deep. * contents not included in lot*	
3193	Dräger Polytron 2 XP Tox Toxic Gas Detector ; Sensor Type: Electrochemical (EC) for toxic gases Output Signals: 4-20 mA (analog), HART, and RS-485 (digital). Operating Voltage: 10 to 32 VDC. Relays (Optional): 3 relays (2 for gas alarms, 1 for fault). Relay Ratings: 250VAC/30VDC, 5A. Display: 2-line, 20-character backlit LCD	
3194	8' Werner Fiberglass Ladder; 8' ladder made by Werner. "A" frame, fiberglass and Aluminum steps.	
3195	6' Werner Fiberglass Ladder	
3196	Dayton floor buffer; The Dayton 40PM20 is a walk-behind floor scrubber (not a floor buffer) with a 17-inch cleaning path, designed for efficient and thorough cleaning of commercial and industrial hard floors. Product Type Floor Scrubber Style Walk-Behind, pad-assisted drive Power Source 120V AC, 60Hz (corded, 66 ft cord) Cleaning Path Width 17 inches Solution Tank Capacity 13 gallons Recovery Tank Capacity 11 gallons Max. Productivity 12,700 sq ft/hr Brush Speed 160 RPM Sound Level 70 dB	
3197	Drum handler ; high-performance drum handling attachments and portable lifting systems. These units are designed to safely lift, transport, and stack 30, 55, or 85-gallon drums made of steel, plastic, or fiber. They utilize a "Parrot-Beak" or automatic clamping mechanism that grips the drum's top lip without requiring hydraulic or electrical connections. Standard single-drum units handle roughly 750 to 1,000 lbs	
3198	Mobile Wire Rack W/ Content	
3199	JUSTRITE Oily Waste Can	
3200	(3) Drum Dollies	
3201	Plastic Pallet And Contents; Includes: Chair, Pallet, Bins, Parts	
3202	Rigid 16-Galloon Blower Vac; 6.5 peak HP	
3203	Nilfisk GM-80 HEPA Vacuum - 3-1/4 Gallon Cap.; Filtration: 4-stage system including a 2.25-gallon paper bag, main filter, microfilter, and HEPA/ULPA exhaust filter. Design: Aluminum container with a wheeled trolley for mobility. Performance: 110-120V motor, 1100 watts, 102" water lift, and 87 cfm airflow. Versatility: Suitable for hazardous dust (lead, silica) and sensitive environments like museums or labs.	
3204	Nilfisk GM 80 Industrial Canister Vacuum; Lightweight aluminum canister vacuum with 4stage filtration	
3205	Nilfisk GM 80 Industrial Canister Vacuum; Lightweight aluminum canister vacuum with 4stage filtration	
3206	IPC Floor Cleaner ; Model: CT15 B35+CB, S/n: 80000509039, MFG: 2023	

3207	Dayton floor buffer; The Dayton 40PM20 is a walk-behind floor scrubber (not a floor buffer) with a 17-inch cleaning path, designed for efficient and thorough cleaning of commercial and industrial hard floors. Product Type Floor Scrubber Style Walk-Behind, pad-assisted drive Power Source 120V AC, 60Hz (corded, 66 ft cord) Cleaning Path Width 17 inches Solution Tank Capacity 13 gallons Recovery Tank Capacity 11 gallons Max. Productivity 12,700 sq ft/hr Brush Speed 160 RPM Sound Level 70 dB	
3208	Jungheinrich Electric Pallet Hand Truck; Type: 24V 2 PZB 150 SN#: 80854154 Date of Mfg: 2016 Nominal Voltage: 24 Number of Cells: 12 Capacity: 150Ah Weight: 151 kg	
3209	Drum cart; a low-profile, circular platform with casters designed for moving 55-gallon drums easily and safely in industrial settings.	
3210	Waterloo ProMaxx Mobile Tool Chest ; This toolbox comes with some tools and PPE. Bottom drawer is bent but still functions correctly. Measurements-18" deep x 27" wide x 32" tall. Box is on casters.	
3211	RIDGID Universal Storage Chest; Dimensions: 48" W x 24" D x 28" H Construction: 16-gauge steel with fully welded seams Storage Volume: 16 cu. ft. Weight: 149 lbs Security: Corner-located lock housing, accepts #5 padlocks, and features a solid lock tang to prevent pry-ins Mobility: Recessed ergonomic handles and 12-gauge steel skids Interior: One 8-inch adjustable shelf/bin, locking cover support **Contents Included**	
3212	8' Werner Fiberglass Ladder	
3213	6' Werner Fiberglass Ladder	
3214	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3215	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3216	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3217	Troemner precision weight; The Troemner 5 kg weight is a precision calibration weight available in various accuracy classes and materials. Weight: 5 kg (11 lbs approx.) Material: Typically high-grade 316 or 303 stainless steel, or Troemner Alloy 8. Design: Cylindrical shape, often with a handling knob or groove, two-piece construction with an internal adjusting cavity. Accessories: Usually includes a protective case	
3218	3M 4-Slot TR-944N Li-Ion Recharble Battery Docking Charge Station ; Model#: TR-944N/TR-944E SN#: 4A1-90296 Input /Output: 19VDC, 7.89A	
3219	3M 4-Slot TR-944N Li-Ion Recharble Battery Docking Charge Station ; Model#: TR-944N/TR-944E SN#: 4A1-90331 Input /Output: 19VDC, 7.89A	
3220	3M 4-Slot TR-944N Li-Ion Recharble Battery Docking Charge Station ; Model#: TR-944N/TR-944E SN#: 4A1-90322 Input /Output: 19VDC, 7.89A	
3221	Lot of (5) 3M TR-340 Lithium Ion Battery Chargers; To Include: (5) 3M Lithium Ion Battery Chargers	
3222	Tote ; This is a Sterilite 45 gallon tote. This tote has some PPE content.	
3223	File cabinet; Steel file cabinet with (4) drawers. Measurements- 42" wide x 20" deep x 50" tall. * contents included*	
3224	File cabinet; Steel file cabinet with (4) drawers. Measurements- 42" wide x 20" deep x 50" tall. * contents included*	
3225	Tall cabinet ; This lot contains a (6) shelf cabinet that stands 6' tall x 2' deep x 3' wide. * this lot contains Some PPE equipment*	
3226	Lockers; This lot contains (6) 3-locker sets. Measurements of both lockers are 6' tall x 3' wide x 1' deep. * contents not included in lot*	
3227	Allegro PAPR Wall Storage Cabinet 32" X 18" x 12"	
3228	PAPR Storage Cabinet ; Dimensions: 32"x18"x12" (HxWxD)	
3229	Steel shelf rack; This steel rack has (4) shelves and sits on 3" caster wheels. Measurements-2' deep x 61" wide x 6' tall. * This lot comes with contents*	

3230	Whirlpool Freezer/Refrigerator ; Model: ETOMSRXTB01, MFG:2010	
3231	Living Accents #FS5-45B Standing Fan; 120V, 0.55A	
3232	Woodtop Desk; NO Contents; 71"x37"x30" (WxDxH)	
3233	Zebra ZT410 Label Printer; Prints 4" Labels; S/N 18J200100393	
3234	Beech 1000LBS Crane; Beech Engineering Premium Hydraulic Floor Crane B-1000 1000 Lb. Capacity	
3235	3M Versaflo M300 Series Respiratory Helmet; Lightweight, integrated headtop providing eye, face, and respiratory protection with high airflow, wide visibility, and compatibility with Versaflo PAPR systems	
3236	3M Versaflo M300 Series Respiratory Helmet; Lightweight, integrated headtop providing eye, face, and respiratory protection with high airflow, wide visibility, and compatibility with Versaflo PAPR systems	