

Auction Catalog

Xalt Energy - Day 6 of 6 - XALT Energy | Midland, Michigan Day 6: Lithium-Ion
Battery Manufacturing Lines, Coating & Automation

Auction Date:

Wednesday, Apr 08 2026

Bidding Starts: 10:00 AM EDT

BidItUp Auctions Worldwide
1101 E. Tropicana Avenue
Suite 3033
Las Vegas, NV 89119

Phone: (818) 508-7034
Email: auctions@biditup.com

Lot Number	Lot Title & Description	Serial Number
0A	LOT LIST COMING SOON!	
0B	<p>How to Bid: This auction features two distinct bidding formats: one online-only before the live webcast auction and one during the live webcast event.</p> <p>Online-Only Bidding Prior to the live webcast, you can place bids online for the auction lots. This allows you to start the bidding process and potentially win the items before the live event.</p> <p>Proxy Bidding Proxy bidding allows you to submit a maximum bid without participating in the live webcast event. Once your proxy bid is placed, the system will automatically bid on your behalf at the increments specified by the auctioneer.</p> <p>Even if you set a proxy bid, you can still actively participate in the live webcast auction if you choose.</p> <p>Example of Proxy Bidding: Let's say Mr. Smith is interested in bidding on lots 4 and 5 but is unable to attend the live event. He can log in ahead of time, place a maximum bid of \$100 for each lot, and set his proxy bid. If Mr. Jones places a bid of \$25 on lot 4, Mr. Smith's proxy bid of \$100 will place him as the highest bidder at \$50. If no one else bids, Mr. Smith wins the lot at \$50. However, if a bidder during the live webcast places a bid of \$60, Mr. Smith's proxy will automatically increase his bid to \$70.</p> <p>Recommendation: To increase your chances of winning, we suggest setting maximum proxy bids for the lots you're interested in. The system will bid for you up to your max bid. Additionally, you can participate in the live virtual webcast to monitor the auction and increase your max bid if you are outbid.</p> <p>Important Note: You are allowed to bid both online and during the live webcast. If you're approved to bid, you may participate in both the online-only auction and the live virtual webcast auction.</p> <p>Important Auction Tips: Multiple Platforms: This auction is being held on multiple platforms. In the case of a tie bid, the auctioneer may ask for a tie-breaker or award the bid to the last, fastest bidder if the tie is not resolved.</p> <p>Choice Lots: When a lot is offered as a choice, the highest bidder can select one or more items from a grouping at the bid price. The bidder can take as many lots as desired at that price.</p> <p>Line and Piece Meal Lots: Some lots may be offered as a line (bulk lot) or piecemeal (individual pieces). When lots are offered both ways, the highest aggregate sum of the individual bids or the highest bulk bid will determine the winning bid.</p> <p>Tie-Breaking Process: This auction will be held as a simulcast event across multiple platforms. If a tie occurs, the auctioneer will attempt to break the tie. If a tie cannot be resolved, the auctioneer may, at their discretion, award the lot to the last fastest bidder.</p> <p>Bid Button and Increments: When you click the bid button online, your bid will be placed automatically at the increment specified by the auctioneer. Custom bid amounts cannot be entered.</p> <p>By following these guidelines, you can participate in both the online and live auction formats and increase your chances of winning your desired lots. Happy bidding!</p>	

Register 24 hours prior to the start of the auction.

A valid credit card, billing address, office address, email address and company address are required to bid online.

If you have a resale certificate or exemption, please provide a PDF copy to our office so that we may amend your invoice properly. In the email please provide your bidder number, your registration information and the name of the auction. This can be emailed to auctions@biditup.com.

First-time registrants - in order to bid for this auction, you MUST HAVE:

- 1) A deposit, 25% of expected purchases or \$1,000 minimum or
- 2) Be in good standing with other auctions held by members of the Industrial Auctioneers Association or
- 3) Belong to the IAA or MDNA or
- 4) Have successfully bid and picked up at 2+ auctions on bidspotter.com

Form of deposit: wire transfer (for wire instructions, please email customerservice@biditup.com).

Please note, all international bidders, or bidders spending over \$20,000 are required to submit a deposit via wire transfer of 25% of your maximum estimated bid. For example, if you are planning to spend a maximum of \$100,000 at auction, a wire transfer must be sent to us of \$25,000 prior to the sale to allow you to bid.

The same deposit requirement is applied for bidders with negative remarks on Bidspotter. You must provide a 25% deposit of your maximum estimated spend limit to be approved for the sale.

If you have any questions on approval, please email customerservice@biditup.com.

Once you have registered with Bidspotter, and Registered for this Auction, we will be notified. If you are approved, you will receive an approval notification status. If you have not been approved, please call us so we may help you through the process: (818) 508-7034

If you need help with registering for Bidspotter: BidSpotter Customer Service Support Department. Have a question pertaining to the bidding process? Visit our Frequently Asked Questions! You can also start a live chat with a Bidspotter Support Representative by selecting Live Chat at the top of Bidspotter.com. More information on our chat system can be found by clicking here.

Customer Support Hours:

Monday - Thursday, 8:00 AM EST - 10:00 PM EST

Friday, 8:00 AM EST - 6:30 PM EST

Email: support@bidspotter.com

Office: (253) 858-6777

Toll Free: (866) 597-2437 for Frequently Asked Questions

OC

BIDITUP AUCTIONS WORLDWIDE, INC.
BIDDERS BINDING CONTRACT

BIDITUP AUCTIONS WORLDWIDE, INC, HEREIN AFTER REFERRED TO AS BIDITUP, AUCTIONEER AND SELLER. BIDDER HEREIN AFTER REFEREED TO AS BIDDER, REGISTERED BIDDER, PURCHASER, UNDERSIGNED AND BUYER. THIS AUCTION WILL BE CONDUCTED PER THE TERMS AND CONDITIONS BELOW AND SUPERSEDED BY ALL OTHER PROVISIONS, AMENDMENTS, MODIFICATIONS AND ANNOUNCEMENTS ADDED BY AUCTIONEER AT ANYTIME PRIOR TO OR DURING THE AUCTION SALE AND OR AS POSTED ON WWW.BIDITUP.COM. BIDDER HEREBY AGREES AND ACKNOWLEDGES AUCTIONEER IS NOT RESPONSIBLE OR LIABLE FOR BIDDERS ACKNOWLEDGEMENT OF ANY SUCH ANNOUNCEMENTS AND BIDDER ASSUMES ALL RISKS AND LIABILITIES BELOW ONCE IT BIDS.

AUCTIONEER SHALL HAVE THE RIGHT TO MAKE IMAGE AND AUDIO VIDEO RECORDINGS OF THE AUCTION, TO USE SAID RECORDINGS AND IF DEEMED APPROPRIATE IN AUCTIONEERS SOLE DISCRETION TO MAKE THIS PUBLIC. BUYERS HEREBY GIVE THEIR PERMISSION AND CONSENT BY PARTICIPATING IN THE AUCTION.

Auctioneer at its sole discretion may deny entry, registration or bidding at any time to any person or entity. Bidder's paddles and invoices are nontransferable. All bids made by the holder of the bid paddle will be the responsibility of the Registered Bidder, Bidder and the Undersigned. All sales are final and there are no refunds, returns, credits, exchanges or rebids once the Auctioneer knocks down the item or declares it sold to the Bidder.

The Bidder, Registered Bidder, Purchaser, Undersigned and Buyer agree a successful bid at auction constitutes a legally binding contract of sale and this contract is binding upon the Registered Bidders Company, the Bidder, Purchaser, Undersigned and Buyer personally for all amounts due and owing at the conclusion of bidding and time of invoice. BUYER BEWARE AND CAVEAT EMPTOR.

"THE BUYER ALONE IS RESPONSIBLE FOR CHECKING THE QUALITY AND SUITABILITY OF GOODS BEFORE A PURCHASE IS MADE."

Auctioneer makes no representations, warranties, promises, covenants or guarantees, expressed or implied, as to defects in or the completeness or accuracy of the description in any advertising of any item(s) being auctioned and is not responsible for any advertising discrepancies, descriptions, nomenclature or inaccuracies of any kind. ALL ITEMS ARE SOLD ON AN "AS IS, WHERE IS" BASIS AND WITH ALL FAULTS WITHOUT EXCEPTION AND WITH REMOVAL AT BUYERS SOLE RISK AND EXPENSE. THE AUCTIONEER MAKES NO REPRESENTATIONS, WARRANTIES, PROMISES, COVENANTS OR GUARANTEES OF ANY KIND, EXPRESSED OR IMPLIED, AS TO THE NATURE, QUALITY, DURABILITY, CAPABILITY, FUNCTION, PERFORMANCE, VALUE OR CONDITION OF THE ITEM(S) BEING AUCTIONED OR ITS (THEIR) SUITABILITY FOR ANY USE. THE AUCTIONEER EXPRESSLY AND SPECIFICALLY DISCLAIM, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OD

The Undersigned hereby waives, releases, remises, acquits and forever discharges the Auctioneer, and their respective employees, agents, or any other person acting on behalf of the Auctioneer, of and from, and shall indemnify and hold the Auctioneer and their respective employees, agents, or other persons acting on behalf of the Auctioneer and against any claims, actions, causes of action, demands, rights, damages, costs, expenses or compensation whatsoever, direct or indirect, known or unknown, foreseen or unforeseen, which the undersigned now has or which may arise in the future on the account of or in any way growing out of or connected with any defects, latent or otherwise, or the physical condition of any item(s) purchased or any law or regulation applicable thereto. The undersigned specifically waives the provisions of California Civil Code section 1542, which provides: "A general release does not extend to claims which the creditor does not know or suspect to exist in his favor at the time of executing the release, which if known by him must have materially affected his settlement with the debtor."

The Auctioneer encourages the Undersigned to avail itself of the opportunity to make inspections prior to bidding and/or purchasing. The Undersigned hereby acknowledges that it has inspected or voluntarily waived said inspection of all of the items upon which it will be bidding and/or does purchase. Once the Auctioneer knocks down the item or declares it sold to the Bidder, there are no credits, returns, exchanges, refunds or rebidding unless at the Auctioneers sole discretion and such request for rebid is made directly to the Auctioneer and within no more than 5 minutes from the Bidder after the item has been sold. No claim will be considered for allowance or rescission of any sales based upon failure of the property to correspond with any standard expected.

In order to participate in the auction, all Bidders must provide Auctioneer a 25% deposit, in cash, cashier's check or company check accompanied by a bank letter of guarantee of unqualified payment to Auctioneer, or a wire transfer (with a wire transfer fee included) of your maximum expected spending. The final payment in full of Bidders invoice must be received by Auctioneer within the first banking day 24 hours after the auction or the Buyer will be in default of this Contract. The Auctioneer will charge all Bidders a taxable sur charge buyer's premium on its invoice. The Undersigned shall provide proof satisfactory to the Auctioneer of its entitlement to claim exemption from sales tax, which proof must be representative of the same industry as the item(s) that are purchased. In the absence of proof satisfactory to the Auctioneer, the Buyer shall pay all taxes. The Auctioneer will not be responsible for any Department of Motor Vehicle fees, tax, registration, licensing, penalties, smog certificate or fees. Certain vehicles as announced and/or noted in the auction catalogue or on Buyers invoice will be sold "AS IS," with a Bill of Sale only, Each titled item will be charged a \$75 title transfer fee. If available by Auctioneer, titles will be sent to Buyers approximately 7-10 business days after receipt of payment. There will be no refunds if Auctioneer is unable to produce a title. Sales tax on Motor Vehicles is the responsibility of the Buyer to be remitted to its appropriate states Department of Motor Vehicles. All vehicles are sold "AS IS, WHERE IS, WITH NO WARRANTIES EXPRESSED OR IMPLIED." It is the Buyer's responsibility to inspect the vehicle to verify accurate description, model, year, mileage, condition and any and all details pertaining to the vehicle. Auctioneer is not responsible for any inaccuracies of any kind. Credit cards are not accepted.

TERMS AND CONDITIONS CONTINUED...

Auction sales and items are subject to cancellation without prior notice.

The Auctioneer reserves the right to augment this auction with items from additional sellers. These items may be interspersed and not specially identified throughout the auction sale.

The Auctioneer shall regulate all matters relating to the conduct of the auction and the Auctioneer's decisions shall be final and binding on all bidders.

The Auctioneer reserves the right to group, regroup, reduce, add to or delete lots as well as accept or reject any or all bids at the Auctioneer's sole and absolute discretion.

The Auctioneer reserves the right to offer any or all of the items in bulk at any time during the auction at the Auctioneer's sole and absolute discretion.

The Auctioneer shall determine the bidding increments and the Auctioneer may bid on any item(s) to protect its financial interest or indebtedness at its sole and absolute discretion.

Immediately upon the Auctioneer announcing sold or knockdown and the Auctioneer has declared the Undersigned to be the Purchaser, all items comprising of the lot become the sole and absolute responsibility of the Undersigned and the Undersigned shall thereupon and thereafter assume all risk of loss (including, but not restricted to loss by way of theft or damage) and liability relating to such items. The Undersigned is advised to pre-arrange insurance coverage for its purchases as there will be no refunds for missing, lost, damaged or stolen items unless and only at the Auctioneer's sole discretion. The Auctioneer shall in no event be liable to the Purchaser for non-delivery of any item(s) for any reason except for the return to the Buyer of the deposit or other sums paid for such non-delivered items. This non-delivery period extends from the knock down until the time allotted for the removal process concludes. In no event will the Auctioneer's liability to the Undersigned exceed the amount actually paid by the Undersigned. THE UNDERSIGNED HEREBY ACKNOWLEDGES AND AGREES THAT THE AUCTIONEER SHALL NOT BE LIABLE FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL DAMAGES.

Title to and possession of the item(s) shall not pass to the Undersigned until the Auctioneer has received payment for all items duly purchased in full. All items and the entirety of the Purchaser's invoice require payment in full prior to Auctioneer releasing any items. If all the items are not paid in full by Purchaser for any reason, and Purchaser has provided Auctioneer any monetary consideration, Auctioneer will retain all the items and the monetary consideration paid by Purchaser to mitigate Auctioneer's financial damages caused by Purchaser. If after the subsequent mitigation amounts (if any) received by Auctioneer exceed the amount of the Purchaser's invoice and below, the auctioneer will refund such amounts to the Purchaser once determined by Auctioneer in its sole discretion. The Purchaser hereby agrees items purchased at this auction will be invoiced in totality, although in some cases separately priced on the invoice, the total amount due Auctioneer of the Purchaser's invoice is deemed a single contract if in the event of a legal dispute.

If for any reason the Undersigned fails to pay the full amount of its invoice within the first banking day 24 hours after the auction, and/or fails to remove all of its items on or before the date posted on Purchaser's invoice, and/or fails to comply with any other terms and conditions of this Contract, all the items on the Purchaser's invoice will be considered abandoned and the Auctioneer in its sole discretion and without further notice to Purchaser may remove, dispose of, scrap, resell at public or private sale any or all the items and the Undersigned hereby agrees to pay to Auctioneer any monetary mitigation deficiency and costs as a result thereof, including all removal, rent, lay and hold over fees. The bidder understands and acknowledges that there is sufficient consideration by both parties to perform, and that if payment in full is not made within the specific time outlined in the contract, the bidder is agreeing to be bound by a "consent judgment" and is in violation and in default of contract. By signing below you are consenting to the terms of a judgment entered against you and are waiving your rights to any court hearing. In addition, relating to such disposition together with all charges, including attorney, court and legal fees, interest and any and all other expenses in connection with such disposition, plus a \$500.00 per diem administrative fee per item until such item(s) is (are) removed.

The Undersigned agrees that the Auctioneer may retain all deposits previously received and apply such deposits to any such deficiency without further notice to Purchaser. Purchaser hereby agrees that "time is of the essence" in regards to this Contract regarding payment of its invoice and removal of its items. For purposes of clarity, Purchaser further acknowledges and agrees Auctioneer will be monetarily damaged for the subsequent disposal of any item(s) for any reason and that the Purchaser will be responsible to pay Auctioneer for all of the above and any other such monetary mitigation deficits, damages known and unknown, and any and all other cost to Auctioneer to collect and enforce this Contract. Any monetary deficiencies to the Auctioneer become the debt of the Undersigned.

This Agreement shall be construed and interpreted according to the laws of the State of California. The Bidder further agrees to have Burbank California as the Forum City & State in the event any lawsuit is initiated by either party. If any action based on the performance, breach or interpretation of this Agreement is brought, the prevailing party in such action (as determined by the court or other body having jurisdiction) shall be entitled to recover from the losing party all actual costs and expenses of litigation or arbitration, including attorney's fees, court costs, costs of investigation, and other costs related to such proceeding.

AUCTIONEER DOES NOT WARRANT THAT THE FUNCTIONS, FEATURES OR CONTENT CONTAINED IN THE ONLINE OR WEBCAST BIDDING PLATFORM OR SOFTWARE, INCLUDING ANY THIRD-PARTY SOFTWARE, PRODUCTS OR OTHER MATERIALS USED IN CONNECTION WITH THE WEBSITE OR BIDDING WILL BE TIMELY, SECURE, UNINTERRUPTED OR ERROR-FREE, OR THAT DEFECTS WILL BE CORRECTED. AUCTIONEER RESERVES THE RIGHT TO ACCEPT AND OR REJECT AND OR REMOVE ANY ELECTRONIC BIDS FOR ANY REASON AT ANY TIME IN ITS ABSOLUTE SOLE DISCRETION. BIDDER AGREES ALL OF ITS ELECTRONIC BIDS ARE BINDING REGARDLESS OF ORDER AND OR TIME IN WHICH THEY ARE ACCEPTED OR REJECTED.

OE

OF	<p>TERMS AND CONDITIONS FOR DISCONNECT AND REMOVAL: All electrical disconnect, liquid removal, rigging, loading, broom cleaning, trash & debris removal, floor stud removal and transportation are the sole and absolute responsibility of the Undersigned. The undersigned agrees to remove its purchases in full, with no abandonment privileges from the premises on or before the date on the Buyers invoice. No item(s), no matter how small, may be removed while the auction is in progress. Representatives of the Auctioneer at the Auctioneer's sole discretion may stay one hour after the auction is completed for the removal of small items. All small subject to disappear items must be removed by 4:00 PM on the day following the auction. The Undersigned must present the Auctioneers personnel with proof of valid workers compensation insurance and a commercial general liability insurance certificate in a minimum amount of \$2,000,000.00 combined single limit per occurrence coverage naming the Auctioneer, the Seller and the Landlord as additional insured. If available at Auctioneers sole and absolute discretion, bridge cranes and hoist may be used by the Undersigned if crane insurance is included on the above certificate and only with the written permission of the crane owner. Should any pits, floor bolts or hazards of any type exist after removal of equipment, it is the responsibility of the Undersigned, at its cost, to reasonably safe guard these areas using generally accepted safety practices, such as safety tapes, pipes or bars welded in place or suitable safety barriers acceptable to the Auctioneer. All floor bolts and/or anchoring fasteners are to be cut flush to the floor and the area left broom clean and all debris removed. It is the responsibility of the Undersigned to be sure that the power to the item(s) is off and then to safely disconnect all electrical wiring and utility piping from the item(s) and to cap at the first electrical or air junction of the item(s). Item(s) are to be staged for loading in the area assigned by the Auctioneer's personnel. It is the Undersigned's responsibility to secure all safety equipment to meet all applicable government safety standards in using or removing any items purchased. Certain items may contain residual chemicals and/or hazardous materials. The Undersigned hereby agrees to indemnify and hold harmless the Auctioneer from any and all damages, claims or liabilities from any injuries to persons or property of any type whatsoever caused by the Undersigned, its agents, employees or contractors during the sale or during the removal, use or operation of the purchased item(s). Any hydraulic fluid removal and/or oil leaks are the Undersigned's responsibility to remove and clean up. The Undersigned must take full responsibility for compliance with applicable environmental laws and exercise all reasonable care to ensure that there is no release to the environment of any hazardous wastes or substances as defined in applicable Federal, State and Local Statues, Regulations, Rules or Ordinances. No trucks are to be left running in an enclosed building. The Auctioneer is not liable for personal belongings left on premises. Any surface or structural damage to the premises including but not limited to the walls, ceilings, floors, overhead doors, gates and/or any other item(s), etc. will be the Undersigned's sole responsibility. The Undersigned will not be permitted to leave with its purchases until repairs are made. Theft will not be tolerated and Auctioneer reserves the right to inspect all trucks, toolboxes and rigger cases, etc. Instances of theft will result in immediate termination of removal privileges and full prosecution by law. All quantities must be checked prior to removal, as adjustments will not be made thereafter. These terms and conditions together with any amendments or modifications, expressly made by the Auctioneer at the time of the auction constitute all the terms and conditions with respect to the sale of items at this auction. There are no representations, warranties, terms, conditions, undertakings or collateral agreements except as hereinabove provided I acknowledge that I have provided BidItUp Auctions Worldwide, Inc. a signed check for which I am the authorized signatory for all purposes, without restriction, sufficient to pay this negotiable instrument upon demand. I authorized BidItUp to obtain my financial information from any source and complete the check as necessary for the amount of my invoice at the auction to be presented for payment. I agree to pay all cost of collections including attorney's fees, to pay interest at the rate of 18%, unless prohibited by law, and in such case at the highest amount permitted by law from the date of issuance of this check if dishonored by a financial institution, to waive any requirement of presentment, to the exclusive jurisdiction of the executed Auction Bidders Agreement for any dispute relating to this instrument. A credit instrument is identical to a personal check. Willfully drawing or passing a credit instrument knowing there are insufficient funds in an account upon which may be drawn, or with the intent to defraud, is a crime which may result in criminal prosecution.</p>	
OG	<p>IMPORTANT PAYMENT INFORMATION Thank you for your interest in our Auction Event! Please see the below information regarding payment. Invoices will be sent out 24 hours AFTER the close of the auction. PAYMENT Payment is due 48hrs after invoices have been released - \$250 fee may apply to late payments Invoices paid with card will incur a 3.5% additional processing fee Card Payments: ONLY USE IF PAYING WITH CREDIT CARD OR DEBIT CARD MAX LIMIT OF \$2,500 (additional 3.5% card processing fee) Wire Payments: if paying by wire Please note if you send us the incorrect payment amount and require a reimbursement, a \$100 fee will apply WE DO NOT ACCEPT ACH - if you send us an ACH, a \$100 fee will apply Methods of payment: Credit/ Debit Card (includes 3.5% convenience fee) Wire Transfer TAXES/ TAX EXCEPTIONS International bidders: NO EXCEPTIONS: You must pay the full amount due. Once we receive a "Bill of Lading" after shipment, we will refund your taxes via ACH/Wire. Please note it is the bidder's responsibility to provide bank information to process the ACH/Wire. Domestic Bidders: Please complete the tax form provided by our accounting team and return to auctions@biditup.com. Once received and approved, tax will be removed from your invoice. Please note, it is the bidder's responsibility to provide tax exemption information.</p>	
OH	<p>Removal will be by appointment ONLY. There will be a link in your invoice to create an appointment- please note all appointments must be made AFTER procesing payment successfully. DO NOT SCHEDULE AN APPOINTMENTIF YOU HAVE NOT RECEIVED A PAID IN FULL INVOICE FROM ACCOUNTING.</p>	

6013	Heavy-Duty Industrial Bearing Housing Assembly with Large Roller Bearing; Heavy-duty industrial bearing housing assembly featuring a large cylindrical roller bearing installed within a precision-machined steel block. Assembly includes integrated grease fittings, machined mounting surfaces, and bolt patterns suitable for fixed installation in industrial machinery. Unit appears configured to support high-load rotating shafts or drums in process equipment. Sold as a complete bearing housing assembly as shown. No additional specifications or ratings provided beyond visible construction.	
6014	Heavy-Duty Industrial Bearing Housing Assembly with Large Roller Bearing; Heavy-duty industrial bearing housing assembly featuring a large cylindrical roller bearing installed within a precision-machined steel block. Assembly includes integrated grease fittings, machined mounting surfaces, and bolt patterns suitable for fixed installation in industrial machinery. Unit appears configured to support high-load rotating shafts or drums in process equipment. Sold as a complete bearing housing assembly as shown. No additional specifications or ratings provided beyond visible construction.	
6015	Heavy-Duty Industrial Bearing Housing Assembly with Large Roller Bearing; Heavy-duty industrial bearing housing assembly featuring a large cylindrical roller bearing installed within a precision-machined steel block. Assembly includes integrated grease fittings, machined mounting surfaces, and bolt patterns suitable for fixed installation in industrial machinery. Unit appears configured to support high-load rotating shafts or drums in process equipment. Sold as a complete bearing housing assembly as shown. No additional specifications or ratings provided beyond visible construction.	
6016	Heavy-Duty Industrial Bearing Housing Assembly with Large Roller Bearing; Heavy-duty industrial bearing housing assembly featuring a large cylindrical roller bearing installed within a precision-machined steel block. Assembly includes integrated grease fittings, machined mounting surfaces, and bolt patterns suitable for fixed installation in industrial machinery. Unit appears configured to support high-load rotating shafts or drums in process equipment. Sold as a complete bearing housing assembly as shown. No additional specifications or ratings provided beyond visible construction.	
6017	Heavy-Duty Industrial Bearing Housing Assembly with Large Roller Bearing; Heavy-duty industrial bearing housing assembly featuring a large cylindrical roller bearing installed within a precision-machined steel block. Assembly includes integrated grease fittings, machined mounting surfaces, and bolt patterns suitable for fixed installation in industrial machinery. Unit appears configured to support high-load rotating shafts or drums in process equipment. Sold as a complete bearing housing assembly as shown. No additional specifications or ratings provided beyond visible construction.	
6018	Assorted Industrial Roller Bearings & Bearing Components – Mixed Sizes, Heavy-Duty Steel Lot; This lot includes an assorted group of industrial roller bearings and bearing assemblies in mixed sizes and configurations. The assortment appears to include cylindrical roller bearings, needle roller bearing assemblies, and separate inner and outer bearing rings, with components presented loose and unsorted as a bulk group. Items show grease presence consistent with prior handling or installation. Exact dimensions, specifications, and compatibility are not defined, and no matching or identification has been performed. Offered as a single mixed lot, exactly as shown, suitable for industrial buyers seeking bulk bearing components for reuse, refurbishment, teardown, part matching, or inventory stock.	
6019	Branson 2000X series ultrasonic welder; Series: 2000X Function: Uses high-frequency vibrations to create fast, clean welds without adhesives or screws Key Features: Multiple weld modes (time, energy, peak power, distance) Available in different output frequencies (15, 20, 30, 40 kHz) and power levels (400W to 4400W) Digital controls, auto-tuning, and system monitoring for process control Can be integrated into automated systems or used as a standalone unit	
6020	Branson 2000X series ultrasonic welder; Series: 2000X Function: Uses high-frequency vibrations to create fast, clean welds without adhesives or screws Key Features: Multiple weld modes (time, energy, peak power, distance) Available in different output frequencies (15, 20, 30, 40 kHz) and power levels (400W to 4400W) Digital controls, auto-tuning, and system monitoring for process control Can be integrated into automated systems or used as a standalone unit	
6021	Branson 2000i Ultrasonic Welder Power Supply & Actuator Assembly, 1100W, 100–120V; This listing is for a Branson 2000i ultrasonic welding system consisting of the Branson 2000i power supply integrated with a vertical actuator/press assembly. The unit is labeled Model 2000iW+ with a rated maximum output power of 1100W and electrical input of 100–120V, single-phase, 50/60 Hz. The system includes a front control interface, pressure gauge, pneumatic connections, and mounting base as shown. The nameplate indicates manufacture in September 2015. No horn, booster, or tooling is visibly attached. Dimensions, operating parameters, and configuration beyond what is shown on the identification labels are not specified. The unit is offered exactly as pictured, with no additional accessories, testing, calibration, or verification performed. Suitable for industrial buyers familiar with ultrasonic welding equipment seeking a Branson 2000-series power supply and actuator assembly for integration, refurbishment, parts, or redeployment.	
6022	Branson Ultraweld L20 ultrasonic metal spot welder; Frequency: 20 kHz Output Power: Available in 3.3 kW, 4.0 kW, and 5.5 kW versions Input Power: 220VAC, 50/60 Hz Pneumatics: Requires 80 psi (5.5 bar) of clean, dry air	
6023	CM Lodestar chain hoist AND AERO-Motive wire rope festoon system ; Lodestar chain hoist. 120vac, 2-ton lifting capacity. Comes with operating pendant. Aero-motive fashion system. Complete Manual operation. 53-70 lbs lifting capacity. Model-70JA	
6024	Baldor 7.5 HP Hazardous-Location Electric Motor, Manchester Tank 10-Gallon Pressure Vessel, Gearmotor, and Assorted Industrial Roller Assemblies – Mixed Lot; Mixed industrial components lot including a Baldor hazardous-location electric motor rated 7.5 HP, 230/460V, 3-phase, 1770 RPM, Class I Group D / Class I Zone 1 Group IIA with inverter-duty specifications; a separate IEC-style gearmotor rated 1.5 kW (2 HP), 3-phase, 50/60 Hz; a Manchester Tank horizontal pressure vessel rated 10 gallons with MAWP 200 PSI at 400°F (ASME stamped, year 2016); and an assortment of precision roller assemblies with shafts, bearings, elastomer rollers, sprocketed hubs, plus associated fasteners. Components appear industrial-grade and suitable for machinery, automation, material handling, or spare parts inventory. Sold together as one lot; mounting hardware and loose components included as shown.	
6025	Baldor Reliancer Motor; Cat No. ECP84407T-4 200HP 1785 RPM 60Hz 460V PH 3	
6026	Baldor Electric Motor with Vacuum Pump; Spec No. 071230X598G1 Horsepower (HP) 10 // 7.5 (Dual Rating) Voltage (Volts) 230/460 // 190/380 (Dual Voltage) Amps (Full Load) 24.5/12.3 // 23.2/11.6 (Amps vary by voltage) RPM 1755 // 1455 Phase (PH) 3 Frequency (Hz) 60 (implied by RPM) // 50 (implied by RPM) Frame 215T Design A	

6026A	Baldor Electric Motor with Vacuum Pump; Spec No. 071230X598G1 Horsepower (HP) 10 // 7.5 (Dual Rating) Voltage (Volts) 230/460 // 190/380 (Dual Voltage) Amps (Full Load) 24.5/12.3 // 23.2/11.6 (Amps vary by voltage) RPM 1755 // 1455 Phase (PH) 3 Frequency (Hz) 60 (implied by RPM) // 50 (implied by RPM) Frame 215T Design A	
6027	Edwards EDS300 Air Blast Dry Vacuum Pump Assembly – 60 Hz Industrial System (Appears new & unused); Edwards EDS300 Air Blast dry vacuum pump assembly configured for 60 Hz operation. Unit includes integrated motor, dry vacuum pump body, and air blast cooling module with external heat exchanger. Nameplate indicates 7500 RPM maximum shaft speed, approximate unit weight of 420 kg, and manufacture date of September 2023. ATEX-rated for specified internal atmosphere applications. Industrial-grade system commonly deployed in high-demand vacuum process environments. Sold as a complete pump assembly as shown.	
6028	Roll press hydraulic drums; (2) hydraulic roll press drums. These drums are made of mild steel and have all hydraulic fitting attached.	
6029	Roll press gear boxes; (2) industrial roll press gear boxes. These gear boxes have attached motors. Gear box shaft I.D is 2". All mild steel.	
6030	(2) Roll Press Drums; Used to apply pressure, guide materials, or transfer substances like ink or adhesives. Used across various industries, from paper manufacturing to lithium-ion battery production.	
6031	(2) Roll Press Drums; Used to apply pressure, guide materials, or transfer substances like ink or adhesives. Used across various industries, from paper manufacturing to lithium-ion battery production.	
6032	Lot of Hydraulic cylinders / Actuators, & Drive shaft components; Hydraulic cylinders for roll press, & Drive shaft components.	
6033	CIS R500 Roll Press Drum Gear Box; Regulates the flow of dry powder or granular material between chambers while maintaining an airlock condition, often under pressure or vacuum. Capable of handling significant pressure differentials (up to 20 psi or more) and high temperatures (up to 750°F or higher), depending on the specific build materials.	
6034	CIS R500 Roll Press Drum Gear Box; Regulates the flow of dry powder or granular material between chambers while maintaining an airlock condition, often under pressure or vacuum. Capable of handling significant pressure differentials (up to 20 psi or more) and high temperatures (up to 750°F or higher), depending on the specific build materials.	
6035	Honeywell Precision Plus Scanner 2084; (2) Honeywell Electrical Panels 380V, 3PH, 4W	
6036	Promess KA-EMF20/150 electro-mechanical assembly servo press with Promess 30 PM Servomotor; Servo Press: Model: KA-EMF20/150 Type: Electro-Mechanical Assembly Press Capacity: 20 kN (kilonewtons) Stroke Length (STRK): 150 mm Rated Output: 1.0 mV/N (millivolt per Newton) Serial Number (Snr.): 1204409 Origin: Made in Germany Servomotor: Model AKM64K-ANA2R-70 Voltage: 640 VCD Current: 3.93 Arms Power: 2.5 kW Speed: 2500 1/min Protection Class: IP54	
6037	Oriental Motor Spartan Conveyor Assembly with Multiple Gearmotors, Control Panel, and Steel Frame; industrial conveyor assembly branded Spartan Conveyor, featuring multiple Oriental Motor gearmotor units mounted to a steel conveyor frame with integrated electrical control panel. Visible components include several Oriental Motor gearmotors with gear heads (including model BH6G2-100RH, made in Japan), mounted shafts, wiring harnesses, emergency stop button, push-button controls, and enclosed electrical junctions. The system is labeled for 277/480V, 3-phase, 4-wire power and includes a factory-built control enclosure with conduit connections. Assembly appears designed as a complete conveyor drive and control platform, offered as a single lot with motors, frame, and electrical components present as shown.	
6038	GoHz Frequency Converter ; GoHz Frequency Converter Model: HZ-50-3320 Capacity: 20KVA Input: 3Ph + N.G 480V 50Hz /60Hz Output: 3Ph + N.G 0-520V 40-120Hz	
6039	Heat exchangers; (5) PRICE heat exchangers. Single duct, 300 cfm and oversized casing. Designed to control the flow of conditioned air into an occupied space, single duct terminal units can be used in almost any application.	
6040	Post glover neutral grounding resistor; This resistor is 8000vac, 600 amps, 10 second duty time and 13.33 ohms. This resistor, Neutral Earthing resistor systems protect power transformers and generators from damaging fault currents. Earthing of the neutral limits the ground fault current to a high level (typically 50 amps or more) in order to operate protective fault clearing relays and current transformers.	
6041	Twin City Fan & Blower BCS industrial fan; Type: BCS-SW (Backward Curved, Single Width) Size: 365 Arrangement (Arr.): 1 Serial Number: 12-177491 Tag: ABORT FAN Electro-Sensors M5000 speed switch. Function: It is a self-contained switch for detecting shaft slowdown or monitoring rotation in industrial equipment. Power Input: It operates on 115vac and 0.063 Amp. Hazardous Location Rating: It is rated for Class I, Group D and Class II, Group E, F, G hazardous environments. Temperature Range: The ambient temperature range is -25°C to +65°C.	
6042	Edwards EDS300 Air Blast Dry Vacuum Pump Assembly – 60 Hz Industrial System (Appears new & unused); Edwards EDS300 Air Blast dry vacuum pump assembly configured for 60 Hz operation. Unit includes integrated motor, dry vacuum pump body, and air blast cooling module with external heat exchanger. Nameplate indicates 7500 RPM maximum shaft speed, approximate unit weight of 420 kg, and manufacture date of September 2023. ATEX-rated for specified internal atmosphere applications. Industrial-grade system commonly deployed in high-demand vacuum process environments. Sold as a complete pump assembly as shown.	
6043	(12) SMART Mechatronics / SAMICK Industrial Linear Transfer Modules – SADP-16 Servo-Driven Units ; Lot of (12) SMART Mechatronics industrial linear transfer modules manufactured by SAMICK, featuring aluminum linear actuator bodies with integrated servo-driven transfer assemblies. Units are labeled SADP-16 (DEP) and include multiple HF-KP43 400W servo motor assemblies (SM02 / SM03) with DC 24V junction boxes. The modules are constructed with precision linear rails, mounting plates, and end-mounted drive housings, consistent with automated transfer or positioning systems used in industrial manufacturing environments. This lot includes multiple matching linear units as shown, configured for integration into automated equipment or production lines.	

6044	Pallet racking parts; This lot contains an assortment of pallet racking parts ranging from cross members, X braces to shelf decking.	
6045	Pallet racking parts; This lot contains a variety of pallet racking parts including bolts, approximately (8) cross members and hex caps.	
6046	Pressure reduction valve; This pressure reduction valve is from Spirax/Sarco. Type-25P. Inlets and outlet size- 1 1/2" The Spirax Sarco 25P is a pilot-operated valve designed to regulate steam down to specific operating pressures.	
6047	Butterfly valve; Victaulic butterfly valve. Model- W/761. Offers an easily installed choice to cumbersome, multi-bolt wafer or lug-type flanged valves. Sizes from 14 – 24 DN350 – DN600. Pressures up to 300 psi 2068 kPa 21 bar.	
6048	Column guards and speed bumpers; In this lot we have (3) column guards and approximately 75' of speed bumpers. This material is used for protecting buildings structure as well as providing safety for the facilities work force.	
6049	Industrial Safety Rails and Posts – Assorted Sizes; Lot of industrial safety rails and posts in assorted sizes, finished in high-visibility yellow coating. Components include straight rail sections, formed rail profiles, vertical posts with base mounting plates, and assorted mounting hardware and brackets as shown. Rails appear to be heavy-gauge metal construction designed for fixed installation, with pre-drilled mounting points on posts and end plates. This lot is offered as a mixed assortment of safety rail components only; quantities, dimensions, and configurations vary. Sold as a single lot exactly as pictured. APPROX Dimensions: (2) posts at 60.5" (1) post at 72.25" (1) post at 42.375" (4) rails at 72" (3) rails at 48"	
6050	(2) Stainless Steel Stands	
6051	Industrial Cell Assembly Cell Press Die Set with Guided Posts and Springs; industrial cell assembly cell press die set removed from a manufacturing line, consisting of stacked precision-machined plates with a large central pocketed cavity, guided posts, compression springs, and integrated alignment hardware. The assembly is designed to maintain controlled vertical alignment during press operations and includes four guide columns with bearing housings, multiple tapped and through-holes, and spring-loaded separation between plates. Markings such as "216-2" and handwritten die identifiers are present on the tooling surfaces. Previously used in a cell assembly press environment associated with battery manufacturing. Sold as a complete mechanical assembly exactly as shown, including all attached components and hardware.	
6052	Industrial Linear LED Machine-Vision Lights from Anode Coating Line (Assorted, DC Powered); Lot of industrial linear LED machine-vision lights removed from an anode coating production line, designed for uniform linear illumination in precision manufacturing environments. These lights feature rigid aluminum housings with integrated heat-dissipation profiles, diffuse linear output faces, and industrial mounting brackets with adjustable hardware. Each unit is DC powered via 2-pin low-voltage connectors and is intended for use with an external constant-current LED driver. Originally installed in a continuous process setting for coating inspection and surface uniformity monitoring. Lot includes multiple matching linear light assemblies and associated mounting hardware as shown. No driver or control electronics included. Suitable for industrial automation, machine vision, or process inspection applications where consistent linear illumination is required.	
6053	Lot of (between 8 and 10) Cooper Lighting Metalux 2 x 4 Recessed Parabolic Troffer Light Fixtures (0.6 m x 1.2 m); Lot of (between 8 and 10) Cooper Lighting Metalux 2 x 4 recessed parabolic troffer light fixtures designed for commercial and industrial grid ceiling systems. Each fixture measures approximately 0.6 m x 1.2 m (24 in x 48 in) and features a deep parabolic louver reflector engineered for glare control and directional light distribution. Housings are metal construction with integrated recessed mounting frame, intended for standard 2 x 4 ceiling cutouts commonly used in offices, schools, healthcare facilities, warehouses, and institutional interiors. Units are shown without lamps installed. Packaging and fixture design indicate traditional Metalux parabolic troffer configuration widely specified in commercial lighting retrofits and new construction.	
6054	Lights and belt guard; (4) 8' LED light fixtures with bulb covers. *no bulbs* This lot also has a mild steel belt guard for a fan or air make-up unit. The guard is oval in shape and measures 6' long and 18" wide.	
6055	Jamesbury Quadra-Powr X pneumatic valve actuator assembly, AND Stainless Steel Braided Flexible Hoses, AND Cable Drag Chain, AND WEG 00336053EP58-5 stainless steel pump motor. ; Jamesbury Quadra-Powr X pneumatic valve actuator: Designed for both modulating control and on-off service. Features a spring diaphragm mechanism for reliable operation. The assembly includes a positioner and cooling fan. Manufactured by Metso/Valmet. WEG Stainless steel Pump Motor: Model: 00336053EP58-5 Power: 30 HP (60 Hz) Voltage: 208-230/460 V Seal: Viton-fitted mechanical seal Certification: NSF /ANSI 61 and 372 certified for drinking water systems	
6056	Lot of (60) Industrial Battery Modules; flat battery modules with robust metal casings and thick red and black cables, typical of high-power applications. They are designed to combine multiple cells for higher voltage and capacity. Application: These types of modules are often used in systems requiring significant power and energy, such as industrial equipment, marine applications, or grid energy storage.	
6057	Lot of (60) Industrial Battery Modules; flat battery modules with robust metal casings and thick red and black cables, typical of high-power applications. They are designed to combine multiple cells for higher voltage and capacity. Application: These types of modules are often used in systems requiring significant power and energy, such as industrial equipment, marine applications, or grid energy storage.	
6058	Lot of (60) Industrial Battery Modules; flat battery modules with robust metal casings and thick red and black cables, typical of high-power applications. They are designed to combine multiple cells for higher voltage and capacity. Application: These types of modules are often used in systems requiring significant power and energy, such as industrial equipment, marine applications, or grid energy storage.	
6059	Assembly test fixtures; This lot contain approximately (20) aluminum/polypro texting fixtures used to precisely hold product for quality functions.	
6060	Aluminum assembly equipment ; This lot contains a variety of aluminum and pvc material for assembly equipment. The majority of this equipment is base plates and spacer blocks, but also includes pvc spacer plates.	

6061	Lot of Assorted Roll Press oil Seals and Bearings	
6062	Lot of Assorted IKO Inner Ring; Part no. LRT 20022580 RNA 4940	
6063	DSK Linear Servo Stage; Manufacturer: DSK Co., Ltd Product Name: Linear Servo Stage Model Name: DBP250W-96M24MM-35-3010-INC10 Voltage: 200-250V / 50-60Hz, 1/3 Phase Rated Current: 5 Amp / 12 Amp Capacity: 17.5 Kva Weight: 150 Kg Year of Manufacture: 2011.05 Location: Made in Korea	
6064	Industrial Controls & Power Equipment Lot – Enovate Portable Power Supplies, Rosemount 3051 Transmitter, Johnson Controls Actuator, Tarp; Single mixed industrial lot consisting of five (5) Enovate eOn+ Super Portable Power Supplies, model HC01-19-C300, each housed in an aluminum enclosure and accompanied by power adapters, multi-tip DC output cables, and user documentation as shown. Lot also includes one (1) Emerson Rosemount 3051 pressure transmitter, supplied with original HART protocol documentation, stainless steel process connection hardware, and transmitter body, as pictured. Additionally included is one (1) Johnson Controls electric valve actuator, spring-return style, commonly used in commercial HVAC and building automation applications. Items are packaged loose and as shown, forming a single combined lot suitable for industrial surplus buyers, controls integrators, automation contractors, and resellers seeking mixed power and instrumentation equipment.	
6065	Pallet of (2) Airguard DP Max pleated air filters, AND (18) Airguard Vari-Pak rigid cell air filters; Airguard DP Max pleated air filters: Brand: Airguard (a division of Parker Hannifin) Product Line: DP Max Model Number: MX40-STD1-143 Item #: 0450143 Nominal Dimensions: 16" x 16" x 1" Actual Dimensions: Typically up to 1/2" less on all dimensions (e.g., 15.5" x 15.5" x 0.75") MERV Rating: 8, which provides a good balance of air flow and particle capture for residential and commercial use. Quantity: 12 pieces per carton Construction: Features a heavy-duty, moisture-resistant "beverage board" frame and a rust-resistant galvanized steel support grid for durability. Airguard Vari-Pak rigid cell air filters: Brand: Airguard (a Parker Hannifin company) Product Name: Vari-Pak (Extended Surface Rigid Cell Filter) Model: RS-915 PH Item #: 1155915 Filter Size (Nominal): 24" x 20" x 12" Actual Dimensions: 23 3/8" x 19 3/8" x 11 1/2" MERV Rating: 14 Frame Material: Corrosion-resistant galvanized steel Media Material: Synthetic	
6066	Air guard filters; Air guard filters. (HEPA filters) Part # RS-915 Size- 24x20x12 Quantity- 24	
6067	Air guard filters; Air guard filters. (HEPA filters) Part # RS-915 Size- 24x20x12 Quantity- 24	
6068	AirGuard 20x24X12 Vari-Pak MERV 14 Single Header Style RS-915-PH Filters ; Dimensions: Nominal 24" x 20" x 12" Efficiency: MERV 14.Type: Vari-pak S (Synthetic Media) Single Header (PH) Media Type: High loft, microfine synthetic Frame Material: Galvanized Steel Airflow Support: Expanded metal grid on air-leaving side prevents fluttering and maintains shape.	
6069	Air guard filters; Air guard filters. (HEPA filters) Part # RS-915 Size- 24x20x12 Quantity- 22	
6070	(8) Boxes of ADA Ramps, (2) Plastic Cable Protectors And Rubber Mats	
6071	Pallet of assorted Cleaning supplies	
6072	Pig mat and socks; This lot contains (12) boxes of absorbent mats and socks used to clean up and contain spills of oils, coolants, solvents, water, and hazardous chemicals, keeping workplaces clean, safe, and productive by preventing slips and protecting equipment from leaks.	
6073	Spill kits and cleanup disposal bags; In this lot are (4) spill kit drums. They appear opened. This lot also contains a roll of disposition bags. All used for cleaning liquid or chemical spills.	
6074	Plastic trays; These blue plastic trays are used for holding finished product for storage. These trays can be used for a number of applications. This lot contains (19) pallets of approximately (45) trays totaling about 7,600.	
6075	Calcium chloride salt; (8) 50 lbs bags of calcium chloride salt. EXCEL brand, pellet style.	
6076	Vermiculite ; Vermiculite from ULINE. Approximately (10) grade 2, 4 cu.ft bags. Vermiculite is a versatile, lightweight, and inorganic mineral primarily used in horticulture to improve soil aeration, moisture retention, and nutrient absorption. It is also widely utilized for packaging hazardous materials, in mushroom cultivation, and as a component in lightweight concrete.	
6077	Cylindrical Roll Press Drum with Heavy-Duty Industrial Bearings; Precision Grinding & Crowning: Ensures exact diameter and concentricity for high-performance web handling. Hard Chromium Plating: Provides wear resistance (68–70 Rockwell C hardness) and corrosion protection. Custom Engineering: Rolls can be designed for heat transfer, laminating, calendering, or coating applications. Thermal Control: Heat transfer rolls maintain uniform temperature across the roll body, critical for processes like laminating and coating.	
6078	Cylindrical Roll Press Drum with Heavy-Duty Industrial Bearings; Precision Grinding & Crowning: Ensures exact diameter and concentricity for high-performance web handling. Hard Chromium Plating: Provides wear resistance (68–70 Rockwell C hardness) and corrosion protection. Custom Engineering: Rolls can be designed for heat transfer, laminating, calendering, or coating applications. Thermal Control: Heat transfer rolls maintain uniform temperature across the roll body, critical for processes like laminating and coating.	

6093	Cylindrical Roll Press Drum ; Rolls can be designed for heat transfer, laminating, calendering, or coating applications. Thermal Control: Heat transfer rolls maintain uniform temperature across the roll body, critical for processes like laminating and coating.	
6094	Cylindrical Roll Press Drum ; Rolls can be designed for heat transfer, laminating, calendering, or coating applications. Thermal Control: Heat transfer rolls maintain uniform temperature across the roll body, critical for processes like laminating and coating.	
6095	Industrial Precision Cylindrical Metal Drums / Sleeves – Battery Manufacturing Process Tooling (Bulk Lot); This lot consists of multiple large-diameter precision cylindrical metal drums or sleeves, manufactured to tight tolerances and finished with smooth, uniform outer surfaces, consistent with industrial process tooling used in lithium-ion battery manufacturing environments. The components appear designed for integration into electrode production lines, such as anode or cathode coating, calendering, drying, or controlled foil handling processes, where dimensional accuracy and surface consistency are critical. Units are crated and bundled as a matched industrial lot, indicative of production spares or line-change tooling rather than general-purpose pipe or structural tubing. Exact material composition, dimensions, and OEM specifications are not labeled and should be verified by the buyer prior to use. Sold as a single bulk lot, as shown, suitable for battery manufacturing facilities, equipment integrators, or industrial refurbishers seeking precision cylindrical process components. APPROX Dimensions: 6" Diameter 31.5" Long 1/8" Thick	
6096	(5) Industrial Precision Cylindrical Metal Drums / Sleeves – Battery Manufacturing Process Tooling ; This lot consists of (5) large-diameter precision cylindrical metal drums or sleeves, manufactured to tight tolerances and finished with smooth, uniform outer surfaces, consistent with industrial process tooling used in lithium-ion battery manufacturing environments. The components appear designed for integration into electrode production lines, such as anode or cathode coating, calendering, drying, or controlled foil handling processes, where dimensional accuracy and surface consistency are critical. Units are crated and bundled as a matched industrial lot, indicative of production spares or line-change tooling rather than general-purpose pipe or structural tubing. Exact material composition, dimensions, and OEM specifications are not labeled and should be verified by the buyer prior to use. Sold as a single bulk lot, as shown, suitable for battery manufacturing facilities, equipment integrators, or industrial refurbishers seeking precision cylindrical process components. APPROX Dimensions: 6" Diameter 31.5" Long 1/8" thick	
6097	(2) Industrial Copper Foil–Wrapped Cylindrical Process Drums / Sleeves – Battery Manufacturing Tooling; This lot includes (2) large precision cylindrical metal drums or sleeves featuring copper foil–wrapped outer sections and machined metal cores, consistent with specialized process tooling used in lithium-ion battery manufacturing environments. The construction and finish indicate use in electrode-related operations such as controlled foil handling, winding, coating, or calendering processes where surface integrity and dimensional accuracy are critical. Units are packaged individually within a protective crate, with copper foil layers secured for surface protection and handling, suggesting production tooling or line spares rather than raw material or structural components. Exact dimensions, material grades, tolerances, and OEM specifications are not marked and should be independently verified by the buyer prior to installation or reuse. Offered as a single industrial lot as shown, suitable for battery manufacturing facilities, equipment integrators, refurbishers, or industrial R&D applications.	
6098	(13) Industrial Precision Cylindrical Process Drums / Sleeves – Battery Manufacturing Tooling; This lot consists of (13) large-diameter precision cylindrical metal drums or sleeves, manufactured with uniform wall thickness and clean, machined edges, consistent with industrial process tooling used in lithium-ion battery manufacturing environments. These components are characteristic of electrode production lines where cylindrical sleeves or drums are installed over cores or shafts to provide controlled surfaces for coating, drying, calendering, or foil handling operations. The pieces are crated as a matched industrial lot, indicating production spares or line-change tooling rather than structural pipe or commodity tubing. No OEM markings, dimensions, or material specifications are visible and should be independently verified by the buyer prior to use. Sold as a single bulk lot as shown, suitable for battery manufacturers, equipment integrators, refurbishers, or industrial R&D applications. APPROX Dimensions: 6" Diameter 31.5" Long 1/8" thick	
6099	(20) Industrial Precision Cylindrical Metal Drums / Sleeves – Battery Manufacturing Process Tooling ; This lot consists of (20) large-diameter precision cylindrical metal drums or sleeves, manufactured to tight tolerances and finished with smooth, uniform outer surfaces, consistent with industrial process tooling used in lithium-ion battery manufacturing environments. The components appear designed for integration into electrode production lines, such as anode or cathode coating, calendering, drying, or controlled foil handling processes, where dimensional accuracy and surface consistency are critical. Units are crated and bundled as a matched industrial lot, indicative of production spares or line-change tooling rather than general-purpose pipe or structural tubing. Exact material composition, dimensions, and OEM specifications are not labeled and should be verified by the buyer prior to use. Sold as a single bulk lot, as shown, suitable for battery manufacturing facilities, equipment integrators, or industrial refurbishers seeking precision cylindrical process components. APPROX Dimensions: 6" diameter 31.5" Long 1/8" Thick	
6100	Robo guard fencing; This lot contains robo guard fencing with access gates, fencing and posts. Approximately 100' of fencing. This robo guard can be used in many applications. The fencing helps block off areas of moving parts/equipment that can be unsafe work environments.	
6101	(4) Cylindrical Roll Press Drums; Rolls can be designed for heat transfer, laminating, calendering, or coating applications. Thermal Control: Heat transfer rolls maintain uniform temperature across the roll body, critical for processes like laminating and coating.	
6102	Dow Kokam Postmaster Roller Machine 1000	
6103	Plain aluminum foil; This is a coil of aluminum. It can be used for many purposes. Size- 15u-700mm-10,000m.	
6104	ROLLTECH Cylindrical Roll Press Drum ; (10) Precision Grinding & Crowning: Ensures exact diameter and concentricity for high-performance web handling. Hard Chromium Plating: Provides wear resistance (68–70 Rockwell C hardness) and corrosion protection. Custom Engineering: Rolls can be designed for heat transfer, laminating, calendering, or coating applications. Thermal Control: Heat transfer rolls maintain uniform temperature across the roll body, critical for processes like laminating and coating.	

6105	Crown PowerHouse 24V-150A industrial battery charger with BHS Battery Stand; It is a heavy-duty charger designed for industrial applications, such as charging forklift batteries. Made in USA Input: AC 3 phase, 480V, 6A Output: DC 24V, 150A Serial Number: 35411060035 Item Number: 10002874.00 Year of Manufacture: 06/2011 BHS Battery Stand Model: CS-24 Serial Number: TOE46704 Manufacturer: BHS (Battery Handling Systems)	
6106	TOVICA electric lift; This electric lift is chain driven and battery powered. Model- TPS-230. Series- Stacker Max lifting capacity- 500 lbs. You this lift for any lifting purposes with ease and safety in mind.	
6107	Jungheinrich EJE electric pallet truck. ; Type Electric pedestrian pallet truck (walkie) Manufacturer Jungheinrich (Made in Germany) Load Capacity 1,600 kg (approx. 3,500 lbs) Drive Motor Powerful, maintenance-free 3-phase AC motor Battery 24 V, typically 150 Ah (lead-acid) or 100 Ah (lithium-ion options available) Travel Speed Up to 6 km/h (approx. 3.7 mph), both laden and unladen Key Features Compact and manoeuvrable design, ProTracLink stability system, on-board charger (optional), and PIN code access	
6108	Gorbel Bridge Crane; Gorbel Bridge Crane 139" x 125" W/ Gorbel 2000lbs Crane, 1ton Harrington Hoist And (2) 1ton Caldwell Attachments	
6109	Spill kit; In this lot is (1) spill kit drum. It appears unopened. This kit is designed for the rapid containment, neutralization, and cleanup of hazardous liquid spills (oils, chemicals, biohazards) in industrial, lab, and transport settings.	
6110	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1112000446	
6111	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1107000578	
6112	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1107000572	
6113	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000039	
6114	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000437	
6115	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1112000444	
6116	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1107000570	
6117	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1112000445	
6118	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000435	
6119	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000038	
6120	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1110000040	
6121	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1108000597	
6122	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C01107000574	
6123	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000034	
6124	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000037	
6125	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1108000605	
6126	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1106000430	
6127	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1110000440	
6128	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1110000017	
6129	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000036	
6130	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000442	

6131	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000438	
6132	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000439	
6133	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000434	
6134	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000433	
6135	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000436	
6136	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1112000447	
6137	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000035	
6138	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000019	
6139	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1110000018	
6140	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1106000428	
6141	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1108000599	
6142	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1106000424	
6143	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1106000424	
6144	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1106000421	
6145	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1108000602	
6146	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1108000603	
6147	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency WEG 4HP Motor S/N C1106000427	
6148	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1106000422	
6149	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C1106000423	
6150	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency NO Motor S/N C0942000014	
6151	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N	
6152	Busch NC 0100 B L03 ZZR Rotary Screw Vacuum Pump w/ Filter Chambers; p= 0.01 hPa; 60Hz Max Op. Frequency S/N C0939000230	
6153	RADNOR welding cart with hoses; Tanks not included	
6154	RADNOR welding cart with hoses; Tanks not included	
6155	JET BP-1648H Bench Model Hand Brake ; Model#: BP-1648H SN#: 14050074 Capacity: 16 GA x 48" Mild Steel Dimensions: 55" x 25" x 62"	
6156	JET Slip Roll machine, Model No. SR-2236M; Stock Number: 756026 Capacity: 22 GA (gauge) mild steel Function: This machine uses three precision-turned carbon steel rolls to shape metal. The material is fed between two bottom rolls and bent around an adjustable top roll to achieve the desired curve or diameter. Applications: It is ideal for light industrial, educational, and vocational shops for projects in HVAC, general fabrication, and custom metalworking. Capacity: It can handle mild steel up to 22 gauge, and also features three integrated grooves (3/16, 1/4, and 5/16 inch) in the rollers for bending solid wire or rod. Operation: The top roller can be lifted via adjusting screws to easily remove finished, fully-formed cylinders.	

6157	Hallowell Cabinet; Height 72" Width 36" Depth 18"	
6158	Lincoln 140C mig welder; Lincoln 150C mig welder. 120vac. 140amp. Wire-feed welder designed for MIG and flux-cored welding. This welder comes with a metal man roller cart. (NO TANK)	
6159	Lincoln V205-T TIG welder; Lincoln V205-T TIG welder. V205-T AC/DC is a compact, TIG power source intended for critical AC or DC TIG welding. This welder comes with custom roller cart and a variety of welding clamps.	
6160	Hypertherm plasma cutter; The Hypertherm Powermax65 SYNC is a 65-amp, industrial-grade plasma cutter designed for high-performance cutting and gouging, typically handling up to 3/4-inch steel with ease. Comes with a roller cart.	
6161	Lincoln Electric Tig200 Square Wave W/ Lincoln Foot Control	
6162	Miller Dynasty 400 Welder W/ Miller Foot Control (NO TANK)	
6163	Miller Millermatic 350P Welder	
6164	Milwaukee Heavy Duty 14" Abrasive Cut-Off Machine ; Model#: 6176-20 Power Supply: 120V, 3900 RPM, 15 A	
6165	BuildPro / Stronghold Tools Welding Table ; SN#: TM232155 Dimensions: 78" x 46" x 36"	
6166	CNC router/ plasma cutting table; Cutting Table: Length 175-1/2" Depth 45" Lockable wheels Bench Vise, Arbor Press, and Bench Grinder NOT Included	
6167	Laramy welding torch; Plastic welder. The Model 30-200 is a complete, portable production welding outfit with its own built-in air compressor. The high quality, continuous duty, oil-less rotary vane compressor provides 2 1/2 cfm at 3 psi and is equipped with factory wired ON-OFF switches for compressor and torch, interlocked to prevent operation of the welder without the compressor.	
6168	Central Hydraulic H- Frame Shop Press, w/ 20 Ton Capacity Bottle Jack; Capacity: 20 Tons (40,000 lbs) Dimensions: 26" x 4" x 60"	
6169	MILLER filtair fume extractor ; Miller FILTAIR Welding Fume Extractor MWX-S 951511 The Miller FILTAIR MWX-S Welding Fume Extractor with 10 foot arm is a source capture system with self-cleaning FilTek filter for extended filter life, increased efficiency and cleaner air.	
6170	Scotchman iron worker ; The Scotchman 50514-EC ironworker is a single operator machine with FIVE built-in workstations. Its single punch station can punch 1-1/4" hole in 1/2" steel plate. 50-ton punching capacity. this machine very accurate for bending, punching, shearing and notching operations.	
6171	Ridgid R4510 10-inch portable table saw; It has a 15 amp motor capable of 4,400 RPM. It operates on 120 V, 60 Hz power. The saw is designed to be portable and suitable for jobsite use. It features a 10-inch blade diameter.	
6172	Clousing Industrial Inc. Metal Cutting Saw; Model#: KC1016VS Manufacturing#: 112CM00838 Power Supply: 230V, 3 Phase, 60Hz, 2.36 KVA Dimensions: 60" x 27" x 42	
6173	Spanco 3-ton gantry; 3 Ton Adjustable Height Aluminum Gantry. Aluminum model. 3-ton Yale chain fall with pendant. 15' wide, Adjustable Height Under I-beam: up to 12' 4.	
6174	JET 14-inch metal/wood vertical bandsaw; Motor: The saw is equipped with a 1 HP motor, typically wired for 115V / 230V single-phase power (for the J-8201VS/K models). Speed: It is designed to cut a variety of materials including metal, wood, non-ferrous metal, and plastic due to a gearbox that allows for different blade speeds. Metal Cutting Speeds: Variable from approximately 90 to 340 surface feet per minute (SFPM). Wood Cutting Speed: A fixed speed of around 2,600 or 3,300 SFPM, depending on the exact model variant. Capacity: It has a throat capacity of 13 1/2 inches and a maximum height capacity of 6 inches (which can often be expanded to 12 inches with an optional riser block). Construction: The bandsaw has a solid, one-piece steel base for stability and a cast-iron frame and table. The 14 x 14-inch cast iron table can tilt 15 degrees to the left and 45 degrees to the right.	
6175	Rikon 18" Wood/Metal Bandsaw, Model #10-370; Model # 10-370 Motor 2-1/2HP, 220V, 60Hz Blade Length 142" Cutting Speeds 82-3280FPM	
6176	Steel work bench; Steel work bench. 34" tall, 6' long, 3' wide. *table only, no tools, parts*	
6177	Steel work bench with wood top; Steel work bench with wood top 34" tall, 6' long, 30" wide. *table only, no tools, parts*	
6178	Heavy duty Steel work bench ; Steel work bench 37" tall, 66" long, 54" wide. *table only, no tools, parts*	
6179	Jet HVBS-7MW Horizontal/Vertical Bandsaw. ; Model: HVBS-7MW Stock No: 414459 Motor: 3/4 HP, 1 Ph, 115/230V Features: Ball bearing blade guides, 3/4 inch carbon steel blade, adjustable material stop, and vertical worktable included. Coolant System: Equipped with a circulating coolant system to keep the blade and material cool during cutting.	
6180	Jet Model No. J-4200A Combination Belt & Disc Finishing Machine; Stock No.: 414551 Motor: 1.5HP motor, 115/230V, 1 Phase Belt Speed: 2850 S.F.P.M. Origin: Made in Taiwan Serial No.: 10090423	

6181	Dayton 2LKT2 10" Bench Grinder ; Model#: 2LKT2 SN#: 09110053 Power Supply: 1 HP, 1725 RPM, 120/240V, 10.0/5.0 A, 60Hz Arbor Length: 1"	
6182	Baileigh Industrial DP-1000G Drilling Machine ; Model#: DP-1000G SN#: 16919251 Date of Mfg: 04/19 Power Supply: 110V, 14.4 A, 60Hz	
6183	Trinco Dry Blast Model: 36/BP	
6184	Saylor-Beall air compressor ; Saylor-Beall 80 gallon air compressor. Max PSI- 200 3-phase, 480vac Like new.	
6185	Willis Vertical Knee Milling Machine, w/ Newall DRO; Model#: 1050-EV SN#: 14265 Power Supply: 3HP, 230V Dimensions: 10" x 50" table, 34" x 16" (or 17") travel, and an electronic variable speed ("EV") head (60-4200 RPM) Jinshin Invertor Motor	
6186	6" Machine Vise; Jaw Width: 6" Jaw Opening: 9"	
6187	Mill vise; This mill vise is KURT brand. Model- D688	
6188	Mill vise; This mill vise comes with (2) separate handles, good use for different projects or friendlier to user.	
6189	KBC Tools & Machinery GRIP-1640GH metal lathe. ; It has a 16-inch swing and 40 inches between centers. The spindle is D1-6 camlock with a 2-inch bore. It offers 16 spindle speeds, ranging from 45 to 1,800 RPM. The universal threading gearbox allows cutting both inch and metric threads without changing gears.	
6189A	Phase II Veritcal/Horizontal Rotary Table; S/N 110302-2	
6189B	Lathe Workholding Faceplate; 14" Dia	
6189C	Vise Swivel Base; 7" Swivel Plate	
6189D	Lathe Steady Rest; Lathe Steady Rest	
6189E	Vortec #631 Lathe Cold Air Gun; Frost Free	
6189F	Assorted Precision Machine Collets & Collet Holders – Mixed Sizes – Bulk Lot; Bulk assortment of precision machine collets and collet-style holders arranged in trays and storage blocks, as shown. Lot includes multiple slotted steel collets in a wide range of fractional and metric bore sizes, along with several longer collet holders and a rectangular metal accessory block. Sizes and quantities vary, and markings visible on individual pieces indicate mixed dimensions throughout the lot. No single size count or complete matched set is guaranteed. Sold strictly as a mixed bulk lot exactly as pictured.	
6189G	MAXI TORQUE Industrial Pneumatic Cylinder / Actuator Assembly with Air Fittings; Industrial pneumatic actuator assembly labeled MAXI TORQUE, featuring a cylindrical metal body with a flanged mounting base and multiple threaded air ports. Unit is equipped with metal elbow air fittings and a side-mounted porous exhaust muffler. Labeling indicates safety and operating instructions; no model number, stroke length, torque rating, or pressure specifications are legible from the exterior. Designed for compressed-air operation in industrial automation or machinery applications.	
6189H	Bison adapter; The set true adapter ensures proper alignment and supports the transfer of shear force between the brake caliper and the axle bracket during braking, which is crucial for preventing pad wear imbalance and maintaining braking effectiveness.	
6189I	Precision Lathe Steady Rest Assembly – Three-Point Roller Style; Precision lathe steady rest assembly featuring a circular cast body with three adjustable internal support rollers arranged in a triangular configuration. Unit includes threaded adjustment points and a lower clamping base for securing to a lathe bed or machine table. Designed to support and stabilize long or slender workpieces during machining operations.	
6189J	Milling adapter; This adapter ensures proper alignment and supports the transfer of shear force between the brake caliper and the axle bracket during braking, which is crucial for preventing pad wear imbalance and maintaining braking effectiveness.	
6189K	Butterfly air wrench AND tool holder; This ASTRO is a compact, pneumatic impact wrench known for its small size and a unique "butterfly" style throttle lever that allows easy, one-handed control for forward and reverse direction and speed.	
6189L	Indexable face mill with a 45-degree lead angle; Used for Metal Removal: It is a cutting tool designed for efficient and high rates of stock removal on various materials. Used for Milling: It is used for milling operations, including: Face Milling: Creating flat, smooth surfaces on a workpiece. Used for Chamfering: Cutting an angled edge on a workpiece. Used for End Milling: Creating profiles and pockets in the material. Used for Surface Finishes: The design of the tool, often with a positive rake and specific lead angle, helps achieve fine surface	
6189M	Assorted Mill Bits ; Varying sizes of assorted mill bits	
6189N	T-slot clamping kit; Used for securing workpieces on machine tables, such as those on a milling machine or lathe. It includes various components like T-nuts, studs, step blocks, and clamping straps. The set appears to be an M12/14mm size kit, as indicated by the text "M12/14 mm" on the red holder.	

6189O	Assorted End mill bits; This lot contains metric and standard sized end mills.	
6189P	Assorted Lathe Tooling Bits ; 1/16-9/32 in black box 5/16-1" in red box	
6189Q	Slotted shims ; 3" x 3" slotted shims, full assortment. Brand- precision Size- B	
6189R	Starrett micrometers; This lot contains a set of Starrett micrometers. Used for skilled tradesmen and machine shops.	
6189S	Assorted Transfer Punches ; From 3/32-1" Function: Transfer punches are used to mark the center of existing holes onto a mating surface for drilling alignment	
6189T	Mitutoyo DMS; Mitutoyo Model DMS is a series of depth micrometers used for precisely measuring the depth of holes, recesses, and slots. These tools feature an analog display and a base with interchangeable measuring rods to cover a wide range of depths.	
6189U	Mitutoyo micrometer; This lot contains a Mitutoyo digital micrometer. Used for skilled tradesmen and machine shops.	
6189V	Lot of V Blocks, Gauge Blocks, and Radius Gage Sets; Purpose: V-blocks securely hold round stock for operations like milling, drilling, and grinding. Material: They are typically made from hardened steel and precision ground for accuracy. Components: The set includes matched pairs of V-blocks and various clamps to secure the workpiece. Mitutoyo Box: A box for a Mitutoyo gauge block is also visible, which is a separate precision measuring standard.	
6189W	Starrett tools; This lot contains (4) separate tools including a dial test indicator, 12" mechanistic level, and shaft alignment clamp.	
6189X	Magnetic base indicator holders; They accept all dial indicators and dial test indicators. An on-off switch controls a strong permanent magnet for instant mounting and dismounting without affecting the workpiece surface. The base features a V-shape for use on both round and flat ferromagnetic surfaces. The articulated arm has adjustable joints that can be moved and locked into position. One of the stands shown is a Mitutoyo 7011S-10 model.	
6189Y	Misc. Brown & Sharpe / Mitutoyo Telescopic Gauge Sets; 5/16" to 3-1/2"; (12) Total Pieces	
6190	Central Machinery 1/2 Ton Arbor Press; Central Machinery 1/2 Ton Arbor Press Capacity: 1/2 Ton Leverage Ratio: 20:1 Ram Square: 3/4" Ram Length: 7-1/2" Maximum Height: 4-1/2" Maximum Diameter: 6-1/2" Largest Arbor: 1" Base Dimensions: 4" x 9-1/2"	
6191	DEWALT DW758 8-Inch Heavy-Duty Bench Grinder; DEWALT Bench Grinder It features a powerful 3/4 HP induction motor for industrial grinding applications. The motor runs at 3,600 rpm for high-speed material removal. It has a rugged cast iron base and motor housing for durability. The distance between the wheels is 12-1/2 inches to accommodate longer and larger grinding applications.	
6192	Wilton Tradesman bench vise 5-1/2" Jaw; Wilton Bench Vise: Made from strong ductile iron, often twice as strong as regular cast iron. Features a 360° swivel base. Designed with replaceable jaws and an enclosed spindle construction for greater durability.	
6193	JET 3-ton arbor press; It is made of heavy ductile iron casting for strength and rigidity. The base, ram housing, framework, and 4-position bottom plate are precision machined for accuracy. It is used for riveting, squeezing, punching, bending, and other pressing applications. The press has a removable machined steel anvil for accurate work support in four slot positions.	
6194	Multi-purpose rotating bench vise; Rotating Head: The clamping jaws can rotate a full 360 degrees vertically, allowing material to be clamped at a variety of angles. Swivel Base: The entire base also swivels 360 degrees horizontally, which provides flexibility in positioning the workpiece. Double Jaws: It features two sets of jaws: Standard serrated jaws for clamping regular, flat workpieces. Integrated pipe jaws (V-jaws) for holding round or awkwardly shaped items like pipes or rods. Integrated Anvil: A large, flat area on the back of the vise functions as an anvil, which is useful for bending or shaping metal objects with a hammer. Construction: These vises are typically constructed from heavy-duty cast iron for durability and strength.	
6195	Craftsman shop vac; Craftsman shop vac. 6.5 HP 16 gallon This vac comes with 6' hose and attachments.	
6196	Work bench; This work Bench is steel frame with wood top. It measures 38" tall, 28" wide and 6' long. *Tools and toolbox not included *	
6197	Storage cabinet ; This storage cabinet is made of high strength steel, stronghold brand. Cabinet measurements are 3' wide, 6.5' tall and 33" deep. *No tools or parts are included in this lot, cabinet only*	

6198	Fluke 190 Series III ScopeMeter portable oscilloscope; Functionality: This instrument combines the functionality of a powerful oscilloscope with a built-in digital multimeter (DMM) and a paperless recorder (TrendPlot™ and ScopeRecord™ modes) in a single, portable device. Application: It is primarily used by plant maintenance engineers and technicians for installing, commissioning, and maintaining industrial machinery, automation, process controls, and power conversion electronics. Safety and Environment: The ScopeMeter is built to withstand harsh, dirty, and hazardous conditions, featuring an IP51 rating (dust and drip-proof) and a high safety rating of CAT III 1000 V / CAT IV 600 V. Isolated Inputs: It has four independently isolated inputs, which allows for safe measurements in mixed circuits with different ground references, reducing the risk of accidental short circuits. Advanced Diagnostics: Features like Connect-and-View™ automatic triggering, 100-screen Replay, and deep memory allow users to capture and analyze complex waveforms, intermittent events, and signal fluctuations to quickly diagnose problems and minimize downtime. Connectivity: The device includes USB ports for transferring data to a PC for further analysis and archiving using FlukeView software, or storing data directly to a USB memory device.	
6199	Lasair III Particle Counter; Manufacturer: Particle Measuring Systems. Purpose: Measures and monitors airborne particles in clean or controlled environments for compliance with standards like ISO 14644-1 and EU GMP Annex 1. Technology: Uses a laser diode-based system for high accuracy particle detection. Interface: Features a large 8.4-inch infrared (IR) touchscreen display that is functional even when wearing gloves. Connectivity: Includes options for Ethernet, USB data download, and optional wireless communication, allowing data archiving and remote operation. Portability: Designed with a lightweight, chemical-resistant enclosure and hot-swappable lithium-ion batteries for continuous mobile use.	
6200	AEMC Model 6550 (6555) digital megohmmeter (insulation tester); Model AEMC 6550 (6555) Device Type Megohmmeter /Insulation Resistance Tester Max Test Voltage Up to 10,000 VDC for the Model 6550 and 15,000 VDC for the Model 6555 Resistance Range Measures up to 25 TΩ (Teraohms) for the 6550 and 30 TΩ for the 6555 Test Modes Includes Fixed/Step, Variable, and Ramp voltage modes Safety Rating IEC 61010-1, IEC 61557, 1000V CAT IV, IP54 rated when closed Power Operates on 9.6V rechargeable NiMH batteries or AC power Connectivity Features an optically-isolated USB port for PC communication and data logging of up to 80,000 measurements using DataView software	
6201	Airy Technology P611 handheld laser particle counter; Function: Measures the concentration of airborne particles in different size ranges, such as 0.3 μm to 10.0 μm. Display: Features a large color display that simultaneously shows data for multiple particle sizes. Data Management: The device can store up to 10,000 data samples in its internal memory, which can be transferred to a PC via a USB cable. Portability: It is a compact and lightweight, battery-operated tool designed for field use. Accessories: The complete kit typically includes the counter, an AC adapter, a USB cable, an isokinetic suction probe, and a zero filter, all housed in a storage case.	
6202	Airy Technology P611 handheld laser particle counter; Function: Measures the concentration of airborne particles in different size ranges, such as 0.3 μm to 10.0 μm. Display: Features a large color display that simultaneously shows data for multiple particle sizes. Data Management: The device can store up to 10,000 data samples in its internal memory, which can be transferred to a PC via a USB cable. Portability: It is a compact and lightweight, battery-operated tool designed for field use. Accessories: The complete kit typically includes the counter, an AC adapter, a USB cable, an isokinetic suction probe, and a zero filter, all housed in a storage case.	
6203	Fixturlaser dial indicator kit; Designed for the Verti-Zontal Compound Moves™ alignment method Reduces the amount of bolt loosening and tightening during alignment Shaft diameter range: 25-450 mm (1-18") Includes chains to secure the unit to the shaft	
6204	SKF TMEB 2 Belt Alignment Tool; Laser Unit: This unit (top left) emits a red laser line and attaches to one pulley. Receiver Unit: This unit (bottom left) has a three-dimensional target area that the laser line is projected onto. The pattern on the target area indicates the type of misalignment (vertical angle, horizontal angle, or parallel). Set of V-Guides: The items on the right are various sizes of V-guides (labeled TMEB G2 or TKBA G2) that fit into the pulley grooves, allowing the main units to be securely and magnetically attached to different pulley widths and types.	
6205	Fluke 325 True RMS Clamp Meter; It measures True RMS AC voltage and current on non-linear signals. It is capable of measuring AC/DC current up to 400A and AC/DC voltage up to 600V. It includes functions for frequency, resistance (up to 40kΩ), continuity detection, and temperature measurements. It has a large, easy-to-read, backlit display and a slim, ergonomic design.	
6206	Acoem Belt Hog laser pulley alignment tool kit; Function: This tool is used to accurately align belts and pulleys on machinery, which helps to reduce downtime, extend the life of belts and bearings, and minimize vibration and noise. Operation: The system uses two laser transmitters with strong magnets that mount into the grooves of the pulleys. A laser beam from one unit is projected onto a target on the opposite unit. When the laser line aligns with the reference marks on the target, the pulleys are aligned. Features: Allows for alignment by a single operator with no specialized training. Can measure vertical angle, horizontal angle, and offset simultaneously. Works on pulley diameters 3 inches and larger, over distances from 6 inches to 20 feet.	
6207	Bierer VDA040P Voltage Detector Meter ; Model: VDA040P Manufacturer: Bierer & Associates, Inc. Functions: Proximity Voltage Detection (P), Voltage Detection URD 0-10kV (URD), Voltage Detection Overhead 0-10kV (OH), Voltage Detection Overhead 0-40kV (X4), and Meter TEST (T).	
6208	Fluke 719Pro Electric Pressure Calibrator; Integrated Electric Pump: Allows for easy one-handed pressure calibration up to 300 psi, eliminating the need for an external hand pump. Measurement Capabilities: It measures, sources, and simulates mA signals, and can also measure DC voltage and temperature with an optional RTD probe. Accuracy: Offers best-in-class pressure measurement uncertainty of 0.025% of full scale. Display: A large, backlit screen displays three parameters simultaneously for maximum flexibility. Programmable Limits: Features a programmable pump limit to eliminate over-pressurization and allow users to set target pressures. Durability: Includes pump cleanout ports and a fluid trap to reduce failures from moisture and fluid damage.	

6209	Fluke 724 Temperature Calibrator; Functionality: It can measure and source (simulate) various types of thermocouples (TCs), Resistance Temperature Detectors (RTDs), volts, and ohms. Loop Power: The calibrator can power transmitters (24V loop power supply) while simultaneously measuring the resulting mA signal. Display: A dual-line display allows users to view both the input (measurement) and output (source) values simultaneously. Ease of Use: It is known for its simple, "no menus" controls, making it easy to operate in the field. Automated Testing: Features like 25% and 100% step functions, along with auto-step and auto-ramp, facilitate fast linearity tests and remote testing. Portability & Durability: It is a compact, handheld, and rugged device designed to withstand field use and runs on four AA alkaline batteries.	
6210	Fluke 773 Milliamp Process Clamp Meter; It measures 4 to 20 mA signals without breaking the loop, which helps in troubleshooting transmitters, valves, and PLCs without disrupting the process. It features 0.2% accuracy and 0.01 mA resolution. The dual backlit display shows both mA measurements and the percent of 4 to 20 mA span. It can source and simulate 4-20 mA or 0-10 V control signals for testing control system I/O.	
6211	Fluke 789 ProcessMeter; Functionality Combines the ability to measure standard electrical parameters (voltage, current, resistance, frequency, continuity, and diode test) with process loop calibration functions (sourcing, simulating, and measuring mA current loops). Process Control Features a built-in 24V loop power supply, which eliminates the need to carry a separate power source when testing transmitters offline. It also has a built-in, selectable 250 ohm HART® resistor. Display Equipped with a large, dual display with two levels of backlighting for better visibility. It can simultaneously show milliamp and percentage-of-scale readings for faster troubleshooting and calibration. Safety Designed to meet CAT III 1000 V and CAT IV 600 V safety standards. Additional Features Includes "SpanCheck" buttons (0% and 100%) to quickly toggle between 4 and 20 mA sourcing, and modes like Min/Max/Average/Hold/Relative	
6211A	FLUKE earth ground clamp; The Fluke 1630 is an earth ground clamp meter designed for non-intrusive measurement of earth ground loop resistance and AC leakage currents without needing to disconnect the ground system.	
6211B	Non-contact high voltage detector ; A non-contact high voltage (HV) detector is a safety tool that identifies the presence of a live alternating current (AC) electrical field from a distance, without requiring physical contact with the conductor. These devices are essential for electricians, utility workers, and maintenance professionals and are commonly used with a "hot stick" for safety at a distance.	
6211C	Digital clamp meter; The Kyoritsu 2002PA is an AC digital clamp meter designed for heavy-duty electrical measurements, capable of measuring large AC currents up to 2000A. This unit comes with a soft carry case.	
6211D	Hydraulic wire crimping tool; hydraulic wire crimping tool that delivers 8 tons of crimping power for creating secure connections on various wire sizes.	
6211E	Open/closed circuit tracer; The ideal open/closed circuit tracer kits are from the IDEAL SureTest series, which are highly praised by professionals for their accuracy and unique features like the rotating display and "CertainCircuit" detection.	
6212	Teslong Digital Borescope Inspection Camera Kit w/ Monitor, Flexible Probe & Hard Case; Teslong handheld digital borescope inspection system featuring an integrated color display, articulated control buttons, and a flexible camera probe designed for internal visual inspection of confined or hard-to-reach areas. The kit includes the Teslong inspection camera unit with built-in screen, detachable flexible probe, USB cable, printed user manual, and fitted hard carrying case. The unit is designed for real-time video and still image inspection in applications requiring internal visual access without disassembly, commonly used in mechanical, industrial, automotive, and facilities inspection environments. All components appear to be stored together in the original molded case as shown.	
6213	Agilent 34410A 6½-Digit Bench Digital Multimeter w/ LXI LAN, USB & GPIB; Agilent Technologies model 34410A 6½-digit bench digital multimeter featuring a front-panel LCD display with soft keys and dedicated measurement controls, supporting DC and AC voltage, resistance (2-wire and 4-wire), current, frequency, and continuity functions as indicated on the front panel. The rear panel includes LXI Class C Ethernet (LAN), USB, and GPIB interfaces for remote control and automated test setups, along with front and rear input terminals, external trigger connections, selectable line voltage, and fused current inputs. Unit is labeled 25 VA max power consumption with CAT II 300V rating, and includes internal cooling fan and reference/service ID labeling as shown. Suitable for laboratory, calibration, test, and industrial measurement environments.	
6214	Tektronix Oscilloscope Probe; The Tektronix Oscilloscope Probe, Probe Type: High Voltage 75MHz 20KV 1:1000, Model-P6015A; is a high-performance probe that can measure voltages above 2.5 kV. It can measure DC voltages up to 20 kVeff and impulses up to 40 kV. The probe has a bandwidth of 75 MHz and uses a silicon connection as dielectric. This unit comes with a hard carry case with foam insert.	
6215	EMERSON AMS Trex Device Communicator; The Emerson AMS Trex Device Communicator is a rugged, handheld tool used by technicians to configure, calibrate, and troubleshoot HART and FOUNDATION Fieldbus devices in hazardous industrial environments. It enables on-site diagnostics, allows powering loops directly, and supports valve diagnostics to minimize downtime. This unit comes with a carry case and original box.	
6216	HART communication protocol ; The HART Communication Protocol is a hybrid analog+digital industrial automation open protocol. Its most notable advantage is that it can communicate over legacy 4–20 mA analog instrumentation current loops, sharing the pair of wires used by the analog-only host systems. Comes with leads and carry case.	
6217	Meriam HART communicator ; This 4150X model is specifically designed for intrinsically safe applications in hazardous environments, such as Class I, Division 1 areas. Key uses include monitoring device data, troubleshooting, and cloning device configurations.	
6218	Handheld infrared (IR) calibrator; This CEM BX-500 is a portable handheld infrared (IR) calibrator used to verify the accuracy of non-contact infrared thermometers, pyrometers, and thermal imagers up to (500C or 932F). It functions as a stable, high-performance blackbody target with an emissivity of 0.95 and a 2.25-inch diameter for wide-angle calibration.	
6219	FLUKE transcat ; The Fluke Transcat 5853T is a handheld, portable dry-well calibrator designed for quick and easy temperature verification in the field. It is primarily used to calibrate industrial temperature sensors, including RTDs, thermocouples, and small bimetal thermometers, with a temperature range of 35°C to 375°C (95°F to 707°F).	

6220	Amprobe ; Amprobe THWD-3 Relative Humidity Temperature Meter. This probe uses a precision capacitance sensor to deliver accurate performance with long term stability. This high accuracy instrument measures the full range of relative humidity from 0% to 100% and features an exceptionally wide ambient temperature measurement range from -4 °F to 140 ° F. Comes with soft carry case.	
6221	Yellow Jacket Digital Refrigeration System Analyzer Manifold Kit w/ Hoses & Case; Yellow Jacket digital refrigeration system analyzer manifold kit featuring an integrated electronic display, membrane-style control keypad, and dual rotary manifold valves for system monitoring and diagnostics. The analyzer is housed in a molded hard carrying case and is accompanied by multiple color-coded charging hoses with printed pressure ratings, electrical connection leads, accessory pouch, and manufacturer reference materials, including a Yellow Jacket Refrigeration System Analyzer user manual visible in the case. The manifold body includes multiple hose ports and control knobs configured for refrigeration and HVAC system analysis. All components shown are stored together in the fitted case as photographed. This type of digital refrigeration analyzer is commonly used in professional HVAC and refrigeration environments for system measurement, diagnostics, and service applications.	
6222	Victaulic PFT510 Crimping Tool, w/ Hydraulic Crimping Jaws Set; To Include: Assorted Sizes (1", 1/2", 3/4")	
6223	Bacharach Tru Pointe Ultra HD Ultrasonic Leak Detector Kit w/ Headphones, Probes & Hard Case; Bacharach Tru Pointe Ultra HD ultrasonic leak detector kit designed for detection of pressurized gas and vacuum leaks using ultrasonic technology. The kit includes the Tru Pointe Ultra HD handheld detector, over-ear headphones with coiled cable, multiple probe attachments with protective caps, accessory components, printed user manual, and warranty registration materials, all housed in a fitted hard carrying case with custom foam insert. The Tru Pointe Ultra HD system is commonly used in HVAC, refrigeration, compressed air, industrial maintenance, and facilities diagnostics to locate leaks by identifying high-frequency ultrasonic signals. All components shown are stored together in the molded case exactly as photographed, with manufacturer documentation present.	
6224	Bacharach Tru Pointe Ultra HD Ultrasonic Leak Detector Kit w/ Headphones, Probes & Hard Case; Bacharach Tru Pointe Ultra HD ultrasonic leak detector kit designed for detection of pressurized gas and vacuum leaks using ultrasonic technology. The kit includes the Tru Pointe Ultra HD handheld detector, over-ear headphones with coiled cable, multiple probe attachments with protective caps, accessory components, printed user manual, and warranty registration materials, all housed in a fitted hard carrying case with custom foam insert. The Tru Pointe Ultra HD system is commonly used in HVAC, refrigeration, compressed air, industrial maintenance, and facilities diagnostics to locate leaks by identifying high-frequency ultrasonic signals. All components shown are stored together in the molded case exactly as photographed, with manufacturer documentation present.	
6225	Shimpo DT-205LR handheld combination laser tachometer; It combines both contact and non-contact capabilities for measuring speed and length. It can measure RPM, mPM, YPM, FPM, and IPM. It has a broad speed range, measuring up to 99,999 RPM. The unit features a rugged die-cast aluminum housing for durability.	
6226	Milwaukee Corded Portable Band Saw w/ Blade & Hard Carrying Case; Milwaukee corded portable band saw housed in a molded red hard carrying case, featuring an integrated electric motor, dual handle design, front blade guard, and continuous-loop band saw blade installed on the saw frame. The tool is configured for handheld cutting applications and includes an attached power cord routed within the case. The interior case is custom-molded to fit the band saw and accessories, with the Milwaukee brand name visible on both the tool housing and exterior case. This type of portable band saw is commonly used in industrial, mechanical, fabrication, electrical, and maintenance environments for controlled cutting of metal and other materials. All components shown are stored together in the case exactly as photographed.	
6227	Milwaukee Corded Hammer Drill Kit w/ Side Handle, Bits & Hard Carrying Case; Milwaukee corded hammer drill housed in a molded red hard carrying case, featuring a pistol-grip handle, auxiliary side handle mount, keyed drill chuck, and integrated power cord. The kit includes visible drill accessories stored within the case, including a packaged masonry-style drill bit, an additional loose drill bit, and a wire cup brush attachment, along with the installed side handle and chuck key as shown. The interior case is custom-molded to fit the hammer drill and accessories, with Milwaukee branding visible on both the tool housing and exterior case. This type of corded hammer drill kit is commonly used in construction, electrical, mechanical, and industrial maintenance environments for drilling and hammer drilling applications. All items shown are included and stored together in the case exactly as photographed.	
6228	Milwaukee M18 Force Logic 600 MCM Crimper Set; CAT#: 2679-20 SN#:G69DD224600127 Power Supply: 18V	
6229	Makita hammer drill; The Makita HR2475 hammer drill comes with a variety of different sized and purposed bits. 7 Amp Corded 1 in. SDS-Plus Concrete/Masonry Rotary Hammer Drill with Hard Case.	
6230	Snap-on Electronic Digital Torque Wrench w/ Display, Calibration Label & Hard Case; Snap-on electronic digital torque wrench featuring an integrated electronic display with multi-button control interface, metal torque shaft, and ratcheting drive head, housed in a molded Snap-on hard carrying case. The wrench includes a visible calibration label affixed to the tool body indicating a calibration date of January 16, 2025 with a due date of January 16, 2026, along with serial and service order identification as shown. The tool is designed for precision torque measurement and controlled fastening in professional automotive, industrial, mechanical, and maintenance environments. All components shown are included and stored in the Snap-on case exactly as photographed, with the electronic torque wrench, case, and calibration labeling present.	
6231	AMPROBE MAN30 Manometer ; Features Gauge Pressure and Differential Pressure; S/N 09090344	
6232	Dwyer Series 475 Mark III Digital Manometer; 0-10.00" W.C. Range; 5 PSIG Max. Pressure; S/N 475-0T-FM-AV	
6233	Extech 407119 CFM/CMM Hot Wire Anenimeter; S/N A.057497	

6234	Milwaukee mag drill; The 4203 electromagnetic variable speed adjustable base features solid state electronic switching and an 11 in. drill travel. 120vac, 12.5 amp.	
6235	Bosch GBH 2-26 RE Professional Rotary Hammer ; It has a rated input power of 800 W. The impact energy is 2.7 J. It features a rotating brush plate for equal power in forward and reverse rotation. The tool holder is SDS plus, allowing for quick, tool-free bit changes. It is designed for drilling into concrete, masonry, wood, and metal.	
6236	Bosch JS365 Corded TOP Handle Jigsaw ; Model#: JS365 SN#: 01000313 Power Supply: 120V, 60Hz, 6.5A, 500-3100 RPM Max Cut Depth: 90mm	
6237	Bosch GRL 800-20HV Rotary Laser Set, w/ Bosch BT 160 Professional Tripod; Model#: GRL800-20HV SN#: 3601K61M10 Laser Projection: Horizontal; Vertical Laser Beam Color:Red Laser Class: 3R Laser Output: <5 mW Number of Dots: 2 Working Range with Receiver (Maximum)2,000 ft Working Range without Receiver (Maximum)100 ft Outdoor Range (Maximum) 2,000 ft Accuracy: ±1/16" @ 100 ft Type: Electronic Self-Leveling Self-Leveling Range: ±5° Overall Depth: 7" Overall Height: 7-1/2" Overall Width: 6-11/16" Tripod Thread Size: 5/8"-11"	
6238	HILTI TE 60-ATC/AVR Combihammer ; Model#: TE 60-ATC/AVR SN#: 087240 Date of Mfg: 06/21 Power Supply: 120V, 60Hz, 13.0 A, 0-350 RPM	
6239	Greenlee 767 Hydraulic Hand Pump / 1/2" - 4" Punch Kit ; To Include: Assorted Size Punches Max PSI: 6,500	
6240	Lincoln 12V Cordless Grease Gun Kit w/ Flexible Hose, Battery & Hard Case; Lincoln 12-volt cordless grease gun kit housed in a molded hard carrying case, featuring a pistol-grip grease gun with metal grease barrel, trigger handle, and flexible high-pressure grease hose with coupler attached. The kit includes a removable 12V battery pack, battery charger, and power cord stored within the case, with Lincoln branding visible on the grease gun body, battery, and charger. Warning and safety labels are present on the grease barrel indicating high-pressure operation and proper use instructions. The interior case is custom-molded to fit the grease gun, hose, battery, charger, and accessories as shown. This type of cordless grease gun is commonly used in automotive, industrial, agricultural, fleet maintenance, and heavy equipment lubrication applications. All items shown are included and stored together in the case exactly as photographed.	
6241	Drill Doctor Drill Bit Sharpener by Darex w/ Power Unit & Hard Carrying Case; Drill Doctor drill bit sharpener system manufactured by Darex, LLC, housed in a molded blue hard carrying case labeled "Drill Doctor – The Drill Bit Sharpener." The kit includes the electric drill bit sharpening unit with integrated power switch and attached power cord, along with multiple molded accessory ports and holders built into the case interior as shown. Manufacturer label on the unit indicates approximately 15,000 RPM operation, 110–120V AC input, 60 Hz, 1.75A, with ETL listing and safety markings visible. The sharpener is designed for restoring cutting edges on drill bits using a guided sharpening mechanism contained within the unit. All components shown are included and stored together in the hard case exactly as photographed.	
6242	Hydraulic Hand Pump with Assorted Punch & Die Kit – Metal Carry Case; This lot features a manual hydraulic hand pump paired with an assorted punch and die set, housed in a fitted metal storage case. The kit includes a hydraulic cylinder with hose and hand lever pump, along with multiple interchangeable round punch and die components in varying sizes, associated threaded hardware, and accessories as shown. Components appear to be steel construction, designed to work together as a hydraulic punch system, with the hand pump providing controlled pressure to the punch assembly.	
6243	Manual Punch & Die Set w/ Assorted Steel Punch Rings – Portable Red Case; This lot consists of a manual punch and die set housed in a red molded carry case, containing an assortment of circular steel punch rings and matching die components in multiple sizes, along with a manual handle, alignment pin, and related accessories as shown. The components are precision-machined metal rings designed to work together as a punch-through system, allowing material to be cut or pressed using manual force applied through the handle and stacked punch/die configuration. The set includes multiple diameter rings arranged in the case, offering a wide range of punch sizes, with all items organized for transport and storage. No manufacturer markings or size specifications are visible	
6244	IET Labs OS-270 ohmSOURCE electronically controlled resistance Box; Model: OS-270 Serial #D1-13350387 Interface: Resistance values are entered using a calculator-style keypad. Resistance Range: It offers a range from approximately 1 Omega to 1.5M Omega Power: The unit is powered by four AAA alkaline batteries and features an auto-off function to conserve power.	
6245	Bosch Electric Angle Grinder – Model 0 601 852 B16, 120V, 15A; This lot features a Bosch electric angle grinder, model number 0 601 852 B16, rated for 120V, 60Hz operation at 15 amps, with a listed no-load speed of 6,000 RPM, as indicated on the manufacturer's data plate. The grinder includes a side auxiliary handle, fixed power cord with standard plug, and metal gear housing, consistent with heavy-duty grinding and cutting tools in industrial and shop environments. The unit carries UL listing markings and manufacturer identification from Robert Bosch Tool Corporation. No grinding discs or accessories beyond what is shown are included. Buyers should review photos to confirm exact configuration, mounting points, and overall form factor.	
6246	DeWalt Industrial Electric Tool Lot – DW235G Drill, DW317 Jig Saw, DWE304 Reciprocating Saw, 120V; Industrial DeWalt electric tool lot consisting of three corded, professional-grade units: DW235G 1/2 VSR drill (7.8A, 0–850 RPM), DW317 variable-speed orbital jig saw (5.5A, 1 stroke, up to 3,100 SPM), and DWE304 variable-speed reciprocating saw (10A, 1-1/8 stroke, up to 2,800 SPM). All tools are 120V AC / 50–60 Hz, UL / CSA / NOM marked per manufacturer nameplates. Heavy-duty housings, industrial switches, and factory cords present as shown. Lot sold as a group; only items visible in photos are included. Ideal surplus package for maintenance shops, fabrication floors, and industrial tool inventory.	
6247	Skilsaw Worm Drive Circular Saw – SPT78MMC, 8-1/4 Blade, 15A, 120V; Industrial Skilsaw worm drive circular saw, model SPT78MMC, featuring an 8-1/4 (203 mm) blade capacity, 15-amp motor, 120V / 60Hz power, and 3,900 RPM no-load speed per manufacturer nameplate. Worm-drive gearing with heavy-duty metal housing and integrated blade guard, consistent with jobsite and shop use. UL listed; manufactured under Chevron North America branding as shown. Includes attached power cord and base plate; no blades or accessories beyond what is pictured. Exact configuration reflected in photos.	

6248	Industrial Sander Lot – Electric Orbital Sander & Pneumatic Disc Sander, Shop Tools; Industrial sander tool lot consisting of one corded electric orbital/palm sander (120V AC, high-speed operation per nameplate) and one pneumatic disc sander with suction-cup style backing pad and air-tool quick-connect fitting. Electric unit includes integrated dust collection port and attached power cord; pneumatic unit features trigger control and metal backing plate assembly as shown. Mixed electric and air-powered configuration suitable for industrial maintenance, fabrication, and shop surplus inventories. Only items visible in photos are included; no additional pads, abrasives, or accessories present. Exact configuration reflected in images.	
6249	(2) Milwaukee 1/2" Driver Drills; CAT#: 2606-20 / 2601-20 SN#: F24EM2340-01129 / B28BD113507383 Power Supply: 18V, 800 RPM	
6250	(3) Milwaukee Impact Drivers ; CAT#: 2650-20 / 2656-20 SN#: B55BD112101051/ B55BD112007239 Power Supply: 18V, 3200 RPM,	
6251	Milwaukee Tool M18 Tool Lot – Grease Gun, Random Orbit Sander, Compact Vacuum; Heavy-duty Milwaukee M18 cordless tool lot including an 18V grease gun (rated up to 10,000 PSI per nameplate), 5 in. random orbit sander (7,000–12,000 OPM, Cat. No. 2648-20), and M18 compact vacuum (Cat. No. 0882-20). Tools are bare units only with no batteries or chargers included. Industrial red lithium platform tools suitable for fleet service, maintenance departments, fabrication shops, and surplus resale. Exact items and configuration shown in photos only.	
6252	RIDGID 18V SubCompact Brushless Cordless 6-1/2 in. Circular Saw, AND Ridgid 18V Brushless Impact Driver, AND Ridgid 18V Hybrid Folding Panel Light, AND (3) 18V RIDGID Battery Chargers; RIDGID Circular Saw Power Source: 18V battery-powered (cordless). Performance: Delivers a no-load speed of up to 5,000 RPM. Design: It has a heavy-duty aluminum base for durability, yet is designed to be compact and lightweight. Capacity: Features a 2-1/4 inch cutting capacity and a 50-degree bevel capacity. Motor: Equipped with a brushless motor, which provides efficiency and longer runtime. Ridgid 18V Brushless Impact Driver: Model R86038 features brushless motor technology for up to 50% more runtime and longer motor life. The tool has a 1/4 inch hex quick-eject chuck. It offers multiple speed settings, with some models having three or four modes. The driver delivers significant torque, often cited around 2250 in./lbs. or more depending on the specific model. Ridgid 18V Hybrid Folding Panel Light: Using an 18V 6.0 Ah battery, it can run for approximately 14 hours.	
6253	(3) DeWalt 20V MAX 1/2 Gallon Wet/Dry Portable Vacuums, AND (2) DeWalt DCB107 12V/20V MAX Lithium Ion chargers, AND DeWalt DW9226 7.2V-18V NiCd 1-Hour Battery Charger, AND (3) 20V Dewalt 2AH Batteries; Cordless vacuum that runs on all DeWalt 20V MAX battery packs. The HEPA wet/dry filter traps 99.97% of dust at 0.3 microns. It features dual clean-up modes with a front utility nozzle or an extendable rubber hose. The 1/2 gallon tank has a heavy-duty latch for easy emptying and cleaning. DeWalt DCB107 12V/20V MAX Lithium Ion chargers: It is compatible with all DeWalt 12V and 20V MAX Li-Ion battery packs. The charger is designed to minimize downtime by charging batteries in one hour or less. It features an LED indicator system to show the battery's charging status (charging, charged, or hot/cold delay). The charger operates at 120 volts input and has a 1.25 amp DC nominal output.	
6254	DeWalt FLEXVOLT 60V MAX 1000 PSI Cordless Power Cleaner; Powerful Cleaning: Delivers up to 1,000 PSI of water pressure and a 1.0 GPM flow rate. Cordless Operation: Uses the DeWalt 60V MAX FLEXVOLT battery system for portability. Versatile Water Source: Can draw water from a standard garden hose or any freshwater source (like a bucket) using the included suction hose. Brushless Motor: Features a high-efficiency brushless motor for performance and runtime.	
6255	Rigol / RH Systems / Schumacher Electric / Hioki Industrial Electrical Test & Battery Service Lot; Industrial electrical testing and battery service equipment lot including a Rigol DM3064 6½-digit digital multimeter, RH Systems Model 973 enclosure (100–240 VAC, 50/60 Hz, 100 W, RS-232 interface, sample gas input/output, external temperature port; made in Switzerland), Schumacher automatic battery charger with heavy-gauge clamp leads, analog battery load tester, Hioki 3454-11 digital insulation/megohmmeter (up to 1000V test range per front panel), and a red metal floor-standing industrial unit with vertical duct/outlet as shown. Mixed laboratory, maintenance, and service-shop instrumentation suitable for facilities, utilities, and industrial surplus resale. Only items visible are included; exact configuration reflected in photos.	
6256	Rigol DM3064 6½-Digit Digital Multimeter + RH Systems Model 973 Instrument Enclosure; Industrial test and measurement lot featuring a Rigol DM3064 6½-digit digital multimeter mounted above an RH Systems Model 973 enclosure with front-panel fan, RS-232 interface, sample gas input/output ports, external temperature connection, and integrated power inlet. RH Systems unit rated 100–240 VAC, 50/60 Hz, 100 W, made in Switzerland per nameplate. Configuration appears set up for laboratory or process-control instrumentation environments. Only components shown are included; exact layout and condition reflected in photos.	
6257	Milwaukee M12 chargers; This lot contains (9) Milwaukee M12 chargers AND (1) M4 charger. Used for and M12 or M4 Milwaukee tool battery charging needs.	
6258	Heat guns; This lot contains (2) 120vac heat guns. (1) Ultra heat brand (1) Steinel brand These heat guns are used for stripping paint, removing wallpaper, thawing frozen pipes, and bending plastics.	
6259	Makita DC18RA Rapid Battery Charger, AND (3) 18V Makita batteries, AND 18V Black & Decker Battery 18V Battery; Compatibility: It charges all Makita 7.2V-18V LXT slide-style batteries, including popular models like BL1830, BL1840, BL1850, and BL1860. Rapid Charging: The charger uses a built-in CPU to communicate with the battery's memory chip, optimizing the charging process for speed and battery life. It can charge an 18V 3.0Ah Li-ion battery in approximately 22-30 minutes and a 5.0Ah battery in about 45 minutes. Cooling System: An integrated fan circulates air to cool the battery during charging, which minimizes charge time and helps extend the battery's overall lifespan. Indicators: LED lights on the front panel display the battery's condition and charging status, while an audible melody sounds upon completion. Makita 18V LXT Lithium-Ion 3.0Ah batteries: Voltage and Capacity: It provides 18V of power with a 3.0Ah (amp-hour) capacity. Charging: The battery is engineered to reach a full charge in approximately 30 minutes using a Makita Rapid Optimum Charger (sold separately). Durability: It features an impact-resistant outer case and a shock-absorbing inner-liner to protect against jobsite conditions. LED Indicator: An integrated L.E.D. battery charge level indicator allows you to monitor the battery's charge status. Compatibility: It is compatible with a wide range of Makita 18V LXT tools and can be used as a replacement for other models like BL1815, BL1840, BL1850, and BL1860, though higher Ah batteries will offer longer run times.	
6260	Three jaw gear puller; (4) gear pullers. These are mechanical tool used to safely and effectively remove press-fit parts from shafts, such as bearings, pulleys, gears, and flywheels, without causing damage to the components.	

6261	Westward Lock-On, Jaw-Type Puller Set; To Include: All Contents	
6262	Assortment of bearings; Motor bearing included in this lot are SKF and NSK brands. The sizes are (21) 6310 AND (11) 6014.	
6263	Lot of Assorted Proto Slide Hammer Puller Sets ; To Include: All Contents	
6264	Lot of Assorted Manual Lock Pullers/ Bearings Splitters / Jaws Pullers; To Include: All Contents	
6265	Bearing puller parts; This lot contains multiple sized claws, center stud and hardware for bearing pullers.	
6266	Lot of Garlock 3545 ring gaskets, AND SPXFLOW O-Rings; Assortment of gaskets & O-Rings	
6267	Assortment of Industrial Silicone Rubber Seals; Variety of different sized rubber seals 88mm - 1250mm	
6268	Assorted Industrial Fasteners Lot – Hex Bolts, Socket Head Cap Screws, Nuts & Washers (Mixed Sizes); Large mixed lot of industrial metal fasteners consisting of assorted hex head bolts, socket head cap screws, matching hex nuts, and flat washers, packaged across multiple boxes as shown. Contents appear to include a range of thread lengths, diameters, and head styles, with both fully and partially threaded fasteners present. Includes loose bulk hardware and some bagged components, with quantities varying by box. This is a mixed, unsorted lot being sold as-is and as-shown, suitable for buyers seeking bulk fasteners for inventory, fabrication, maintenance, or resale.	
6269	Assortment of VMQ (Vinyl Methyl Quality)/ Oil seals; Variety of different sized seals	
6270	Industrial Machined Steel Shafts with Coiled Rubber Extrusion / Hose – Mixed Lot; Mixed industrial lot consisting of three precision-machined cylindrical steel shafts and a large coiled length of black rubber extrusion or hose, bundled and stored together as shown. The steel components appear to be solid machined shafts with stepped diameters, threaded sections, and axial holes, each tagged and grouped as a set. The coiled material is a continuous rubber profile with a solid cross-section, supplied in bulk coil form. Exact specifications, dimensions, material grades, and intended applications are not marked and have not been verified. Lot is sold as a single unit, as-shown, with all contents included.	
6271	Mixed Industrial Roller Bearing Lot – Assorted Brands & Sizes (Boxed & Loose); Mixed lot of industrial roller bearings from multiple manufacturers, including a combination of boxed units and loose bearings stored in protective packaging, as shown. The lot appears to include spherical roller bearings and related components in varying sizes and configurations, with some original branded boxes present alongside unboxed items. Markings, part numbers, and packaging vary by unit, and not all bearings are matched or complete sets. All items pictured are included and sold together as one mixed, unsorted lot, offered as-shown.	
6272	(25) SKF 39135 shaft seals, (20) Dichtomatik TCM Oil Seals; Manufacturer: SKF, a global leader in sealing solutions. Specifications: It is a metric seal with a 100mm shaft diameter. Features: Provides superior protection against dirt and water. Application: Designed for use in various industrial and automotive applications, keeping lubricants in and contaminants out. Manufacturer: Freudenberg-NOK Sealing Technologies is the parent company and manufacturer of the Dichtomatik brand. Type: Radial shaft seal (oil seal), often featuring a dual lip (TC type) with a garter spring for enhanced sealing and protection from contaminants. Material: Commonly made with Nitrile Rubber (NBR) for the lip material and carbon steel components, which provides good resistance to oils and a wide range of service temperatures.	
6273	Rosemount manifold ; These manifolds are high-performance valve solutions designed for pressure, differential, and flow transmitters, featuring 2-, 3-, and 5-valve configurations to enable secure isolation, calibration, and venting. They are commonly used with Coplanar™ or in-line transmitters to reduce leak points and improve safety in harsh industrial environments.	
6274	Rosemount manifold ; These manifolds are high-performance valve solutions designed for pressure, differential, and flow transmitters, featuring 2-, 3-, and 5-valve configurations to enable secure isolation, calibration, and venting. They are commonly used with Coplanar™ or in-line transmitters to reduce leak points and improve safety in harsh industrial environments.	
6275	Rosemount manifold ; These manifolds are high-performance valve solutions designed for pressure, differential, and flow transmitters, featuring 2-, 3-, and 5-valve configurations to enable secure isolation, calibration, and venting. They are commonly used with Coplanar™ or in-line transmitters to reduce leak points and improve safety in harsh industrial environments.	
6276	Rosemount manifold. (head only); These manifolds are high-performance valve solutions designed for pressure, differential, and flow transmitters, featuring 2-, 3-, and 5-valve configurations to enable secure isolation, calibration, and venting. They are commonly used with Coplanar™ or in-line transmitters to reduce leak points and improve safety in harsh industrial environments.	
6277	Rosemount manifold WITH pressure diaphragm ; These manifolds are high-performance valve solutions designed for pressure, differential, and flow transmitters, featuring 2-, 3-, and 5-valve configurations to enable secure isolation, calibration, and venting. They are commonly used with Coplanar™ or in-line transmitters to reduce leak points and improve safety in harsh industrial environments.	
6278	Rosemount manifold WITH pressure diaphragm ; These manifolds are high-performance valve solutions designed for pressure, differential, and flow transmitters, featuring 2-, 3-, and 5-valve configurations to enable secure isolation, calibration, and venting. They are commonly used with Coplanar™ or in-line transmitters to reduce leak points and improve safety in harsh industrial environments.	

6279	Emerson Micro Motion 2700R transmitter; This Emerson 2700R is a rugged, field-mount multivariable flow and density transmitter designed for use with Micro Motion Coriolis sensors, offering precise measurement and a variety of output options.	
6280	Emerson Micro Motion 2700R transmitter; This Emerson 2700R is a rugged, field-mount multivariable flow and density transmitter designed for use with Micro Motion Coriolis sensors, offering precise measurement and a variety of output options.	
6281	Emerson Micro Motion 2700R transmitter; This Emerson 2700R is a rugged, field-mount multivariable flow and density transmitter designed for use with Micro Motion Coriolis sensors, offering precise measurement and a variety of output options.	
6282	Emerson Micro Motion 2700R transmitter; This Emerson 2700R is a rugged, field-mount multivariable flow and density transmitter designed for use with Micro Motion Coriolis sensors, offering precise measurement and a variety of output options.	
6283	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6284	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6285	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6286	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6287	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6288	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6289	Drager Polytron 2 XP Tox; This is an explosion-proof fixed gas detector used for continuous monitoring of toxic gases and oxygen in the ambient air of hazardous areas.	
6290	Drager PIR 7000 assembled to a Drager Polytron 8000; This Drager PIR 7000 is an explosion-proof point infrared gas detector designed for continuous monitoring of flammable hydrocarbon gases in harsh industrial environments such as offshore installations. It features a rugged stainless steel enclosure and advanced 4-beam technology for reliable, drift-free operation. Assembled to this infrared gas detector is a Drager Polytron 8000 which is a high-end, explosion-proof fixed gas detector transmitter designed for monitoring over 100 different toxic gases and oxygen using a range of compatible electrochemical sensors.	
6291	Crystal Engineering XP2i digital test gauge; This unit is an ultra-rugged, intrinsically safe pressure gauge known for its high accuracy, stability across a wide temperature range, and user-friendly interface. It is a top choice for demanding field calibration and pressure testing applications.	
6292	Ashcroft Type 8409 Duragauge; The Ashcroft Type 8409 Duragauge is a 4.5" dial receiver pressure gauge designed for use with pneumatic transmitters, indicating process parameters like pressure, temperature, flow, or level, based on a standard air pressure signal. 0 PSI to 160 PSI.	
6293	VAC V200E; The VAC V200E is a rugged, compact electro-pneumatic valve positioner known for its high repeatability and reliability in a wide range of industrial applications. It converts an electronic control signal (typically 4-20 mA or 0-10 VDC) into a pneumatic signal to precisely control valve or actuator position.	
6294	Rotork YT-1000 Positioner ; The Rotork YT-1000 is a durable and economical analog electro-pneumatic positioner designed for high performance in various industrial settings. It receives a standard 4-20 mA DC input signal and translates it into a proportional pneumatic output pressure to control the valve position. This unit has a high resistance to vibration.	
6295	YTC YT-1000 Positioner ; The YTC YT-1000 is a durable and economical analog electro-pneumatic positioner designed for high performance in various industrial settings. It receives a standard 4-20 mA DC input signal and translates it into a proportional pneumatic output pressure to control the valve position. This unit has a high resistance to vibration.	
6296	YTC YT-1000 Positioner ; The YTC YT-1000 is a durable and economical analog electro-pneumatic positioner designed for high performance in various industrial settings. It receives a standard 4-20 mA DC input signal and translates it into a proportional pneumatic output pressure to control the valve position. This unit has a high resistance to vibration.	
6297	Rotork YT-1000 Positioner ; The Rotork YT-1000 is a durable and economical analog electro-pneumatic positioner designed for high performance in various industrial settings. It receives a standard 4-20 mA DC input signal and translates it into a proportional pneumatic output pressure to control the valve position. This unit has a high resistance to vibration.	
6298	Endress + Hauser Vibronic Point level detection Liquiphant FTL51; Specialities Foamdetection Detect a densitychange second line of defense Supply / Communication PROFIBUS PA 19...253V AC 10...55V DC-PNP 19...253V AC or 10...55V DC 8 /16mA, 11...36V DC NAMUR PFM Ambient temperature -50 °C...+70 °C (-58 °F...+158 °F) Process temperature -50 °C...+150 °C (-58 °F...+302 °F) Process pressure / max. overpressure limit Vacuum...100 bar Min. density of medium 0.5g/cm³(0.4g/cm³ optional) Main wetted parts 316L / Alloy Process connection Thread: G3/4A, G1A, R3/4", R1, NPT3/4, NPT1 Flange: DN25... DN100, ASME 1"...4", JIS 25A...100A Process connection hygienic Tri-Clamp ISO2852 Sensor length Length 130mm (5.12") (Liquiphant II) 148mm...6000mm (5.83"...236")	

6299	Endress + Hauser Vibronic Point level detection Liquiphant FTL51; Order#: FTL51-RAL2CB5E5A SN#: E300C915027 Specialities Foamdetection Detect a densitychange second line of defense Supply / Communication PROFIBUS PA 19...253V AC 10...55V DC-PNP 19...253V AC or 10...55V DC 8/16mA, 11...36V DC NAMUR PFM Ambient temperature -50 °C...+70 °C (-58 °F...+158 °F) Process temperature -50 °C...+150 °C (-58 °F...+302 °F) Process pressure / max. overpressure limit Vacuum...100 bar Min. density of medium 0.5g/cm ³ (0.4g/cm ³ optional) Main wetted parts 316L / Alloy Process connection Thread: G3/4A, G1A, R3/4", R1, NPT3/4, NPT1 Flange: DN25...DN100, ASME 1"...4", JIS 25A...100A Process connection hygienic Tri-Clamp ISO2852 Sensor length Length 130mm (5.12") (Liquiphant II) 148mm...6000mm (5.83"...236")	
6300	Endress + Hauser Vibronic Point level detection Liquiphant FTL51; Order#: FTL51-RA82CB5E5A SN#: E300CA15027 Specialities Foamdetection Detect a densitychange second line of defense Supply / Communication PROFIBUS PA 19...253V AC 10...55V DC-PNP 19...253V AC or 10...55V DC 8/16mA, 11...36V DC NAMUR PFM Ambient temperature -50 °C...+70 °C (-58 °F...+158 °F) Process temperature -50 °C...+150 °C (-58 °F...+302 °F) Process pressure / max. overpressure limit Vacuum...100 bar Min. density of medium 0.5g/cm ³ (0.4g/cm ³ optional) Main wetted parts 316L / Alloy Process connection Thread: G3/4A, G1A, R3/4", R1, NPT3/4, NPT1 Flange: DN25...DN100, ASME 1"...4", JIS 25A...100A Process connection hygienic Tri-Clamp ISO2852 Sensor length Length 130mm (5.12") (Liquiphant II) 148mm...6000mm (5.83"...236")	
6301	(2) Resistance Thermometers; To Include: Wika TR10, GINICE GPT-100	
6302	ASCO solenoid and actuator ; These ASCO is proven for air or gas applications. 35psi-130psi. 1/4" pipe. This lot contains (5) solenoids.	
6303	Rosemount stainless steel isolation valves; These are a two-valve, block-and-bleed manifold designed for direct assembly with pressure transmitters and gauges. There are (3) valves in this lot.	
6304	Mixed Industrial Sensors, Detectors & Electrical Components Lot – Assorted Brands & Types; Mixed lot of industrial electrical and instrumentation components consisting of assorted sensors, detectors, control modules, power adapters, wiring, and related hardware, sold together as one unsorted lot. Items appear to include gas or process detectors with probe assemblies, digital display modules, industrial housings, power supplies, and miscellaneous electronic components and accessories, stored in bins and loose as shown. Multiple brands, models, and configurations are present, with varying connection types and mounting styles.	
6305	RIDGID 535 Series Auto Chuck Pipe Threading Machine ; Model#: 535-A SN#: EBC038371011 Power Supply: 120V, 60Hz, 18.0 A	
6306	AVL 2 Ton Hydraulic Engine Hoist; Powered by 8 Ton Long Ram Jack Hydraulic Piston; S/N 673.65142318	
6307	Craftsman gas powered power washer; This Craftsman power washer is gas powered, 3,300psi, 2.4gpm and comes with different degree tips for different purposes. Honda GCV200 engine.	
6308	U.S. General 30 5-Drawer Rolling Mechanic's Cart with Casters – Includes Contents; U.S. General 30-inch, 5-drawer rolling mechanic's cart with hinged top compartment and lower storage shelf, mounted on four heavy-duty swivel casters as shown. Cart includes multiple drawers, lid struts, side handle, and integrated drawer locking when lid is closed. The cart is being sold with assorted contents present at time of photography, including paint rollers and frames, putty knives, scrapers, tape, small hand tools, containers, and miscellaneous shop supplies stored in the drawers and lower tray.	
6309	Vidmar 11-Drawer Toolbox; Photos Taken While in Use - CONTENTS NOT INCLUDED	
6310	Huot 3-Drawer Parts Cabinets and Misc. Parts; CONTENTS NOT INCLUDED	
6311	Justrite Sure-Grip® EX Flammable Liquid Storage Cabinet – 90-Gallon, Double Door; Justrite Sure-Grip® EX flammable liquid storage cabinet with double doors, bright yellow steel construction, and factory safety labeling, as shown. Cabinet is marked 90-gallon (340 liter) capacity, FM Approved, and labeled for NFPA Code 30 / OSHA regulations, with manufacturer identification indicating Made in USA. Interior includes adjustable steel shelving and currently contains assorted containers and materials visible at time of photography; contents are shown for reference only. Cabinet features recessed handle, reinforced doors, and welded seams typical of industrial flammable storage units. APPROX measurements: 43"x34"x65.75"	
6312	Justrite Sure-Grip® EX Acid & Corrosive Storage Cabinet – 45-Gallon, FM Approved; Justrite Sure-Grip® EX acid and corrosive storage cabinet constructed of corrosion-resistant steel with factory blue finish, double doors, and recessed locking handle, as shown. Cabinet is clearly labeled Acid / Acido / Acide, FM Approved, and marked for NFPA Code 30 / OSHA regulations, with a 45-gallon (170-liter) capacity and Part No. 894522, manufactured in the USA. Interior includes integrated spill containment sump and adjustable shelf supports, with assorted containers visible at time of photography. Sold as one cabinet, as-shown, with contents shown for reference only. APPROX Measurements: 43"x18"x65.5"	
6313	RIDGID Universal Storage Chest; Dimensions: 48" W x 24" D x 28" H Construction: 16-gauge steel with fully welded seams Storage Volume: 16 cu. ft. Weight: 149 lbs Security: Corner-located lock housing, accepts #5 padlocks, and features a solid lock tang to prevent pry-ins Mobility: Recessed ergonomic handles and 12-gauge steel skids Interior: One 8-inch adjustable shelf/bin, locking cover support **CONTENTS NOT INCLUDED**	
6314	Lot of Assorted Electrical PPE; To Include: Arc Flash Face Shields, Tool Belts, Zip Ties, Electrical Tape, Plastic Bottles, Etc.	
6315	(3) Hybrid GEN5X Universal Collapsible Tripod Lighting Stand, w/ 1/4"-20 Threads for Mounting; Dimensions: 30.00" x 30.00" x 6.00"	
6316	Assortment of tools; This lot contains (3) different tools. (1) Extech temperature gun. used to measure surface temperatures quickly and safely in a wide array of Applications. (1) Probe Master Model 4915 is a comprehensive passive voltage probe master kit designed for high-performance oscilloscopes (1) Parker gas pressure test kit.	

6317	Magnehelic gauges; This lot contains (7) magnehelic gauges, a variety of measurements including PSI and inches of water. Pressures on gauges range from 0-1 psi to 0-100 psi. These are used for pressure differential reading in industrial settings.	
6318	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 36”Dx48”Wx77.5”H	
6319	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx48”Wx77.5”H	
6320	Testing equipment ; This lot contains testing equipment such as a psychrometer, dewpoint transmitter, tank pressure kit and partial counter kit. There are some empty carrying cases within this cabinet. * The Cabinet is not included in this lot*	
6321	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx48”Wx77.5”H	
6322	CS Instruments LD 500 Ultrasonic Leak Detector; Ultrasonic Detection: The LD 500 converts inaudible ultrasound into an audible frequency range, allowing users to precisely pinpoint the source of a leak even in noisy industrial environments with the included headset. Documentation and Reporting: It features a built-in camera and touchscreen display that allows users to photograph the exact location of a leak, add descriptions, and record the estimated flow rate (l/min) and annual cost (€ /year or \$/year) of the lost gas. This data can be exported via USB to software for creating reports that comply with ISO 50001 standards. Energy Savings: By accurately identifying and quantifying leaks, the device helps companies significantly reduce energy costs and improve the efficiency of their systems, as compressed air leaks are a major source of energy waste. Portability: It is a lightweight, battery-powered device designed for all-day use during leak detection surveys.	
6323	CM manual chain fall; This lot contains (1) CM chain fall, series 622, 5-Ton capacity.	
6324	CM manual chain fall; This lot contains (1) CM chain fall, series 622, 5-Ton capacity.	
6325	OZ lifting products manual chain fall; This lot contains (1) OZ chain fall, 6x18 chain, 1-Ton capacity.	
6326	B/A Heavy-Duty Alloy Chain Slings, AND Heavy-Duty Cable ties, Sherline suspended hydraulic scale, AND Heavy-Duty Chain link assembly; B/A Heavy-Duty Alloy Chain Slings: 5-1/16” Grade 100 Capacity 5700lbs Variety of Heavy-Duty chains/ties	
6327	Assortment of Lift-All Webmaster 1600 polyester web slings, AND TOOLWELL Polyester Abrasion Protection Pad; Material: 2-ply polyester webbing. Width: 2 inches. Capacity: 6,400 lbs (vertical), 5,000 lbs (choker), 12,800 lbs (basket). Features: Lightweight, flexible, and has low stretch for better load control.	
6328	Northern Tool + Equipment heavy-duty cargo trolley; Model 143640 Capacity 4,400lbs Purpose: Designed to move and position heavy loads along an I-beam track. Construction: Constructed from quality metal with precision for navigating I-beam tracks effortlessly.	
6329	Pittsburgh long ram; This lot contains (2) Pittsburgh 3-Ton long rams. Both are flat bottom jacks. (1) has a plate welded on it for bigger lifting surface area.	
6330	TOYO-INTL 5-Ton Hydraulic Toe Jack, AND (2) Craftsman 6-ton hydraulic bottle jacks, ANDEagle G-60 3-Ton hydraulic toe jack ; TOYO-INTL Toe Jack: Model: MHC-5RS Top Capacity: 5 Ton Jaw Capacity: 2.5 Ton Craftsman 6-ton hydraulic bottle jacks: Capacity: 6 tons Min Height: 8-1/2" (216 mm) Max Height: 16-1/6" (413 mm) Features: Extension screw, wide base for stability Eagle G-60 3-Ton hydraulic toe jack: Capacity: 3 tons Feature: Equipped with a safety valve to prevent overload. Design: Features two lifting points (the toe and the head) for versatility. Use: Suitable for lifting heavy machinery and industrial equipment.	
6331	(2) Craftsman 2.25 Ton manual jack stands; 2.25 Ton It features a ductile iron rack that automatically locks into position when raised. The unique structural leg design combines integral bracing and welded corner support for greater stability.	
6332	TIRE SOCKS; Non-marking tire covers used to protect finished flooring from scuff marks caused by industrial equipment tires.	
6333	Fall protection (ppe); This lot has a variety of fall protection, including; Anchorage connector straps, beamers and shock absorbing lanyards.	
6334	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Contents Not Included); Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx72”Wx77.5”H	
6335	Global Industrial Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents); Heavy-duty Global Industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx60”Wx77.5”H	

6336	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx48”Wx77.5”H	
6337	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx48”Wx77.5”H	
6338	Lot of Assorted Formation/ Cell Assembly Cutting/ Trimming Dies; To Include: Assorted Sizes	
6339	(2) Pelican 1550 Hard Cases ; Interior Dimensions: 18.63" L x 14.18" W x 7.72" D Exterior Dimensions: 20.66" L x 17.20" W x 8.40" D Lid/Base Depth: 1.75" / 5.87" Weight (with foam): 11.90 lbs Weight (without foam): 10.58 lbs Buoyancy: 69.89 lbs	
6340	(3) Pelican 1550 Hard Cases ; Interior Dimensions: 18.63" L x 14.18" W x 7.72" D Exterior Dimensions: 20.66" L x 17.20" W x 8.40" D Lid/Base Depth: 1.75" / 5.87" Weight (with foam): 11.90 lbs Weight (without foam): 10.58 lbs Buoyancy: 69.89 lbs	
6341	Durham MFG Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Durham MFG industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx48.25”Wx78.25”H	
6342	Strong Hold Heavy-Duty Industrial Storage Cabinet – Double Door (Without Contents; Heavy-duty Strong Hold industrial steel storage cabinet with double locking doors and reinforced construction, designed for secure storage in manufacturing, maintenance, or facility environments. Cabinet features a full-height interior with adjustable shelving rails and a robust welded steel body. Offered without contents—only the cabinet itself is included. Ideal for tools, instrumentation, parts, or general industrial storage applications. APPROX Measurements: 24”Dx48”Wx78”H	
6343	Vacutec WV608 Leak Detection System ; The Vacutec WV608 is a low-pressure diagnostic smoke machine used for quickly and accurately finding leaks in various vehicle systems, including EVAP, induction, and exhaust systems. This system come with a battery and a plastic rolling craftsman tool box.	
6344	SKF induction heater; The SKF TIH 030M is a compact, portable induction heater designed for the hot mounting of bearings and other metal workpieces up to 40 kg (88 lb). It is known for its high heating capacity relative to its size and ease of use. *cart is not included *	
6345	Bessey tools induction bearing heater; The Bessey Model SC is an induction bearing heater used for safely and efficiently heating bearings, gears, sprockets, and couplings for proper installation. This model is designed for smaller to medium-sized workpieces. *cart is not included *	
6346	Miscellaneous electrical supplies; This lot contains miscellaneous electrical supplies such as tie mounts, panel washers, plastic outlet covers, small motor bearings and metal outlet boxes. This lot also includes (2) metal shelves seen pictured.	
6347	Miscellaneous industrial parts; This lot contains miscellaneous parts such as concrete anchors, motor bearings, susol motor contactors, limit switch’s, control relays, steam bucket traps, plc with cards. This lot also includes (2) metal shelves pictured.	
6348	Mitsubishi Graphic Operation Terminal ; Model#: GT1695M-XTBD SN#: 79124216RB20024-C Power Supply: Max 60W	
6349	Mitsubishi Graphic Operation Terminal ; Model#: GT1695M-XTBD SN#: 79124227RB10056-C Power Supply: Max 60W	
6350	Mitsubishi Graphic Operation Terminal ; Model#: GT1695M-XTBD SN#: D80011216XK00001-B Power Supply: Max 60W	
6351	Miscellaneous industrial supplies ; This lot contains an assortment of industrial supplies such as pipe hangers, smoke detectors, gas shut off valves, EMT fittings and small motor bearings.	
6352	Miscellaneous electrical supplies ; This lot contains miscellaneous electrical supplies such as EMT fittings in many sizes, circuit breakers, contactors, overloads, selector switches and one hole straps. This lot also includes (2) Metal shelving units. (Pictured)	
6353	Miscellaneous industrial supplies ; This lot contains miscellaneous industrial supplies such as unistrut nuts, zip screws, machine screws, metal electrical boxes, hose clamps, motor bearings, o-rings and flange gaskets. This lot also includes (2) metal shelving units. (Pictured)	
6354	Miscellaneous industrial supplies ; This lot contains miscellaneous industrial supplies such as floor anchors, bolts, washers, steam bucket traps, wall anchors and wire nuts. This lot also includes (2) metal shelving units. (Pictured)	
6355	ULINE Storage Cabinet with contents; Height 72” (6ft) Width 36” (3ft) Depth 18” Misc. supplies Thermostatic Mixing Valves Adhesive tape Molykote Vacuum Grease Sealant Silicone Gaskets Cord Concealers RIDGID Power Spin Drain Cleaner PLT LED Lights Caution Tape etc.	
6356	Electrical fuse assortment ; This lot contains a variety of fuses in many sizes and other electrical components. *The metal cabinet is not included in this lot*	
6357	Bin storage cabinet ; This bin storage cabinet has plenty of hanging space for your bins. The cabinet measures 3’ wide x 78” tall x 33” deep. *Cabinet only, no bins or parts are included*	

6358	Mobile Industrial Workbench with Drawer Storage, Hardware & Organized Parts Assortment (Soldering iron/accessories and vice not included); Industrial mobile workbench setup consisting of a heavy-duty steel workbench with integrated drawer cabinet, rear safety panels, adjustable leveling feet with casters, and a large assortment of organized hardware and components stored in drawers, small-parts organizers, and compartment cases; contents include mixed fasteners, connectors, small mechanical and electrical hardware, bulk packaged components, spools of consumables, cable ties, and assorted shop supplies as shown, with multiple labeled and unlabeled storage bins and cases beneath and within the bench; soldering tool, soldering-related equipment, and bench-mounted vise are not included in this lot, while all other visible drawers, organizers, contents, and the workbench itself are included exactly as shown; quantities, sizes, and specifications vary across the assortment.	
6359	Weller WE1010 power unit, digital soldering station, AND assortment of Splices, AND (2) Microscopes, AND Ready-made Concrete patch, AND electrical components, etc.; Model WE1010 (Specifically WE1010NA for North America) Power Supply 120 V~, 60 Hz Power Consumption 85 W (unit), 70 W (soldering iron) Temperature Range 200°F – 850°F (100°C – 450°C) Display Digital LCD screen Safety Features ESD safe, heat-resistant silicone cable, reinforced safety rest DAP Concrete patch Small part storage bins	
6360	Bench vise; This is a bench mount vise, 5". Locking nuts for needed positioning. *Work bench and other tools pictured are not included*	
6361	Hand Truck of Electrical Wire Spools; Black Main "hot" or live wire carrying power from the source. Red Secondary "hot" wire, often used in 240-volt systems, switch legs, or for interconnecting smoke detectors. Blue & Yellow "Hot" wires, often found in electrical conduit for three- or four-way switches or ceiling fans. White Neutral wire, which carries current back to the electrical panel. Green or Bare Copper Grounding wire, providing a safe path for electricity in the event of a fault.	
6362	Steel Rack of Electrical Wiring Spools; Black Main "hot" or live wire carrying power from the source. Red Secondary "hot" wire, often used in 240-volt systems, switch legs, or for interconnecting smoke detectors. Blue & Yellow "Hot" wires, often found in electrical conduit for three- or four-way switches or ceiling fans. White Neutral wire, which carries current back to the electrical panel. Green or Bare Copper Grounding wire, providing a safe path for electricity in the event of a fault.	
6363	Cart of Electrical Wire spools, & electrical wiring components, & (2) RIDGID BC-210 bench chain vises, & (2) Greenlee 1810 Little Kicker Offset Benders for 1/2" EMT conduit; RIDGID BC-210 bench chain vise: It features a rugged cast-iron base for durability. The crank handle is securely anchored to the base. It is designed to be mounted to a workbench or other stable horizontal surface. It often includes a built-in pipe rest and bender feature. Greenlee 1810 Little Kicker Offset Bender for 1/2" EMT conduit: Bends offsets in one simple operation. Creates consistent, identical offsets every time. Designed to match the knockout in a box. Maximum offset capacity of 0.56 inches (9/16") Black Main "hot" or live wire carrying power from the source. Red Secondary "hot" wire, often used in 240-volt systems, switch legs, or for interconnecting smoke detectors. Blue & Yellow "Hot" wires, often found in electrical conduit for three- or four-way switches or ceiling fans. White Neutral wire, which carries current back to the electrical panel. Green or Bare Copper Grounding wire, providing a safe path for electricity in the event of a fault.	
6364	Steel Rack of Electrical Wiring Spools; Black Main "hot" or live wire carrying power from the source. Red Secondary "hot" wire, often used in 240-volt systems, switch legs, or for interconnecting smoke detectors. Blue & Yellow "Hot" wires, often found in electrical conduit for three- or four-way switches or ceiling fans. White Neutral wire, which carries current back to the electrical panel. Green or Bare Copper Grounding wire, providing a safe path for electricity in the event of a fault.	
6365	Square D 30 Amp General Duty Fusible Safety Switch, AND Square D general-purpose transformer (Cat. No. 7S1F). ; Square D 30 Amp General Duty Fusible Safety Switch: Amperage/Voltage: 30A, 240 Vac. Poles: 2-pole. Enclosure: NEMA 1 galvanized steel, designed for indoor use. Application: Suitable for residential and commercial uses such as lighting, air conditioning, and appliances. Safety Features: Visible blades, quick-make/quick-break operating mechanism, and multiple padlock provisions when in the 'Off' position. Square D general-purpose transformer (Cat. No. 7S1F): Power Rating: 7.5 kVA Phase: 1 Frequency: 60 Hz Enclosure Type: Rainproof, Type 3R	
6366	Miscellaneous industrial supplies ; This lot contains miscellaneous industrial supplies such as black pipe fittings (1/2"-1"). Some S.S fittings, small springs and bolts. Metal rack is included. (Pictured)	
6367	Miscellaneous hardware; This lot contains miscellaneous hardware such as nuts, bolts, washers, lock washers and screws. There are a variety of sizes, please see pictures. This lot also includes metal rack. (Pictured)	
6368	Industrial Pneumatic Tubing & Push-to-Connect Fittings Assortment on Mobile Cart; Large mixed industrial lot consisting of assorted pneumatic air tubing and push-to-connect style pneumatic fittings organized on a rolling parts cart, including multiple coils of flexible tubing in various colors and diameters along with bulk bins of straight, elbow, tee, reducer, and threaded pneumatic fittings in plastic and metal constructions; tubing appears to include common polyurethane and flexible air-line types, while fittings include panel-mount, bulkhead, male-threaded, and quick-connect styles typical of automated manufacturing, assembly, robotics, packaging, and industrial air systems; lot is sold as a single mixed assortment exactly as shown, with quantities, sizes, and specifications varying throughout the cart.	
6369	Lot of Assorted Mechanical Hardware ; To Include: Rollers, Washers, Screws, Brackets, Nuts, Bolts, Etc.	
6370	Lot of Assorted Hosing/Tubing ; To Include: Assorted Sizes	
6371	heavy-duty safety disconnect switch; 30A 600VAC switch, typically a heavy-duty safety disconnect switch, is used in commercial and industrial applications to manually de-energize equipment for safety and maintenance.	
6372	Enerpac P-142; The Enerpac P-142 is a two-speed, lightweight hydraulic hand pump designed for powering single-acting hydraulic cylinders and tools in various industrial applications up to 10,000 psi. This pump is Not in working order.	
6373	Enerpac P-142; The Enerpac P-142 is a two-speed, lightweight hydraulic hand pump designed for powering single-acting hydraulic cylinders and tools in various industrial applications up to 10,000 psi.	

6374	BANNER SC22-3; This lot contains (3) Banner Engineering SC22-3 is a configurable safety controller designed to replace multiple traditional safety modules in industrial applications. It can integrate various safety devices, such as light screens, E-stops, and interlocking switches, and is certified for high safety integrity levels.	
6375	SUSOL circuit breaker ; The LS Electric Susol TS250HU is a 3-pole molded case circuit breaker (MCCB) with a 250 ampere frame size, designed for protecting low-voltage electrical systems from overloads and short circuits.	
6376	FLOMEC flow meter ; The FLOMEC G2S05N09GMA is a 1/2-inch stainless steel industrial-grade turbine flow meter with a local digital display, designed for accurate measurement of various chemicals, fuels, and water in a range of industrial applications.	
6377	METASYS controller; The Johnson Controls Metasys CVM03050 is a variable air volume (VAV) box controller used in commercial HVAC systems. It is designed for energy-efficient control of VAV terminal units and can operate as a standalone controller or be integrated into a larger Metasys network.	
6378	Servo motors; This lot contains (4) servo motors. (1) is a Mitsubishi HG-KR43, It is designed for applications requiring precise and fast movement, such as in robotics and CNC machines. (1) oriental motor 5IK90GU-SWM, is a 90-watt (1/8 HP) three-phase AC induction motor that includes a built-in electromagnetic brake and a pinion shaft. (2) Mitsubishi HF-KP73, designed for applications that require precise and rapid motion control, such as in robotics and assembly automation.	
6379	SICK S30B Safety Laser Scanner – Class 1 Industrial Machine Safety Sensor; Industrial SICK S30B-2011DA safety laser scanner, Class 1 laser product, housed in a yellow safety-rated enclosure with black optical window and attached cabling as shown; nameplate indicates 24 V DC operation, IP65 enclosure rating, and functional safety certifications including IEC 61496-3 Type 3, SIL 2, and Category 3 / PL d per EN 13849-1; manufacture date listed as February 2011 with serial and identification numbers visible; unit is sold exactly as pictured, including attached cables and connectors.	
6380	Rosemount Explosion-Proof Level Transmitter with Flanged Probe Assembly; Industrial level measurement transmitter identified by cast housing markings as Rosemount, featuring an explosion-proof blue aluminum enclosure with threaded conduit entry and a stainless steel flanged probe assembly; unit includes a machined stainless mounting flange and tapered metal probe element as shown, with manufacturer data plate indicating explosion-proof construction, hazardous-area ratings, and single-seal design per visible labeling; exact model number, measurement technology, range, and electrical configuration are limited to what is readable on the nameplate only; sold exactly as pictured, with no additional cabling, mounting hardware beyond the attached flange, or documentation included	
6381	Dräger PIR 7000 Fixed Gas Detector / Transmitter – Methane (LEL); Fixed industrial gas detection transmitter identified by the manufacturer label as a Dräger PIR 7000, configured for methane detection, featuring a flanged mounting base and integrated sensor housing with status indicators labeled FAULT and POWER; visible data plate indicates methane gas category with LEL setting of 5.0 %v/v, full scale 100% LEL, calibration gas methane at 50% LEL, and software version 3.0.0; secondary nameplate shows ATEX and IECEx markings with explosion-proof classifications, IP65 enclosure rating, and temperature range markings as shown; unit is sold exactly as pictured, with no additional cabling, controllers, accessories, or documentation included.	
6382	Jordan Valve Pneumatic Control Valve Assembly with Diaphragm Actuator – Model 70T-18; Industrial pneumatic control valve assembly consisting of a flanged stainless steel valve body paired with a diaphragm-style pneumatic actuator, external tubing, and mounted pressure gauge, as shown; actuator nameplate indicates Jordan Valve Model 70T-18 with Cv 15 and maximum differential pressure rating of 127 PSI, featuring stainless steel body and trim (316 / 316SS) and labeled for 4–20 mA control range per the actuator plate; assembly includes all visible mechanical linkages, tubing, fittings, and mounting hardware exactly as pictured, with specifications, configuration, and certifications limited to what is readable on the manufacturer label; sold as a single assembled unit, with no additional accessories, controls, or documentation included.	
6383	Endress+Hauser Liquiphant M Vibrating Fork Level Switches – Multi-Unit Lot; Industrial lot of Endress+Hauser Liquiphant M vibrating fork level switches consisting of multiple flange-mounted stainless steel probe assemblies with integral blue instrument housings, as shown; units feature long rigid probe extensions with circular mounting flanges and electrical connection housings labeled Liquiphant M, with visible manufacturer data plates indicating Endress+Hauser branding and factory order codes; exact models, probe lengths, electrical configurations, and certifications vary by unit and are identified only where readable on the nameplates; lot is sold as a mixed multi-unit assortment exactly as shown, with no additional accessories, cabling, or documentation included.	
6384	Bessey K Body REVO parallel clamp; Model KRE3.550 It provides powerful 90° no-slip clamping force, with a nominal 1700 lbs of force. The jaws remain parallel to each other when pressure is applied, which is crucial for square glue-ups in woodworking. The upper and lower sections are made of reinforced PA6 plastic with integrated metal inserts for added strength.	
6385	Yokogawa DPharp EJA105 Differential Pressure Transmitter; Model: EJA105, Style S2, Suffix JAS7N Supply: 10.5-49 VDC Output: 4-20 mA DC Technology: Uses a DPharp digital sensor which measures differential pressure, static pressure, and sensor temperature from a single sensor for real-time compensation. Origin: Made in Japan by Yokogawa Electric Corporation.	
6386	(3) Boxes of 4 D/A Manufacturing Inc. Manifold Valves (Appears unused); The seals are made of Teflon. It has a maximum pressure rating of 1500 Psi at 125°F and 125 Psi at 375°F. The item is made in the U.S.A.	
6387	(3) Boxes of 4 D/A Manufacturing Inc. Manifold Valves (Appears unused); The seals are made of Teflon. It has a maximum pressure rating of 1500 Psi at 125°F and 125 Psi at 375°F. The item is made in the U.S.A.	
6388	Vanaire flowtek valves; This lot contains (2) 1", (1) 2", (2) 4" and (1) 6" valve. These are valves only, actuators are not included. These are a pneumatic, rack and pinion actuator designed to automate quarter-turn valves (like ball valves) in industrial applications.	

6389	Mixed Lot of Industrial Instrumentation – Rosemount Transmitters, Pressure Gauge & Explosion-Proof Housing; Mixed industrial instrumentation lot including multiple Rosemount smart transmitters and related components, featuring blue aluminum transmitter housings with threaded process connections, a stainless steel analog pressure gauge marked in psi and kPa with glycerin-filled construction, and an explosion-proof green instrument housing with conduit entry and certification markings visible on the nameplate. Units appear to include electronic transmitter modules, display heads, and field-mount process interfaces commonly used in industrial process control and measurement environments.	
6390	(4) Industrial Grade Wheels ; New in bags APPROX 8" diameter	
6391	Valve control systems; This lot contains (4) electro pneumatic positioners (valve control systems) These devices are widely used in industrial process control to accurately position pneumatic valve actuators. It receives a standard 4-20 mA input signal from a control system and translates this into a precise pneumatic output pressure to move a valve actuator to the desired position.	
6392	ABB sense 7; The ABB Sense 7 is a coded magnetic non-contact safety switch used for monitoring the position of movable guards, gates, and hatches on machinery in industrial environments. It is a two-part system consisting of a sensor and an actuator, offering a non-mechanical alternative to traditional safety switches. There are (24) of these safety switches in this lot.	
6393	Greenlee crimping tool; The Greenlee K09-2GL is a manual, long-handle crimping tool designed for crimping small to mid-range copper connectors and wire sizes from 8 AWG to 4/0 AWG. This tool features integrated color-coded, hexagonal rotating dies and a full-cycle mechanism to ensure proper crimps.	
6394	HILTI adhesive dispenser; This hilti dispenser is designed to accommodate certain 500 ml (16.9 fl. oz) foil packs of injectable adhesive mortar. Also included in this lot are (3) standard caulk guns.	
6395	FLUKE clamp meter AND ZIRCON stud finder; The Fluke 325 is a True RMS AC/DC clamp meter designed as a general troubleshooting tool for commercial and residential electricians. The zircon studfinder is a popular and cost-effective stud finder for general household use.	
6396	Battery load tester ; This OTC is a battery load tester is a device used to assess the health and capacity of a battery by applying an electrical load that simulates real-world demands.	
6397	Steel jib crane structure ; This steel jib crane structure is not whole, it has (2) of (3) pieces. One upright and the cross member. The JLB FM6 is a heavy-duty steerable transport trolley manufactured by JUNG Hebe- und Transporttechnik. It is designed for moving massive industrial loads across floors.	
6398	Demag DC-PRO electric chain hoist; Model DC-PRO 5-250 1/1 HS V19.2/4.0 Serial number 94310214 Type DC-PRO 5-250 1/1 HS V19.2/4.0 Year of Manufacture 04/2012 Safe Working Load (SWL) 550 lbs (250 kg) Hook Path 16.4 ft (5 m) Voltage 440-480 V at 60 Hz Enclosure/Insulation IP-55 Enclosure, Insulation Class F Duty Rating FEM/ISO: 4m/M7 Speeds Two lifting speeds are standard Motor Type ZNK 80 B 8/2 Ambient Temp Range -4 °F to +113 °F (-20 °C to +45 °C)	
6399	Heavy-duty Crane Buffer; Function: Absorbs impact energy to prevent damage to cranes or end stops. Application: Used in industrial settings for overhead cranes and similar heavy machinery. Design: Built for heavy-duty use in demanding environments. Mechanism: Converts kinetic energy from impact into thermal energy.	
6400	THK Electric Actuator; Manufacturer: THK Corporation, a leader in linear motion systems. Model Number: USW12T-20-1000A-0B-6-SR-T-A. Type: Electric Actuator (part of the Universal Series US). Features: This series uses Caged Ball LM Guide model SHS for maintenance-free operation and is designed for high speed and long service life.	
6401	Baldor-Reliance Super-E Motor, model number EM3218T-G. ; Horsepower: 5 HP Voltage: 208-230/460 V, 3 Phase (PH 3) RPM: 1750 Features: Class H insulation and an internal AEGIS shaft grounding ring to protect against bearing current issues. Applications: Commonly used in HVAC blower and fan systems, pumps, and other general-purpose industrial applications.	
6402	SM Electric three-phase induction motor; Model: TEI90LF015 Power: 2 KW Voltage: 220/380 Volts at 60 Hz Amperage: 6.5/3.7 Amps Insulation Class: B	
6403	SM three-phase induction motor ; Type 3 Phase Induction Motor Model Number 874002 Output 1.0 kW / 1.4 HP Poles 2 Volts 220 V Hz (Frequency) 60 Hz Amps 4.7 A R.P.M. (Speed) 3450 Rating Cont. (Continuous duty) S.F. (Service Factor) 1.0 Ins. (Insulation Class) AVB (likely A, V, B classes combined) Amb. (Ambient Temp) 72°C (appears to be 40°C in similar models) Eff. (Efficiency) 67% / 70% Serial No. 0031285 Manufacturing Date 2011 Origin Made In Korea	
6404	(2) 1 Ton Push Trolleys, AND Crosby L-3322B alloy ball bearing swivel hook with a latch, AND Crosby Bullard Golden Gate Hook; Crosby L-3322B alloy ball bearing swivel hook with a latch: Capacities range from 2 through 15 metric tons. It is forged, quenched, and tempered for maximum strength. The anti-friction bearing design allows the hook to rotate freely under load. The hook features Crosby's QUIC-CHECK® indicators for safer inspections and proper angle indication Crosby Bullard Golden Gate Hook: It features a heavy-duty, corrosion-resistant locking mechanism to keep it securely closed. The hook utilizes a "Pin-Lok" gate mechanism, common for its size. It is designed for various lifting applications, including use with hoists and load blocks. Various information, including the manufacturer's name ("Crosby Bullard") and a size or stock number ("6" and "60291"), is visible on the hook body.	
6405	Assorted Plastic Modular Conveyor Chain Sections in Metal Storage Rack; Lot consists of stacked plastic modular conveyor chain sections arranged in a welded metal storage rack. The chains feature interlinked plastic segments with integrated rollers or bearing-style inserts, suitable for modular conveyor systems and material-handling lines. Assortment includes multiple continuous loop sections stacked vertically; exact quantities, pitch, dimensions, manufacturer, and material composition are not specified. Metal rack is included as shown.	
6406	Honeywell Genesis Series 45061104 18 AWG Plenum-Rated Fire Alarm Cable, AND SIMPLE UTP Cable; Honeywell Genesis Series 45061104 18 AWG Plenum-Rated Fire Alarm Cable: Conductors: 2 solid copper conductors Rating: Plenum (FPLP /CL3P) Length: 1000 ft (304.8 m) pull box Jacket Color: Red Voltage/Temperature: Rated for 300 Volts and -20 °C to 75 °C Honeywell Genesis Series 45061104 18 AWG Plenum-Rated Fire Alarm Cable: Category 5E, AND GENSPEED 6 CAT 6 Riser Cable	

6407	Condor Industrial Absorbent Socks / Spill Control Absorbents – Boxed Lot; Boxed lot of Condor-branded industrial absorbent socks used for spill containment and fluid control. Contents include multiple white absorbent socks designed to be laid around equipment, along floor edges, or encircling leaks to help contain liquids. Items appear unused and packaged in the original Condor box.	
6408	Wrapped White Industrial Plastic Block / Machined Polymer Stock; Single white industrial plastic block supplied as a solid rectangular piece, packaged and wrapped as shown. Appears to be machined polymer or engineering plastic stock intended for industrial, manufacturing, or fabrication use, with smooth flat faces and squared edges. No branding or material type is stated on the visible packaging. Sold as one individual block only, exactly as photographed, with no additional contents included.	
6409	Rosemount Industrial Pressure Transmitter with Flanged Process Connection; Industrial pressure transmitter featuring a Rosemount-branded blue explosion-proof style electronics housing, stainless steel body, and flanged process connection. Unit includes angled conduit entry, engraved stainless identification band, and heavy-duty mounting flange with protective cover on the process end. Housing markings indicate hazardous-location rated construction and field wiring terminals; exact model number, pressure range, output type, and calibration status are not specified. Sold as a single standalone transmitter assembly as shown, with no additional accessories, documentation, or testing performed.	
6410	Industrial Instrumentation & Controls Parts Lot – Gauges, Hoses, Fittings, Manuals, Mixed Brands; Mixed lot of industrial instrumentation and control components consisting of assorted pressure gauges, flow or level indicators, pneumatic hoses, threaded fittings, electrical and control accessories, and related documentation and manuals, including items branded Emerson, Amprobe, Dwyer, Pepperl+Fuchs, and other manufacturers. Contents appear to include spare parts, unused accessories, measurement devices, and supporting components housed together as a single lot. Exact quantities, specifications, and compatibility are not verified; items are sold as pictured only. Suitable for surplus inventory, maintenance spares, industrial resale, or parts recovery.	
6411	Drylok Industrial Valve Assembly with Lever Handle and Threaded Ports; Industrial valve assembly featuring a Drylok-branded cast metal body with lever-operated mechanism, threaded inlet/outlet ports, and stainless shaft hardware. Unit includes cam-style locking features, chain-retained cap, and integrated control stem, consistent with heavy-duty fluid handling or process control applications. Markings indicate Drylok manufacture and stainless steel components.	
6412	OPW Drylok 3" Stainless Steel Camlock Valve / Coupler – 300 PSI Rated; Industrial stainless steel OPW Drylok cam-and-groove style valve/coupler assembly featuring a lever-operated mechanism, safety chain, and threaded inlet, marked "DRYLOK," "3," and "300 PSI." Heavy-duty cast construction with internal shutoff component visible through the bore, designed for secure fluid transfer and containment in industrial applications. Includes cam arms, locking hardware, and dust cap assembly as shown. Sold exactly as pictured, single unit, standalone lot.	
6413	Assorted Industrial Electronics & Hardware Components Lot – Boards, Relays, Springs, Wiring; Mixed lot of assorted industrial electronics and hardware components including multiple circuit/control boards, electronic modules, relays, panel-mount switches, metal coil springs, spooled wire and braided cabling, and related small electrical and mechanical parts, all grouped together as shown. Components appear to be industrial-grade items typically used in control systems, instrumentation, automation, or equipment assemblies.	
6414	(2) Feit Electric 32 W T8 48 in. L fluorescent bulb 10-pack, AND (2) Maintenance struts, AEROCEL Thermal Insulation, AND Satco S8690 LED T5 Tube Lights, AND assortment of Industrial Aluminum Extrusion Profiles; Type: 4 ft. T8 linear fluorescent tube light bulb. Color: Cool White at 4100K. Wattage: 32 Watts. Base: Medium Bi-Pin (G13). Features: Contains mercury and is non-dimmable. Aerocel AC Elastomeric Sheet Insulation: Material: Closed cell elastomeric thermal insulation. Dimensions: Insulation Thickness 3/4" Width 36" Length 48" R-Value 3.1 Compliance: Complies with ASTM C534 & C1534 standards. Satco S8690 LED T5 Tube: Watts: 13W Volts: 120V-277V Lumens: 1600L Technology: LED, Type B (Ballast Bypass) Rated Hours: 50,000	
6415	Industrial Aluminum Extrusion Profiles – Large Assorted Lot (Bulk Quantity); Large bulk lot of industrial aluminum extrusion profiles featuring assorted cross-section geometries, including multi-channel and structural profile designs commonly used in modular framing, machine builds, guarding systems, automation structures, and industrial fabrication. Profiles appear uniform in finish and stored as bundled lengths, with multiple identical pieces per profile type. Exact dimensions, alloy, temper, and manufacturer are not specified. Lot is offered as a single mixed assortment exactly as shown, including all visible extrusions and packaged material. APPROX Measurements: 20' Long x 4" Tall x 1 3/4" Wide 17'9" Long x 4" Tall x 1 3/4" Wide	
6416	Heavy-Duty Industrial Pallet Racking Section with Wire Decking – Approx. 3000 lb Capacity (Contents Not Included); Heavy-duty industrial pallet racking section constructed with steel uprights and orange horizontal load beams, equipped with multiple levels of galvanized wire decking. Rack appears to be a multi-tier configuration suitable for warehouse or industrial storage applications. A visible load marking indicates an approximate 3000 lb capacity per level (capacity based on posted signage; buyer to verify for intended use). Includes uprights, beams, and wire decking only. All items shown on the rack are not included in this lot. Rack is sold as a single assembled section as pictured, disassembled for removal unless otherwise arranged. Ideal for buyers seeking industrial warehouse shelving, pallet racking, or heavy-duty storage infrastructure. APPROX Measurements: (4)Beams 8'Hx3.5'W (8)Cross Beams 8'W	
6417	Proto Industrial mobile tool storage cabinet WITH Contents; 26 drawers Height 62" Width 54-1/2" Depth 17-5/8" Construction: The cabinet body is made from 14-gauge steel and the drawers from 18-gauge steel, offering robust support. Drawers: It features full-extension drawers with ball-bearing slides, each with a load capacity of up to 125 lbs. Mobility: The unit has heavy-duty casters rated for 700-900 lbs each, making it easy to move around the workspace. Security: The cabinet includes a heavy-duty tubular lock system to keep contents secure. Accessories: It comes with a vinyl top mat and drawer liners. Capacity: The total storage capacity is approximately 15,390 cubic inches.	
6418	Proto Industrial tool box WITH Contents; 12 Drawers Height 22" Width 54-1/2" Depth 17-1/2" Construction: These systems are built from heavy-gauge steel, typically 14, 16, and 18 gauge, for industrial strength and durability. Drawers: They feature 100% full-extension drawers with ball-bearing slides, offering capacities up to 125-200 lbs per drawer for complete access to tools. Finish: The powder-coated finish resists scratches and damage from common industrial chemicals like hydraulic fluids, oils, and greases. Security: Heavy-duty locks with tubular keys help keep valuable tools secure. Modularity: Proto storage systems are designed to be modular, allowing top chests and side cabinets to be mixed and matched with roller cabinets to expand storage space as needed.	

6419	Pressure gauges ; This lot contains (9) 4" 60 psi gauges. Part# 20TV48	
6420	FUJI inverter; These Fuji Electric FRN0004C2S-2U variable frequency drive (VFD) are a compact inverter from the FRENIC-Mini C2 series, designed for basic motor control applications. There are (2) in this lot.	
6421	Graymills ultrasonic ; The Graymills BT60-SE is a specific model of an industrial immersion-style centrifugal pump and tank system used for supplying coolant to machinery.	
6422	Pipe rack AND miscellaneous pip and material ; This lot contains miscellaneous material including galvanized pipe, unistrut, threaded rod, aluminum sheet metal and round poly stock. * The Pipe rack is included in the lot*	
6423	Spare parts from pallet wrapper; These spare parts from a pallet wrapper are from a Smart Mechtronics SAD-16. Made of Aluminum with internal bussing.	
6424	DeWALT wet/dry vacuum ; This is a DeWALT 1/2 gallon wet/dry vacuum. Part# DCV517. Battery operated with a 20vmax. (1) battery included)	
6425	Bumper guards; These guards are designed to absorb impacts and prevent damage to equipment, walls, and people in high-traffic environments such as warehouses and factories. (4) rolls approximately 15' long.	
6426	Radians 12-gallon portable emergency eyewash station.; It is a gravity-fed unit designed to provide immediate, hands-free eye flushing. It activates in one second with a single pull action. The station delivers a continuous flow of water for a full 15 minutes, meeting ANSI Z358.1 standards. It is designed for wall mounting or use with a stand in areas where a continuous water supply is unavailable. The unit features an integrated drainage system to manage wastewater.	
6427	U.S. GENERAL 5-Drawer Mechanics Cart; Dimensions Height 41-3/4" Width 33-1/2" Depth 22-3/4" Weight Capacity 700 lb. total capacity Drawer Slide Capacity 75 lb. per pair (full-extension ball bearing) Material All-steel construction with a tough powder-coated finish Casters 5 in. (2 fixed, 2 locking swivel) Weight Approx. 144 lb. Lid Features Easy-opening with dual gas struts; automatically locks drawers when closed	
6428	Craftsman Stainless Steel Tool box; Height 41-1/4" Width 40-1/2" Depth 18-1/4" 11 drawers	
6429	(2) Kito electric hoist pendant control station, AND Conductix 80 Series push-button pendant control station; Kito electric hoist pendant control station: It is a rainproof push-button switch used for controlling hoists or cranes. The yellow shell is made of durable ABS plastic. It features two buttons for "up" and "down" operation. The device is suitable for remote control in outdoor, snowy, or dusty environments. Conductix 80 Series push-button pendant control station: Brand/Series: Conductix 80 Series Electrical Rating: 240V, 5A Enclosure: High-impact yellow ABS plastic, rated NEMA 4X (IP65) for indoor /outdoor use Certifications: cULus Listed, E193531 Design: Two-piece design for simplified field wiring	
6430	Super air knife; The EXAIR Super Air Knife is an efficient, engineered compressed air device that produces a uniform, high-impact laminar sheet of air to clean, dry, or cool surfaces. It significantly reduces compressed air usage and noise levels compared to traditional blowoffs like drilled pipes or open tubes.	
6431	Mitsubishi Electric FR-E720-050SC-NA E700 series compact inverter drive; It is designed for 3-phase, 200-240VAC input systems. It functions as a variable frequency drive (VFD) to control motor speed efficiently. It is suitable for a variety of industrial applications, including fans, pumps, and conveyors. Key features include a safety stop function and built-in Modbus RTU communication capabilities.	
6432	SMC ITV2050-313N electro-pneumatic regulator; Type Electro-pneumatic proportional valve/regulator Input Signal Voltage type: 0-10 VDC Power Voltage 24 VDC Pressure Range 0.005 to 0.9 MPa Max. Flow Rate 1500 L/min (ANR) Monitor Output Analog output (1-5 VDC)	
6433	Keyence counter ; The Keyence RC-19 is an electronic preset counter and timer module used in industrial automation for precise counting and control applications. It features a 4-digit 7-segment LED display and operates on a 12 to 24 VDC power supply.	
6434	Keyence laser sensor ; CMOS laser sensors, utilizing Complementary Metal-Oxide Semiconductor technology for stable, high-speed, and high-accuracy detection and measurement, regardless of a target's color, surface, or angle.	
6435	CRST 50ft Retractable Extension Cord Reel; features a heavy-duty 14AWG cord. It has a lighted triple-tap outlet. It includes a built-in 13A circuit breaker with a reset button for safety. The system includes an adjustable stopper and can be wall or ceiling mounted.	
6436	CRST 50ft Retractable Extension Cord Reel; features a heavy-duty 14AWG cord. It has a lighted triple-tap outlet. It includes a built-in 13A circuit breaker with a reset button for safety. The system includes an adjustable stopper and can be wall or ceiling mounted.	
6437	RocketSocket LTS-XP013 Cord Reel; 125VAC Max, 13A	
6438	CRST 50ft Retractable Extension Cord Reel; features a heavy-duty 14AWG cord. It has a lighted triple-tap outlet. It includes a built-in 13A circuit breaker with a reset button for safety. The system includes an adjustable stopper and can be wall or ceiling mounted.	
6439	ReelCraft 7650 OLP Hose Reel; S/N 240805-004D	

6440	Kobalt Wall-Mounted Hose Reel with Enclosed Drum, Blue Steel Assembly; This lot consists of a wall-mounted Kobalt enclosed hose reel featuring a blue steel drum and fixed mounting bracket. The reel is shown installed vertically and includes a coiled hose currently mounted on the drum, with hose guides and metal inlet fittings visible at the reel hub. The assembly appears to be a manual rewind style with an enclosed side-plate drum design and steel support arm. No model number, hose length, hose diameter, pressure rating, or service type are stated on the visible labels. Sale includes the hose reel and hose exactly as shown in the photos; no additional accessories or documentation are included.	
6441	Reelcraft Industrial Hose Reel – Model 7850 OLP, Red Steel Reel Assembly; This lot features a heavy-duty industrial hose reel manufactured by Reelcraft Industries, Inc., identified on the manufacturer tag as Model 7850 OLP with reel part number 240801-004N. The unit is a wall-mounted steel hose reel with an enclosed drum design and fixed mounting arm, finished in red industrial coating. Visible fittings indicate a fluid or air service configuration, though no hose specifications are stated on the label. The reel appears to be a spring-driven manual rewind style consistent with Reelcraft's 7800-series industrial reels. Sale includes the reel assembly only, exactly as shown in photos; no additional accessories, hoses, or mounting hardware beyond what is visible are included. Suitable for industrial, commercial, or facility maintenance environments where Reelcraft hose management equipment is used.	
6444	(2) Large Pipe Wrenches ; RIDGID and IRWIN	
6445	Werner ladder; Werner 2' ladder. "A" frame. 300lbs capacity.	
6446	Werner ladder; Werner 8' ladder. "A" frame. 300lbs capacity.	
6447	Werner Ladder; Werner 6' ladder. "A" frame. 300lbs capacity.	
6448	Ladder; 3' step ladder, 375lbs capacity. Type-IAA	
6449	Werner Extension Ladder; 15' Maximum Reach Highest Standing Reach 9'5" Model D6216-3 300lbs weight capacity	
6450	Werner 14 ft Fiberglass Extension Ladder, Model 7414, 300 lb Load Rating; This lot includes a Werner fiberglass extension ladder identified on the factory label as Model 7414 (Mk 12). The ladder has a 14 ft ladder size, 18 ft maximum reach, and a highest standing level of 11 ft 6 in, assuming a 5 ft 6 in user with a 12 in vertical reach. It is rated for a 300 lb load capacity per side and features non-conductive fiberglass side rails. The ladder is marked compliant with ANSI A14.5 standards and bears an OSHA manufacturer certification label.	
6451	Werner 8' Ladder; 300lbs Max Load; 12' Max Reach	
6452	Werner 4' Ladder; 300lbs Max Load; 8'5" Max Reach	
6453	Jordan Valve Mark 701/702 Series High-Flow Sliding Gate Pneumatic Control Valve Assembly w/ Regulator & Gauge (Flanged); Jordan Valve pneumatic diaphragm-actuated sliding gate control valve assembly consistent with the Mark 701 /702 Series high-flow design, built to deliver higher Cv/Kv without stepping up to a larger valve, featuring straight-through flow and ease of maintenance. The Mark 701/702 high-flow sliding gate platform is known for shorter stroke vs globe/plug-style valves (faster response), reduced turbulence/erosion/noise, and a smaller/lighter package than globe-style valves. Lot includes the flanged valve body marked Jordan Valve, diaphragm actuator, and a mounted air supply regulator with pressure gauge as shown; actuator supply tag indicates approximately 35 PSI minimum / 40 PSI maximum air requirement. Only the valve/actuator/regulator/gauge assembly is included—no additional controls, positioners, tubing, wiring, or documentation beyond what is pictured.	
6454	Jordan Valve Sliding Gate Control Valve Assembly with Honeywell Electric Actuator, Flanged Industrial Valve; Jordan Valve sliding gate control valve assembly featuring a flanged inline valve body paired with an electric actuator manufactured by Honeywell, mounted via a steel actuator bracket and linkage. Valve nameplate identifies Jordan Valve – Sliding Gate Valves, with a model marking of 701, body material listed as CS, trim listed as 316 SS, and pressure rating shown on the tag. The valve includes a Jordan Valve position indicator mounted on the stem assembly. The electric actuator is labeled Honeywell Modutrol IV Motor, with markings indicating the motor has been modified with auxiliary switch kit 220736B and interface module Q7230A1005. Assembly includes the valve body, actuator, mounting hardware, linkage, and nameplates exactly as shown. No additional controls, wiring, accessories, or documentation are included beyond what is visible in the images.	
6455	Versawipe ; The VersaWipe TX629 is a nonwoven wiper that combines the absorbency of natural cellulose fiber with the strength and cleanliness of synthetic polyester. (8) boxes of 10 bags, bags have 300 wipers.	
6456	ARO pump; This is a air powered fluid pump. Used for many types of liquids. Model- 666150-3EB-C	
6457	Graco Husky 1590 Double Diaphragm Pump; DB4311; 120 Max PSI; S/N FG25D6185	
6458	Miscellaneous air equipment ; This lot contains miscellaneous air equipment such as air regulators, air solenoids and push to connect valves. This equipment is used to precisely apply air to air powered equipment ran from a PLC.	
6459	SMC pneumatic air cylinder; Model: CS1FN250-100 Manufacturer: SMC Max. Pressure: 140 PSI (1.0 MPa) Origin: Made in USA Function: Generates linear motion using compressed air	
6460	Nidec/US Motors 7.5 HP Close-Coupled Pump Motor; Model #: FK40 Horsepower: 7.5 HP RPM: 3600 (at 60 Hz) Voltage: 208-230/460V (at 60 Hz) Enclosure: TEFC (Totally Enclosed Fan Cooled)	

6461	Goulds Model EZ3296 centrifugal process pump & Pump housing; Model: EZ3296 Size: 1x1.5-6 Material: 316SS (Stainless Steel) Capacity: 46 GPM (gallons per minute) Max RPM: 3600	
6462	WEG motor ; WEG 3-phase motor, 1.5 HP, 1760rpm. This motor can be used on many different industrial applications.	
6463	Marathon motor; This marathon 3-phase electric motor has .5 HP, 1725 rpm. Great motor for any industrial applications.	
6464	Jordan Valve Sliding Gate Control Valve Assembly with Honeywell Modutrol IV Electric Actuator, Flanged; Industrial control valve assembly consisting of a Jordan Valve sliding gate control valve with flanged inline body and an attached Honeywell Modutrol IV electric actuator, mounted via a steel bracket and mechanical linkage. The valve features a Jordan Valve stem position indicator and flanged process connections, with flow direction cast into the body. The electric actuator is identified as a Honeywell Modutrol IV motor, labeled for 24 V operation with control input markings visible on the actuator tag. Assembly includes the valve body, electric actuator, mounting plate, linkage hardware, and nameplates exactly as shown. No additional wiring, controls, accessories, or documentation are included beyond what is visible in the photos.	
6465	Baldor-Reliance Motor; The ABB EHM3313T is a Baldor-Reliance Super-E® 10 HP general purpose AC motor designed specifically for HVAC applications, featuring high efficiency and an open slotted band (OPSB) enclosure.	
6466	Baldor-Reliance Motor; The ABB EHM3313T is a Baldor-Reliance Super-E® 10 HP general purpose AC motor designed specifically for HVAC applications, featuring high efficiency and an open slotted band (OPSB) enclosure.	
6467	TIDLAND Electronic Knife Holder ; Model C1CSEKH Tidland Control Series knifeholders are designed and manufactured for cutting material webs according to the shear slitting procedure in the direction of motion of the material. Any other use is deemed as not being in accordance with the intended purpose. The manufacturer will not be liable for any damage resulting from this improper use.	
6468	Jordan Valve MK701 Control; SIEMENS PS2 Valve Positioner	
6469	Jordan Valve MK701 High Flow Sliding Gate Valve; Siemens PS2 Valve Positioner	
6470	Jordan Valve Sliding Gate Control Valve Assembly with Pneumatic Actuator, Siemens SIPART PS2 Positioner & Air Regulator, Flanged; Industrial control valve assembly consisting of a Jordan Valve sliding gate control valve with flanged inline body, paired with a pneumatic diaphragm actuator, mounted linkage hardware, and an integrated Siemens SIPART PS2 valve positioner. The positioner label identifies SIPART PS2, 2-wire, without HART, with item number 6DR5013-0FN00-0AA9. The assembly also includes an air supply regulator with pressure gauge mounted to the actuator. Valve nameplate identifies Jordan Valve sliding gate construction with documented flow and pressure ratings as shown on the tag. Assembly includes the valve body, pneumatic actuator, Siemens positioner, air regulator, gauge, mounting bracket, and linkage exactly as pictured. No additional tubing, wiring, accessories, or documentation are included beyond what is visible in the photos.	
6471	Stainless steel plates ; This lot contains (8) s.s plates. They measure 12"x12" and are 1/2" thick.	
6472	Jordan valve assembly; Jordan sliding gate valve. Model: MK701-18 The valve features a Jordan Valve stem position indicator and flanged process connections, with flow direction cast into the body.	
6473	GTR 3-phase induction motor; Power: 1.5 kW Voltage/Frequency Options: 220V 60Hz or 380V 60Hz Efficiency (NOM. EFF): 85.3% (at 220V) or 86.5% (at 380V)	
6474		
6475	Kitz ball valve with actuator; The KITZ model FA-150UTB is a 6-inch (DN150) Class 150 cast stainless steel ball valve with a pneumatic actuator, used for automated flow control in industrial applications.	
6476	Kitz ball valve with actuator; The KITZ model FA-150UTB is a 6-inch (DN150) Class 150 cast stainless steel ball valve with a pneumatic actuator, used for automated flow control in industrial applications.	
6477	BUSCH Vacuum Pump/Compressor; Pumping Speed: 35 m³/h (at 50 Hz) / 42 m³/h (at 60 Hz) Nominal Motor Rating: 0.75 kW Ultimate Pressure: 0.01 hPa (mbar) Operation: Dry, oil-free scroll compression technology	
6478	Grundfos CRI3-19 Vertical Multistage Centrifugal Pump with WEG 3 HP TEFC Motor, 230/460V; Vertical multistage centrifugal pump assembly manufactured by Grundfos, model CRI3-19, paired with a WEG NEMA Premium 3 HP TEFC electric motor. Pump nameplate indicates 60 Hz, nominal 15.4 GPM, max head 444 ft, max pressure 363 PSI, and NSF/ANSI 61 & 372 compliance. Motor nameplate identifies 3-phase, 230/460V, 182/4TC frame, IP55, Class F insulation, TEFC enclosure, and 3515 RPM operation. Assembly includes the pump, motor, mounting hardware, and fittings exactly as shown, shipped in original packaging materials. No additional accessories, controls, or external components are included beyond what is visible in the photos.	
6479	ROKI Techno Cilia-Clean; The ROKI Techno Cilia-Clean EZ-Change 500 L refers to a series of capsule filter cartridges used for high-precision filtration in industrial applications, particularly for high-viscosity liquids and paints. This lot contains approximately (80) canisters. (8) boxes of 10.	
6480	Industrial Sheet Metal Coating Roller; Used for copper or aluminum battery sheet	
6481	Stainless steel plates; This lot contains (2) 1" thick x 16" wide x 14" s.s plate. These plates are for assembly tooling bases.	

6482	Nippon Technart IMP-3800E; The Nippon Technart IMP-3800E is an industrial insulation impulse tester used to detect insulation defects (such as pinholes or metal powder contamination) in lithium-ion battery separators and other capacitor components.	
6483	Maxcess LAG-10-10-6-A Electromechanical Actuator; S/N 05132025	
6484	Kitz valve; The KITZ FA-150UTB is a pneumatic-actuated, Class 150 floating ball valve featuring a cast stainless steel (CF8) body and a full bore design, commonly used for automated flow control.	
6485	Kitz valve; The KITZ FA-150UTB is a pneumatic-actuated, Class 150 floating ball valve featuring a cast stainless steel (CF8) body and a full bore design, commonly used for automated flow control.	
6486	Maxcess LAG-10-10-4-A EPC Actuator; S/N 09172024	
6487	EDrive HD302 Actuator ; W/ Heavy Duty Eliminator	
6488	Maxcess GAG-2-6-A Actuator ; S/N 04242024	
6490	Grundfos CM3-5 Horizontal Multistage Centrifugal Pump w/ IEC Motor Assembly; Industrial horizontal multistage centrifugal pump assembly manufactured by Grundfos, identified as model CM3-5 A-S-G-E-AQQE-A-A-N, factory-paired with a Grundfos IEC electric motor. Nameplate ratings indicate 60 Hz operation with a nominal flow of 3.7 m ³ /h (16.4 GPM), nominal head of 49.6 m (70.6 PSI), and maximum head of 66.1 m (94 PSI), with a maximum working pressure of 10 bar (145 PSI) and maximum liquid temperature rating of 120 °C (248 °F). Unit features inline suction and discharge ports, multistage stainless steel pump section, IEC 60034 motor compliance, insulation class F, and carries UL, cUL, CE, UKCA, and EAC certifications. Factory assembled pump and motor configuration; mounting feet and electrical enclosure present as shown.	
6491	Industrial Fluid & Gas Control Instrumentation Set – Sensors, Valves, Switches, Solenoid Assembly; This lot is a coordinated set of industrial process-control components designed to function together in a fluid or gas handling system. The pressure transmitter monitors line pressure and provides a continuous feedback signal, while the solenoid valve assembly controls on /off flow in response to electrical commands. Flow or level sensing components verify movement or presence within the line, and the mechanical switch housings provide physical process interaction points. Together, these components form a closed-loop control arrangement where system conditions are sensed, electrically interpreted, and mechanically actuated to regulate flow, pressure, and system state within an automated or semi-automated process environment. Sold as a complete set only.	
6492	ROKI Techno Cilia-Clean; The ROKI Techno Cilia-Clean EZ-Change 500 L refers to a series of capsule filter cartridges used for high-precision filtration in industrial applications, particularly for high-viscosity liquids and paints. This lot contains approximately (80) canisters. (8) boxes of 10.	
6493	Sankyo indexing drive; Sankyo CD series indexing drives (often referencing roller gear cam technology) are used for high-speed, high-precision, and heavy-load automation, featuring zero-backlash for applications like assembly, inspection, and filling machines.	
6494	NEW IN BOX: SMC Pneumatic Air Cylinder – Model CDA2B100-520Z, 100 mm Bore; This is an SMC pneumatic air cylinder, a linear actuator designed to convert compressed air into straight-line mechanical motion for industrial automation and machinery. The unit is identified as model CDA2B100-520Z from SMC's CDA2 series and features a 100 mm bore with a 520 mm stroke. It is a tie-rod style cylinder with an aluminum body and threaded piston rod, built to operate at a maximum pressure of 145 PSI (1.0 MPa). The cylinder includes threaded air ports with protective plugs installed and is marked assembled in the USA. Manufacturer labels and pressure ratings are clearly visible. Item is sold exactly as shown in the photos.	
6495	NEW IN BOX: SMC Pneumatic Air Cylinder – Model CDA2B100-520Z, 100 mm Bore; This is an SMC pneumatic air cylinder, a linear actuator designed to convert compressed air into straight-line mechanical motion for industrial automation and machinery. The unit is identified as model CDA2B100-520Z from SMC's CDA2 series and features a 100 mm bore with a 520 mm stroke. It is a tie-rod style cylinder with an aluminum body and threaded piston rod, built to operate at a maximum pressure of 145 PSI (1.0 MPa). The cylinder includes threaded air ports with protective plugs installed and is marked assembled in the USA. Manufacturer labels and pressure ratings are clearly visible. Item is sold exactly as shown in the photos.	
6496	NEW IN BOX: SMC Pneumatic Air Cylinder – Model CDA2B100-520Z, 100 mm Bore; This is an SMC pneumatic air cylinder, a linear actuator designed to convert compressed air into straight-line mechanical motion for industrial automation and machinery. The unit is identified as model CDA2B100-520Z from SMC's CDA2 series and features a 100 mm bore with a 520 mm stroke. It is a tie-rod style cylinder with an aluminum body and threaded piston rod, built to operate at a maximum pressure of 145 PSI (1.0 MPa). The cylinder includes threaded air ports with protective plugs installed and is marked assembled in the USA. Manufacturer labels and pressure ratings are clearly visible. Item is sold exactly as shown in the photos.	
6497	NEW IN BOX: SMC Pneumatic Air Cylinder – Model CDA2B100-520Z, 100 mm Bore; This is an SMC pneumatic air cylinder, a linear actuator designed to convert compressed air into straight-line mechanical motion for industrial automation and machinery. The unit is identified as model CDA2B100-520Z from SMC's CDA2 series and features a 100 mm bore with a 520 mm stroke. It is a tie-rod style cylinder with an aluminum body and threaded piston rod, built to operate at a maximum pressure of 145 PSI (1.0 MPa). The cylinder includes threaded air ports with protective plugs installed and is marked assembled in the USA. Manufacturer labels and pressure ratings are clearly visible. Item is sold exactly as shown in the photos.	
6498	Inficon membrane frame; This is a membrane filter for a Inficon FTC3000. It helps separate foreign partials from entering the leak detection unit during quality checks on products.	

6499	AB MP-Series MPL 480VAC Rotary Servo Motor; S/N 302589557	
6500	Black pipe bucket traps; This lot contains (2) 3/4" mild steel bucket traps. These bucket traps can be used inline any water or steam system to help pull any unwanted material from said system to protect equipment.	
6501	(2) Armstrong C5297 3/4 Steam Traps - UNUSED; (2) 811 Traps - IN BOX	
6502	Cable carrier; This lot contains approximately 15' of cable carriers and locks. These IGUS cable carriers are versatile, plastic, maintenance-free systems used to guide and protect moving cables, hoses, and fiber optics in automation, robotics, machine tools, and cranes.	
6503	PHD CVAS6V63X750X-DB1 Pneumatic Cylinder; 34" Cylinder	
6504	PHD CVAS6V63X750X-DB1 Pneumatic Cylinder; 34" Cylinder	
6505	SMC Rodless Pneumatic Linear Actuator, SMC MY1B50G-600, 50mm Bore, 600mm Stroke; This is a rodless pneumatic linear actuator designed to produce straight-line motion using compressed air while eliminating the need for an external piston rod, allowing for a compact installation footprint and guided load support. The unit is identified as SMC model MY1B50G-600 and features a 50 mm bore with a 600 mm stroke length, utilizing an integrated carriage that travels along an aluminum extrusion body. Multiple threaded ports and mounting points are machined into the end blocks for pneumatic connection and system integration. The construction and layout indicate suitability for precision linear movement in automated industrial equipment and manufacturing systems.	
6506	SMC Rodless Pneumatic Linear Actuator, SMC MY1B50G-600, 50mm Bore, 600mm Stroke; This is a rodless pneumatic linear actuator designed to produce straight-line motion using compressed air while eliminating the need for an external piston rod, allowing for a compact installation footprint and guided load support. The unit is identified as SMC model MY1B50G-600 and features a 50 mm bore with a 600 mm stroke length, utilizing an integrated carriage that travels along an aluminum extrusion body. Multiple threaded ports and mounting points are machined into the end blocks for pneumatic connection and system integration. The construction and layout indicate suitability for precision linear movement in automated industrial equipment and manufacturing systems.	
6507	Automation cylinder; This is a pneumatic rodless cylinder. The rodless cylinder moves the load alongside the piston. This gives the main advantages of having the same stroke length in significantly less space. The bore size is 63 mm	
6508	Transfer arm; Samick THK transfer arms (or robot modules) are high-precision, industrial automation components designed for rapid, accurate workpiece, wafer, or material handling	
6509	Transfer arm; Samick THK transfer arms (or robot modules) are high-precision, industrial automation components designed for rapid, accurate workpiece, wafer, or material handling	
6510	Transfer cell; The SAD 16-10 is an industrial linear actuator manufactured by Samick THK, designed for precision motion in automation and robotic systems. It integrates a linear motion (LM) guide with a ball screw drive to provide high-rigidity and accurate positioning.	
6511	Transfer cell; The SAD 16-10 is an industrial linear actuator manufactured by Samick THK, designed for precision motion in automation and robotic systems. It integrates a linear motion (LM) guide with a ball screw drive to provide high-rigidity and accurate positioning.	
6512	Transfer cell; The SAD 16-10 is an industrial linear actuator manufactured by Samick THK, designed for precision motion in automation and robotic systems. It integrates a linear motion (LM) guide with a ball screw drive to provide high-rigidity and accurate positioning.	
6513	Samick Linear Electric Actuator / Mechatronic Slide Assembly, Samick SMART SAD-16-N-H-800-D-110220; This is a linear electric actuator and integrated mechatronic slide assembly designed to provide controlled, precise linear motion along a guided aluminum rail using an internal drive system. The actuator incorporates a rigid carriage plate for load mounting, an enclosed linear guide structure, and an integrated drive channel intended for automated positioning and repeatable motion in industrial equipment. The unit is identified as a Samick Mechatronic System SMART series actuator, model SAD-16-N-H-800-D-110220, manufactured by Samick THK Co., Ltd., with labeling indicating Made in Korea. The assembly features a long-stroke rail configuration with pre-mounted carriage block and factory-installed end assemblies. Only the actuator shown is included; no motors, cables, controllers, or accessories beyond what is visible are included.	
6514	NEW IN BOX Samick Linear Electric Actuator / Mechatronic Slide Assembly, Samick-THK SMART SAD-16-N-H-800-D-110220; This is a linear electric actuator and integrated mechatronic slide assembly designed to generate controlled, repeatable linear motion along a rigid guided rail using an internal drive mechanism. The unit features an enclosed aluminum extrusion body with an integrated linear guide, a pre-mounted carriage plate for load attachment, and an end-mounted drive housing intended for precise positioning in automated machinery and industrial motion systems. The actuator is identified as a Samick-THK SMART series unit, model SAD-16-N-H-800-D-110220, manufactured by Samick THK Co., Ltd., with labeling indicating Made in Korea. The assembly is configured as a long-stroke slide with factory-installed carriage and end assemblies.	
6515	NEW IN BOX Samick Linear Electric Actuator / Mechatronic Slide Assembly, Samick-THK SMART SAD-16-N-H-800-D-110220; This is a linear electric actuator and integrated mechatronic slide assembly designed to generate controlled, repeatable linear motion along a rigid guided rail using an internal drive mechanism. The unit features an enclosed aluminum extrusion body with an integrated linear guide, a pre-mounted carriage plate for load attachment, and an end-mounted drive housing intended for precise positioning in automated machinery and industrial motion systems. The actuator is identified as a Samick-THK SMART series unit, model SAD-16-N-H-800-D-110220, manufactured by Samick THK Co., Ltd., with labeling indicating Made in Korea. The assembly is configured as a long-stroke slide with factory-installed carriage and end assemblies.	

6516	Flow-Rite Deionizer Cartridge ; Disposable; UNUSED; 100 PSI Max	
6517	Flow-Rite Deionizer Cartridge ; Disposable; UNUSED; 100 PSI Max	
6518	Oriental motor; The Oriental Motor model- EZSM6RD065AZAK is an electric linear slide from the EZS Series, featuring a compact, high-rigidity design and the AZ Series stepper motor with a battery-free absolute encoder.	
6519	NEW IN BOX - SMC Pneumatic Rodless Cylinder Linear Slide Assembly-MY1C25-900L; Rodless pneumatic cylinder linear slide assembly identified as SMC MY1C25-900L, featuring an extruded aluminum body with integrated carriage and long-stroke configuration. The assembly includes end blocks with pneumatic ports, a guided carriage plate with mounting provisions, and sealed internal components consistent with the MY1C series design. Labeling confirms MY1C25-900L specification, indicating a 25 mm bore class with extended stroke length supplied as a complete cylinder assembly.	
6520	Unwinder cell; The SAD 18-05 is a high-precision industrial linear actuator that belongs to the same family as the SAD 16-10. The primary difference lies in the ball screw lead, which directly impacts its speed and resolution.	
6521	Unwinder cell; The SAD 18-05 is a high-precision industrial linear actuator that belongs to the same family as the SAD 16-10. The primary difference lies in the ball screw lead, which directly impacts its speed and resolution.	
6522	SMC MY1C25-900L Cylinder; 116 PSI Max	
6523	Bonding cell; The Samick THK SAS 10-10 is a ball-screw-driven orthogonal coordinate robot (linear actuator) designed for high-precision industrial positioning. It is a smaller, more compact alternative to the SAS 16 and SAS 18 series.	
6524	Bonding cell; The Samick THK SAS 10-10 is a ball-screw-driven orthogonal coordinate robot (linear actuator) designed for high-precision industrial positioning. It is a smaller, more compact alternative to the SAS 16 and SAS 18 series.	
6525	Ultra Web 2.0 Protura Filter Cartridge; 26" Filter	
6526	NEW IN BOX: Daesung-Nachi Piston Pump Hydraulic Assembly (Model PVS-C); Hydraulic piston pump assembly manufactured by Daesung-Nachi Hydraulics Co., Ltd., identified by the attached metal nameplate as a Daesung-Nachi piston pump with model marking "PVS-C" visible on the tag. The unit features a cast housing with multiple hydraulic ports, a top-mounted drive shaft, and integrated mounting surfaces consistent with industrial hydraulic piston pump designs. Nameplate confirms Daesung-Nachi branding and Made in Korea origin. Item is bagged and shown exactly as included in this lot.	
6527	NEW IN BOX: Daesung-Nachi Piston Pump Hydraulic Assembly (Model PVS-C); Hydraulic piston pump assembly manufactured by Daesung-Nachi Hydraulics Co., Ltd., identified by the attached metal nameplate as a Daesung-Nachi piston pump with model marking "PVS-C" visible on the tag. The unit features a cast housing with multiple hydraulic ports, a top-mounted drive shaft, and integrated mounting surfaces consistent with industrial hydraulic piston pump designs. Nameplate confirms Daesung-Nachi branding and Made in Korea origin. Item is bagged and shown exactly as included in this lot.	
6528	Protura Ultra Web 2.0 Filter Cartridge; 26" Filter	
6529	PES50P2SH Filter Bags; (50) Total	
6530	Stainless steel valves; This lot contains kitz valves. Size ranging from 1 1/2" to 6". These S.S valves are known for their superior corrosion resistance and durability in demanding industrial applications.	
6531	GTR 3-phase induction motor; Power: 1.5 kW Voltage/Frequency Options: 220V 60Hz or 380V 60Hz Efficiency (NOM. EFF): 85.3% (at 220V) or 86.5% (at 380V)	
6532	Kits valve parts; This lot contains a variety of kits stainless steel valve parts including linkage kits, seal kits, actuator and mounting brackets. Kits valves are known for their superior corrosion resistance and durability in demanding industrial applications.	
6533	Pallet Lot of Greenwood Certified 250 mL HDPE Sample Bottles w/ COA (26 boxes); Palletized lot of Greenwood Products certified 250 mL HDPE leakproof wide-mouth sample bottles with 43-415 linerless caps, supplied in factory-packed cases and accompanied by original Greenwood Certificate of Analysis documentation. COA confirms containers meet or exceed U. S. EPA specifications for contaminant-free sample containers, including testing for volatile organics, semi-volatiles, pesticides, PCBs, metals, and other regulated analytes. Boxes appear labeled as 28 bottles per case. Bottles are unused, capped, and packaged for laboratory, environmental sampling, and compliance testing applications. Lot includes all cases and paperwork shown; pallet contents sold as one lot.	
6534	(14) Boxes of 250mL SMART Leakproof Wide Mouth Bottles; 43-415 Linerless Caps; (28) Bottles per Box [392 Total Boxes]	
6535	Wire rope; This lot contains approximately (12) muratec brand wire ropes. (2) boxes) Each rope is approximately 25' long. There are many uses for this product, weather in industrial or residential locations.	

6536	Bulk Lot of Industrial Battery Electrode Die-Cutting Templates / DieFlex 400 Cutting Rules – Assorted ; This lot includes assorted industrial die-cutting templates used in battery electrode manufacturing, designed to cut precise anode or cathode patterns from coated electrode sheets during cell production. The tooling consists of formed cutting-rule edges mounted in rigid backing frames, manufactured to specific electrode geometries and intended for use in press-based or automated die-cutting systems. Visible markings reference DieFlex 400 tooling with serialized identifiers, consistent with production-grade battery manufacturing processes. Items are housed in custom foam-lined industrial totes labeled for anode cutting applications. Sold as an assorted lot exactly as shown, with no material composition or dimensional specifications implied.	
6537	Mitsubishi Electric FR-XC-7.5K Multifunction Regenerative Converter - NEW, IN BOX; Mitsubishi Electric FR-XC series advanced inverter designed for precise motor speed and torque control in industrial automation environments. This unit is identified as model FR-XC-7.5K, part of Mitsubishi's Intelligent & Advanced Inverter line, and is housed in a compact industrial enclosure with an integrated aluminum heat sink for thermal management. The front interface includes an integrated display and control keypad area, with internal cooling and vented side panels typical of variable frequency drives. Manufacturer documentation shown indicates compatibility with PWM control variants within the FR-XC family. Unit is boxed with original packaging and printed instruction manual as shown. S/N F29677005	
6538	Mitsubishi Electric FR-XC-7.5K Multifunction Regenerative Converter - NEW, IN BOX; Mitsubishi Electric FR-XC series advanced inverter designed for precise motor speed and torque control in industrial automation environments. This unit is identified as model FR-XC-7.5K, part of Mitsubishi's Intelligent & Advanced Inverter line, and is housed in a compact industrial enclosure with an integrated aluminum heat sink for thermal management. The front interface includes an integrated display and control keypad area, with internal cooling and vented side panels typical of variable frequency drives. Manufacturer documentation shown indicates compatibility with PWM control variants within the FR-XC family. Unit is boxed with original packaging and printed instruction manual as shown. S/N F29677009	
6539	Mitsubishi Electric FR-XC-7.5K Multifunction Regenerative Converter - NEW IN BOX ; Mitsubishi Electric FR-XC series advanced inverter designed for precise motor speed and torque control in industrial automation environments. This unit is identified as model FR-XC-7.5K, part of Mitsubishi's Intelligent & Advanced Inverter line, and is housed in a compact industrial enclosure with an integrated aluminum heat sink for thermal management. The front interface includes an integrated display and control keypad area, with internal cooling and vented side panels typical of variable frequency drives. Manufacturer documentation shown indicates compatibility with PWM control variants within the FR-XC family. Unit is boxed with original packaging and printed instruction manual as shown. S/N F29677010	
6540	Mitsubishi Electric FR-XC-7.5K Multifunction Regenerative Converter - NEW IN BOX ; Mitsubishi Electric FR-XC series advanced inverter designed for precise motor speed and torque control in industrial automation environments. This unit is identified as model FR-XC-7.5K, part of Mitsubishi's Intelligent & Advanced Inverter line, and is housed in a compact industrial enclosure with an integrated aluminum heat sink for thermal management. The front interface includes an integrated display and control keypad area, with internal cooling and vented side panels typical of variable frequency drives. Manufacturer documentation shown indicates compatibility with PWM control variants within the FR-XC family. Unit is boxed with original packaging and printed instruction manual as shown. S/N F29677007	
6541	Mitsubishi Electric FR-XC-7.5K Multifunction Regenerative Converter - NEW IN BOX ; Mitsubishi Electric FR-XC series advanced inverter designed for precise motor speed and torque control in industrial automation environments. This unit is identified as model FR-XC-7.5K, part of Mitsubishi's Intelligent & Advanced Inverter line, and is housed in a compact industrial enclosure with an integrated aluminum heat sink for thermal management. The front interface includes an integrated display and control keypad area, with internal cooling and vented side panels typical of variable frequency drives. Manufacturer documentation shown indicates compatibility with PWM control variants within the FR-XC family. Unit is boxed with original packaging and printed instruction manual as shown. S/N F29677008	
6542	Mitsubishi Electric FR-XC-7.5K Multifunction Regenerative Converter - NEW IN BOX ; Mitsubishi Electric FR-XC series advanced inverter designed for precise motor speed and torque control in industrial automation environments. This unit is identified as model FR-XC-7.5K, part of Mitsubishi's Intelligent & Advanced Inverter line, and is housed in a compact industrial enclosure with an integrated aluminum heat sink for thermal management. The front interface includes an integrated display and control keypad area, with internal cooling and vented side panels typical of variable frequency drives. Manufacturer documentation shown indicates compatibility with PWM control variants within the FR-XC family. Unit is boxed with original packaging and printed instruction manual as shown. S/N F29677006	
6543	; This lot contains (3) boxes of 3/4-inch inside diameter, 50-foot long heater hose manufactured by Gates. Used in many different applications commercial or residential.	
6544	Kokam coating die; Kokam coating dies are used to apply a uniform and precise layer of electrode slurry (containing active materials) onto a substrate, such as aluminum or copper foil. The dies are critical components of a larger roll-to-roll production line.	
6545	Batteries; This lot contains (2) different batteries. (1) 12.8v, 7ah lifep04. This is a low voltage battery used on many different applications. (1) Duracell marine and RV deep cycle battery. 12v, 650 cold cranking amps. This battery is also used for many different applications.	
6546	Mitsubishi Electric FR-XCCP01 Converter Enclosure - NEW, IN BOX; Enclosure and Installation Screw for Mitsubishi FR-XC Converter	
6547	Mitsubishi Electric FR-XC-11K Advanced Inverter / Converter Module - NEW in Box ; Mitsubishi Electric FR-XC series advanced inverter / converter module, model FR-XC-11K, designed for industrial motor drive systems requiring controlled DC bus output. This unit accepts 3-phase AC 200–240V, 50/60 Hz input and provides a DC output range of 282–339 V, with a maximum rated output power of 17.3 kW as indicated on the manufacturer nameplate. The enclosure features integrated ventilation, a front display/control interface area, and a rear aluminum heat-sink assembly for thermal dissipation. Nameplate confirms common-mode and regenerative current ratings, UL/CE/EAC certifications, and manufacture date 2022-09, made in Japan. Unit is shown with original Mitsubishi Electric packaging and documentation.	

6548	Mitsubishi Electric FR-XC-11K Advanced Inverter / Converter Module - NEW in Box; Mitsubishi Electric FR-XC series advanced inverter / converter module, model FR-XC-11K, designed for industrial motor drive systems requiring controlled DC bus output. This unit accepts 3-phase AC 200–240V, 50/60 Hz input and provides a DC output range of 282–339 V, with a maximum rated output power of 17.3 kW as indicated on the manufacturer nameplate. The enclosure features integrated ventilation, a front display/control interface area, and a rear aluminum heat-sink assembly for thermal dissipation. Nameplate confirms common-mode and regenerative current ratings, UL/CE/EAC certifications, and manufacture date 2022-09, made in Japan. Unit is shown with original Mitsubishi Electric packaging and documentation.	
6549	Mitsubishi Electric FR-XC-11K Advanced Inverter / Converter Module; Mitsubishi Electric FR-XC series advanced inverter / converter module, model FR-XC-11K, designed for industrial motor drive systems requiring controlled DC bus output. This unit accepts 3-phase AC 200–240V, 50/60 Hz input and provides a DC output range of 282–339 V, with a maximum rated output power of 17.3 kW as indicated on the manufacturer nameplate. The enclosure features integrated ventilation, a front display/control interface area, and a rear aluminum heat-sink assembly for thermal dissipation. Nameplate confirms common-mode and regenerative current ratings, UL/CE/EAC certifications, and manufacture date 2022-09, made in Japan. Unit is shown with original Mitsubishi Electric packaging and documentation.	
6550	Mitsubishi Electric FR-XC-11K Advanced Inverter / Converter Module; Mitsubishi Electric FR-XC series advanced inverter / converter module, model FR-XC-11K, designed for industrial motor drive systems requiring controlled DC bus output. This unit accepts 3-phase AC 200–240V, 50/60 Hz input and provides a DC output range of 282–339 V, with a maximum rated output power of 17.3 kW as indicated on the manufacturer nameplate. The enclosure features integrated ventilation, a front display/control interface area, and a rear aluminum heat-sink assembly for thermal dissipation. Nameplate confirms common-mode and regenerative current ratings, UL/CE/EAC certifications, and manufacture date 2022-09, made in Japan. Unit is shown with original Mitsubishi Electric packaging and documentation.	
6551	Mitsubishi 11k reactor; The "Mitsubishi 11k reactor" is an 11 kW (15 HP) electrical reactor used with Mitsubishi Electric industrial inverters (VFDs) or servo amplifiers to suppress harmonics and improve power factor.	
6552	Mitsubishi 11k reactor; The "Mitsubishi 11k reactor" is an 11 kW (15 HP) electrical reactor used with Mitsubishi Electric industrial inverters (VFDs) or servo amplifiers to suppress harmonics and improve power factor.	
6553	Mitsubishi 11k reactor; The "Mitsubishi 11k reactor" is an 11 kW (15 HP) electrical reactor used with Mitsubishi Electric industrial inverters (VFDs) or servo amplifiers to suppress harmonics and improve power factor.	
6554	Mitsubishi Electric FR-XCL-7.5K DC Reactor - NEW IN BOX; For Mitsubishi FR-XC Converters	
6555	Mitsubishi Electric FR-XCL-7.5K DC Reactor - NEW IN BOX; For Mitsubishi FR-XC Converters	
6556	Quartz glass tubes; This lot contains (4) quartz glass tubes. 27mm x 30mm x 780mm These tubes are used for boiler or water application sight glasses to check for level of solution.	
6557	Samick LM parts; This lot contains (2) ball screws from the Samick THK LM system, the Ball Screw serves as a high-efficiency feed screw that converts rotary motion into precise linear motion using recirculating ball bearings.	
6558	Kuri Tech Flexible Polyethylene Tubing; (2) Boxes, Length 100ft, 0.380"x0.593"	
6559	Rollers and polypropylene stock; This lot contains approximately (40) rollers used for conveyors or other assembly part movement operations. Also included is polypropylene round and plate stock.	
6560	(2) Salisbury WBS Full Frame Assemblies 12 Cal - IN BOX, UNUSED; AS-1200-CV Flash Face Shield, A79 Hard Hat	
6561	Verkada CD51 Indoor Dome Camera - UNUSED; S/N GJ7F-ALG3-LRYQ	
6562	Coveralls; Kleenguard coveralls, sized XL. These all white coveralls can be used for personal protection equipment in any job or activity. There are approximately (20) suits in this box.	
6563	MRP adhesive strips ; This lot contains red rhino adhesive strips, 1/8"-12mm. Approximately 912 strips total. These are cut into strips and used as an ejector (stripping rubber) in commercial die-cutting to help separate finished parts from the waste material. They can also be used on many other projects.	
6564	Mixed Industrial Items Lot ; This mixed industrial lot includes a multi-slot barcode scanner battery charging station with integrated status display windows, a handheld USB barcode scanner, a caged industrial light fixture with integrated LED module, multiple plastic utility containers with threaded caps, electrical junction boxes with metal mounting plates, assorted power and data cables, and a roll of high-visibility yellow industrial tape labeled "Pathfinder." The charging station appears designed for simultaneous charging of multiple removable scanner batteries, while the handheld scanner and accessories suggest use in warehouse, manufacturing, or logistics environments.	
6565	Mixed Industrial Electronics, Cables & Hardware Lot; This mixed industrial lot includes coiled blue Ethernet-style network cabling with modular connectors, a yellow portable power inverter labeled 400W with attached power leads and clamps, a handheld wired barcode scanner with USB connection, a single-slot scanner battery charging base, assorted KOYO-branded bearing boxes, packaged fasteners and threaded hardware, and miscellaneous small electronic and shop items including a basic desktop calculator. Items appear intended for warehouse, maintenance, or light industrial environments and are sold together as one lot.	
6566	Assorted Bin of Westchester / Showa Cut Resistant / Heat Resistant Gloves; Several Packs Westchester #730TBU XL Cut Resistant Gloves; (7) Pairs Showa Heat Resistant Gloves	

6567	Honeywell S540-0028 Neoprene 8" Dia. Cuff, 32" Length (10H) Glove Box Gloves; Tested for 10,000V DC	
6568	Baldor 15HP Induction Motor; 2700 RPM Max; PYM Inverter	
6569	Allen Bradley Powerflex 400 AC Drive; The Allen-Bradley PowerFlex 400 from Rockwell Automation is an adjustable frequency AC drive specifically optimized for variable torque applications such as commercial and industrial fans and pumps. It provides a cost-effective solution for speed control with features that simplify integration into building automation systems.	
6570	Over 80 Lichtzen Long Arc UV Lamps; 100V, Overall Length: 850	
6571	Marathon 3-Phase 10HP Electric Motor; 460V; 1765 RPM	
6572	Marathon 3-Phase Electric Motor ; Industrial AC electric motor manufactured by Marathon Electric, part of the Blue Chip Severe Duty line and labeled Marine Duty. Nameplate indicates model RVD215THFS9001AFL with TEFC enclosure and NEMA Frame 215T. Rated at 10 horsepower (7.5 kW), 460V, 3-phase, 60 Hz, operating at 3535 RPM with continuous duty. Insulation class F with 1.15 service factor, inverter-duty compatible (PWM VFD rated), and premium efficiency listed at 91.7%. Foot-mounted configuration with drive-end and opposite-end bearings noted on the plate. Manufactured 04/2016, Made in USA.	
6573	Baldor 3-Phase 25HP Electric Motor; 460V; 1770RPM	
6574	Baldor Reliance Super E AC Electric Motor, 1.5 HP, 230/460V, 3-Phase, 1760 RPM, Frame 145T; AC electric motor manufactured by Baldor (by ABB), part of the Baldor Reliance Super E motor line. Nameplate shows catalog number EM3554T, rated at 1.5 horsepower with dual voltage 230/460V, 3-phase, 60 Hz operation and nominal speed of 1760 RPM. NEMA Frame 145T with 1.15 service factor, Design B, Code L, Class F insulation, and continuous duty rating at 40°C ambient. Motor is packaged in original Baldor box as shown, with motor visible inside packaging.	
6575	Baldor 3-Phase 1.5 HP Electric Motor; 230/460V; 1760RPM	
6576	Protech 3-Phase 2HP Electric Motor; S/N 38EP02H4A3	
6577	Magna-Power Programmable DC Power Supply, 0–100 VDC, 0–100 ADC, 10 kW, Model SL100-100-380; Programmable DC power supply manufactured by Magna-Power. Nameplate identifies model SL100-100-380 with adjustable DC output from 0–100 VDC and 0–100 ADC, rated up to 10 kW output power. Input power is specified at 380/400 VAC ±10%, 22 A AC, 50–400 Hz, three-phase. Unit is certified to UL and CSA standards and marked with CE and ETL approvals. Manufacturing date listed as September 2022. Serial number and work order number are visible on the label. Model #: SL 100-100/380	
6578	Magna Power, DC Power Supply Formation; Model #: SL 100-100/380; 0-10kW, 100VDC, 100A Output; 380/400V Input	
6579	Magna Power DC Power Supply Formation; Model #: SL 100-100/380; 10kW, 100VDC, 100A Output; 380/400V Input	
6580	Magna-Power Programmable DC Power Supply, 0–100 VDC, 0–100 ADC, 10 kW, Model SL100-100-380; Programmable DC power supply manufactured by Magna-Power. Nameplate identifies model SL100-100-380 with adjustable DC output from 0–100 VDC and 0–100 ADC, rated up to 10 kW output power. Input power is specified at 380/400 VAC ±10%, 22 A AC, 50–400 Hz, three-phase. Unit is certified to UL and CSA standards and marked with CE and ETL approvals. Manufacturing date listed as September 2022. Serial number and work order number are visible on the label. Model #: SL 100-100/380	
6581	Ulvac GLD-040 Vacuum Pump; 48L/min Pumping Speed; S/N 2493007	
6582	Ulvac GLD-040 Vacuum Pump; 48L/min Pumping Speed; S/N 2493007	
6583	HoneyWell Upper and Lower Power Track Assemblies; Full Upper and Lower Cables w/ Cable Carrier and Drag Chain	
6584	HoneyWell Upper and Lower Power Track Assemblies; Full Upper and Lower Cables w/ Cable Carrier and Drag Chain	
6585	Assorted Kitz Mixing Valves; (3) Boxes Total: (1) CF8 3-150 S13A Valve. (2) 150 UTB Valves. (1) CF6 Valve.	
6586	SMC Pneumatic Air Cylinder; Model: CS1FN250-100 Manufacturer: SMC Max. Pressure: 140 PSI (1.0 MPa) Origin: Made in USA Function: Generates Linear Motion Using Compressed Air	
6587	Industrial Vibratory Rivet Bowl Feeder System with Rodix Feeder Cube Controller; Industrial vibratory rivet bowl feeder assembly used for automated part orientation and feeding in manufacturing or assembly lines. The system includes a stainless steel vibratory bowl labeled "Cell Assy Rivet Bowl" with SAP #93114951, originally built as part of a rivet feeding system for XALT Energy by Feeding Concepts (Vibratory Feeders), job serial number FC-23-20024. The lot also includes a Rodix Feeder Cube Auto Tune Series controller, model VF-3 (P/N 121-200-0754), with selectable 120/240 VAC input and variable frequency output (5–180 Hz), housed in a Type 1 enclosure with integrated controls and cabling. Components are mounted and stored together in a wooden crate.	

6588	Armstrong / Yoshitake GP-2000 Pressure Reducing Valve, 4 in, ANSI 300; Industrial pressure reducing valve packaged in original carton, identified as an Armstrong Yoshitake GP-2000 series valve. Label indicates 4 in (100 mm) size with ANSI 300 lb connection (A30R). Rated inlet pressure range of 15–285 psig (1–20 bar) with reduced pressure range marked “B” at 15–200 psig (1–14 bar). Marked model configuration GP-2000-A30R-B with Yoshitake branding and Armstrong distribution labeling, made in Thailand. Factory carton shows part references including GP2000 4 300RF 15-200 DI and Armstrong /Yoshitake identification; contents not removed from packaging and only what is pictured is included.	
6589	(2) RTV Rack Jacks; This mechanical device is a linear actuator based on the rack and pinion principle for precise positioning and lifting of loads in manufacturing and machine tools. Part no. S650-0489	
6590	(880) Total 5.5W Ceramic Pulseaters; (24) boxes of (40) parts. ceramic composition resistor designed by the company Ohmite to withstand high-energy electrical pulses and surges.	
6591	Calpeda 4HP Electric Motor and Centrifugal Pump; 220V; 3450RPM	
6592	Industrial Motor Assembly, Shinmyung SMV05H4A VT, 5 HP; Industrial motor assembly packaged on pallet and identified by labeling as part number SMV05H4A VT, rated 5 HP, 4-pole, with 2/3V UL marking. Unit is tagged under internal reference S650-0363 and lists Shinmyung as the maker, with supplier noted as Geard on internal labeling. Additional carton identification references Freudenberg article number 0093087480. Motor is wrapped and secured for storage or transport; listing includes the motor assembly only as shown, with no accessories, controls, or documentation beyond what is pictured.	
6593	Sew Eurodrive 3-Phase 2HP Electric Motor; 1740RPM; 230/460V	
6594	SEW Eurodrive 3-Phase 2HP Electric Motor; 1740RPM; 230/460V	
6595	AMETEK SGI100X-100D High Power Modular DC Power Supply; AMETEK Sorensen SG Series programmable DC power supply module with an output of 100V and 100A, which combines to a total output power of 10 kW. The "D" in the model number indicates that it is configured for a 342-440 VAC input voltage range.	
6596	Emerson 63-13-210-6 1kVA Constant Voltage Power Conditioner; The Emerson (SolaHD) MCR series (MCR1000) constant voltage power conditioner is a robust, industrial-grade unit that utilizes ferroresonant transformer technology to provide extremely reliable voltage regulation and power conditioning. It is specifically designed to protect sensitive equipment in harsh electrical environments, such as those with frequent sags, swells, brownouts, and electrical noise.	
6597	Emerson 63-13-210-6 1kVA Constant Voltage Power Conditioner; The Emerson (SolaHD) MCR series (MCR1000) constant voltage power conditioner is a robust, industrial-grade unit that utilizes ferroresonant transformer technology to provide extremely reliable voltage regulation and power conditioning. It is specifically designed to protect sensitive equipment in harsh electrical environments, such as those with frequent sags, swells, brownouts, and electrical noise.	
6598	Emerson 63-13-210-6 1kVA Constant Voltage Power Conditioner; The Emerson (SolaHD) MCR series (MCR1000) constant voltage power conditioner is a robust, industrial-grade unit that utilizes ferroresonant transformer technology to provide extremely reliable voltage regulation and power conditioning. It is specifically designed to protect sensitive equipment in harsh electrical environments, such as those with frequent sags, swells, brownouts, and electrical noise.	
6599	Emerson 63-13-210-6 1kVA Constant Voltage Power Conditioner; The Emerson (SolaHD) MCR series (MCR1000) constant voltage power conditioner is a robust, industrial-grade unit that utilizes ferroresonant transformer technology to provide extremely reliable voltage regulation and power conditioning. It is specifically designed to protect sensitive equipment in harsh electrical environments, such as those with frequent sags, swells, brownouts, and electrical noise.	
6600	Emerson 63-13-210-6 1kVA Constant Voltage Power Conditioner; The Emerson (SolaHD) MCR series (MCR1000) constant voltage power conditioner is a robust, industrial-grade unit that utilizes ferroresonant transformer technology to provide extremely reliable voltage regulation and power conditioning. It is specifically designed to protect sensitive equipment in harsh electrical environments, such as those with frequent sags, swells, brownouts, and electrical noise.	
6601	Baldor-Reliance Super-E Industrial Electric Motor, 15 HP, 3-Phase, 1765 RPM; Industrial electric motor identified as a Baldor-Reliance Super-E motor, catalog number EHM2333T. Nameplate indicates 15 HP, 3-phase, 60 Hz, with dual voltage ratings of 208–230/460 VAC and full-load speeds listed at 1765 RPM. Motor is built on a 254T frame, rated 40°C ambient continuous duty, with 1.15 service factor, Code H, Design B, and Class F insulation. NEMA nominal efficiency is marked at 92.4%, with power factor 82%. Enclosure is TEFC (Totally Enclosed Fan Cooled). Bearing sizes listed as DE 6309 and ODE 6208. Serial number Z1207260381 shown on plate.	
6602	(960) Total 5.5W Ceramic Pulseaters; (24) boxes of (40) parts. ceramic composition resistor designed by the company Ohmite to withstand high-energy electrical pulses and surges.	
6603	(980) Total 5.5W Ceramic Pulseaters; (49) boxes of (20) parts. ceramic composition resistor designed by the company Ohmite to withstand high-energy electrical pulses and surges.	
6604	Automatic warehouse system ; Automatic MRO storage picking/lifting system by system logistics. Serial #: MC1100061 Model#: modula MC50-12100 Power requirement: 480vac, 13amp. The Modula MC50-12100 is a specific configuration of the Modula Lift Vertical Lift Module (VLM), an automated storage and retrieval system designed to maximize vertical space and improve picking efficiency in warehouses and manufacturing facilities. -The MC model has a tray width of 98.42 inches. - tray payload capacity of 500 kg (1,102 lbs). -system is 36' tall. -The system automatically delivers the requested tray directly to the operator at an ergonomic picking bay. -featuring a steel load-bearing structure and steel-reinforced toothed belts, allows for a gross total unit capacity of up to (154,000 lbs) -It features an intuitive 10.4-inch color touchscreen operator console (called Copilot) that displays item locations and manages inventory.	

6605	2012 System Logistics 36' MRO Automatic Warehouse Vertical Lift Module System; Automatic MRO storage picking/lifting system by system logistics. Serial #: MC1100060 Model#: modula MC50-12100 Power requirement: 480vac, 13amp. The Modula MC50-12100 is a specific configuration of the Modula Lift Vertical Lift Module (VLM), an automated storage and retrieval system designed to maximize vertical space and improve picking efficiency in warehouses and manufacturing facilities. -The MC model has a tray width of 98.42 inches. -tray payload capacity of 500 kg (1,102 lbs). -system is 36' tall. - The system automatically delivers the requested tray directly to the operator at an ergonomic picking bay. -featuring a steel load-bearing structure and steel-reinforced toothed belts, allows for a gross total unit capacity of up to (154,000 lbs) -It features an intuitive 10.4-inch color touchscreen operator console (called Copilot) that displays item locations and manages inventory.	
6606	Divider of Tray 2001 - Seal Shaft Kit, Rebuild Kits, Diaphragm Kit, etc.; Contents: -(2) Filter Element Paper 850 Rolls (for 160-225 Bus) -Ashcroft Pressure Gauge -Graco DOB001 Diaphragm Kit -Grundfos Seal Shaft Kit -(3) Parker Auto Drain Rebuild Kits	
6607	Divider of Tray 2001 - Rotary Union Joint, Filter Regulators, etc.; Contents: -Kwang Jin Rotary Union Joint -(2) 1/4" Filter Regulators	
6608	Divider of Tray 2001 - Pressure Switch, Rotary Union Joint, Cylinder, etc.; Contents: -Dwyer 1950-10-2F Pressure Switch -(3) 1" Kitz Valve Repair Kits -Kwang Jin Rotary Union Joint -SMC Cylinder -(2) 1.5" & 2" Kitz SS LKG Kits	
6609	Divider of Tray 2001 - Kunkle Valves, Kitz Valve Repair Kits, PD Valve Packing, etc.; Contents: -(4) 1/2"x1/2" Kunkle Valves -(6) PD Valve Packing Kits -(3) 3/4" Kunkle Valves -(3) Kitz Valve Repair Kits (3"/4"/6")	
6610	Divider of Tray 2001 - Quartz Mechanical Switch Assemblies, Valve Control Kits, Solenoid Valves, etc.; Contents: -(3) Quartz Damper Mechanical Switch Assemblies -(3) 3/4" Valve Control Kits -(4) ASCO Solenoid Valves	
6611	Divider of tray 2001- Hydra cell rebuild kits, hydraulic fluid, servo motors, electric motor and bollard caps; This lot contains an assortment of supplies including - concrete or steel 4" rubber bollard caps. Quantity (8) - US motors 120vac, 1725 rpm electric motor. Quantity (1) -servo motors. 36vdc 3000rpm with connector pins. Quantity (3) -hydra oil pump lubricants. (2) one quart synthetic 5W-30. Hydra cell rebuilt kits with seals and rings. Quantity (4)	
6612	Divider of tray 2001- Servo pack, relays, door hinges and 3-way valves; This lot contains an assortment of supplies including - Three way valve from MAC valves, model: 35A. Quantity (2) -high temp rated door hinges used on industrial ovens. Brand: Kong Jin. Quantity (7) -24vdc control relays, model:RH3B. Quantity (12) -Yaskawa servo pack designed to control the position, speed, and torque of servo motors. Quantity (1)	
6613	Divider of tray 2001- parts kit, pumps, fuses and relays; This lot contains an assortment of supplies including -JLS300 fuses quantity of (7) -Class J 35A 600v fuses quantity of (approximately 60) -24vdc relays quantity of (4) - KNF 24vdc liquid pumps Quantity of (4) -hydra cell bearing and spring parts kit.	
6614	Divider of Tray 2002 - seal bolt clamps and high temp filters; This lot contains an assortment of supplies including -6" tight seal bolt clamps. Quantity (3) -high temperature filter cartridge. These filters utilize specialized materials like microfine glass media, stainless steel frames, and inorganic sealants to withstand extreme heat. Quantity (6)	
6615	Divider of Tray 2002- Allen Bradley VFDs; This lot contains (2) Allen Bradley power flex 4 variable frequency drives. These are 22A, 240vac. designed for basic, machine-level speed control applications like fans, pumps, and conveyors.	
6616	Divider of Tray 2002- Allen Bradley VFDs; This lot contains (3) Allen Bradley power flex 4 variable frequency drives. These are 22A, 240vac. designed for basic, machine-level speed control applications like fans, pumps, and conveyors.	
6617	Divider of Tray 2002- Panel fans; This lot contains panel cooling fans, there are (3) different sizes. These fans are used to mount on electrical panels to move air through the electrical panel to ensure no heat build up from internal components and keep an ambient air temperature within the panel. This prolongs life cycles of electrical devices.	
6618	Divider of Tray 2002- RTD probes; This lot contains (2) 100 OHM, 18", resistance temperatures detectors that are 120vac.	
6619	Divider of Tray 2002 - Allen Bradley Controller, Hoffman Heater Controller, AB Compact I/O, etc.; Contents: -(2) Allen Bradley MicroLogix 1000 Programmable Controllers -Hoffman 800W Heater Controller -(2) Allen Bradley Compact 16pt. I/O Unit	
6620	Divider of Tray 2003- booster welder and booster welder cables ; This lot contains assembly welding components such as booster welders for metal and plastic and booster welder cables. The "Booster Gold 500" is not a model of arc or MIG welder, but rather a specific ultrasonic welding booster (part number 101-149-052) manufactured by Branson Ultrasonics (now part of Emerson). This component is used as an accessory in industrial ultrasonic welding machines, not traditional metal inert gas (MIG) or arc welders. It acts as an amplitude booster, modifying the amplitude of the ultrasonic vibrations transmitted from the converter to the welding horn to ensure a proper weld for plastics and other materials. Quantity (3) As mentioned above there are also (2) silver models and (2) 2000 series models. All used for ultrasonic assembly welding for different material and thicknesses. Connection and power cables for these welders are included. Quantity (5)	
6621	Divider of Tray 2003- Booster welder anodes, horn, converter and shells; This lot contains assembly welding components such as - (3) welder shells used to protect the welder tool. - (5) rev4 boosters - (5) anodes for welders. - (6) cathodes for welders. - (1) 6-pin converter - (1) welding horn.	
6622	Divider of Tray 2003- Parts counter, plc analog card and welding horns; This lot contains assembly welding components such as - Branson welding horns for anode and cathode applications. Quantity (9) - Mitsubishi PLC analog card, model: Q68DAIN. Quantity (1) - Mitsubishi part counter. Model: QD62. Quantity (2)	
6623	Divider of Tray 2003- welder converter, welder sensor switch's and air regulators for welding components ; This lot contains assembly welding components such as - (2) Brandon metal assembly welders. Model: 932R CE. - (2) sensor switch's for welders. - (1) air regulator. model: R734	
6624	Divider of Tray 2003- metal diaphragms, aluminum male plugs, air cylinder, air manifold ; This lot contains miscellaneous assembly parts such as - (1) Branson air cylinder model: 100-034-055 REV. 08 - (1) MAC valve air manifold. 24vdc, model: PME-501BAAA - assortment of many sized aluminum male plugs for airlines. - aluminum diaphragms for pump rebuild kits.	

6625	Divider of Tray 2003 - Power Supplies, Sensor Bumpers, PC Board, Power Kit, etc.; Contents: -(3) Vapel Switching Power Supply Kits -(2) Switch Bumpers -Branson 2000 Series IW Welder Power Module Replacement Kit -Branson PC Board Assembly	
6626	Divider of Tray 2004- filter cartridges, flow switch and pneumatic air cylinder ; This lot contains water flow components such as - (1) CKD SCM Series round-shaped pneumatic air cylinder with specific dimensions, not just a sensor. The cylinder has a magnet in its piston, allowing for the addition of a separate sensor switch to detect its position. - (1) Burkert flow switch. Model: 438087 - (6) 10" water filters, ptfe. - (4) 10" water filters. Brand: PALL. Model: DFN50-10UV	
6627	Divider of Tray 2004 - Labo Pure Filter Capsules; Contents: -Appx. (50) Labo-Pure LPA-HC-100-N3 Filter Capsules	
6628	Divider of Tray 2004 - Hioki Tip Pins, Clip Type Leads, Oven Door O-Rings; Contents: -(5) Hioki 9770-90 Tip Pins -(5) Hioki L2107 Clip Type Leads -(2) Rolls Zatkoff RZ513 Oven Door O-Rings	
6629	Divider of Tray 2004 - Allen Bradley AC Drives, Resin Spacers; Contents: -(2) Allen Bradley PowerFlex 400 480V AC Drives -(106) Misumi Resin 10mm Spacer/Washers	
6630	Divider of Tray 2005- wire cat-track; This lot contain approximately 54' of CPS cat-track used for protecting wire or cables on moving equipment. This cat-track is 2" wide, there are (27) sections of 2' spans. This lot comes with replacement parts.	
6631	Divider of Tray 2005 - Assorted CAT Tracks, Glove Box Seal Bladders; Contents: -(6) Hanshin 3' (4"W) Cable Tracks -Appx. (10) Hanshin 3' (2"W) Cable Tracks -Appx. (126) CPS Cable Track Ext. Assemblies -(1) 1M (2"W) CPS Cable Track -Assorted Sealing Bladders for Glove Boxes	
6632	Divider of Tray 2006- stainless push to connect air fittings, air cylinders, harmonic drives, pump seal kits; This lot contains a variety of air cylinders and harmonic drive components such as -SMC air cylinders. There are many sizes (see pictures) - (2) harmonic drives from HD Systems - (11) seal kits for vacuum pumps.	
6633	Divider of Tray 2006- Air cylinders, rotary actuators and rotary clamp cylinders; This lot contain a variety of assembly equipment such as - (2) locking air cylinders with two posts. -(6) SMC rotary clam cylinders - (3) rotary actuators.	
6634	Divider of Tray 2006 - Misc. Air Fittings, Sensors, Bulbs, Connectors, etc.; Contents: -Connector Pins -Optical Sensors - Puncher Sensors -Rolling Assemblies -Shock Absorbers -Photo Micro Sensors -Vacuum Oven Connectors -Plunger Balls - Relay Sockets -Air Chucks and Cylinder -Linear Bushings -Cosel PBA75G Power Supply -Couplings -MR16 Halogen Bulbs - Thickness Sensors -Heat Sensors -Regulator Assembly -Assorted Air Fittings [Flow Controls, Elbows, Reducers, etc.	
6635	Divider of Tray 2007 - Guide cylinders, air cylinders, vacuum pumps, vacuum filters, air valve solenoids and conveyor switches ; This lot contains a variety of assembly equipment parts including - Guide cylinders and grippers, these are used for any type of end of arm robot tooling. - vacuum pump solenoids made by Solvac (4) also includes (13) replacement filters. - 24vdc solenoid valves made by SMC (20) - assembly conveyor start/stop cycle switch's.	
6636	Divider of Tray 2007 - Cylinders, air filters,vacuum pump, pallet stoppers; This lot contains a variety of assembly equipment parts including - variety of air cylinders, many sizes for most assembly applications. Approximately (20) - filters for vacuum pumps (20) - (1) vacuum pump.	
6637	Divider of Tray 2007 - SolVac Vacuum Pumps, SMC Solenoids, Vacuum Ejector, etc.; Contents: - (3) SolVac VMP20 Vacuum Pumps -Hydraulic Cylinder Cap, Seal, and Rebuild Kits -(8) JA63 SMC Float Joints -(7) SMC VAC Generator Solenoid Modules - Misc. SMC Pressure Switches -SMC ZM131H Vacuum Ejector -Misc. SMC Fittings -(9) SMC CDQ2B40 Compact Cylinders	
6638	Divider of Tray 2008- aluminum robot welding horns, solid state proximity switches, copper anvil for robotic welding, spanner wrench's; This lot contains a variety of robotic welding assembly equipment parts Including - (8) Branson spanner wrenches. - approximately (10) solid state proximity sensors. - (5) aluminum horns for robotic welding. - (3) aluminum anvil cantilevers. - (1) copper anvil - (4) copper horns.	
6639	Divider of Tray 2008 - Contrinex Light Curtain, Capacitance Sensors, SMC Cylinders, etc.; Contents: -Contrinex Safetinex 3' Light Curtain and Mounting Brackets -Told Light Curtain Relay Module -(2) Yamamoto YAE-13G Capacitance Level Sensors -(5) SMC CDA2F50 Cylinders -Sine Rodless Cylinder -SMC CDA2L63-500 Cylinder -Allied Maxhinery ATM 1500 Tapered Chuck -(2) Puncher Unwinder Chucks -Box of Copper Anvil Welding Cantilevers -Welding Horn -Assoerted Sensor Cabling	
6640	Divider of Tray 2009- strip covers, heating bands, pressure gauges, vacuum pump filters, air filter housings, gearbox reducers, locating pins and pallet locating pins; This Divider of Tray 2008 lot contains a variety of Assembly parts including - heat seal strip covers. Approximately (20) rolls at 40'. These are used to prevent melted plastic material from sticking to the heat seal band during the sealing process. - heat seal bands. Approximately (440) bands. These are used to join thermoplastic films and materials. - vacuum pump air filters and housings. Used in many air delivering systems. - motovario gearbox reducers. (2) - locating pins of different sizes. These pins are used to stop pallets or parts in a precise location during assembly of product.	
6641	Divider of Tray 2009- Valve solenoids, locator pin bushings, cutters and single point load cells; This lot contains a variety of assembly parts and materials including - heat seal wire. (3) rolls of 500'. - cutting blades. Four edge. (5) - o-ring kits for valve solenoid rebuilds. - Mac valve air solenoids. Model- 44B-AAA-GDF0-1KJ - (4) 0-160 psi SMC pressure gauges. - (4) Rice Lake RL1521A Aluminum, Single Point Load Cells. Used for Safe Overload Output Resistance Input Resistance Full Scale Output Insulation Resistance Red +Signal. White -Signal. Cable Color Code.	
6642	Divider of Tray 2009 - Mitutoyo Linear Gauges, A&D Weighing Indicators, SMC 40 Bore Cylinders, etc.; -(3) Mitutoyo LGB-110 Linear Gauges -(2) A&D AD-4401A Weighing Indicators -(3) SMC CDS1FN140-KRD03 40 Bore Cylinders -Misumi Insulation Plate -(12) IKO TA5020Z Roller Bearings -Rebuild Seal Kits -(2) Mitsubishi Electric 16DC Block CC Links -(4) AB 100-C2EJ10 Contactors -Assorted Slot Dies, Blades -(2) RKC SA200 Temperature Monitor Relays -Pfeiffer Vacuum Sensor	

6643	Divider of Tray 2010- pump pistons and gearboxes; This lot contains mechanical parts for many applications. These parts include - Yuken model AR22-FR01C-22 is a variable displacement axial piston pump with a compact design and an aluminum body, utilizing high-strength steel pistons for performance and durability. Quantity- 5 - The Oriental Motor model BH6G2-25RH is a right-angle, hollow shaft gearhead from the BH Series, designed for use with Oriental Motor's 200 W (1/4 HP) AC motors. It provides a 25:1 gear ratio and is used to transmit power perpendicularly to the motor axis, which saves space in equipment design. Quantity- 3	
6644	Divider of Tray 2010- Electric motors, gearheads, domino printer maintenance kits, gear reducers and domino printer cables ; This lot contains mechanical parts for many applications. This lot includes - oriental 220vac electric motors. (2) these are speed control motors. - oriental gear heads. (3) model- 5GU36KB. - Domino printer maintenance kits including screws, filters and cables. The Domino Ax-Series is a line of continuous inkjet (CIJ) printers designed for high-speed, non-contact coding and marking in demanding industrial environments. *Printer not included*	
6645	Divider of Tray 2010 - Oriental Motor Gear Heads, Induction Motors, Domino Printer Tool Kit, etc.; Contents: -(8) Oriental Motors 5GU36KB Gear Heads -(5) Oriental Motors 5IK90GUSWM Induction Motors -Domino Tool Kit -Assorted Sensors and Assemblies for Printer Cell	
6646	Divider of Tray 2011- air cylinders, bearings, aluminum railing and a feel unit; This lot contains a variety of assembly equipment parts Including - air cylinders (8) with runner rails. All made of aluminum and used for many different applications. - shaft bearings in a variety of sizes including LMK linear bush bearings sized LMK 12 to LMF 40s.	
6647	Divider of Tray 2011- motor bearings.; This lot contains a variety of assembly equipment parts Including - motor bearings of many sizes and brands. To name a few; NSK, Koyo, SKF and SBC brands. To name a few sizes; 6005, 5650-0697, 6309, 697ZZ, and 6201. These bearing can be used for electric motor rebuilds or custom tasks.	
6648	Divider of Tray 2011 - SKF, NTN, Nachi Bearings, etc.; Contents: -(4) Nachi 7212CYDU/GL Bearings -(4) THK Ball Nut Screws - Assorted SKF Bearings (6203-6213) -Assorted NTN Bearings (1203-6210) -Other Misc. Bearings	
6649	Divider of Tray 2012- barcode readers, proximity sensors, alarms, relays, temp sensors, safety switches and network communication; This lot contains various high end electrical components including - Banner barcode readers. There are (4), model- IVUTBNR16. These Sensors in this family are typically used to read 1D and 2D barcodes (such as QR codes, DataMatrix, and standard UPCs), even if they are damaged or distorted - Keyence DL-CL1, a CC-Link network communication unit used to integrate industrial sensors into a network. There are (8) in this lot. - temperature sensors by servicefirst. There are (5) total. The sensor monitors temperatures within commercial Heating, Ventilation, and Air Conditioning (HVAC) and refrigeration systems to help regulate conditions and ensure efficient operation. - Banner proc sensor. Model- S18RW3D. EZ-BEAM Technology: Designed for reliable sensing without the need for manual adjustments, featuring specially designed optics and electronics. - Banner safety interlock. Model- SI-LS42DSI. These are designed to lock machine guards and gates, ensuring hazardous motion has stopped before access is granted. - 3-phase monitor relays. Made by Macromatic. Model- PMPU. 190-500vac. Approximately (8) in this lot. - there are (4) audible 12-24vdc horns made by Kacon. Model- KSP-42S.	
6650	Divider of Tray 2012 - Maxcess DST-1 Sensor, Banner Barcode Readers, Misc. Sensors; Contents: -Maxcess DST-1 Sensor and O/I Assembly for Opertaor Interface -(8) Balluff BGL 30A Sensors -(2) Mitsubishi Electric 16PT CC Master Links -(2) Mitsubishi Electric 16PT Digital Module -(3) IFM I/O Link Sensors -(11) IFM E20752 Fiber Optic Through Beam Sensors -IFM E20633 Fiber Optic Cable -(2) IFM GF711S Inductive Sensors -(2) Mitsubishi Electric QJ71C24N Serial Communication Modules - Mitsubishi Electric Fiber Links -Misc. Fiber Optic Sensors -(4) Banner barcode readers. There are (4), model- IVUTBNR16. These Sensors in this family are typically used to read 1D and 2D barcodes (such as QR codes, DataMatrix, and standard UPCs), even if they are damaged or distorted	
6651	Divider of Tray 2012 - Fife D-Max Controller, Relays, Connectors, Sensors, etc. ; Contents: -Maxcess Fife D-Max 1 Controller -(2) Mercotac 830 Switch Connectors -Omron Relay Socket -Assorted IFM Cable Connectors -Misc. Photoelectric. Sensors	
6652	Divider of Tray 2013- gear boxes, gear box reducers and equipment vibration springs; This lot contains parts such as - Equipment vibration spring made by the VMC Group. There are (6) springs total. - Oriental brand gear head. There are (5) of them in this lot, model- H6G2-50RH. This model is a right-angle, hollow shaft gearhead from their BH Series and is typically paired with a 200W AC motor. - The PBL120-H-16 is a high-precision planetary gear reducer manufactured by companies such as ATG (Automatic Transmission Group) and used for servo motor applications.	
6653	Divider of Tray 2013- Shaft Seal Elements, Tension Idler, Screws, Drive Trains; Contents: MegTec Seal Shaft Elements, Screws, Bolts, Silicone, Drive Chains	
6654	Divider of Tray 2013- Bearings etc. ; (4) Dodge Bearing Model: 0093087309, (4) Dodge Bearing Model: 0093087310, Johnson Controls Field Equipment Controller FEC2611	
6655	Divider of Tray 2013 - Baldor Dodge Bearings, IOM I/O Modules; Contents: -(2) Johnson Controls IOM3731 Metasys I/O Modules -(4) Baldor Dodge 2.688 Pillow Block Bearings	
6656	Divider of Tray 2014 - Equipment door seals, bearing caps, equipment vibration springs and s.s shaft; Contents: (6) Equipment Vibration Springs, (6) Teflon/Glass Cloth Equipment Door Seals - bearing seals/caps. These are used to close or encase bearing for protection.	
6657	Divider of Tray 2014 - SKF and Asahi Pillow Block Bearings; -(4) SKF 0093087307 Pillow Block Bearings -(2) Asahi 0093087311 Pillow Block Bearings	
6658	Divider of Tray 2015 - Zatkoff Oven Rings, Bellows Valves, Bellows Kit, Replacement Seal Kit, Dispensing Valves, Amplifiers, Pressure Transducers; Contents- Zatkoff Oven Rings, Sawgelok Open Air/Nitro Bellows Kit, Gasket Kits, Keyance Amplifier Units, Dell Head Printers	
6659	Divider of Tray 2015- Keyence electronics ; (2) Keyence CZ-H32, Keyence LV-N11CN, Keyence GT2-H12L, Keyence GV-21, (4) Keyence IL-SO25	

6660	Divider of Tray 2015- Keyence electronics ; This lot contains a variety of Keyence electronic components such as - The Keyence OP-87056 is a 2-meter sensor head cable used to connect various laser and vision sensor heads to their respective amplifiers in industrial automation systems. - The Keyence FU-50 is a thru-beam type fiber optic sensor head designed for precision object detection in industrial automation. - The Keyence IL-100 is a high-precision, compact CMOS analog laser displacement sensor head used in industrial automation for non-contact measurement of position, thickness, and vibration. - The Keyence DL-CL1 is a CC-Link network communication unit that integrates laser, digital contact, and digital flow sensor amplifiers into an industrial automation network, significantly reducing wiring and enabling remote operation and monitoring. - The Keyence LR-W500 is a self-contained, full-spectrum photoelectric sensor designed for reliable appearance and color detection in industrial automation. - The Keyence LR-ZH490CB is a self-contained, M18 threaded mount CMOS laser sensor with a long detection range, designed for industrial automation applications requiring accurate distance-based object detection.	
6661	Divider of Tray 2015 - Keyence Sensor Cables, Receivers, Sensors, Switches, etc.; Contents: -(3) Keyence OP-87058 Sensor Cables -(4) Keyence OP-87637 4 Pin Cables -(4) GS7A Safety Relays -Sensing Tube Kit -Johnson Controls Receiver -(2) Gems FS-200 Shuttle Flow Switches -(2) Omron ZX2-LD50L Smart Sensors -Misc. Pressure Sensors	
6662	Divider Tray of 2016- Motor Servo, 90 Degree Gearbox, AC Servo Amplifier, CC Block Repeater Hub ; Contents- Mitsubishi Motor Servo HF-SP352BK, Apex Dynamics 90 Degree Gearbox, Mitsubishi Melservo J4 AC Servo Amplifier, Cameron Sino CS-PLC267SL Batteries	
6663	Divider of Tray 2016- Mitsubishi electronic components ; (4) Mitsubishi QD62, (3) Mitsubishi Q64DAN, (2) Mitsubishi QJ71C24N-R2,	
6664	Divider of Tray 2016- Mitsubishi electronic components ; (2) Mitsubishi AC Servo Amplifier Model: MR-J4-200B4-RJ, (1) Mitsubishi AC Servo Amplifier model: MR-J3-200TN, (1) Mitsubishi Amplifier Servo Drive MR-J3-40A (3) Mitsubishi MR-J3-20B, (10) Mitsubishi Programmable Controller Model: A6TBXY36	
6665	Divider of Tray 2016- Mitsubishi electronic components ; This lot contains Mitsubishi electronic components such as - The Mitsubishi AJ65SBTB1 is the base model number for a series of CC-Link digital remote I/O modules within the MELSEC-A range. These modules connect input (sensors) and output (actuators) devices to a PLC network via fieldbus communication. There are (15) in this lot. - The Mitsubishi Q173DCPU is a high-performance Motion Controller CPU module from the MELSEC-Q Series designed for precise, multi-axis control of servo systems via the SSCNET III network. (1) in this lot. - The Mitsubishi QD62D is a high-speed counter module from the MELSEC-Q Series PLC, used for precisely counting high-frequency pulse signals from encoders and other sensors in industrial automation. (3) in this lot. - pressure transducer. Brand: setra systems. Ideal for monitoring pumps, load differential pressures in HVAC systems, flow measurement, and liquid level measurement in pressurized vessels.	
6666	Divider of Tray 2016- Mitsubishi electronic components ; This lot contains Mitsubishi electronic components such as - The Mitsubishi Q06UDEHCPU is a universal Programmable Logic Controller (PLC) CPU module from the MELSEC-Q Series, designed for high-speed industrial automation systems. - The EIP4CCPU Scanner Configuration Utility is a PC-based tool used to set up the network parameters and discover devices regardless of their subnet. - The Mitsubishi FR-A8TR is a screw terminal block option used to provide physical wiring terminals for the control circuits of the Mitsubishi Electric FR-A800 and FR-F800 series inverters. - The Mitsubishi AJ65SBT-62DA is a MELSEC-A series analog output module with two channels, used as a remote device station in a CC-Link network for industrial automation. - The Mitsubishi R65B is a 5-slot extension base unit (backplane/rack) for the MELSEC iQ-R series PLC systems. It is used to expand the system's capacity by providing additional slots for I/O and intelligent function modules.	
6667	Divider Tray of 2017- 15 Meter Brake Cables, Manual Motor Starter, Air Motor, Rotary Encoder; Contents- Mitsubishi 15 Meter Brake Cables, Autonics Rotary Encoder, LS AGV Manual Motor Starter, SPC Tech Air Motor	
6668	Divider of Tray 2017- encoder cables, forming die(s); This lot contains an assortment of encoder cables and cell dies such as - 20 meter, 12-wire encoder cables. There are (4) of these. - (9) encoder cables approximately 10' in length with connectors on each. - assembly dies and cutters that can be used for a number of applications.	
6669	Divider of Tray 2018- Mitsubishi ; (4) Mitsubishi Q63P, Mitsubishi Advanced Inverter FR-A820-2.2k-I-26, (2) Mitsubishi Tension Detector LX-050TD	
6670	Divider of Tray 2018- aluminum couplings; This lot contains a variety of aluminum coupling in many sizes. These couplings are components of a jaw-type flexible coupling manufactured by Sung-II Machinery (SIM), specifically within their SJC series. Sizes range from 35C to 80C. These couplings are designed for high precision applications where zero backlash is required.	
6671	Divider Tray of 2018- Punch Shoulders, Heater Elements, Degassing Heat Sensors, Pin Probes, Silicone Rubber Sheets, Heater Cartridge, Chamfer Tools, ; Contents- Misumi Heat Sensors, Misumi Punch Shoulder, Heater Element, Accupro Chamfer Tools,	
6672	Divider Tray of 2019-; Assorted Ev Components, Electronics, etc.	
6673	Divider Tray of 2019- Cylinder Protech, Circuit Protector, Resistors, Inverter Parts, Converter, Heatsink; Contents- Mitsubishi Terminal Block, P&M Cylinder Protech, Mitsubishi Drive, Mitsubishi Resistor, P&M Circuits	
6674	Divider Tray of 2020; (4) Jamagawa Servomotors model: Z90-3752-50, (2) GTR Geared Motor model: G3F18N020-UTB020NN and (2) Huminty Transmitter 120v AC	
6675	Divider Tray of 2021; Mitsubishi Programmable Controller FX2N-16EX-ES/UL, FX3U-2HC, FX3U-16MR/DS, Q68ADI, Susol Magnetic Contactor part no. MC-95, MC-75, Advantech Converter model: EKI-1521	

6676	Divider tray 2021- humidity transmitter, RTD probes, air locks, auto door controllers and actuator valve; This lot contains an assortment of industrial components such as - Resistance temperature detectors, various sizes. Used in a number of liquids and chemicals. (11) RTd probes. Lengths are various with a minimum of 16" and a maximum of 3'. - Actuator valves. Made by KITZ. Size, 3/4". - Air bolt locks. (2) in total. These can be used in a number of applications requiring locking of doors or mechanisms for safety. - Automatic door controllers. (3) in total. These are used for soft close applications in an automation scene.	
6677	Divider Tray of 2022 - Damper Motors; (9) Honeywell MS7520A207007 Damper Motors	
6678	Divider tray 2022- chain and seals; This lot contains (2) items for industrial applications such as - (1) chain, approximately 50' in length. Part # RS-60 2L-K. - V-zone viton seal sheet. There are (2) sheets at 1.2M x 5'.	
6679	Divider Tray of 2022; GTR 3-Phase Induction Motor Model: G3LM-32-450-T020WX	
6680	Divider Tray of 2023 - GTR 400 Watt Motors ; (4) GTR 3-Phase G3L28N100-UTM040WAX, 4P Ratio 100:1 Induction Motor; 380V 60Hz 1680 rpm	
6681	Divider Tray of 2023; (6) Orientalmotor Motor model: 51K90A-CW2E	
6682	Divider tray 2023- electric motors; This lot contains (4) 3-phase electric motors. Brand: GTR HP: 3 The GTR G3LM motor is a series of three-phase industrial induction gearmotors manufactured by Nissei Corp. GTR. These motors are used for various power transmission applications due to their durability and wide range of available power ratings and reduction ratios.	
6683	Divider tray 2024- ; (5) GTR 3 Phase Induction Motor Model: FS30N080-UTM020WAX	
6684	Divider Tray of 2024- electric motor and assortment of relays; This lot contains (1) electric motor and an assortment of relays, details are as follows - The GTR F3SB motor is a series of three-phase or single-phase industrial induction gearmotors manufactured by Nissei Corp. GTR. These are part of the F3 Series of gearmotors which feature a concentric solid or hollow shaft and are known for their high efficiency, low noise, and durable hypoid/helical gearing. - relays ac200-230v. These are brake relays.	
6685	Divider tray 2025; Lot Of Assorted Yukon Valves Model: DSG-03-3C4-A120-50, DSG-01-2D2-D24-70, THK ball screws, and Kluber Lubrication	
6686	Divider Tray of 2025 - Keyence Scanner; (2) Keyence SZ-01S Scanners Roll Press; 24VDC, 9.5W	
6687	Divider Tray of 2025- power supplies, motor starters, air flow switch, eye wash station pump, lubricants, phoenix plugs and more; This lot contains an assortment of electronic devices and other mechanical parts such as - (9) 4oz bottles of lubricant. Brand- superlube. -phoenix contact plugs, female. Part# subcon 15/F-SH - air regulators. There are (5). Brand- SMC Model- IR2000-02BG - electric eye wash station pump. This can be used to pump away used water from an eyewash station with no drain nearby. - Airflow switches. From Cleveland controls. Model- AFS-460 -(2) Motor contactors from MEC. Model- MMS-100H 80-100 amp. - Mean-Well power supplies. Model- ESC-240-27	
6688	Divider Tray of 26 - Index Motors, Data Cables, Circuit Boards; (2) GTR F3S25N40-MM02TNNTN 3-Phase Index Motor, Banner XS26- 2DE Safety Controller. (6) Schneck Circuit Board V139130-B02, (5) Solenoid VQC2100N, (4) Breaker Control Design 10A, Asst'd Data Cable, Sanko Motor Shaft Keys	
6689	Divider tray 2026; Dodge Bushing TT Reduducer, Power Supply, Computer on logic, Servo Motor,	
6690	Divider tray 2026- Keyence electronics; This lot contain various Keyence electronics such as - The Keyence CL-L030 is a quad-type, 30mm confocal displacement sensor head belonging to the CL-3000 series of industrial measurement sensors. (2) of these in this lot. - The Keyence CL-3050 is a confocal displacement sensor controller that functions as the main processing unit for the CL-3000 series sensor heads. (1) in this lot. - The Keyence GV-21 is the main amplifier unit for the GV series of laser sensors, providing the processing and I/O capabilities for a connected sensor head. (6) of these in the lot. - The Keyence LV-H32 is a reflective spot type laser sensor head that is typically paired with an amplifier unit (like the LV-21AP or LV-11SA) to perform detection tasks, including edge detection. there are (2) in this lot. - The Keyence CL-C10 is a 10-meter (32.8 ft) extension cable for connecting a sensor head to a controller unit within the Keyence CL-3000 series of confocal displacement sensors.	
6691	Divider tray 2027- Yaskawa Motors; (2) Yaskawa Servo Motor Model: SGMGV-30ADC61, (2) Yaskawa Servo Motor model: SGMGV-09ADA21, (2) Yaskawa Servo Motor Model: SGMGV-13ADA21, (2) Yaskawa Servo Motor Model: SGMGV-09ADA21, (3) Yaskawa AC Servo Motor Model: SGMVAV-08ADA21 and (2) Yaskawa Ac Servo Motor Model: SGMVAV-02ADA21	
6692	Divider tray 2027- assortment of mixing equipment ; This lot contains an assortment of mixing parts such as - rubber loading hoppers - (4) mixing shafts of different diameters. - polypropylene rollers These parts are used for a variety of projects and applications.	
6693	Divider tray 2028- assortment of air cylinders ; This lot contains an assortment of air cylinders in different sizes. Brand- SMC Many model numbers including - 125 NZ - 600L6Z - M9B - 100Z - MMGGMB32-350 - MGGMB40-100 And many more.	
6694	Divider Tray of 29 - Roller Chains ; (17) DBC DBC2060VRP Roller Chains, 80L	
6695	Divider tray 2029- assortment of air cylinders ; This lot contains approximately (20) air cylinders. Brand- SMC Model- NCMB125-0500 The SMC NCMB125-0500 is a double-acting, single-rod, round body air cylinder with a 1 1/4 inch (1.25") bore and a 5 inch stroke. It is a standard, non-repairable, stainless steel cylinder in the NCM series designed for general industrial use.	

6696	Divider tray 2029; Lot Of Assorted Formation Conveyor Chain	
6697	Divider tray 2030- electric motors; This lot contain (2) electric 3-phase motors. (1) model- G3L28N020 (1) model- G3L28N20 These motors are featuring a parallel shaft gearhead and a 20:1 gear ratio. The full model number often includes suffixes indicating specific motor capacity, voltage, and other features like brakes or terminal boxes.	
6698	Divider tray 2031- Industrial chains; This lot contains industrial chains and roller links there are (10) boxes ranging in different sizes from 2'- 5'. Also there are (2) Marley mechanical vibration switches. Model- M5-111-010	
6699	Divider Tray of 32 - Ac Servo Motors ; (6) Mistubishi HG-KR13 AC Servo Motor, (3) Mistubishi HG-KR053, (6) Mistubishi HG-KR13B, (2) HG-KR23, (1) HF-KP23, (4) HG-KR43, (6) HG-KR43B, (2) HF-KP43B, (4) HG-KR43K, and (1) AllenBradley B4560F Servo Motor	
6700	Divider tray 2032- Mitsubishi Compact Size Inverters; (6) Mitsubishi Compact Size Inverter Model: FR-E740-040SC-NA, (2) Mitsubishi Compact Size Inverter Model: FR-E740-026SC-NA, (1) Mitsubishi Compact Size Inverter Model: FR-E740-0.4K, (1) Mitsubishi Compact Size Inverter model: FR-E740-016SC-NA And (5) Mitsubishi Electric Repair Kit Model: FR-A7NC-E Kit-SC-E	
6701	Divider tray 2032- electric motors, pneumatic vibrators, exhaust transmitters and motor couplers; This lot contains a variety of motors and other industrial components such as - (2) Oriental motors, 3-phase 240vac. Model- 5IK90GU - (8) other KII /KIIS Series and the BMU/BLE2 Series. These motors are designed for various industrial applications requiring compact, high-power, and efficient performance. - pneumatic vibrators from Vibco. Model- VS-190 MCD - (9) exhaust transmitters from KIMO. Model-CP100. This is a series of pressure and differential pressure transmitters designed for measuring air or neutral gas pressure, commonly used in HVAC systems, clean rooms, and industrial exhaust applications.	
6702	Divider tray 2033- robot unloader; This lot has (1) robot unloader. a linear motion actuator or module manufactured by Samick THK, which is used as a component within a robot unloader system.	
6703	Divider tray 2034- ; Lot Of Assorted Belts	
6704	Divider tray 2035- assortment of weather stripping , brush rollers; This lot contains an assortment of supplies such as - (3) brush rollers. There are many different applications for it to be used. Soft bristle. - (1) strand of weather stripping used for doors. Approximately 12' of material. - stainless steel shafts and plates.	
6705	Divider tray 2035- Roller; Idler Roller	
6706	Divider tray 2036- ; Lot of Assorted Chiller Repair kit O rings, Belts, Metrix Vibrations Switch, Armstrong Chiller Pump, Chillers	
6707	Divider tray 2037; Lot of Assorted Fluoropolymer Tubing And Belts	
6708	Divider tray 2038; (10) Orientalmotor Motor Induction Model: BHI62E-A FFU 1 Phase	
6709	Divider Tray of 38 - OrientalMotors ; (5) OrientalMotor BH162S-G2 200 Watt Induction Motor; 1250 RPM, 240V 3-Phase AC	
6710	Divider Tray of 2038- exhaust fans, belts and fan motors; This lot contains exhaust fans and parts such as - (3) The K2S165-AA77-15 is an AC centrifugal fan manufactured by ebm-papst that is frequently used as a component within Rittal cabinet cooling systems. 120vac, 2650 rpm. - (4) Gates 3L380 SF V belts. - fan motors and blades for replacement parts.	
6711	Divider tray 2039- current amp cards; Current amplifier boards. Approximately (300) cards.	
6712	Divider Tray - Bearings, Linear Rail, Cylinders and Hardware ; Contents: THK Rail linear Guides, LM Guides Cell, Bearing Linear NSK, NSK Bearings, Rotary Gearbox Mounts, Filter Silencer, SMC CDM2620 Cylinders, SMC MX012 ASSY, Asst'd Belts, Panasonic DH58911K1 Trolley Collector Arm	
6713	Divider tray 2040- ; Orientalmotor Gearbox Model: 5GU50RH, Orientalmotor Reducer Model: 5GU25RH, Orientalmotor Linear Head Model: 4LF20N-5, (4) Liming Reducers, Omron Camera Model: FH-SM02, Keyence Sensor Fibet Optic Model: FU-35FA	
6714	Divider tray 2041- Cylinders and cylinder rebuild kits ; This lot contains cylinders and actuator components for assembly cells including; - Samick smart actuators (3) model- SAD09-N-H-100-D-110281 - small rebuild kits for cylinders including o-rings for rodless cylinders.	
6715	Divider tray 2042- Cylinder Hydraulic ; (7) KYC Hydraulic Cylinders, (3) Digital Frequency Controller DF05C And Seal Kits	
6716	Divider tray 2042- gas detectors, Mitsubishi clutch brake and SMC rod less cylinders ; This lot contains an assortment of industrial components such as - SMC rod less cylinders used for industrial automation applications that require long linear motion in confined spaces. - Mitsubishi clutch brake. Model- zkb The Mitsubishi ZKB is a series of magnetic powder brakes used for industrial tension control and general braking applications, known for their precise control and smooth operation.	
6717	Divider tray 2043- Mitsubishi Servo Motor; Mitsubishi Electric AC Servo Motor Model: HF-SP352BK	
6718	Divider tray 2043- air cylinders and slides; This lot contains a variety of SMC air cylinders and slides including - these SMC are industrial automation applications that require long linear motion in confined spaces. They are valued for their compact design, stability, and ability to move heavy or offset loads without the bending or buckling issues associated with traditional piston rods.	

6719	Divider tray 2044- Conveyor Rollers; Lot of Assorted Aluminum and Urethane Conveyor Rollers	
6720	Divider tray 2045- air cylinders and slides; This lot contains a variety of SMC air cylinders and slides including - these SMC are industrial automation applications that require long linear motion in confined spaces. They are valued for their compact design, stability, and ability to move heavy or offset loads without the bending or buckling issues associated with traditional piston rods.	
6721	Divider tray 2046- Assorted Stacker Repair parts; Bearings, Rails, Bushings,Support Units, Pullys	
6722	Divider tray 2046- SMC guided cylinders; This lot contains (5) SMC MXW12-125 is a pneumatic, double-acting, long-stroke precision slide table (guided cylinder) from the SMC MXW series, designed for industrial automation applications that require stable and precise linear movement of loads.	
6723	Divider Tray of 47 - T5 Shaft and Belts ; Contents: Asst'd T5 Belt(267Wx1610L), T5 (267Wx900L), T5 Belt (150x1400mm), T5 IBS19 1202 & 3003 Shafts, MGP20 Kit Seal Repair	
6724	Divider tray 2047- open crankcase ventilation clips; This small retainer clip secures the OCV filter shaft within the OCV assembly during maintenance. It is a critical, though small, component that is part of the regular OCV filter service procedure on these engines. There are (16) boxes of approximately (25) clips.	
6725	Divider Tray 2048- SMC brand slides, cylinders, stops, and shafts; This lot contains a variety of SMC components such as - air cylinders, many models from mxs8-10p to cdg1bn40. These cylinders are both rod and rod less. They are used for industrial automation applications that require long linear motion in confined spaces.	
6726	Divider tray 2048 SMC; (3) SMC Regulators Model: ITV2030-312N, (2) SMC Regulator Model: ITV2030-312CL, SMC Cylinder Model: MXQ16-30P	
6727	Divider Tray of 49 - Stacker Plates and Parts; Contents: Cutting Blade, Photo Sensor E3NX, Tensioner Mounting Plate, Gripper Finger, Plate Top, Transfer Hand, Rivet Pickup Detail, Seal Bar Upper, Vacuum Unit Plate, Glue Nozzels	
6728	Divider Tray 2049- SMC brand cylinders, shafts and inverters; This lot contains a variety of assembly machine electronic components and Samick linear parts such as - (1) Mitsubishi MELSERVO-J4 is a high-performance series of AC servo amplifiers and compatible servo motors used for sophisticated industrial automation and motion control applications. - (3) The Mitsubishi FR-E720-0.1K is a compact variable frequency drive (VFD) or inverter from the FREQROL-E700 series, used for precise speed control of small industrial motors. - aluminum shafts and cylinder support shafts. - (2) The Samick THK SR15WUU C1 is a specific configuration of a linear motion (LM) guide block used in industrial machinery to provide smooth, high-precision linear movement.	
6729	Divider tray 2049- Banseok ; (2) Banseok Dispenser, (2) Banseok Percision Valve Model: BV-325	
6730	Divider Tray of 50 - automation welding and electronic equipment ; This lot contains a variety of electronic and automation welding components such as - stop start sensors for conveyors. These sensors will see product and stop conveyor to reduce manpower and quality defects. Brand- Banner. Model- qs18vp6lpq8 Quantity- 2 - Welding shells, and blocks for end of arm. - stack cylinders (2). Brand- Enerpac Model- RW53	
6731	Divider tray 2050; (4) Banner EZ- Screen LP, Converter Weld, Booster Pack Tab Weld, And Collet Chuck	
6732	Divider tray 2051- Pisco; This lot contains all PISCO vacuum products including fittings, valves, tubing, and vacuum components. Their products are known for their innovation, high quality, and extensive range of applications. - also included in this lot is Parker air regulator. Model- MCD	
6733	Divider tray 2051- Ribbed belts, strand of belt stock and cutting guide; This lot contains equipment belts from Dayton and belt stock and a cutting guide/tool for making custom sized belts.	
6734	Pallet Racking; 6 Section Of Pallet racking 190" x 48" W/ (32) Pallet Trays 48" x 48	
6735	Pallet Racking; 2 Section Of Pallet racking 190" x 48" W/ (11) Pallet Trays 48" x 48. (3) uprights.	
6800	Divider Tray of 1001- Thermocouple, Pressure Valves, Assorted Fixtures, Tapers, Cell Assembly Tooling, Cables, Serial Communication Unit; Contents- Photoelectric Sensors, Rittal Brackets, Pouching Roller Trim Blades, MagnaScale Measuring Device, Omron Invertor Switches, O-Rings, Mitsubishi Serial Communication Unit	
6801	Divider Tray of 1003 - Lot of Liberty Tacky Roll Mop Sheets; Contents- Liberty Industries Model#: 6-300R Tacky Roll Mop	
6802	Divider Tray of 1005- Weighing Indicators, Power Cables, Invertor, Manual Motor Starters, Servo Amplifiers, 1D/2D Code Reader, Cables, Directional Valves, Graphic Operational Terminal; Contents- Yuken Kogyo Directional Valve, Keyence Cables, Keyence 1D/2D Code Reader, A&D Weighing Indicator, Mitsubishi Graphic Operational Terminal, Mitsubishi AC Servo Amplifier, Mitsubishi Invertor	
6803	Divider of Tray 1005 - SMC Cylinder, 2" Cat Tack, Oriental Motor Gear Heads, etc.; Contents: -SMC MY1C25G-540L Guided Cylinder (115 Max. PSI) -SMC CDQ2B40-45DMZ Cylinder -SMC ITV2050 E/P Regulator -SMC AW40-04-B Filter Regulator - Dong TB6-5150D6DH Noise Filter -Misc. Strips of 2" Cat Tack -(8) Oriental Motors BH6G2-100RH Gear Heads -(15) Parker 20XR55 3/4" Bore Air Cylinders -(3) Masscool 80mm Cooling Fans -Hokuyo FBX-25JC Photoelectric Sensor -Misc. Bearings	
6804	Divider Tray of 1010- Lot of KleenGuard A20/A10 Breathable Particle Protection Coveralls (White) ; Contents- KleenGuard A20/A10 Breathable Particle Protection Coveralls (White)	

6805	Divider Tray of 1011- Linear Slide Kit Parts; Contents- Linear Slide Kit Parts	
6806	Divider Tray of 1012- Assorted Lot of Hand Straps, Barcode Scanners, Progloves, Transmitters, Charging Stations; Contents- Progloves Hand Straps, Gateway Transmitters, Progloves Charging Station, Mark Barcode Scanners, Proglove Index Triggers	
6808	Divider of Tray 1013 - Keyence Safety Laser Scanner, VPL Servo Motors, Power Clamp Cylinder, etc.; Contents: -Keyence SZ-VH1 Safety Laser Scanner Head -Telemecanique XCSLF3737313 Safety Interlock Switch -SMC CKZ2N80-90DP Power Clamp Cylinder -AB VPL-B1153E-PJ14AA Servo Motor -AB VPL-B0632F-PJ14AA Servo Motor -AB VPL-B0751M-PK12AA Servo Motor -Banner Q5XKLA2000-Q8 Laser Field Range -(2) Banner D10 Amplifiers -IFM Laser Distance Sensor -Keyence OP-88656 /88666 Power / Ethernet Cabling -Guide Rail	
6809	Divider Tray of 1014- Lot of Assorted Air Cylinders, Clamp Arms, Processed Wire, Rodless Cylinders; Content- SMC Compact Air Cylinders CDLQA63-75DM, SMC Double Act Air Cylinder CP96SDB63, SMC Rodless Cylinders, SMC Clamp Arm CKZ, Lutze Silflex TC-ER(C) 12/3C UL/TC-ER/CE/WTTC Gray Processed Wire Spools	
6810	Divider of Tray 1014 - SMC Guided Cylinders, Assorted Sensors, Assorted Cabling; Contents: -SMC MPGM50-25Z Guided Cylinder -SMC MPGS50-125 Guided Cylinder -SMC RSDQA50-30DZ Stopper Cylinder -SMC MPGM40-100Z Guided Cylinder - SMC MGPM25-300Z Guided Cylinder -SMC MGPN40-50Z Guided Cylinder -SMC MGPM25-25Z Guided Cylinder -Assorted SMC Double Acting Cylinders -(4) SMC MDLUB25 Plate Cylinders -Assorted Sensor Cabling -Assorted IFM Reflective Sensors	
6811	Divider Tray of 1015- (3) MicroVU Tempered 1/8" 11" x 14" Tempered Glass Sheets ; Contents- (3) MicroVU 1/8" 11" x 14" Tempered Glass Sheets, PushButton Vacuum Lifter Suction Cups	
6813	Divider of Tray 1016 - Mitsubishi Electric AC Servo Amplifier, CC Links, Rotary Joints, Rack and Pins, etc.; Contents: - Mitsubishi Electric MR-J4-10B-RJ AC Servo Amplifier -(2) Mitsubishi Electric CL1PAD1 CC Link / LT Modules -(4) Kamo Rack and Pin Zero Backlash Mechanical Devices (Misc. Sizes) -(3) Kokam AR3725-40A Rotary Union Joins -Tsubaki Roll Press Chain -(20) Kokam S670-0383 Circuit Protectors -Appx. (50) Assorted IDEC Control Units (S670-0392, S670-0391, S670-0390, S670-0387, S670-0389, S670-0388)	
6814	Divider Tray of 1017- Break Rectifiers, Photo Switch, Panasonic Industrial Devices, Ebmpapst Fans, Bluffs Read/Write Head, Sigma Lamp Halogen Bulbs, Etc. ; Contents- Schaltschrank Temp Regulator, Balluff Read/Write Head, Balluff Data Carrier, Formation Spring OCV Clips, Rhino Tool House Safety Clips, Kaltec Co. Ltd. S670-0224 Power Supply, Misumi Locking Nut, Kaltec 24018A Right Charge Interlok Sensor, IGUS Cable Carrier, Kokam Turn Shaft, (4) Balluff Read/Write Head w/ Processor, Sixnet Power Injector, (4) Mitsubishi Q25HCPU PLC Modules, (2) Kokam Z07-90351-00 Laser Scanner, Toyo Electronics 4 Bit Receiver Sensor, Fittings, Newark Resistors, Sixnet Ethernet Port, (3) Keyence USB Cable, (3) Rittal Fan /Filter Units, (2) IDEC HG1T-SB12UH-MK1373-L5 4-1 Crane Controllers, Mitsubishi FR-CV-7.5K PLC Unit, Assorted Custom Stands, (19) Emerson TL-350 Torque Limiters, Muratec Urethane AGV Tires, Muratec Circuit Boards, Assorted Bearings, Fittings, Muratec Z90 Crane Pendant, SMT750RM2U APC Unit, (3) Toyo SD115907 Magiceye Sensors, (9) Take Up UCTM 204 /5A Bearings, Wirtz S650-0643 Cylinder, Motion 4" Cable Carrier, (2) KM-J300 Turn Shafts, (3) Sigma Halogen Light Bulbs	
6815	Divider Tray of 1018- Assorted Fixture Plates/Parts for Cell Assembly; Contents- Assorted Fixture Plates, Freudenberg Wheel Shaft, (13) NCJ-207-RM Connectors, (4) River Peening Tool, (4) Cell Assembly Metal Brackets	
6816	Divider Tray of 1019- Connector 4 Wire Pico, Bandpass Filter Blue, Monochrome Camera, Fixed Focal Lens, Single Arm Swivel Links, Adapters, Etc. ; Contents- Barnum Swivel Link Arm Connectors, Cognex Monochrome Camera, (2) Midopt Bandpass Blue Filters, Assorted IFM Connector 4 Wire Pico, Edmund Optics Fixed Focal Lens, Swivelink AFSB-5 Adapter, Riken Keiki SD-2500 Furnace Gas Monitor, (8) Auto CFT Leveling Feet, Cognex IS9912M Monochrome Camera, Noga Magnetic Base, Cognex, Power I/O Cable, Cognex IVSL-5PM12-10 Cable, Turck M12 Cable	
6817	Divider Tray of 1020- RID/Stacker Taper - Pusher, Grip Cylinders, Power Locks, Magnetic Pieces, Bearings, Monitors, PC, Etc. ; Contents- Dell Optiplex 790 PC, Protec PH22-20 Grip Cylinder, Misumi Set Collar, (2) Misumi Power Locks, (5) Bearings, Misumi Magnetic Pieces, Protec PBM30N-75-A1 Air Cylinder, (2) Insignia NS-19D220NA16-A 19" TV Monitors, Metal Fixture Plates, Hamilton PSD4 Syringe Pump Drive Controller, (2) Wörner Separating Stops w/ Damping, (10) SMC SY7420-5DZ-C8 Air Solenoid Valves, (3) SMC MY1H20G-800L-A93L Guided Cylinders, Assorted Rebuild Kits, (3) Pora PR-DTC-2200RC Manual Tension Controllers, Assorted SBC, PEC Board, Pora PR-DTC-2200 Manual Tension Controller	
6818	Divider Tray of 1021- Liberty Industries #6-300 Tacky Roll Mop, Tough Guy 2-Ply Filter Bag Paper; Contents-Liberty Industries #6-300 Tacky Roll Mop Sheets, (5) Tough Guy 49AJ55 Filter Bag Paper 2 Ply	
6819	Divider Tray of 1023- Assorted Samick Smart Mechatronic Assembly Pieces, Plastic Clips/Assembly Pieces, Etc. ; Contents- Samick Smart Mechatronic SAD09RR-10-0100-AL-E42L-MA40BS-F5-29, Samick-THK Mechatro SAD12RU-XX-0300-AL Transfer Cell, (2) Samick Smart Mechatronic Robot SAD07RL-10-0800-AL, Samick SAD09RR-10-0100-AL-N-MA40, Samick Smart Mechatronic SAD09RR-10-0100-AL Tension Assorted Plastic Clips, Plastic Mechanical Fixtures, Gears, Assorted Cat Track - 3' 6"W CPS Cat Track, 4" Hashin Cat Track, Misc. Track Ends Mitsubishi Electric, 5L-1BD1W-1P-OGVM Melservo AC Servo	
6820	Divider Tray of 1024- Assorted Lot of Outdoor Equipment; Contents- (2) Uline S-23787/S-20399BL Camp Chairs, Simple Human Mini Can Trash Can, BlackStone 3 Seasonings Pack, Fieldsheer Mobile Warming Squall 2.0 Heated Gloves, Uline Tote Bag / Beach Towel, Uline Knit Hat Carhartt XALT Energy Lunch Box, Milwaukee M18 Jobsite Fan, Uline H-5221 Tabletop Patio Heater, (2) Uline S-23879 / S-23787 Rolling Coolers [Black/Lime and Mossy Oak], Bogg Beach Bag	
6821	Divider Tray of 1025- (4) Containers of Global Scientific 52JX76 Pipettes ; Contents- (4) Containers of Global Scientific 52JX76 Pipettes	
6822	Divider Tray of 1028- (7) TexWipe TX 1040 Polysat Packs of 200; Contents- (7) TexWipe TX 1040 Polysat Packs of 200	
6823	Lot of (2) MapleSystems 17" HMI Panels and (2) 24V Power Supply Maple Systems ; (2) MapleSystems 17" HMI Panels and (2) 24V Power Supply	

6824	Divider of Tray 1029 - Prominent Solenoid Metering Pump, Rotork Positioners, Auxiliary Power Boards, etc.; Contents: - Prominent Beta b BT4b Solenoid Metering Pump -(2) Rotork Electro-Pneumatic YT-1000LSaf135S0 Positioners -(10) Auxiliary Power Boards -(5) IFM Retro Reflective Photo Sensors Misc. Probes, Sensors, Pins	
6825	Divider Tray of 1031- Bearings Pillow Blocks, ISOFLEX Nbu 15 Grease, Spacer Flanges, Actuators, Sleeve Exhaust Fan ; Contents- (3) Honeywell MS4120F-1204 2 Poistion Direct Coupled Actuators, Dodge Bearings Pillow Blocks, ISOFLEX Nbu 15 Grease, TB Woods (2) Spacer Flanges, (2) Sleeve Exhaust Fan	
6826	Divider Tray of 1032- (70) Steel Rule Anode Dies; Contents- (70) Steel Rule Anode Dies	
6827	Divider Tray of 1033- Foam Rule Die Tab Cathode .79" x 3.19", (42) Steel Rule Anode Die Tab ; Foam Rule Die Tab Cathode .79" x 3.19", (42) Steel Rule Anode Die Tab	
6828	Divider Tray of 1034- Graphic Operation Terminals, Transformers, Pressure Sensors, Fuses, Batteries, Self-Closing CL Hinge, LS Contactor, Etc. ; Contents- Mitsubishi Graphic Operation Terminal GOT1000, LS Magnet Contactor, (2) Nationwide Industries HD Self-Closing CL Hinges, (3) SKF Motor Bearings, (4) Air Static Pressure Sensors, (2) Shinhan Transformers, LifePlus Reservoir, Jefferson Electric 631-1103-000	
6829	Divider of Tray 1034 (1) Mexion Control Panel (2) Mitsubishi Programable Controller (3) THK Ball Screws (4) Autonics Sensors (13) Ball Bearings (3) Metal Fans ; (1) Mexion Control Panel Makes Excelent Incense of Nature (2) Mitsubishi Q3NB-UHW Programable Controller (3) THK Ball Screws BTK2005V – 2.6 ZZ (4) Autonics Sensors model: PR 08–1.5DN(13) Ball Bearings Koyo and NTK (3) Metal Fans Model MVC 40–2 5–2	
6830	Divider of Tray 1034 - Trane ACT00882 Actuator, Liming ATG PGX142-H-5 Cylinder, ABB / Mitsubishi Drives, etc.; Contents: - ABB ACS150-03U-02A4-2 Open Type Drive -Mitsubishi FR-E720-008 AC Servo Drive -Mitsubishi MR-J4-350B-RJ AC Servo Drive -Hanil DWT-1KVAU Transformer -Trane ACT00882 Actuator -Liming ATG PGX142-H-5 Cylinder -(10) Eaton 6A Fuses - Yukon Piston Pump	
6831	Divider Tray of 1035- (13) Boxes of 2080 Zebra Z-Perform 1500T Labels 4.375" x 3.000" ; (13) Boxes of 2080 Zebra Z-Perform 1500T Labels 4.375" x 3.000", Peak Industries Labels, Grand Rapids Label Co. RP3T-279147617, Uline S-7476 Labels	
6832	Divider of Tray 1036- (5) Mitsubishi Electric GOT2000 15" Touch Screen HMI Displays; Model#: GT2715-XTBD Article#: 93085956 Date of Mfg: 06/25 Display: 15" Power Supply: IN 24VDC, Max 48W	
6833	Divider Tray of 1036- Lot of Assorted Battery Servo Amps MR-BAT6V1SET HMI, (2) Red Odo 12.8V 140Ah Batteries ; Contents- Assorted Cameron Sino CS-PLC267SL Battery Servo Amps 1650mAh 6.0V MR-BAT6V1SET, (2) Red Odo 12.8V 140Ah Batteries Rated Energy: 1792Wh Charging Voltage: 14.4V±0.2V Max Continuous Charge/Discharge Current: 140A /150A Max Continous Output: 1920W	
6834	Divider of Tray 1036 - Mitsubishi Electric GOT2000 and GOT1000 Graphic Operation Terminals, Balluff Network CC Links, 12V Rechargeable Batteries; Contents: -(3) Mitsubishi Electric GOT2000 GT2506HS-VTBD Graphic Operator Panels - IN BOX, UNUSED -(1) Mitsubishi Electric GOT1000 GT1665HS-VTBD Graphic Operator Panel - IN BOX, UNUSED -(3) Mitsubishi Electric GT16H-C60-42P 42 Pin Ext. Cable for GOT1000 Operator Panel -(1) Balluff BNI0040 8 Channel Network Interface CC-Links -(1) Balluff BNI0074 8 Input Newtork Interface I/O Link -(3) Sepe Poder LifeP04 12.8V Rechargeable Batteries	
6835	Divider of Tray 1036 - Keysight 3470A Data Acquisition / Switch Unit, Keysight 34901A Armature Multiplexer Module; Contents: -Keysight 34970A Data Acquisition/ Switch Unit GPIB, RS232, Internal 6.5 Digit DMM, 120V Line Selection (S/N MY58005095) -Cable Assembly Power Cord -9 Pin RS232 Cable -Supplemental Documents -CD ROM Product Reference - Keysight 34901A Armature Multiplexer Module for 34970A/34972A, 20 Channel (S/N MY59002128) -Supplemental Documents	
6836	Divider Tray of 1037- Assorted HDPE Glass/Plastic Sample Bottles; Contents- (11) Packs of Greenwood 125mL HDPE Leakproof Wide Mouth Bottle w/38-415 Linerless Cap, (6) Packs of Duran Wheaton Kimble Glass Sample Bottles w/Plastic Top	
6837	Divider Tray of 1038- (5) Boxes of 2080 Zebra Z-Perform 1500T Labels 4.375" x 3.000", Assorted Labels ; Contents- (5) Boxes of 2080 Zebra Z-Perform 1500T Labels 4.375" x 3.000", Assorted Labels	
6838	Divider Tray of 1039- Lot of Assorted 55 Gal Drum Vacuum Filters w/Bag, High Speed PD Mixer Belts, Diaph Pump Repair Kit, Etc.; Contents- Emerson DYH01081 Fitler Line Trane Chiller, Trane Lube Oil Filter FLR01592, (4) Solenoid Trane Purge2 VAL07378, (6) HEPA HAFCOVAC HV-7063 55 gal Drum Filters, High Speed PD Mixer Belts, Diaph Pump Repair Kit	
6839	Divider Tray of 1040- (5) Seahan Leaf Air Shaft Chucks, Bladder Air Shaft 27L126466 SRPO Puncher ; Contents- (5) Seahan Leaf Air Shaft Chucks Length: 43"/Diameter: 6", (1) Bladder Air Shaft 27L126466 SRPO Puncher	
6840	Divider Tray of 1041- Diaphragm Kit, Browning V-Belts, (4) Mixing Cylinders, Micro Motion Transmitter, Etc. ; Contents- Metso Automation Ball Valve Repair Kit, Mucon JS12 Medium Poly Diaphragm Kit, SolaHD S4KC Installation CD, (2) Bando Narrow V-Belts, Dtech USB to Serial Cable, Actuator Repair Kit, Metso 4" Wafer Butterfly Valve, Metso 3" Lug Body Butterfly Valve Repair Kit, Emerson Micro Motion Transmitter 2700R12BBMEZZX, Emerson S4K2U1500C Power Supply 110/115/120V Power Factor: 0.9, (6) Dwyer Magnahelic Pressure Gauges, Marathon Electric Black Max Invertor-Duty Motor LH56H17E5303BP 1/2 HP 230/460V 60Hz 1725 RPM 1.6/.8 FLA	
6841	Divider of Tray 1041 - Mitsubishi Inverter, Tension Detectors, AB Limit Switches, Omron Relays, etc.; Contents: -Mitsubishi FREQROL-A740-15K Inverter -(3) Mitsubishi LX-030TD Tension Detectors -Mitsubishi LM-10PD Tension Meter -Yaskawa SGDV-5R5A11A002000 Servopack -(30) Omron G6B-47BND 24V Relays -(2) AB 802X-A7 Limit Switches -(2) Electro-Sensors Split-Collar Pulsar Wraps (1.5x2.688x5.688x16 MAG AL) -(2) StarTech 2 Port HDMI USB KVM Switches (w/ Audio, USB 2.0 Hub) -Sigmas SP 12-7.5HR Rechargeable Lead Acid Battery -Misc. Amphenol Connectors (Box, Straight Plug) -Misc. Cables and Switches (Spill Detection, Motor Cable, Leader, Proximity Switch Cable, etc.)	
6842	Divider Tray of 1042- Lot of Assorted Motorola Radios/ Scanning Equipment, Chargers ; Contents- Assorted Motorola Radios, (2) MOTOTRBO R7 Motorola Radios, Adaptus HWREVK SKU Scanner	

6843	Divider Tray of 1044- Rollers, Power Supplies, Sensor Cables, Etc.; Contents- (3) Autonics E50S8-8000-6-L-5 Rotary Encoders, (2) Assorted Gears PD-XM-009-17T, FIFE SE-26 Sensor w/ Cables, (3) Rollers Length: 34"/38" Diameter: 4" , (18) Tensei Lambda Power Supplies: (7) 50W 24V #HWS50-24/A Power Supplies, (6) 100W 24V #HWS100-24/A Power Supplies, (5) 80W, 12V #HWS80-12/A Power Supplies, (1) 24V LS100-24 HFP Power Supply	
6844	Divider of Tray 1044 - Fife Data Web Guide Controllers; Contents: -(3) Fife CDP-01-M High Precision Data Web Guide Controllers -Fife OI-B D-Max Web Guide Controller	
6845	Divider Tray of 1045- Power Supplies, Bearings, Transmitters, Rittal Filters, Differential Pressure Switch, MagnaLight Flood Light, Maestro Laminate Flooring, Seals, Etc. ; Contents- Litchzen Temperature Sensors, (3) MagnaLight HID-5500-S Flood Lights, SKF 563720 25x25x10 HMS5 RG Seals, Tidland 131972F4 Bearing, Temperature Sensors, (6) TDK Lamba HWS80A-12 /A Power Supplies, (3) Packs of Omron 3LY2N-D2 24VDC Relays, (3) Rittal SK3323 Outlet Filters, (9) Kimo CP100 Pressure Transmitters 24Vac/Vdc±10%, Dwyer 1639-0-WP Differential Pressure Switch, Assorted SKF Bearings (2) 24024 CC/W33 / (4) 6217 2RSJEM / (3) 6210 2RSJEM, Tidland 131972 Bearing	
6846	Divider of Tray 1045 - Mitsubishi Inverter, Riken Keiki Gas Monitor, Festo Valve Manifolds; Contents: -Mitsubishi FR-A740-37K Inverter -Riken Keiki SD-2500(UL) Portable Gas Monitor -(2) Festo CPX-FB23 Manifolds w/ (3) MPA1-FB-EMS-8 Valve Modules Per -Sam Heung 65KG Gas Springs (Appx. 30 Total)	
6847	Divider of Tray 1046- Hope Industrial Systems 22" Panel Mount Monitor Revision C, LS Magnetic Contactor, Bearings, Springs, Seals, Etc. ; Contents- (3) LS Magnetic CONTACTOR MC-9, Peer Insert Ball Bearings, Misumi High Torque Timing Pulley, Calendar Pump Silicone Mechanical Seals, Noritake Cam Followers, (5) Sticky Back Foam Sheets, (3) Igus Echains, Misumi MCK-1016 Clamps, (3) MVC40-25-2 Fan Oil Coolers	
6848	Divider of Tray 1046 - Mitsubishi A700 Inverter, Mitsubishi GM-S Geared Motors, Couplings; Contents: -Mitsubishi FREQROL-A740-7.5KInverter -(3) Mitsubishi GM-S 0.1kW Geared Motors -(6) Parker A3-30 Couplings -(2) Indexer Transfer Shafts	
6849	Divider Tray of 1047- Bearings, O-Rings, Seals, Etc. ; Contents- (5) Assorted Sizes Global O-Ring and Seal 5.7MM x 169.3MM, NSK Bearings 50MM x 110MM, Global O-Rings and Seals Silicone 6MM x 1MM x 1100MM O-Rings, Global O-Rings and Seals CR 100 x 125 x 12 HMS5 V MCD, SKF Small Bore Seal CR-53151 MCD, S14M x 1246 Timing Belt MCD	
6850	Divider of Tray 1047 - Mitsubishi Electric E700 Inverters; Contents: -(4) Mitsubishi Electric FR-E740-095SC-NA Inverter Drives	
6851	Divider of Tray 1047 - Mitsubishi Inverters, CC Links; Contents: -(3) Mitsubishi Electric FR-E840-0060-5-60 Inverters -(2) Mitsubishi Electric FR- A8NC CC Link V2's	
6852	Divider Tray of 1048- Watlow Single Phase Microprocessor-Based SCR Power Controller; Model#: PC31-N20B-0000 SN#: 00012427 Power Supply: 400V (ac) 50/60 Hz 65 AMP 50° C 90° C WIRE MIN USE COPPER CONDUCTOR ONLY, SCCR 200KA TYPE 2/ BUSSMANN 170N-1317-1322 FUSE. TERMINAL TORQUE 16 FT-LBS (20 N-M) 46%	
6853	Divider Tray of 1048- Watlow Power Series PC31-N20B-0000 Single-Phase Microprocessor-Based SCR Power Controller; Model#: PC31-N20B-0000 SN#: 00002965 Power Supply: 400V (ac) 50/60 Hz 65 AMP 50° C 90° C WIRE MIN USE COPPER CONDUCTOR ONLY, SCCR 200KA TYPE 2/ BUSSMANN 170N-1317-1322 FUSE. TERMINAL TORQUE 16 FT-LBS (20 N-M) 46%	
6854	Divider Tray of 1048- Watlow ASPYRE SCR Power Controller; Model#: ASPYRE DT248-1804B-10AAA SN#: 067020-188159-001 Power Supply: 3-phase, 2 controlled leg, 180A Nominal Voltage 380, 400, 415, 440 or 480VAC	
6855	Divider Tray of 1048- Watlow ASPYRE SCR Power Controller / Watlow DIN-A-MITE Compact Power Controller; Model#: ASPYRE DT248-1804B-10AAA / DC2T-24F0-S000 SN#: 067020-188159-001 Power Supply: 3-phase, 2 controlled leg, 180A Nominal Voltage 380, 400, 415, 440 or 480VAC - Nvent Hoffman Electric Heater DAH8001B Article Number: 70590 Height: 7.5in Width: 4.25in Depth: 4.38in Nominal Voltage: 115V Nominal Capacity Watts: 800W Voltage AC: 100V Max Current: 7.37A Material: Aluminum Finish Brushed Thickness:0.06in Weight: 2.5lb	
6856	Divider Tray of 1048- Check Valves, Gas Springs, Multi Power Meters, RTD Convertors ; Contents- (38) Swagelok M10-SCVU-3/1 Check Valves, -(4) Shinhan M2RS-4A-AM2/UL RTD Convertors, -(3) ACUVIM-CL Multi Power Meters -(30) Lichtzen 500-50 Gas Springs -Dormeyer Solenoid 2536-M Door Latch -(6) Exergen IRT/c 10A-K-1500HIE Temperature Sensors	
6857	Divider Tray of 1048- (4) Kokam Mesh Mixing Filters, Assorted Size Mixing Blades; Contents- (4) Kokam Mesh Mixing Filters - Assorted Size Mixing Line Blades	
6858	Divider Tray of 1049- UV Light Lamps, Filters, Filter Hoods, Flat Belts, Coater/Glitter Guide Rolls, Etc. ; Contents- (3) Lichtzen Long Arc UV Lamps, - (4) Kokam 0118-750L Coater/Glitter Guide Rolls - (3) Clamp Bars - (3) Kokam L-500 Flat Belts - ADC NonMetallic 8" Air Duct/Connector -(3) M25 Compressed Air Filter Scrubbing System Cartridge -(2) Operator Side Chucks -(3) 239 MIXER Filter Canisters -(26) Hosokawa Filter Hoods - Drive Side Chucks -(2) 100mm x 74mm Kokam Mixing Sleeve Bearings - Basic Acuator Bearing	
6859	Divider Tray of 1050- Rollers, Sensors, Valves, Bearings, Press Stamps, Etc.; GTR 3 Phase Inductuion Motor G3L28N050-UTM040WAX, Stamps, Honeywell Upgrade Kit, Cathode Coating Rollers, Bearings, Safety Shelids, Inductive Sensors	
6860	Divider of Tray 1051 - Labels, Film Resistors, Band Heat Seals, Zener Diodes, Etc.; Contents: -(24) Rolls of 4" Inventory Labels -(5) Boxes of Standex-Meder Electronics KT05-1A-40L-SMD -Toss Copper Band Heat Seals -OHMITE P/n 5910E Saddle Holder For AZ Series -32B 1M Flash 128kRAM NXP 32-bit Microcontroller - MCU (12) pack -(17) SIBA 450A Fuse Links -Roll of 1A Surface Mount Fuses -(75) Supercapacitors	
6861	Divider Tray of 1052- RFID Processor CC Link Unit, RFID Read/Write Head, Surface Mounts, Etc.; Contents- -Balluff BIS00LY RFID Processor CC Link Unit, -Balluff BIS0055 RFID Read/Write Head -Assorted Size Connection Cables -Allen Bradley Bullentin 855T Suface Mount Base and Cap, Flashing LED, Signal Tone Sound, and Steady LED	
6862	Siemens Simatic HMI; (5) Siemens Simatic HMI IPC477C Pro	